

G 7104 SC Front

Freestanding dishwasher with 3D MultiFlex tray and ExtraComfort basket design for maximum convenience.

Price: \$ 2,349.00

: Stainless steel/CleanSteel



GO TO SHOP









More product information

Freestanding dishwasher with 3D MultiFlex tray and ExtraComfort basket design for maximum convenience.

Perfect results in less than one hour – QuickPowerWash ①
Everything completely dry – AutoOpen drying ①
Fresh water dishwashers – from 6L in the Automatic programme.
Very easy door opening and closing – ComfortClose ①
Versatile and secure – ExtraComfort basket design

Product details - G 7104 SC Front

Construction type	-
Freestanding dishwasher	• 🛈
60 cm dishwasher	•
Design	-
Fascia colour	Stainless steel/CleanSteel
Control panel version	Straight fascia
Control type	Programme selector button
Display	1-line text display
Display colour	White
MultiLingua	•
Convenience	-
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	44
Time left display	• ①
Delay start up to 24 hours	• ①
In-operation indicator light	Display

Efficiency and sustainability	
Water consumption in the Automatic programme in from	6.0
EcoFeedback	•
EcoPower technology	• 🕦
Proven hygiene	• 🛈
Hot water connection	• 🛈
Half load	• 🛈
Gentle treatment of crockery and glassware	
Fresh water dishwasher	• (i)
AutoOpen drying	• 🕦
SensorDry	• 🛈
Active condensation drying	• 🛈
BrilliantGlassCare	•
Wash programmes	
ECO	• 🛈
Automatic	• (i)
Intensive 75 °C	• 🛈
PowerWash 60 °C	• 🛈
Gentle	• 🛈
QuickPowerWash	• 🛈
ExtraQuiet 40 dB(A)	• 🛈
Appliance care.	• ①
Dishwashing options	
Extra dry	•
IntenseZone	•
Express	•
extra clean	•
Basket design	
Cutlery loading	3D MultiFlex tray (i)
FlexCare glass holder	2
FlexCare cup rack	1
Basket design	ExtraComfort 60 cm
Safety	
Waterproof system	• ①
Filter indicator light	•
Safety lock	• ①
Technical data	
Niche width in mm	600
	600 845
	040
Niche height in mm	-

Niche depth in mm	600
Appliance width in mm	598
Appliance height in mm	845
Appliance depth in mm	600
Depth with door open in cm	119.5
Net weight in kg	57.0
Total rated load in kW	2.0
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Energy stars	4.5
Water stars	6.0
Length of water inlet hose in m	1.50
Length of water drain hose in m	1.50
Length of supply lead in m	1.90

Installation sketch

Whether you want to replace a household appliance or planning a kitchen - under Downloads you will find all the relevant installation diagrams for your Miele appliance.

<u>Downloads</u>

Subject to technical changes; no liability accepted for the accuracy of the information given!

¹ DE102007008950B4, EP2120671B1

2 According to certification by the Institute for Integrative Hygiene and Virology with respect to the removal of enveloped and non-enveloped viruses (e.g. coronaviruses, influenza viruses or noroviruses) in the tested Hygiene and Intensive programmes, in all cases using PowerDisk/UltraTabs. Details on the test criteria can be found at www.miele.com/g7000-c.

3 In the sensor wash gentle/ gentle programme

⁴ EP1967121B1

5 _{DE102006042486B3}, EP1902659B1

6 Patent: DE102008062761B3, EP2433549B1

 $\boldsymbol{7}$ For details please refer to our warranty terms and conditions for water protection.





Shop | Miele@home | Contact | User manuals | About us | Member Benefits | Dealers | Architects & Builders | Suppliers |
Careers | Press | Miele
Corporate | Data Protection |
Legal Information | Terms of Use |
Sitemap

