



TCB140 WP  
T1 heat-pump dryer: for high efficiency at an attractive entry-level price.

Price: \$ 1,899.00

: Lotus white



GO TO SHOP



More product information

T1 heat-pump dryer: for high efficiency at an attractive entry-level price.

- Savings for the life of your tumble dryer – EcoDry technology ⓘ
- Fragrant laundry just the way you like it – FragranceDos ⓘ
- Precision drying of all fabrics – PerfectDry
- Perfect room and furniture protection – best condensation effect ⓘ
- Easy fingertip operation – DirectSensor

Product details - TCB140 WP

Construction type	-
Suitable for stacking	• ⓘ
Side-by-side	• ⓘ
Slot-in	• ⓘ
Can be built-under	• ⓘ
Door hinge	left
Model	-
Heat pump dryer	•
Design	-
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Lotus white
Rotary selector colour	Lotus White
Control panel version	Straight
Control type	Rotary selector
Display	DirectSensor yellow, 7 segment

<b>Drying results</b>		<b>—</b>
PerfectDry precision drying	• ⓘ	
FragranceDos fragrance system	• ⓘ	
Intelligent drum reversal	•	
<b>Gentle laundry care</b>		<b>—</b>
Honeycomb drum	• ⓘ	
Load in kg	7.0	
<b>User convenience</b>		<b>—</b>
Delay start up to 24 hours	•	
Time left display	•	
Drum lighting	LED	
Condensate container	•	
Integrated condensed water drainage	• ⓘ	
AddLoad	• ⓘ	
<b>Efficiency and sustainability</b>		<b>—</b>
EcoDry technology	•	
Maintenance-free heat exchanger	• ⓘ	
<b>Drying programmes</b>		<b>—</b>
Cottons (coloureds)	•	
Cottons Eco	•	
Minimum iron	•	
Delicates	•	
Shirts	• ⓘ	
Woollens handcare	• ⓘ	
Express	• ⓘ	
Denim	• ⓘ	
Proofing	• ⓘ	
Warm air	•	
Pre-ironing	• ⓘ	
Bed linen	•	
<b>Drying extras</b>		<b>—</b>
Anti-crease	•	
Gentle tumble	•	
<b>Quality</b>		<b>—</b>
Soft ribs	•	
<b>Safety</b>		<b>—</b>
PIN code lock	•	
"Empty out container" indicator	•	
"Clean filter" indication	•	
Optical interface	•	

#### Technical data

–

Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	640
Appliance depth in mm with opened door	1,054
Weight in kg	58
Total rated load in kW	1.1
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2
Hermetically sealed	•
Type of coolant	R290

#### Standard accessories

–

Fragrance flacon	•
Voucher for a second fragrance flacon	•

#### Installation sketch

Whether you want to replace a household appliance or planning a kitchen - under Downloads you will find all the relevant installation diagrams for your Miele appliance.

#### Downloads

Subject to technical changes; no liability accepted for the accuracy of the information given!

<sup>1</sup> Patent: EP 2 431 516

<sup>2</sup> Patent: EP 1 293 594

<sup>3</sup> Patent: EP 2 532 779



Shop | Miele@home | Contact |  
User manuals | About us |  
Member Benefits | Dealers |  
Architects & Builders | Suppliers |  
Careers | Press | Miele  
Corporate | Data Protection |  
Legal Information | Terms of Use |  
Sitemap

