

G 5000 Active

Freestanding dishwasher in tried-andtested Miele quality at an affordable entrylevel price.

Price: \$ 1,449.00

: Brilliant White



GO TO SHOP









More product information

Freestanding dishwasher in tried-and-tested Miele quality at an affordable entry-level price.

Perfect results in less than one hour – QuickPowerWash ①
Save up to 50 % more electricity – hot water connection
Versatile and secure – comfort basket design
Very easy door opening and closing – ComfortClose ①
Maximum versatility – Height-adjustable upper basket ①

Product details - G 5000 Active

Construction type	-
Freestanding dishwasher	• 🕠
60 cm dishwasher	•
Design	-
Fascia colour	Brilliant White
Control panel version	Straight fascia
Control type	Programme selector button
Display	3-digit 7-segment display
Display colour	Yellow
Convenience	-
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	46
Time left display	• 🛈
Delay start up to 24 hours	• 🕠
In-operation indicator light	acoustic

Inform 6.0 EcoPower technology . ① Proven hygiene . ① Hot water connection . ① Gentile treatment of crockery and glassware Fresh water dishwasher . ① Wash programmes ECO . ① Automatic . ① Intensive 75 ° C . ① Gentile . ② QuickPowerWash . ① Dishwashing options Extra dry . ② Express . ③ Extra clean . ③ Cutlery loading . Cutlery basket . ② Basket design . Comfort 60 cm Safety Waterproof system . ① Safety . ② Technical data Niche height in mm	Water consumption in the Automatic programme in		
Proven hyglene Hot water connection Gentle treatment of crockery and glassware Fresh water dishwasher Wash programmes ECO	l from	6.0	
Hot water connection Gentle treatment of crockery and glassware Fresh water dishwasher Wash programmes ECO	EcoPower technology	• (i)	
Gentle treatment of crockery and glassware Fresh water dishwasher Wash programmes ECO	Proven hygiene	_	
Fresh water dishwasher Wash programmes ECO	Hot water connection	• (i)	
Wash programmes ECO	Gentle treatment of crockery and glassware		
ECO Automatic Intensive 75 °C Gentle QuickPowerWash Dishwashing options Extra dry Express extra clean Cutlery loading Cutlery basket FlexCare cup rack Basket design Cutlery system Safety Waterproof system Safety Waterproof system Safety lock Technical data Niche width in mm 600 Appliance beight in mm 600 Appliance depth in mm 600 Depth with door open in cm Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A Number of phases 1	Fresh water dishwasher	• ①	
Automatic Intensive 75 °C Gentle QuickPowerWash Dishwashing options Extra dry Express extra clean Cutlery loading Cutlery basket FlexCare cup rack Basket design Comfort 60 cm Safety Waterproof system Safety lock Technical data Niche width in mm Niche width in mm Appliance width in mm Appliance width in mm Appliance width in mm Appliance height in mm Appliance height in mm Appliance depth in depth	Wash programmes		
Intensive 75 °C Gentle QuickPowerWash Dishwashing options Extra dry Express Extra clean Basket design Cutlery loading Cutlery loading Cutlery basket FlexCare cup rack Basket design Comfort 60 cm Safety Waterproof system Safety lock Technical data Niche width in mm 600 Niche width in mm 600 Appliance width in mm 600 Appliance width in mm 598 Appliance height in mm 600 Appliance depth in door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	ECO	• (i)	
Gentle	Automatic	• (i)	
QuickPowerWash Dishwashing options Extra dry Express extra clean Cutlery loading Cutlery loading Cutlery basket PlexCare cup rack Basket design Comfort 60 cm Safety Waterproof system Safety lock Technical data Niche width in mm Niche width in mm Appliance height in mm Appliance width in mm Appliance width in mm Appliance depth in mm Appliance de	Intensive 75 °C	• (i)	
Dishwashing options Extra dry Express extra clean Cutlery loading Cutlery basket FlexCare cup rack Basket design Comfort 60 cm Safety Waterproof system Safety lock Technical data Niche width in mm Niche width in mm Appliance width in mm Appliance width in mm Appliance width in mm Appliance depth in kg Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Gentle	• (i)	
Extra dry Express extra clean Cutlery loading Cutlery loading Cutlery basket FlexCare cup rack Basket design Comfort 60 cm Safety Waterproof system Safety lock Technical data Niche width in mm Niche eight in mm Niche depth in mm Appliance width in mm Appliance width in mm Appliance depth in mm Coultery basket Safety 10 11 12 13 14 15 15 16 16 17 17 18 18 18 18 18 18 18 18	QuickPowerWash	• (i)	
extra clean Basket design Cutlery loading Cutlery basket FlexCare cup rack 2 Basket design Comfort 60 cm Safety Waterproof system • ① Safety lock • ① Technical data Niche width in mm 600 Niche height in mm 600 Appliance width in mm 880 Appliance height in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Dishwashing options		
Basket design Cutlery loading Cutlery basket FlexCare cup rack 2 Basket design Comfort 60 cm Safety Waterproof system • ① Safety lock • ① Technical data Niche width in mm 600 Niche height in mm 845 Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Extra dry	•	
Cutlery loading Cutlery loading Cutlery basket FlexCare cup rack 2 Basket design Comfort 60 cm Safety Waterproof system Safety lock Technical data Niche width in mm 600 Niche height in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A Number of phases 1	Express	•	
Cutlery loading Cutlery basket FlexCare cup rack 2 Basket design Comfort 60 cm Safety • ① Waterproof system • ① Safety lock • ① Technical data Niche width in mm 600 Niche height in mm 845 Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	extra clean	•	
FlexCare cup rack 2 Basket design Comfort 60 cm Safety . ● Waterproof system . ● Safety lock . ● Technical data Niche width in mm Niche height in mm - Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 600 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Basket design		
Basket design Comfort 60 cm Safety . ● Waterproof system . ● Safety lock . ● Technical data 600 Niche width in mm - Niche height in mm 845 Niche depth in mm 600 Appliance width in mm 600 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Cutlery loading	Cutlery basket	
Safety Waterproof system • ① Safety lock • ① Technical data Niche width in mm - Niche height in mm - Niche depth in mm 600 Appliance width in mm 600 Appliance height in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	FlexCare cup rack	2	
Waterproof system • ⊕ Safety lock • ⊕ Technical data Niche width in mm - Niche height in mm - Niche depth in mm - Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Basket design	Comfort 60 cm	
Safety lock • ● Technical data 600 Niche width in mm - Niche height in mm 845 Niche depth in mm 600 Appliance width in mm 600 Appliance height in mm 845 Appliance depth in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Safety		
Technical data Niche width in mm - 600 845 Niche height in mm - 880 80 Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Waterproof system	• (i)	
Niche width in mm	Safety lock	• (i)	
Niche width in mm - 600 845 Niche height in mm - 880 880 Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Technical data		
Niche height in mm 845 Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1		600	
Niche height in mm - 880 880 Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Niche width in mm	- 600	
Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1			
Niche depth in mm 600 Appliance width in mm 598 Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Niche height in mm	- 880	
Appliance height in mm 845 Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Niche depth in mm		
Appliance depth in mm 600 Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Appliance width in mm	598	
Depth with door open in cm 119.5 Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Appliance height in mm	845	
Net weight in kg 52.5 Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Appliance depth in mm	600	
Total rated load in kW 2.0 Voltage in V 230 Fuse rating in A 10 Number of phases 1	Donaldo collidado en casa de casa	119.5	
Voltage in V 230 Fuse rating in A 10 Number of phases 1	Depth with door open in cm	52.5	
Fuse rating in A 10 Number of phases 1	Deptn with door open in cm Net weight in kg	2.0	
Number of phases 1		2.0	
	Net weight in kg Total rated load in kW		
Energy stars 4.0	Net weight in kg Total rated load in kW	230	
	Net weight in kg Total rated load in kW Voltage in V	230 10	
	Net weight in kg Total rated load in kW Voltage in V Fuse rating in A Number of phases Energy stars	230 10 1 4.0	
Length of water inlet hose in m 1.50	Net weight in kg Total rated load in kW Voltage in V Fuse rating in A Number of phases Energy stars Water stars	230 10 1 4.0 6.0	

Installation sketch

Whether you want to replace a household appliance or planning a kitchen - under Downloads you will find all the relevant installation diagrams for your Miele appliance.

Downloads

Subject to technical changes; no liability accepted for the accuracy of the information given!

1 According to certification by the Institute for Integrative Hygiene and Virology with respect to the removal of enveloped and non-enveloped viruses (e.g. coronaviruses, influenza viruses or noroviruses) in the tested Hygiene and Intensive programmes, in all cases using PowerDisk/UltraTabs. Details on the test criteria can be found at www.miele.com/g7000-c.

2 In the sensor wash gentle/ gentle programme

 $\boldsymbol{3}$ For details please refer to our warranty terms and conditions for water protection.





Shop | Miele@home | Contact |
User manuals | About us |
Member Benefits | Dealers |
Architects & Builders | Suppliers |
Careers | Press | Miele
Corporate | Data Protection |
Legal Information | Terms of Use |
Sitemap

