



G 5210 SC Active Plus

Freestanding dishwasher for optimum drying results thanks to AutoOpen drying.

Price: \$ 1,999.00

GO TO SHOP



















More product information

Freestanding dishwasher for optimum drying results thanks to AutoOpen drying.

- Perfect results in less than one hour – QuickPowerWash ⓘ
- Innovative design and maximum convenience – 3D MultiFlex Tray ⓘ
- Fresh water dishwashers – from 6L in the Automatic programme.
- Save up to 50 % more electricity – hot water connection
- Versatile and secure – comfort basket design

Product details - G 5210 SC Active Plus

Construction type		-
Freestanding dishwasher		• ⓘ
60 cm dishwasher		•
Design		-
Control panel version	Straight fascia	
Control type	Programme selector button	
Display	3-digit 7-segment display	
Display colour	Yellow	
Convenience		-
Door closing aid	ComfortClose	
Operating noise dB(A) re 1 pW	45	
Time left display		• ⓘ
Delay start up to 24 hours		• ⓘ
In-operation indicator light	acoustic	
Efficiency and sustainability		-

Water consumption in the Automatic programme in l from	6.0
EcoPower technology	• 
Proven hygiene	• 
Hot water connection	• 
Half load	• 
Gentle treatment of crockery and glassware -	
Fresh water dishwasher	• 
AutoOpen drying	• 
SensorDry	• 
Active condensation drying	• 
BrilliantGlassCare	•
Wash programmes -	
ECO	• 
Automatic	• 
Intensive 75 °C	• 
Gentle	• 
QuickPowerWash	• 
Dishwashing options -	
Extra dry	•
Express	•
extra clean	•
Basket design -	
Cutlery loading	3D MultiFlex tray 
Basket design	Comfort 60 cm
Safety -	
Waterproof system	• 
Safety lock	• 
Technical data -	
Niche width in mm	600
	-
Niche height in mm	600
	845
	-
Niche depth in mm	880
	600
Appliance width in mm	598
Appliance height in mm	845
Appliance depth in mm	600
Depth with door open in cm	119.5
Net weight in kg	54.5
Total rated load in kW	2.0
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Energy stars	4.5

Water stars	6.0
Length of water inlet hose in m	1.50
Length of water drain hose in m	1.50
Length of supply lead in m	1.90

Installation sketch

Whether you want to replace a household appliance or planning a kitchen - under Downloads you will find all the relevant installation diagrams for your Miele appliance.

Downloads

Subject to technical changes; no liability accepted for the accuracy of the information given!

¹ Patent: DE102008062761B3, EP2433549B1

² According to certification by the Institute for Integrative Hygiene and Virology with respect to the removal of enveloped and non-enveloped viruses (e.g. coronaviruses, influenza viruses or noroviruses) in the tested Hygiene and Intensive programmes, in all cases using PowerDisk/UltraTabs. Details on the test criteria can be found at www.miele.com/g7000-c.

³ In the sensor wash gentle/ gentle programme

⁴ EP1967121B1

⁵ DE102007008950B4, EP2120671B1

⁶ DE102006042486B3, EP1902659B1

⁷ For details please refer to our warranty terms and conditions for water protection.



[Shop](#) | [Miele@home](#) | [Contact](#) |
[User manuals](#) | [About us](#) |
[Member Benefits](#) | [Dealers](#) |
[Architects & Builders](#) | [Suppliers](#) |
[Careers](#) | [Press](#) | [Miele](#)
[Corporate](#) | [Data Protection](#) |
[Legal Information](#) | [Terms of Use](#) |
[Sitemap](#)

