

Terminal

```
npm install -D tailwindcss postcss autoprefixer  
npx tailwindcss init --p
```

postcss.config.js

```
module.exports = {  
  plugins: {  
    tailwindcss: {},  
    autoprefixer: {},  
  },  
}
```

tailwind.config.js

```
/** @type {import('tailwindcss').Config} */  
module.exports = {  
  content: ["../src/**/*.{js,ts,jsx,tsx,mdx}",],  
  theme: {  
    extend: {},  
  },  
  plugins: [],  
}
```

main.css

```
<!doctype html>  
<html>  
<head>  
  <meta charset="UTF-8">  
  <meta name="viewport" content="width=device-width, initial-scale=1.0">  
  <link href="/dist/main.css" rel="stylesheet">  
</head>  
<body>  
  <h1 class="text-3xl font-bold underline">  
    Hello world!  
  </h1>  
</body>  
</html>
```

Create html with tailwindcss

Terminal

```
npm install -D tailwindcss
npx tailwindcss init
```

tailwind.config.js

```
/** @type {import('tailwindcss').Config} */
module.exports = {
  content: ["/src/**/*.html,js"],
  theme: {
    extend: {},
  },
  plugins: [],
}
```

src/input.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;
```

Terminal

```
npx tailwindcss -i ./src/input.css -o ./src/output.css --watch
```

src/index.html

```
<!doctype html>
<html>
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<link href="./output.css" rel="stylesheet">
</head>
<body>
<h1 class="text-3xl font-bold underline">
  Hello world!
</h1>
</body>
</html>
```

Extend css

```
/** @type {import('tailwindcss').Config} */
module.exports = {
  content: ["/src/**/*..{js,ts,jsx,tsx,mdx}"],
  theme: {
    extend: {
      fontSize: {
        '10x1': ['18rem', { lineHeight: '1' }],
      },
      colors: {
        custom: '#ff0022',
        primary: {
          light: '#d4fc79', // Lime Green Light
          DEFAULT: '#96e072', // Lime Green Default
          dark: '#4c9a2a', // Lime Green Dark
        },
      },
    },
  },
  plugins: [],
}
```

Local Font in next

Layout.tsx

```
import localFont from "next/font/local";

const playfairDisplay = localFont({
  src: './fonts/playfairDisplay.ttf',
  variable: "--playfair",
});

const playfairDisplayItalic = localFont({
  src: './fonts/PlayfairDisplay-Italic.ttf',
  variable: '--playfair_italic'
});

export default function RootLayout({
  children,
}: Readonly<{
  children: React.ReactNode;
}>) {
  return (
    <html lang="en">
      <body className={` ${playfairDisplay.variable} ${playfairDisplayItalic.variable}`}>
        {children}
      </body>
    </html>
  );
}
```

```
    </html>
  );
}
```

Google fonts in nextjs

```
import { Playfair_Display, Instrument_Sans } from 'next/font/google'

const playfairDisplay = Playfair_Display({
  subsets: ['latin'],
  style: ['normal', 'italic'],
  variable: '--heading-font',
  display: 'swap',
  weight: ['400', '500', '600', '700', '800', '900']
})

const Instrument = Instrument_Sans({
  subsets: ['latin'],
  style: ['normal', 'italic'],
  variable: '--body-font',
  display: 'swap',
  weight: ['400', '500', '600', '700',]
})

export default function RootLayout({ children }) {
  return (
    <html lang="en" className={` ${playfairDisplay.variable} ${Instrument.variable}`} >
      <body>
        <ClientLayout>
          <Navbar />
          {children}
          <Footer />
        </ClientLayout>
      </body>
    </html>
  );
}
```

Parent to child

Page.tsx

```
export default function Home() {

  const data = "parent to child";
  const data2 = "parent to child 2";

  return (
    <>
      <Card data={data} data2={data2} />
    </>
  )
}
```

```
);
}
```

Card.tsx

```
import React from "react";

export default function Card({data, data2}: { data: string, data2:string }){
  return(<>
    <h3>Card {data} <br/>{data2}</h3>
  </>)
}
```

Component in nextjs

```
"use client";
import React, {useState, useEffect, useRef} from 'react';
export default function Header() {
  return(
    <> HTML </>
  );
}
```

Page.jsx

```
"use client";
import React, { useState, useEffect } from 'react';
export default function Product() {
  return(
    <> HTML </>
  );
}
```

Card.tsx

```
import React from "react";

export default function Card(){
  return(<>
    <h3>Card</h3>
  </>
  )
}
```

Page.tsx

```
import Image from "next/image";
import Card from "@app/components/card";

export default function Home() {
  return (
    <>
```

```
<Card />
```

```
</>
```

```
);
```

```
}
```