



# Metasploitable2 Vulnerability Scan

---

Report generated by Tenable Nessus™

Thu, 14 May 2026 20:32:41 EDT

---

---

TABLE OF CONTENTS

---

**Vulnerabilities by Host**

- 172.30.2.101..... 4

---

## **Vulnerabilities by Host**

---

---

**172.30.2.101**

10

CRITICAL

7

HIGH

26

MEDIUM

9

LOW

138

INFO

---

## Scan Information

---

Start time: Thu May 14 20:11:48 2026

End time: Thu May 14 20:32:40 2026

## Host Information

---

Netbios Name: METASPLOITABLE

IP: 172.30.2.101

MAC Address: 08:00:27:12:BA:36

OS: Linux Kernel 2.6 on Ubuntu 8.04 (hardy)

---

## Vulnerabilities

**171340 - Apache Tomcat SEoL (<= 5.5.x)**

### Synopsis

---

An unsupported version of Apache Tomcat is installed on the remote host.

### Description

---

According to its version, Apache Tomcat is less than or equal to 5.5.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

### See Also

---

<https://tomcat.apache.org/tomcat-55-eol.html>

### Solution

---

Upgrade to a version of Apache Tomcat that is currently supported.

### Risk Factor

---

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2023/02/10, Modified: 2024/05/06

Plugin Output

tcp/8180/www

```
URL : http://172.30.2.101:8180/
Installed version : 5.5
Security End of Life : September 30, 2012
Time since Security End of Life (Est.) : >= 13 years
```

## 51988 - Bind Shell Backdoor Detection

### Synopsis

The remote host may have been compromised.

### Description

A shell is listening on the remote port without any authentication being required. An attacker may use it by connecting to the remote port and sending commands directly.

### Solution

Verify if the remote host has been compromised, and reinstall the system if necessary.

### Risk Factor

Critical

### CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:I/C/A:C)

### Plugin Information

Published: 2011/02/15, Modified: 2022/04/11

### Plugin Output

tcp/1524/wild\_shell

```
Nessus was able to execute the command "id" using the
following request :
```

```
This produced the following truncated output (limited to 10 lines) :
----- snip -----
root@metasploitable:/# uid=0(root) gid=0(root) groups=0(root)
root@metasploitable:/#
----- snip -----
```

## 201352 - Canonical Ubuntu Linux SEoL (8.04.x)

### Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

### Description

According to its version, Canonical Ubuntu Linux is 8.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

### See Also

<http://www.nessus.org/u?3bdb2d2e>

### Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

### Risk Factor

Critical

### CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

### Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

### Plugin Output

tcp/80/www

```
OS : Ubuntu Linux 8.04
Security End of Life : May 9, 2013
Time since Security End of Life (Est.) : >= 13 years
```

## 32314 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness

### Synopsis

The remote SSH host keys are weak.

### Description

The remote SSH host key has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to set up decipher the remote session or set up a man in the middle attack.

### See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

### Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

### Risk Factor

Critical

### VPR Score

5.1

### EPSS Score

0.0165

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

### CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

### References



|      |               |
|------|---------------|
| BID  | 29179         |
| CVE  | CVE-2008-0166 |
| XREF | CWE:310       |

Exploitable With

---

Core Impact (true)

Plugin Information

---

Published: 2008/05/14, Modified: 2024/07/24

Plugin Output

---

tcp/22/ssh

## 32321 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

### Synopsis

The remote SSL certificate uses a weak key.

### Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.

### See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

### Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

### Risk Factor

Critical

### VPR Score

5.1

### EPSS Score

0.0165

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

### CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

### References

|      |               |
|------|---------------|
| BID  | 29179         |
| CVE  | CVE-2008-0166 |
| XREF | CWE:310       |

Exploitable With

---

Core Impact (true)

Plugin Information

---

Published: 2008/05/15, Modified: 2020/11/16

Plugin Output

---

tcp/25/smtp

## 32321 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

### Synopsis

The remote SSL certificate uses a weak key.

### Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.

### See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

### Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

### Risk Factor

Critical

### VPR Score

5.1

### EPSS Score

0.0165

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

### CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

### References

|      |               |
|------|---------------|
| BID  | 29179         |
| CVE  | CVE-2008-0166 |
| XREF | CWE:310       |

Exploitable With

---

Core Impact (true)

Plugin Information

---

Published: 2008/05/15, Modified: 2020/11/16

Plugin Output

---

tcp/5432/postgresql

## 20007 - SSL Version 2 and 3 Protocol Detection

### Synopsis

---

The remote service encrypts traffic using a protocol with known weaknesses.

### Description

---

The remote service accepts connections encrypted using SSL 2.0 and/or SSL 3.0. These versions of SSL are affected by several cryptographic flaws, including:

- An insecure padding scheme with CBC ciphers.
- Insecure session renegotiation and resumption schemes.

An attacker can exploit these flaws to conduct man-in-the-middle attacks or to decrypt communications between the affected service and clients.

Although SSL/TLS has a secure means for choosing the highest supported version of the protocol (so that these versions will be used only if the client or server support nothing better), many web browsers implement this in an unsafe way that allows an attacker to downgrade a connection (such as in POODLE). Therefore, it is recommended that these protocols be disabled entirely.

NIST has determined that SSL 3.0 is no longer acceptable for secure communications. As of the date of enforcement found in PCI DSS v3.1, any version of SSL will not meet the PCI SSC's definition of 'strong cryptography'.

### See Also

---

<https://www.schneier.com/academic/paperfiles/paper-ssl.pdf>

<http://www.nessus.org/u?b06c7e95>

<http://www.nessus.org/u?247c4540>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<http://www.nessus.org/u?5d15ba70>

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://tools.ietf.org/html/rfc7507>

<https://tools.ietf.org/html/rfc7568>

### Solution

---

Consult the application's documentation to disable SSL 2.0 and 3.0.

Use TLS 1.2 (with approved cipher suites) or higher instead.

### Risk Factor

---

Critical

### CVSS v3.0 Base Score

---

## CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

## Plugin Information

Published: 2005/10/12, Modified: 2026/04/13

## Plugin Output

## tcp/25/smtp

- SSLv2 is enabled and the server supports at least one cipher.

## Low Strength Ciphers (&lt;= 64-bit key)

| Name                      | Code  | KEX | Auth | Encryption   | MAC |
|---------------------------|-------|-----|------|--------------|-----|
| -----                     | ----- | --- | ---  | -----        | --- |
| EXP-RC2-CBC-MD5<br>export |       | RSA | RSA  | RC2-CBC (40) | MD5 |
| EXP-RC4-MD5<br>export     |       | RSA | RSA  | RC4 (40)     | MD5 |

## Medium Strength Ciphers (&gt; 64-bit and &lt; 112-bit key, or 3DES)

| Name         | Code  | KEX | Auth | Encryption     | MAC |
|--------------|-------|-----|------|----------------|-----|
| -----        | ----- | --- | ---  | -----          | --- |
| DES-CBC3-MD5 |       | RSA | RSA  | 3DES-CBC (168) | MD5 |

## High Strength Ciphers (&gt;= 112-bit key)

| Name    | Code  | KEX | Auth | Encryption | MAC |
|---------|-------|-----|------|------------|-----|
| -----   | ----- | --- | ---  | -----      | --- |
| RC4-MD5 |       | RSA | RSA  | RC4 (128)  | MD5 |

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

- SSLv3 is enabled and the server supports at least one cipher.

Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

## Low Strength Ciphers (&lt;= 64-bit key)

| Name                                   | Code  | KEX | Auth | Encryption   | MAC |
|----------------------------------------|-------|-----|------|--------------|-----|
| -----                                  | ----- | --- | ---  | -----        | --- |
| EXP-EDH-RSA-DES-CBC-SHA<br>SHA1 export |       | DHE | RSA  | DES-CBC (40) |     |
| EDH-RSA-DES-CBC-SHA<br>[...]           |       | DHE | RSA  | DES-CBC (56) | SHA |

## 20007 - SSL Version 2 and 3 Protocol Detection

### Synopsis

---

The remote service encrypts traffic using a protocol with known weaknesses.

### Description

---

The remote service accepts connections encrypted using SSL 2.0 and/or SSL 3.0. These versions of SSL are affected by several cryptographic flaws, including:

- An insecure padding scheme with CBC ciphers.
- Insecure session renegotiation and resumption schemes.

An attacker can exploit these flaws to conduct man-in-the-middle attacks or to decrypt communications between the affected service and clients.

Although SSL/TLS has a secure means for choosing the highest supported version of the protocol (so that these versions will be used only if the client or server support nothing better), many web browsers implement this in an unsafe way that allows an attacker to downgrade a connection (such as in POODLE). Therefore, it is recommended that these protocols be disabled entirely.

NIST has determined that SSL 3.0 is no longer acceptable for secure communications. As of the date of enforcement found in PCI DSS v3.1, any version of SSL will not meet the PCI SSC's definition of 'strong cryptography'.

### See Also

---

<https://www.schneier.com/academic/paperfiles/paper-ssl.pdf>

<http://www.nessus.org/u?b06c7e95>

<http://www.nessus.org/u?247c4540>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<http://www.nessus.org/u?5d15ba70>

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://tools.ietf.org/html/rfc7507>

<https://tools.ietf.org/html/rfc7568>

### Solution

---

Consult the application's documentation to disable SSL 2.0 and 3.0.

Use TLS 1.2 (with approved cipher suites) or higher instead.

### Risk Factor

---

Critical

### CVSS v3.0 Base Score

---



CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2005/10/12, Modified: 2026/04/13

Plugin Output

tcp/5432/postgresql

- SSLv3 is enabled and the server supports at least one cipher.  
Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                 | Code  | KEX | Auth | Encryption     | MAC |
|----------------------|-------|-----|------|----------------|-----|
| -----                | ----- | --- | ---- | -----          | --- |
| EDH-RSA-DES-CBC3-SHA |       | DHE | RSA  | 3DES-CBC (168) |     |
| SHA1                 |       |     |      |                |     |
| DES-CBC3-SHA         |       | RSA | RSA  | 3DES-CBC (168) |     |
| SHA1                 |       |     |      |                |     |

High Strength Ciphers (>= 112-bit key)

| Name               | Code  | KEX | Auth | Encryption    | MAC |
|--------------------|-------|-----|------|---------------|-----|
| -----              | ----- | --- | ---- | -----         | --- |
| DHE-RSA-AES128-SHA |       | DHE | RSA  | AES-CBC (128) |     |
| SHA1               |       |     |      |               |     |
| DHE-RSA-AES256-SHA |       | DHE | RSA  | AES-CBC (256) |     |
| SHA1               |       |     |      |               |     |
| AES128-SHA         |       | RSA | RSA  | AES-CBC (128) |     |
| SHA1               |       |     |      |               |     |
| AES256-SHA         |       | RSA | RSA  | AES-CBC (256) |     |
| SHA1               |       |     |      |               |     |
| RC4-SHA            |       | RSA | RSA  | RC4 (128)     |     |
| SHA1               |       |     |      |               |     |

The fields above are :

{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 46882 - UnrealIRCd Backdoor Detection

### Synopsis

The remote IRC server contains a backdoor.

### Description

The remote IRC server is a version of UnrealIRCd with a backdoor that allows an attacker to execute arbitrary code on the affected host.

### See Also

<https://seclists.org/fulldisclosure/2010/Jun/277>

<https://seclists.org/fulldisclosure/2010/Jun/284>

<http://www.unrealircd.com/txt/unrealsecadvisory.20100612.txt>

### Solution

Re-download the software, verify it using the published MD5 / SHA1 checksums, and re-install it.

### Risk Factor

Critical

### VPR Score

8.4

### EPSS Score

0.872

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

### CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

### References

BID 40820

CVE CVE-2010-2075

### Exploitable With

172.30.2.101

CANVAS (true) Metasploit (true)

## Plugin Information

---

Published: 2010/06/14, Modified: 2022/04/11

## Plugin Output

---

tcp/6667/irc

```
The remote IRC server is running as :  
uid=0 (root) gid=0 (root)
```

## 61708 - VNC Server 'password' Password

### Synopsis

A VNC server running on the remote host is secured with a weak password.

### Description

The VNC server running on the remote host is secured with a weak password. Nessus was able to login using VNC authentication and a password of 'password'. A remote, unauthenticated attacker could exploit this to take control of the system.

### Solution

Secure the VNC service with a strong password.

### Risk Factor

Critical

### CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

### Plugin Information

Published: 2012/08/29, Modified: 2015/09/24

### Plugin Output

tcp/5900/vnc

```
Nessus logged in using a password of "password".
```

## 136769 - ISC BIND Service Downgrade / Reflected DoS

### Synopsis

The remote name server is affected by Service Downgrade / Reflected DoS vulnerabilities.

### Description

According to its self-reported version, the instance of ISC BIND 9 running on the remote name server is affected by performance downgrade and Reflected DoS vulnerabilities. This is due to BIND DNS not sufficiently limiting the number fetches which may be performed while processing a referral response.

An unauthenticated, remote attacker can exploit this to cause degrade the service of the recursive server or to use the affected server as a reflector in a reflection attack.

### See Also

<https://kb.isc.org/docs/cve-2020-8616>

### Solution

Upgrade to the ISC BIND version referenced in the vendor advisory.

### Risk Factor

Medium

### CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H)

### CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:P/RL:O/RC:C)

### VPR Score

5.2

### EPSS Score

0.1988

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

### CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

#### STIG Severity

---

I

#### References

---

|      |                    |
|------|--------------------|
| CVE  | CVE-2020-8616      |
| XREF | IAVA:2020-A-0217-S |

#### Plugin Information

---

Published: 2020/05/22, Modified: 2024/03/12

#### Plugin Output

---

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.19
```

## 42256 - NFS Shares World Readable

### Synopsis

The remote NFS server exports world-readable shares.

### Description

The remote NFS server is exporting one or more shares without restricting access (based on hostname, IP, or IP range).

### See Also

<http://www.tldp.org/HOWTO/NFS-HOWTO/security.html>

### Solution

Place the appropriate restrictions on all NFS shares.

### Risk Factor

Medium

### CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2009/10/26, Modified: 2024/02/21

### Plugin Output

tcp/2049/rpc-nfs

```
The following shares have no access restrictions :
```

```
/ *
```

## 42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

### Synopsis

The remote service supports the use of medium strength SSL ciphers.

### Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

### See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

### Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

### Risk Factor

Medium

### CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

### VPR Score

6.1

### EPSS Score

0.3775

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

### References

CVE CVE-2016-2183



Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/25/smtp

```
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name          Code          KEX          Auth          Encryption          MAC
-----
DES-CBC3-MD5   0x07, 0x00, 0xC0 RSA          RSA          3DES-CBC (168)      MD5
EDH-RSA-DES-CBC3-SHA 0x00, 0x16 DHE          RSA          3DES-CBC (168)
SHA1
ADH-DES-CBC3-SHA 0x00, 0x1B DH           None         3DES-CBC (168)
SHA1
DES-CBC3-SHA   0x00, 0x0A RSA          RSA          3DES-CBC (168)
SHA1

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

## 42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

### Synopsis

The remote service supports the use of medium strength SSL ciphers.

### Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

### See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

### Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

### Risk Factor

Medium

### CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

### VPR Score

6.1

### EPSS Score

0.3775

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

### References

CVE CVE-2016-2183

## Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

## Plugin Output

tcp/5432/postgresql

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                 | Code       | KEX | Auth | Encryption     | MAC |
|----------------------|------------|-----|------|----------------|-----|
| -----                | -----      | --- | ---- | -----          | --- |
| EDH-RSA-DES-CBC3-SHA | 0x00, 0x16 | DHE | RSA  | 3DES-CBC (168) |     |
| SHA1                 |            |     |      |                |     |
| DES-CBC3-SHA         | 0x00, 0x0A | RSA | RSA  | 3DES-CBC (168) |     |
| SHA1                 |            |     |      |                |     |

The fields above are :

{Tenable ciphertype}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 90509 - Samba Badlock Vulnerability

### Synopsis

An SMB server running on the remote host is affected by the Badlock vulnerability.

### Description

The version of Samba, a CIFS/SMB server for Linux and Unix, running on the remote host is affected by a flaw, known as Badlock, that exists in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A man-in-the-middle attacker who is able to intercept the traffic between a client and a server hosting a SAM database can exploit this flaw to force a downgrade of the authentication level, which allows the execution of arbitrary Samba network calls in the context of the intercepted user, such as viewing or modifying sensitive security data in the Active Directory (AD) database or disabling critical services.

### See Also

<https://www.samba.org/samba/security/CVE-2016-2118.html>

### Solution

Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.

### Risk Factor

Medium

### CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H)

### CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

### VPR Score

5.9

### EPSS Score

0.7852

### CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

## CVSS v2.0 Temporal Score

---

5.0 (CVSS2#E:U/RL:OF/RC:C)

## References

---

|      |               |
|------|---------------|
| BID  | 86002         |
| CVE  | CVE-2016-2118 |
| XREF | CERT:813296   |

## Plugin Information

---

Published: 2016/04/13, Modified: 2025/11/17

## Plugin Output

---

tcp/445/cifs

```
Nessus detected that the Samba Badlock patch has not been applied.
```

## 10205 - rlogin Service Detection

### Synopsis

The rlogin service is running on the remote host.

### Description

The rlogin service is running on the remote host. This service is vulnerable since data is passed between the rlogin client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rlogin is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

### Solution

Comment out the 'login' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

### Risk Factor

High

### VPR Score

6.7

### EPSS Score

0.5006

### CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

### References

CVE CVE-1999-0651

### Exploitable With

Metasploit (true)

### Plugin Information

Published: 1999/08/30, Modified: 2022/04/11

## Plugin Output

---

tcp/513/rlogin

## 10245 - rsh Service Detection

### Synopsis

The rsh service is running on the remote host.

### Description

The rsh service is running on the remote host. This service is vulnerable since data is passed between the rsh client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rsh is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

### Solution

Comment out the 'rsh' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

### Risk Factor

High

### VPR Score

6.7

### EPSS Score

0.5006

### CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

### References

CVE CVE-1999-0651

### Exploitable With

Metasploit (true)

### Plugin Information

Published: 1999/08/22, Modified: 2022/04/11



## Plugin Output

---

tcp/514/rsh

## 12085 - Apache Tomcat Default Files

### Synopsis

The remote web server contains default files.

### Description

The default error page, default index page, example JSPs and/or example servlets are installed on the remote Apache Tomcat server. These files should be removed as they may help an attacker uncover information about the remote Tomcat install or host itself.

### See Also

<http://www.nessus.org/u?4cb3b4dd>

[https://www.owasp.org/index.php/Securing\\_tomcat](https://www.owasp.org/index.php/Securing_tomcat)

### Solution

Delete the default index page and remove the example JSP and servlets. Follow the Tomcat or OWASP instructions to replace or modify the default error page.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2004/03/02, Modified: 2024/09/03

### Plugin Output

tcp/8180/www

The following default files were found :

<http://172.30.2.101:8180/tomcat-docs/index.html>

The server is not configured to return a custom page in the event of a client requesting a non-existent resource.  
This may result in a potential disclosure of sensitive information about the server to attackers.



## 12217 - DNS Server Cache Snooping Remote Information Disclosure

### Synopsis

The remote DNS server is vulnerable to cache snooping attacks.

### Description

The remote DNS server responds to queries for third-party domains that do not have the recursion bit set.

This may allow a remote attacker to determine which domains have recently been resolved via this name server, and therefore which hosts have been recently visited.

For instance, if an attacker was interested in whether your company utilizes the online services of a particular financial institution, they would be able to use this attack to build a statistical model regarding company usage of that financial institution. Of course, the attack can also be used to find B2B partners, web-surfing patterns, external mail servers, and more.

Note: If this is an internal DNS server not accessible to outside networks, attacks would be limited to the internal network. This may include employees, consultants and potentially users on a guest network or WiFi connection if supported.

### See Also

[http://cs.unc.edu/~fabian/course\\_papers/cache\\_snooping.pdf](http://cs.unc.edu/~fabian/course_papers/cache_snooping.pdf)

### Solution

Contact the vendor of the DNS software for a fix.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2004/04/27, Modified: 2020/04/07

### Plugin Output

udp/53/dns

Nessus sent a non-recursive query for example.edu  
and received 2 answers :

104.20.35.130  
172.66.148.61

## 11213 - HTTP TRACE / TRACK Methods Allowed

### Synopsis

Debugging functions are enabled on the remote web server.

### Description

The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods that are used to debug web server connections.

### See Also

<http://www.nessus.org/u?e979b5cb>

<http://www.apacheweek.com/issues/03-01-24>

<https://download.oracle.com/sunalerts/1000718.1.html>

### Solution

Disable these HTTP methods. Refer to the plugin output for more information.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

### CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

### VPR Score

4.0

### EPSS Score

0.6899

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

### CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

## References

---

|      |               |
|------|---------------|
| BID  | 9506          |
| BID  | 9561          |
| BID  | 11604         |
| BID  | 33374         |
| BID  | 37995         |
| CVE  | CVE-2003-1567 |
| CVE  | CVE-2004-2320 |
| CVE  | CVE-2010-0386 |
| XREF | CERT:288308   |
| XREF | CERT:867593   |
| XREF | CWE:16        |
| XREF | CWE:200       |

## Plugin Information

---

Published: 2003/01/23, Modified: 2024/04/09

## Plugin Output

---

tcp/80/www

To disable these methods, add the following lines for each virtual host in your configuration file :

```
RewriteEngine on
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

Alternatively, note that Apache versions 1.3.34, 2.0.55, and 2.2 support disabling the TRACE method natively via the 'TraceEnable' directive.

Nessus sent the following TRACE request : \n\n----- snip  
-----\nTRACE /Nessus671926675.html HTTP/1.1

```
Connection: Close
Host: 172.30.2.101
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8
```

----- snip ----- \n\nand received the  
following response from the remote server : \n\n----- snip  
-----\nHTTP/1.1 200 OK

```
Date: Fri, 15 May 2026 00:18:50 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: message/http
```

```
TRACE /Nessus671926675.html HTTP/1.1
Connection: Keep-Alive
Host: 172.30.2.101
```

```
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8
```

```
----- snip -----\n
```



## Synopsis

The remote name server is affected by a denial of service vulnerability.

## Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is version 9.x prior to 9.11.22, 9.12.x prior to 9.16.6 or 9.17.x prior to 9.17.4. It is, therefore, affected by a denial of service (DoS) vulnerability due to an assertion failure when attempting to verify a truncated response to a TSIG-signed request. An authenticated, remote attacker can exploit this issue by sending a truncated response to a TSIG-signed request to trigger an assertion failure, causing the server to exit.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

## See Also

<https://kb.isc.org/docs/cve-2020-8622>

## Solution

Upgrade to BIND 9.11.22, 9.16.6, 9.17.4 or later.

## Risk Factor

Medium

## CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:N/A:H)

## CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

## VPR Score

4.4

## EPSS Score

0.0067

## CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:N/A:P)

## CVSS v2.0 Temporal Score

---

3.0 (CVSS2#E:U/RL:OF/RC:C)

## STIG Severity

---

I

## References

---

|      |                    |
|------|--------------------|
| CVE  | CVE-2020-8622      |
| XREF | IAVA:2020-A-0385-S |

## Plugin Information

---

Published: 2020/08/27, Modified: 2021/06/03

## Plugin Output

---

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.22, 9.16.6, 9.17.4 or later
```

## 136808 - ISC BIND Denial of Service

### Synopsis

The remote name server is affected by an assertion failure vulnerability.

### Description

A denial of service (DoS) vulnerability exists in ISC BIND versions 9.11.18 / 9.11.18-S1 / 9.12.4-P2 / 9.13 / 9.14.11 / 9.15 / 9.16.2 / 9.17 / 9.17.1 and earlier. An unauthenticated, remote attacker can exploit this issue, via a specially-crafted message, to cause the service to stop responding.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

### See Also

<https://kb.isc.org/docs/cve-2020-8617>

### Solution

Upgrade to the patched release most closely related to your current version of BIND.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:N/A:H)

### CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

### VPR Score

4.4

### EPSS Score

0.9263

### CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

### CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

#### STIG Severity

---

I

#### References

---

|      |                    |
|------|--------------------|
| CVE  | CVE-2020-8617      |
| XREF | IAVA:2020-A-0217-S |

#### Plugin Information

---

Published: 2020/05/22, Modified: 2023/03/23

#### Plugin Output

---

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.19
```

## 33447 - Multiple Vendor DNS Query ID Field Prediction Cache Poisoning

### Synopsis

The remote name resolver (or the server it uses upstream) is affected by a DNS cache poisoning vulnerability.

### Description

The remote DNS resolver does not use random ports when making queries to third-party DNS servers. An unauthenticated, remote attacker can exploit this to poison the remote DNS server, allowing the attacker to divert legitimate traffic to arbitrary sites.

### See Also

<https://www.cnet.com/news/massive-coordinated-dns-patch-released/>

[https://www.theregister.co.uk/2008/07/21/dns\\_flaw\\_speculation/](https://www.theregister.co.uk/2008/07/21/dns_flaw_speculation/)

### Solution

Contact your DNS server vendor for a patch.

### Risk Factor

Medium

### CVSS v3.0 Base Score

6.8 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:N/I:H/A:N)

### CVSS v3.0 Temporal Score

6.1 (CVSS:3.0/E:P/RL:O/RC:C)

### VPR Score

6.0

### EPSS Score

0.867

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

### CVSS v2.0 Temporal Score

STIG Severity

---

I

References

---

|      |                  |
|------|------------------|
| BID  | 30131            |
| CVE  | CVE-2008-1447    |
| XREF | CERT:800113      |
| XREF | IAVA:2008-A-0045 |
| XREF | EDB-ID:6122      |
| XREF | EDB-ID:6123      |
| XREF | EDB-ID:6130      |

Plugin Information

---

Published: 2008/07/09, Modified: 2024/04/03

Plugin Output

---

udp/53/dns

The remote DNS server uses non-random ports for its  
DNS requests. An attacker may spoof DNS responses.

List of used ports :

+ DNS Server: 138.99.75.109  
| - Port: 44587  
| - Port: 44587  
| - Port: 44587  
| - Port: 44587

## 57608 - SMB Signing not required

### Synopsis

---

Signing is not required on the remote SMB server.

### Description

---

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

### See Also

---

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

### Solution

---

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v3.0 Temporal Score

---

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

### CVSS v2.0 Base Score

---

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

### CVSS v2.0 Temporal Score

---

3.7 (CVSS2#E:U/RL:OF/RC:C)

### Plugin Information

---

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

---

tcp/445/cifs



## 52611 - SMTP Service STARTTLS Plaintext Command Injection

### Synopsis

The remote mail service allows plaintext command injection while negotiating an encrypted communications channel.

### Description

The remote SMTP service contains a software flaw in its STARTTLS implementation that could allow a remote, unauthenticated attacker to inject commands during the plaintext protocol phase that will be executed during the ciphertext protocol phase.

Successful exploitation could allow an attacker to steal a victim's email or associated SASL (Simple Authentication and Security Layer) credentials.

### See Also

<https://tools.ietf.org/html/rfc2487>

<https://www.securityfocus.com/archive/1/516901/30/0/threaded>

### Solution

Contact the vendor to see if an update is available.

### Risk Factor

Medium

### VPR Score

7.3

### EPSS Score

0.427

### CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:N)

### CVSS v2.0 Temporal Score

3.1 (CVSS2#E:POC/RL:OF/RC:C)

### References

BID 46767

|      |               |
|------|---------------|
| CVE  | CVE-2011-0411 |
| CVE  | CVE-2011-1430 |
| CVE  | CVE-2011-1431 |
| CVE  | CVE-2011-1432 |
| CVE  | CVE-2011-1506 |
| CVE  | CVE-2011-2165 |
| XREF | CERT:555316   |

## Plugin Information

---

Published: 2011/03/10, Modified: 2019/03/06

## Plugin Output

---

tcp/25/smtp

```
Nessus sent the following two commands in a single packet :
```

```
STARTTLS\r\nRSET\r\n
```

```
And the server sent the following two responses :
```

```
220 2.0.0 Ready to start TLS
250 2.0.0 Ok
```

## 90317 - SSH Weak Algorithms Supported

### Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

### Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

### See Also

<https://tools.ietf.org/html/rfc4253#section-6.3>

### Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

### Risk Factor

Medium

### CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2016/04/04, Modified: 2026/01/12

### Plugin Output

tcp/22/ssh

The following weak server-to-client encryption algorithms are supported :

aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

The following weak client-to-server encryption algorithms are supported :

aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

## 31705 - SSL Anonymous Cipher Suites Supported

### Synopsis

The remote service supports the use of anonymous SSL ciphers.

### Description

The remote host supports the use of anonymous SSL ciphers. While this enables an administrator to set up a service that encrypts traffic without having to generate and configure SSL certificates, it offers no way to verify the remote host's identity and renders the service vulnerable to a man-in-the-middle attack.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

### See Also

<http://www.nessus.org/u?3a040ada>

### Solution

Reconfigure the affected application if possible to avoid use of weak ciphers.

### Risk Factor

Low

### CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

### CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

### VPR Score

3.6

### EPSS Score

0.027

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

### CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

## References

BID 28482  
CVE CVE-2007-1858

## Plugin Information

Published: 2008/03/28, Modified: 2023/10/27

## Plugin Output

tcp/25/smtp

The following is a list of SSL anonymous ciphers supported by the remote TCP server :

### Low Strength Ciphers (<= 64-bit key)

| Name                               | Code       | KEX | Auth | Encryption  | MAC |
|------------------------------------|------------|-----|------|-------------|-----|
| EXP-ADH-DES-CBC-SHA<br>SHA1 export | 0x00, 0x19 | DH  | None | DES-CBC(40) |     |
| EXP-ADH-RC4-MD5<br>export          | 0x00, 0x17 | DH  | None | RC4(40)     | MD5 |
| ADH-DES-CBC-SHA<br>SHA1            | 0x00, 0x1A | DH  | None | DES-CBC(56) |     |

### Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                     | Code       | KEX | Auth | Encryption    | MAC |
|--------------------------|------------|-----|------|---------------|-----|
| ADH-DES-CBC3-SHA<br>SHA1 | 0x00, 0x1B | DH  | None | 3DES-CBC(168) |     |

### High Strength Ciphers (>= 112-bit key)

| Name                   | Code       | KEX | Auth | Encryption   | MAC |
|------------------------|------------|-----|------|--------------|-----|
| ADH-AES128-SHA<br>SHA1 | 0x00, 0x34 | DH  | None | AES-CBC(128) |     |
| ADH-AES256-SHA<br>SHA1 | 0x00, 0x3A | DH  | None | AES-CBC(256) |     |
| ADH-RC4-MD5            | 0x00, 0x18 | DH  | None | RC4(128)     | MD5 |

The fields above are :

{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 51192 - SSL Certificate Cannot Be Trusted

### Synopsis

---

The SSL certificate for this service cannot be trusted.

### Description

---

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

### See Also

---

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

### Solution

---

Purchase or generate a proper SSL certificate for this service.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

### CVSS v2.0 Base Score

---

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

## Plugin Information

---

Published: 2010/12/15, Modified: 2025/06/16

## Plugin Output

---

### tcp/25/smtp

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject    : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After  : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

## 51192 - SSL Certificate Cannot Be Trusted

### Synopsis

---

The SSL certificate for this service cannot be trusted.

### Description

---

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

### See Also

---

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

### Solution

---

Purchase or generate a proper SSL certificate for this service.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

### CVSS v2.0 Base Score

---

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)



## Plugin Information

---

Published: 2010/12/15, Modified: 2025/06/16

## Plugin Output

---

tcp/5432/postgresql

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject    : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After  : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

## 15901 - SSL Certificate Expiry

### Synopsis

The remote server's SSL certificate has already expired.

### Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

### Solution

Purchase or generate a new SSL certificate to replace the existing one.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

### Plugin Information

Published: 2004/12/03, Modified: 2025/12/08

### Plugin Output

tcp/25/smtp

The SSL certificate has already expired :

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Not valid before : Mar 17 14:07:45 2010 GMT
Not valid after  : Apr 16 14:07:45 2010 GMT
```

## 15901 - SSL Certificate Expiry

### Synopsis

The remote server's SSL certificate has already expired.

### Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

### Solution

Purchase or generate a new SSL certificate to replace the existing one.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

### Plugin Information

Published: 2004/12/03, Modified: 2025/12/08

### Plugin Output

tcp/5432/postgresql

The SSL certificate has already expired :

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Not valid before : Mar 17 14:07:45 2010 GMT
Not valid after  : Apr 16 14:07:45 2010 GMT
```

## 45411 - SSL Certificate with Wrong Hostname

### Synopsis

The SSL certificate for this service is for a different host.

### Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

### Solution

Purchase or generate a proper SSL certificate for this service.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

### Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

### Plugin Output

tcp/25/smtp

```
The identities known by Nessus are :
```

```
172.30.2.101
172.30.2.101
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

## 45411 - SSL Certificate with Wrong Hostname

### Synopsis

The SSL certificate for this service is for a different host.

### Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

### Solution

Purchase or generate a proper SSL certificate for this service.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

### Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

### Plugin Output

tcp/5432/postgresql

```
The identities known by Nessus are :
```

```
172.30.2.101
172.30.2.101
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

## 89058 - SSL DROWN Attack Vulnerability (Decrypting RSA with Obsolete and Weakened eNcryption)

### Synopsis

The remote host may be affected by a vulnerability that allows a remote attacker to potentially decrypt captured TLS traffic.

### Description

The remote host supports SSLv2 and therefore may be affected by a vulnerability that allows a cross-protocol Bleichenbacher padding oracle attack known as DROWN (Decrypting RSA with Obsolete and Weakened eNcryption). This vulnerability exists due to a flaw in the Secure Sockets Layer Version 2 (SSLv2) implementation, and it allows captured TLS traffic to be decrypted. A man-in-the-middle attacker can exploit this to decrypt the TLS connection by utilizing previously captured traffic and weak cryptography along with a series of specially crafted connections to an SSLv2 server that uses the same private key.

### See Also

<https://drownattack.com/>

<https://drownattack.com/drown-attack-paper.pdf>

### Solution

Disable SSLv2 and export grade cryptography cipher suites. Ensure that private keys are not used anywhere with server software that supports SSLv2 connections.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

### CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

### VPR Score

3.6

### EPSS Score

0.9043

### CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

|      |               |
|------|---------------|
| BID  | 83733         |
| CVE  | CVE-2016-0800 |
| XREF | CERT:583776   |

Plugin Information

Published: 2016/03/01, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

The remote host is affected by SSL DROWN and supports the following vulnerable cipher suites :

Low Strength Ciphers (<= 64-bit key)

| Name                      | Code             | KEX | Auth | Encryption   | MAC |
|---------------------------|------------------|-----|------|--------------|-----|
| -----                     | -----            | --- | ---- | -----        | --- |
| EXP-RC2-CBC-MD5<br>export | 0x04, 0x00, 0x80 | RSA | RSA  | RC2-CBC (40) | MD5 |
| EXP-RC4-MD5<br>export     | 0x02, 0x00, 0x80 | RSA | RSA  | RC4 (40)     | MD5 |

High Strength Ciphers (>= 112-bit key)

| Name    | Code             | KEX | Auth | Encryption | MAC |
|---------|------------------|-----|------|------------|-----|
| -----   | -----            | --- | ---- | -----      | --- |
| RC4-MD5 | 0x01, 0x00, 0x80 | RSA | RSA  | RC4 (128)  | MD5 |

The fields above are :

{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 65821 - SSL RC4 Cipher Suites Supported (Bar Mitzvah)

### Synopsis

---

The remote service supports the use of the RC4 cipher.

### Description

---

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

### See Also

---

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

[https://www.imperva.com/docs/HII\\_Attacking\\_SSL\\_when\\_using\\_RC4.pdf](https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf)

### Solution

---

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

### CVSS v3.0 Temporal Score

---

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

### VPR Score

---

7.3

### EPSS Score

---

0.9076



CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:U/RL:ND/RC:C)

References

|     |               |
|-----|---------------|
| BID | 58796         |
| BID | 73684         |
| CVE | CVE-2013-2566 |
| CVE | CVE-2015-2808 |

Plugin Information

Published: 2013/04/05, Modified: 2025/05/09

Plugin Output

tcp/25/smtp

List of RC4 cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

| Name                      | Code             | KEX | Auth | Encryption | MAC |
|---------------------------|------------------|-----|------|------------|-----|
| -----                     | -----            | --- | ---  | -----      | --- |
| EXP-RC4-MD5<br>export     | 0x02, 0x00, 0x80 | RSA | RSA  | RC4 (40)   | MD5 |
| EXP-ADH-RC4-MD5<br>export | 0x00, 0x17       | DH  | None | RC4 (40)   | MD5 |
| EXP-RC4-MD5<br>export     | 0x00, 0x03       | RSA | RSA  | RC4 (40)   | MD5 |

High Strength Ciphers (>= 112-bit key)

| Name        | Code             | KEX | Auth | Encryption | MAC |
|-------------|------------------|-----|------|------------|-----|
| -----       | -----            | --- | ---  | -----      | --- |
| RC4-MD5     | 0x01, 0x00, 0x80 | RSA | RSA  | RC4 (128)  | MD5 |
| ADH-RC4-MD5 | 0x00, 0x18       | DH  | None | RC4 (128)  | MD5 |
| RC4-MD5     | 0x00, 0x04       | RSA | RSA  | RC4 (128)  | MD5 |
| RC4-SHA     | 0x00, 0x05       | RSA | RSA  | RC4 (128)  | MD5 |

SHA1

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

## 65821 - SSL RC4 Cipher Suites Supported (Bar Mitzvah)

### Synopsis

---

The remote service supports the use of the RC4 cipher.

### Description

---

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

### See Also

---

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

[https://www.imperva.com/docs/HII\\_Attacking\\_SSL\\_when\\_using\\_RC4.pdf](https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf)

### Solution

---

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

### CVSS v3.0 Temporal Score

---

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

### VPR Score

---

7.3

### EPSS Score

---

0.9076

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:U/RL:ND/RC:C)

References

|     |               |
|-----|---------------|
| BID | 58796         |
| BID | 73684         |
| CVE | CVE-2013-2566 |
| CVE | CVE-2015-2808 |

Plugin Information

Published: 2013/04/05, Modified: 2025/05/09

Plugin Output

tcp/5432/postgresql

List of RC4 cipher suites supported by the remote server :

High Strength Ciphers (>= 112-bit key)

| Name    | Code       | KEX | Auth | Encryption | MAC |
|---------|------------|-----|------|------------|-----|
| -----   | -----      | --- | ---- | -----      | --- |
| RC4-SHA | 0x00, 0x05 | RSA | RSA  | RC4 (128)  |     |
| SHA1    |            |     |      |            |     |

The fields above are :

{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 57582 - SSL Self-Signed Certificate

### Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

### Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

### Solution

Purchase or generate a proper SSL certificate for this service.

### Risk Factor

Medium

### CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

### CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

### Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

### Plugin Output

tcp/25/smtp

```
The following certificate was found at the top of the certificate
chain sent by the remote host, but is self-signed and was not
found in the list of known certificate authorities :
```

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-
base.localdomain
```

## 57582 - SSL Self-Signed Certificate

### Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

### Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

### Solution

Purchase or generate a proper SSL certificate for this service.

### Risk Factor

Medium

### CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

### CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

### Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

### Plugin Output

tcp/5432/postgresql

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

## 26928 - SSL Weak Cipher Suites Supported

### Synopsis

The remote service supports the use of weak SSL ciphers.

### Description

The remote host supports the use of SSL ciphers that offer weak encryption.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

### See Also

<http://www.nessus.org/u?6527892d>

### Solution

Reconfigure the affected application, if possible to avoid the use of weak ciphers.

### Risk Factor

Medium

### CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

### CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

### References

|      |         |
|------|---------|
| XREF | CWE:326 |
| XREF | CWE:327 |
| XREF | CWE:720 |
| XREF | CWE:753 |
| XREF | CWE:803 |
| XREF | CWE:928 |
| XREF | CWE:934 |

### Plugin Information

Published: 2007/10/08, Modified: 2021/02/03

### Plugin Output

172.30.2.101

Here is the list of weak SSL ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

| Name                                   | Code             | KEX | Auth | Encryption  | MAC |
|----------------------------------------|------------------|-----|------|-------------|-----|
| -----                                  | -----            | --- | ---- | -----       | --- |
| EXP-RC2-CBC-MD5<br>export              | 0x04, 0x00, 0x80 | RSA | RSA  | RC2-CBC(40) | MD5 |
| EXP-RC4-MD5<br>export                  | 0x02, 0x00, 0x80 | RSA | RSA  | RC4(40)     | MD5 |
| EXP-EDH-RSA-DES-CBC-SHA<br>SHA1 export | 0x00, 0x14       | DHE | RSA  | DES-CBC(40) |     |
| EDH-RSA-DES-CBC-SHA<br>SHA1            | 0x00, 0x15       | DHE | RSA  | DES-CBC(56) |     |
| EXP-ADH-DES-CBC-SHA<br>SHA1 export     | 0x00, 0x19       | DH  | None | DES-CBC(40) |     |
| EXP-ADH-RC4-MD5<br>export              | 0x00, 0x17       | DH  | None | RC4(40)     | MD5 |
| ADH-DES-CBC-SHA<br>SHA1                | 0x00, 0x1A       | DH  | None | DES-CBC(56) |     |
| EXP-DES-CBC-SHA<br>SHA1 export         | 0x00, 0x08       | RSA | RSA  | DES-CBC(40) |     |
| EXP-RC2-CBC-MD5<br>export              | 0x00, 0x06       | RSA | RSA  | RC2-CBC(40) | MD5 |
| EXP-RC4-MD5<br>export                  | 0x00, 0x03       | RSA | RSA  | RC4(40)     | MD5 |
| DES-CBC-SHA<br>SHA1                    | 0x00, 0x09       | RSA | RSA  | DES-CBC(56) |     |

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

## 81606 - SSL/TLS EXPORT\_RSA <= 512-bit Cipher Suites Supported (FREAK)

### Synopsis

The remote host supports a set of weak ciphers.

### Description

The remote host supports EXPORT\_RSA cipher suites with keys less than or equal to 512 bits. An attacker can factor a 512-bit RSA modulus in a short amount of time.

A man-in-the-middle attacker may be able to downgrade the session to use EXPORT\_RSA cipher suites (e.g. CVE-2015-0204). Thus, it is recommended to remove support for weak cipher suites.

### See Also

<https://www.smacktls.com/#freak>

<https://www.openssl.org/news/secadv/20150108.txt>

<http://www.nessus.org/u?b78da2c4>

### Solution

Reconfigure the service to remove support for EXPORT\_RSA cipher suites.

### Risk Factor

Medium

### VPR Score

1.4

### EPSS Score

0.9199

### CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

### CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

### References

BID 71936

CVE CVE-2015-0204



Plugin Information

Published: 2015/03/04, Modified: 2026/04/13

Plugin Output

tcp/25/smtp

```
EXPORT_RSA cipher suites supported by the remote server :

  Low Strength Ciphers (<= 64-bit key)

    Name                               Code           KEX           Auth           Encryption           MAC
    -----
    EXP-EDH-RSA-DES-CBC-SHA            0x00, 0x14      DHE           RSA            DES-CBC(40)
    SHA1 export
    EXP-DES-CBC-SHA                     0x00, 0x08      RSA           RSA            DES-CBC(40)
    SHA1 export
    EXP-RC2-CBC-MD5                     0x00, 0x06      RSA           RSA            RC2-CBC(40)          MD5
    export
    EXP-RC4-MD5                         0x00, 0x03      RSA           RSA            RC4(40)              MD5
    export

The fields above are :

  {Tenable ciphername}
  {Cipher ID code}
  Kex={key exchange}
  Auth={authentication}
  Encrypt={symmetric encryption method}
  MAC={message authentication code}
  {export flag}
```

## 104743 - TLS Version 1.0 Protocol Detection

### Synopsis

The remote service encrypts traffic using an older version of TLS.

### Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

### See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

### Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

### Risk Factor

Medium

### CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

### CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

### References

XREF           CWE:327

### Plugin Information

Published: 2017/11/22, Modified: 2026/04/13

### Plugin Output

tcp/25/smtp

TLsv1 is enabled and the server supports at least one cipher.

## 104743 - TLS Version 1.0 Protocol Detection

### Synopsis

The remote service encrypts traffic using an older version of TLS.

### Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

### See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

### Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

### Risk Factor

Medium

### CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

### CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

### References

XREF           CWE:327

### Plugin Information

Published: 2017/11/22, Modified: 2026/04/13

### Plugin Output

tcp/5432/postgresql

```
TLShv1 is enabled and the server supports at least one cipher.
```

## 42263 - Unencrypted Telnet Server

## Synopsis

The remote Telnet server transmits traffic in cleartext.

| Description |
|-------------|
|-------------|

The remote host is running a Telnet server over an unencrypted channel.

Using Telnet over an unencrypted channel is not recommended as logins, passwords, and commands are transferred in cleartext. This allows a remote, man-in-the-middle attacker to eavesdrop on a Telnet session to obtain credentials or other sensitive information and to modify traffic exchanged between a client and server.

SSH is preferred over Telnet since it protects credentials from eavesdropping and can tunnel additional data streams such as an X11 session.

### Solution

---

Disable the Telnet service and use SSH instead.

| Risk Factor                      | Impact                                       | Control                                            |
|----------------------------------|----------------------------------------------|----------------------------------------------------|
| 1. Lack of industry connections  | Reduced sales and market penetration         | Networking events, industry conferences            |
| 2. Limited marketing budget      | Low brand awareness                          | Strategic partnerships, social media marketing     |
| 3. Intense competition           | Price wars, reduced profit margins           | Product differentiation, customer loyalty programs |
| 4. Economic downturn             | Reduced consumer spending                    | Cost-cutting measures, flexible pricing            |
| 5. Technological changes         | Obsolescence of products                     | R&D investment, agile development                  |
| 6. Regulatory changes            | Increased compliance costs                   | Legal counsel, proactive regulatory engagement     |
| 7. Supply chain disruptions      | Increased costs, delayed shipments           | Diversified suppliers, inventory management        |
| 8. Talent acquisition challenges | Reduced productivity, innovation             | Competitive salaries, employee development         |
| 9. Customer churn                | Reduced revenue, increased acquisition costs | Excellent customer service, loyalty programs       |
| 10. Global market fluctuations   | Revenue volatility                           | Global expansion strategy, hedging                 |

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:N)

### Plugin Information

Published: 2009/10/27, Modified: 2024/01/16

## Plugin Output

tcp/23/telnet

```
Nessus collected the following banner from the remote Telnet server :

----- snip -----

_ _ _ _ _ | _ _ _ _ _ _ _ | _ _ ( ) _ _ _ | _ _ | _ _ _ _ _ \
| ' _ ' \ / _ \ _ / _ \ | ' \ | / _ \ | | _ / _ ' _ \ | / _ \ _ ) |
| | | | | _ / | | ( | \ _ | | | ( ) | | | | ( | | | | _ / _ / _ |
| _ | | | | \ _ | \ _ \ , _ | _ . _ / | | \ _ \ , _ | _ . _ / | | \ _ | _ _ |
                                     | _ |

Warning: Never expose this VM to an untrusted network!
```

```
Nessus collected the following banner from the remote Telnet server :

----- snip -----

_ _ _ _ _ | _ _ _ _ _ _ _ | _ _ ( ) _ _ _ | _ _ | _ _ _ _ _ \
| ' _ ' \ / _ \ _ / _ \ | ' \ | / _ \ | | _ / _ ' _ \ | / _ \ _ ) |
| | | | | _ / | | ( | \ _ | | | ( ) | | | | ( | | | | _ / _ / _ |
| _ | | | | \ _ | \ _ \ , _ | _ . _ / | | \ _ \ , _ | _ . _ / | | \ _ | _ _ |
                                     | _ |

Warning: Never expose this VM to an untrusted network!
```

```
Contact: msfdev[at]metasploit.com
Login with msfadmin/msfadmin to get started
metasploitable login:
----- snip -----
```

## 10114 - ICMP Timestamp Request Remote Date Disclosure

### Synopsis

It is possible to determine the exact time set on the remote host.

### Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

### Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

### Risk Factor

Low

### VPR Score

2.2

### EPSS Score

0.0037

### CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

### References

|      |               |
|------|---------------|
| CVE  | CVE-1999-0524 |
| XREF | CWE:200       |

### Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

### Plugin Output

icmp/0



The remote clock is synchronized with the local clock.

## 70658 - SSH Server CBC Mode Ciphers Enabled

### Synopsis

The SSH server is configured to use Cipher Block Chaining.

### Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

### Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

### Risk Factor

Low

### CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

### VPR Score

1.4

### EPSS Score

0.0307

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

### CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

### References

|      |               |
|------|---------------|
| BID  | 32319         |
| CVE  | CVE-2008-5161 |
| XREF | CERT:958563   |
| XREF | CWE:200       |

## Plugin Information

---

Published: 2013/10/28, Modified: 2026/01/12

## Plugin Output

---

tcp/22/ssh

The following client-to-server Cipher Block Chaining (CBC) algorithms are supported :

    aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

The following server-to-client Cipher Block Chaining (CBC) algorithms are supported :

    aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

## 153953 - SSH Weak Key Exchange Algorithms Enabled

### Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

### Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) RFC9142. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-\*

gss-group1-sha1-\*

gss-group14-sha1-\*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

### See Also

<https://datatracker.ietf.org/doc/html/rfc9142>

### Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

### Risk Factor

Low

### CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2021/10/13, Modified: 2026/01/12

## Plugin Output

---

tcp/22/ssh

The following weak key exchange algorithms are enabled :

```
diffie-hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1
diffie-hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1
```

## 71049 - SSH Weak MAC Algorithms Enabled

### Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

### Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

### Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

### Risk Factor

Low

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2013/11/22, Modified: 2026/01/12

### Plugin Output

tcp/22/ssh

```
The following client-to-server Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-
sha1-96,hmac-md5-96
```

```
The following server-to-client Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-
sha1-96,hmac-md5-96
```

## 83875 - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

### Synopsis

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits.

### Description

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party may be able to find the shared secret in a short amount of time (depending on modulus size and attacker resources). This may allow an attacker to recover the plaintext or potentially violate the integrity of connections.

### See Also

<https://weakdh.org/>

### Solution

Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

### Risk Factor

Low

### CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

### VPR Score

2.9

### EPSS Score

0.9374

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

### CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

## References

---

BID 74733  
CVE CVE-2015-4000  
XREF CEA-ID:CEA-2021-0004

## Plugin Information

---

Published: 2015/05/28, Modified: 2025/12/15

## Plugin Output

---

tcp/25/smtp

Vulnerable connection combinations :

SSL/TLS version : SSLv3  
Cipher suite : TLS1\_DHE\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA  
Diffie-Hellman MODP size (bits) : 512  
Logjam attack difficulty : Easy (could be carried out by individuals)

SSL/TLS version : SSLv3  
Cipher suite : TLS1\_DHE\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA  
Diffie-Hellman MODP size (bits) : 512  
Logjam attack difficulty : Easy (could be carried out by individuals)

SSL/TLS version : TLSv1.0  
Cipher suite : TLS1\_DHE\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA  
Diffie-Hellman MODP size (bits) : 512  
Logjam attack difficulty : Easy (could be carried out by individuals)

SSL/TLS version : TLSv1.0  
Cipher suite : TLS1\_DHE\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA  
Diffie-Hellman MODP size (bits) : 512  
Logjam attack difficulty : Easy (could be carried out by individuals)



## 83738 - SSL/TLS EXPORT\_DHE <= 512-bit Export Cipher Suites Supported (Logjam)

### Synopsis

The remote host supports a set of weak ciphers.

### Description

The remote host supports EXPORT\_DHE cipher suites with keys less than or equal to 512 bits. Through cryptanalysis, a third party can find the shared secret in a short amount of time.

A man-in-the-middle attacker may be able to downgrade the session to use EXPORT\_DHE cipher suites. Thus, it is recommended to remove support for weak cipher suites.

### See Also

<https://weakdh.org/>

### Solution

Reconfigure the service to remove support for EXPORT\_DHE cipher suites.

### Risk Factor

Low

### CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

### CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

### VPR Score

2.9

### EPSS Score

0.9374

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

### CVSS v2.0 Temporal Score

2.2 (CVSS2#E:U/RL:ND/RC:C)

## References

BID 74733  
CVE CVE-2015-4000  
XREF CEA-ID:CEA-2021-0004

## Plugin Information

Published: 2015/05/21, Modified: 2026/04/13

## Plugin Output

tcp/25/smtp

EXPORT\_DHE cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

| Name                                   | Code       | KEX | Auth | Encryption  | MAC |
|----------------------------------------|------------|-----|------|-------------|-----|
| -----                                  | -----      | --- | ---- | -----       | --- |
| EXP-EDH-RSA-DES-CBC-SHA<br>SHA1 export | 0x00, 0x14 | DHE | RSA  | DES-CBC(40) |     |
| EXP-ADH-DES-CBC-SHA<br>SHA1 export     | 0x00, 0x19 | DH  | None | DES-CBC(40) |     |
| EXP-ADH-RC4-MD5<br>export              | 0x00, 0x17 | DH  | None | RC4(40)     | MD5 |

The fields above are :

{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 78479 - SSLv3 Padding Oracle On Downgraded Legacy Encryption Vulnerability (POODLE)

### Synopsis

---

It is possible to obtain sensitive information from the remote host with SSL/TLS-enabled services.

### Description

---

The remote host is affected by a man-in-the-middle (MitM) information disclosure vulnerability known as POODLE. The vulnerability is due to the way SSL 3.0 handles padding bytes when decrypting messages encrypted using block ciphers in cipher block chaining (CBC) mode.

MitM attackers can decrypt a selected byte of a cipher text in as few as 256 tries if they are able to force a victim application to repeatedly send the same data over newly created SSL 3.0 connections.

As long as a client and service both support SSLv3, a connection can be 'rolled back' to SSLv3, even if TLSv1 or newer is supported by the client and service.

The TLS Fallback SCSV mechanism prevents 'version rollback' attacks without impacting legacy clients; however, it can only protect connections when the client and service support the mechanism. Sites that cannot disable SSLv3 immediately should enable this mechanism.

This is a vulnerability in the SSLv3 specification, not in any particular SSL implementation. Disabling SSLv3 is the only way to completely mitigate the vulnerability.

### See Also

---

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://tools.ietf.org/html/draft-ietf-tls-downgrade-scsv-00>

### Solution

---

Disable SSLv3.

Services that must support SSLv3 should enable the TLS Fallback SCSV mechanism until SSLv3 can be disabled.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

3.4 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:C/C:L/I:N/A:N)

### CVSS v3.0 Temporal Score

---

3.1 (CVSS:3.0/E:P/RL:O/RC:C)

#### VPR Score

---

4.9

#### EPSS Score

---

0.9402

#### CVSS v2.0 Base Score

---

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

#### CVSS v2.0 Temporal Score

---

3.4 (CVSS2#E:POC/RL:OF/RC:C)

#### References

---

|      |               |
|------|---------------|
| BID  | 70574         |
| CVE  | CVE-2014-3566 |
| XREF | CERT:577193   |

#### Plugin Information

---

Published: 2014/10/15, Modified: 2026/04/13

#### Plugin Output

---

tcp/25/smtp

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the Fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

## 78479 - SSLv3 Padding Oracle On Downgraded Legacy Encryption Vulnerability (POODLE)

### Synopsis

---

It is possible to obtain sensitive information from the remote host with SSL/TLS-enabled services.

### Description

---

The remote host is affected by a man-in-the-middle (MitM) information disclosure vulnerability known as POODLE. The vulnerability is due to the way SSL 3.0 handles padding bytes when decrypting messages encrypted using block ciphers in cipher block chaining (CBC) mode.

MitM attackers can decrypt a selected byte of a cipher text in as few as 256 tries if they are able to force a victim application to repeatedly send the same data over newly created SSL 3.0 connections.

As long as a client and service both support SSLv3, a connection can be 'rolled back' to SSLv3, even if TLSv1 or newer is supported by the client and service.

The TLS Fallback SCSV mechanism prevents 'version rollback' attacks without impacting legacy clients; however, it can only protect connections when the client and service support the mechanism. Sites that cannot disable SSLv3 immediately should enable this mechanism.

This is a vulnerability in the SSLv3 specification, not in any particular SSL implementation. Disabling SSLv3 is the only way to completely mitigate the vulnerability.

### See Also

---

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://tools.ietf.org/html/draft-ietf-tls-downgrade-scsv-00>

### Solution

---

Disable SSLv3.

Services that must support SSLv3 should enable the TLS Fallback SCSV mechanism until SSLv3 can be disabled.

### Risk Factor

---

Medium

### CVSS v3.0 Base Score

---

3.4 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:C/C:L/I:N/A:N)

### CVSS v3.0 Temporal Score

---

3.1 (CVSS:3.0/E:P/RL:O/RC:C)

#### VPR Score

---

4.9

#### EPSS Score

---

0.9402

#### CVSS v2.0 Base Score

---

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

#### CVSS v2.0 Temporal Score

---

3.4 (CVSS2#E:POC/RL:OF/RC:C)

#### References

---

|      |               |
|------|---------------|
| BID  | 70574         |
| CVE  | CVE-2014-3566 |
| XREF | CERT:577193   |

#### Plugin Information

---

Published: 2014/10/15, Modified: 2026/04/13

#### Plugin Output

---

tcp/5432/postgresql

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the Fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

## 10407 - X Server Detection

### Synopsis

An X11 server is listening on the remote host

### Description

The remote host is running an X11 server. X11 is a client-server protocol that can be used to display graphical applications running on a given host on a remote client.

Since the X11 traffic is not ciphered, it is possible for an attacker to eavesdrop on the connection.

### Solution

Restrict access to this port. If the X11 client/server facility is not used, disable TCP support in X11 entirely (-nolisten tcp).

### Risk Factor

Low

### CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

### Plugin Information

Published: 2000/05/12, Modified: 2019/03/05

### Plugin Output

tcp/6000/x11

```
X11 Version : 11.0
```

## 18261 - Apache Banner Linux Distribution Disclosure

### Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

### Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

### Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

### Risk Factor

None

### Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

### Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Ubuntu 8.04 (gutsy)
```



## 48204 - Apache HTTP Server Version

### Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

### Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

### See Also

<https://httpd.apache.org/>

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0530

### Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

### Plugin Output

tcp/80/www

```
URL      : http://172.30.2.101/
Version  : 2.2.8
Source   : Server: Apache/2.2.8 (Ubuntu) DAV/2
backported : 1
modules  : DAV/2
os       : Ubuntu
```

## 39446 - Apache Tomcat Detection

### Synopsis

The remote web server is an Apache Tomcat server.

### Description

Nessus was able to detect a remote Apache Tomcat web server.

NOTE: When paranoia levels are elevated, this plugin will also consider versions obtained from responses with non-200 HTTP status codes.

### See Also

<https://tomcat.apache.org/>

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0535

### Plugin Information

Published: 2009/06/18, Modified: 2026/01/22

### Plugin Output

tcp/8180/www

```
URL      : http://172.30.2.101:8180/
Version  : 5.5
backported : 0
source    : Apache Tomcat/5.5
```

## 39519 - Backported Security Patch Detection (FTP)

### Synopsis

Security patches are backported.

### Description

Security patches may have been 'backported' to the remote FTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

### See Also

[https://access.redhat.com/security/updates/backporting/?sc\\_cid=3093](https://access.redhat.com/security/updates/backporting/?sc_cid=3093)

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

### Plugin Output

tcp/2121/ftp

```
Give Nessus credentials to perform local checks.
```

## 84574 - Backported Security Patch Detection (PHP)

### Synopsis

Security patches have been backported.

### Description

Security patches may have been 'backported' to the remote PHP install without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

### See Also

[https://access.redhat.com/security/updates/backporting/?sc\\_cid=3093](https://access.redhat.com/security/updates/backporting/?sc_cid=3093)

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2015/07/07, Modified: 2024/11/22

### Plugin Output

tcp/80/www

```
Give Nessus credentials to perform local checks.
```

## 39520 - Backported Security Patch Detection (SSH)

### Synopsis

Security patches are backported.

### Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

### See Also

[https://access.redhat.com/security/updates/backporting/?sc\\_cid=3093](https://access.redhat.com/security/updates/backporting/?sc_cid=3093)

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

### Plugin Output

tcp/22/ssh

```
Give Nessus credentials to perform local checks.
```

## 39521 - Backported Security Patch Detection (WWW)

### Synopsis

Security patches are backported.

### Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

### See Also

[https://access.redhat.com/security/updates/backporting/?sc\\_cid=3093](https://access.redhat.com/security/updates/backporting/?sc_cid=3093)

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

### Plugin Output

tcp/80/www

```
Give Nessus credentials to perform local checks.
```

## 45590 - Common Platform Enumeration (CPE)

### Synopsis

It was possible to enumerate CPE names that matched on the remote system.

### Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

### See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

### Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.2.8 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:tomcat:5.5 -> Apache Software Foundation Tomcat
cpe:/a:isc:bind:9.4. -> ISC BIND
cpe:/a:isc:bind:9.4.2 -> ISC BIND
cpe:/a:mysql:mysql:5.0.51a-3ubuntu5 -> MySQL MySQL
cpe:/a:openbsd:openssh:4.7 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:4.7p1 -> OpenBSD OpenSSH
cpe:/a:php:php:5.2.4 -> PHP PHP
cpe:/a:php:php:5.2.4-2ubuntu5.10 -> PHP PHP
cpe:/a:postgresql:postgresql -> PostgreSQL
cpe:/a:samba:samba:3.0.20 -> Samba Samba
```

## 10028 - DNS Server BIND version Directive Remote Version Detection

### Synopsis

It is possible to obtain the version number of the remote DNS server.

### Description

The remote host is running BIND or another DNS server that reports its version number when it receives a special request for the text 'version.bind' in the domain 'chaos'.

This version is not necessarily accurate and could even be forged, as some DNS servers send the information based on a configuration file.

### Solution

It is possible to hide the version number of BIND by using the 'version' directive in the 'options' section in named.conf.

### Risk Factor

None

### References

XREF IAVT:0001-T-0583

### Plugin Information

Published: 1999/10/12, Modified: 2022/10/12

### Plugin Output

udp/53/dns

```
Version : 9.4.2
```



## 11002 - DNS Server Detection

### Synopsis

A DNS server is listening on the remote host.

### Description

The remote service is a Domain Name System (DNS) server, which provides a mapping between hostnames and IP addresses.

### See Also

[https://en.wikipedia.org/wiki/Domain\\_Name\\_System](https://en.wikipedia.org/wiki/Domain_Name_System)

### Solution

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

### Risk Factor

None

### Plugin Information

Published: 2003/02/13, Modified: 2017/05/16

### Plugin Output

tcp/53/dns

## 11002 - DNS Server Detection

### Synopsis

---

A DNS server is listening on the remote host.

### Description

---

The remote service is a Domain Name System (DNS) server, which provides a mapping between hostnames and IP addresses.

### See Also

---

[https://en.wikipedia.org/wiki/Domain\\_Name\\_System](https://en.wikipedia.org/wiki/Domain_Name_System)

### Solution

---

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

### Risk Factor

---

None

### Plugin Information

---

Published: 2003/02/13, Modified: 2017/05/16

### Plugin Output

---

udp/53/dns

## 72779 - DNS Server Version Detection

### Synopsis

Nessus was able to obtain version information on the remote DNS server.

### Description

Nessus was able to obtain version information by sending a special TXT record query to the remote host.

Note that this version is not necessarily accurate and could even be forged, as some DNS servers send the information based on a configuration file.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0937

### Plugin Information

Published: 2014/03/03, Modified: 2024/09/24

### Plugin Output

tcp/53/dns

```
DNS server answer for "version.bind" (over TCP) :
```

```
9.4.2
```

## 35371 - DNS Server hostname.bind Map Hostname Disclosure

### Synopsis

The DNS server discloses the remote host name.

### Description

It is possible to learn the remote host name by querying the remote DNS server for 'hostname.bind' in the CHAOS domain.

### Solution

It may be possible to disable this feature. Consult the vendor's documentation for more information.

### Risk Factor

None

### Plugin Information

Published: 2009/01/15, Modified: 2011/09/14

### Plugin Output

udp/53/dns

```
The remote host name is :  
metasploitable
```

## 54615 - Device Type

### Synopsis

It is possible to guess the remote device type.

### Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

### Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

## 35716 - Ethernet Card Manufacturer Detection

### Synopsis

The manufacturer can be identified from the Ethernet OUI.

### Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

### See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

### Plugin Output

tcp/0

```
The following card manufacturers were identified :
```

```
08:00:27:12:BA:36 : PCS Systemtechnik GmbH
```

## 86420 - Ethernet MAC Addresses

### Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

### Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

### Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 08:00:27:12:BA:36
```

## 10092 - FTP Server Detection

### Synopsis

An FTP server is listening on a remote port.

### Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

### Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

### Plugin Output

tcp/21/ftp

```
The remote FTP banner is :
```

```
220 (vsFTPd 2.3.4)
```



## 10092 - FTP Server Detection

### Synopsis

An FTP server is listening on a remote port.

### Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

### Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

### Plugin Output

tcp/2121/ftp

```
The remote FTP banner is :  
220 ProFTPD 1.3.1 Server (Debian) [::ffff:172.30.2.101]
```

## 10107 - HTTP Server Type and Version

### Synopsis

A web server is running on the remote host.

### Description

This plugin attempts to determine the type and the version of the remote web server.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0931

### Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

### Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.2.8 (Ubuntu) DAV/2
```

## 10107 - HTTP Server Type and Version

### Synopsis

A web server is running on the remote host.

### Description

This plugin attempts to determine the type and the version of the remote web server.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0931

### Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

### Plugin Output

tcp/8180/www

```
The remote web server type is :  
Apache-Coyote/1.1
```

## 24260 - HyperText Transfer Protocol (HTTP) Information

## Synopsis

Some information about the remote HTTP configuration can be extracted.

| Description |
|-------------|
|-------------|

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

### Solution

n/a

| Risk Factor                      | Impact                                                | Control                                               |
|----------------------------------|-------------------------------------------------------|-------------------------------------------------------|
| 1. Lack of industry connections  | Reduced sales and market penetration                  | Networking and strategic partnerships                 |
| 2. Limited marketing budget      | Low brand awareness and visibility                    | Targeted digital marketing and social media           |
| 3. Intense competition           | Price wars and reduced profit margins                 | Product differentiation and customer loyalty programs |
| 4. Economic downturn             | Reduced consumer spending and demand                  | Cost-cutting measures and flexible pricing            |
| 5. Technological obsolescence    | Loss of competitive edge and market share             | Continuous R&D and innovation                         |
| 6. Regulatory changes            | Increased compliance costs and operational challenges | Proactive legal and regulatory monitoring             |
| 7. Supply chain disruptions      | Increased costs and delayed deliveries                | Diversification of suppliers and inventory management |
| 8. Talent shortage               | Reduced productivity and innovation                   | Competitive compensation and employee development     |
| 9. Poor timing of product launch | Missed market opportunities and low initial sales     | Thorough market research and timing analysis          |
| 10. Inconsistent quality control | Customer dissatisfaction and reputational damage      | Strict quality assurance protocols                    |

None

### Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

### Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

```
HTTP/2 TLS Support: No
```

HTTP/2 Cleartext Support: No

SSL : no

```
Keep-Alive : yes
```

Options allowed : (Not implemented)

Headers :

Date: Fri, 15 May 2026 00:21:42 GMT

Server: Apache/2.2.8 (Ubuntu) DAV/2

X-Powered-By: PHP/5.2.4-2ubuntu5.10

Content-Length: 891

```
Keep-Alive: timeout=15, max=98
```

Connection: Keep-Alive

Content-Type: text/html

Response Body :

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>
```

|\_| |\_| |\_| \\_| \\_| \\_|, |\_| |\_| .\_| / |\_| \\_| / |\_| \\_| \\_|, |\_| .\_| / |\_| \\_| |\_| |\_|  
|\_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>
```

## 24260 - HyperText Transfer Protocol (HTTP) Information

### Synopsis

Some information about the remote HTTP configuration can be extracted.

### Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

### Plugin Output

tcp/8180/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : no

Options allowed : GET, HEAD, POST, PUT, DELETE, TRACE, OPTIONS

Headers :

Server: Apache-Coyote/1.1

Content-Type: text/html; charset=ISO-8859-1

Transfer-Encoding: chunked

Date: Fri, 15 May 2026 00:21:33 GMT

Response Body :

<!--

Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to You under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

```
-->
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
    "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">

<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
  <head>
    <title>Apache Tomcat/5.5</title>
    <style type="text/css">
/*<![CDATA[*]
    body {
      color: #000000;
      background-color: #FFFFFF;
font-family: Arial, "Times New Roman", Times, serif;
      margin: 10px 0px;
    }

    img {
      border: none;
    }

    a:link, a:visited {
      color: blue
    }

    th {
      font-family: Verdana, "Times New Roman", Times, serif;
      font-size: 110%;
      font-weight: normal;
      font-style: italic;
      background: #D2A41C;
      text-align: left;
    }

    td {
      color: #000000;
font-family: Arial, Helvetica, sans-serif;
    }

    [...]
```

## 11156 - IRC Daemon Version Detection

### Synopsis

The remote host is an IRC server.

### Description

This plugin determines the version of the IRC daemon.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/11/19, Modified: 2016/01/08

### Plugin Output

tcp/6667/irc

```
The IRC server version is : Unreal3.2.8.1. FhIXOoE [*=2309]
```



## 10397 - Microsoft Windows SMB LanMan Pipe Server Listing Disclosure

### Synopsis

It is possible to obtain network information.

### Description

It was possible to obtain the browse list of the remote Windows system by sending a request to the LANMAN pipe. The browse list is the list of the nearest Windows systems of the remote host.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

### Plugin Output

tcp/445/cifs

```
Here is the browse list of the remote host :
```

```
METASPLOITABLE ( os : 0.0 )  
VAGRANT-2008R2 ( os : 0.0 )
```

### Synopsis

---

It was possible to obtain information about the remote operating system.

### Description

---

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

### Solution

---

n/a

### Risk Factor

---

None

### Plugin Information

---

Published: 2001/10/17, Modified: 2021/09/20

### Plugin Output

---

tcp/445/cifs

```
The remote Operating System is : Unix
The remote native LAN manager is : Samba 3.0.20-Debian
The remote SMB Domain Name is : METASPLOITABLE
```

## 11011 - Microsoft Windows SMB Service Detection

### Synopsis

A file / print sharing service is listening on the remote host.

### Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

### Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

## 11011 - Microsoft Windows SMB Service Detection

### Synopsis

A file / print sharing service is listening on the remote host.

### Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

### Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

## 100871 - Microsoft Windows SMB Versions Supported (remote check)

### Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

### Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

### Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
SMBv1
```

## 106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

### Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

### Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

### Plugin Output

tcp/445/cifs

```
The remote host does NOT support the following SMB dialects :
__version__  __introduced in windows version__
2.0.2        Windows 2008
2.1          Windows 7
2.2.2        Windows 8 Beta
2.2.4        Windows 8 Beta
3.0          Windows 8
3.0.2        Windows 8.1
3.1          Windows 10
3.1.1        Windows 10
```

## 10719 - MySQL Server Detection

### Synopsis

A database server is listening on the remote port.

### Description

The remote host is running MySQL, an open source database server.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0802

### Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

### Plugin Output

tcp/3306/mysql

```
Service : mysql
Version : 5.0.51a-3ubuntu5
```

tcp/3306/mysql

```
Version : 5.0.51a-3ubuntu5
Protocol : 10
Server Status : SERVER_STATUS_AUTOCOMMIT
Server Capabilities :
  CLIENT_LONG_FLAG (Get all column flags)
  CLIENT_CONNECT_WITH_DB (One can specify db on connect)
  CLIENT_COMPRESS (Can use compression protocol)
  CLIENT_PROTOCOL_41 (New 4.1 protocol)
  CLIENT_SSL (Switch to SSL after handshake)
  CLIENT_TRANSACTIONS (Client knows about transactions)
  CLIENT_SECURE_CONNECTION (New 4.1 authentication)
```

## 10437 - NFS Share Export List

### Synopsis

The remote NFS server exports a list of shares.

### Description

This plugin retrieves the list of NFS exported shares.

### See Also

<http://www.tldp.org/HOWTO/NFS-HOWTO/security.html>

### Solution

Ensure each share is intended to be exported.

### Risk Factor

None

### Plugin Information

Published: 2000/06/07, Modified: 2019/10/04

### Plugin Output

tcp/2049/rpc-nfs

```
Here is the export list of 172.30.2.101 :
```

```
/ *
```



### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/21/ftp

```
Port 21/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/22/ssh

```
Port 22/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/23/telnet

```
Port 23/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/25/smtp

```
Port 25/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/53/dns

```
Port 53/tcp was found to be open
```

### Synopsis

It is possible to determine which TCP ports are open.

### Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

Protect your target with an IP filter.

### Risk Factor

None

### Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/111/rpc-portmapper

```
Port 111/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/139/smb

```
Port 139/tcp was found to be open
```



### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/445/cifs

```
Port 445/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/512

```
Port 512/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/513/rlogin

```
Port 513/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/514/rsh

```
Port 514/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/1099/rmi\_registry

```
Port 1099/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/1524/wild\_shell

```
Port 1524/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/2049/rpc-nfs

```
Port 2049/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/2121/ftp

```
Port 2121/tcp was found to be open
```



### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/3632

```
Port 3632/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/5432/postgresql

```
Port 5432/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/5900/vnc

```
Port 5900/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/6000/x11

```
Port 6000/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/6667/irc

```
Port 6667/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/8009

```
Port 8009/tcp was found to be open
```

### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/8180/www

```
Port 8180/tcp was found to be open
```



### Synopsis

---

It is possible to determine which TCP ports are open.

### Description

---

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

### Solution

---

Protect your target with an IP filter.

### Risk Factor

---

None

### Plugin Information

---

Published: 2009/02/04, Modified: 2025/07/14

### Plugin Output

---

tcp/8787

```
Port 8787/tcp was found to be open
```

## 19506 - Nessus Scan Information

### Synopsis

This plugin displays information about the Nessus scan.

### Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

### Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.0
Nessus build : 20184
Plugin feed version : 202605141537
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : debian10-x86-64
Scan type : Normal
Scan name : Metasploitable2 Vulnerability Scan
```

```
Scan policy used : Basic Network Scan
Scanner IP : 172.30.2.100
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 63.144 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/14 20:11 EDT (UTC -04:00)
Scan duration : 1233 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

## 209654 - OS Fingerprints Detected

### Synopsis

Multiple OS fingerprints were detected.

### Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

### Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 2.x on Red Hat Enterprise Linux Server  
Confidence level : 56  
Method : MLSinFP  
Type : unknown  
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (hardy)  
Confidence level : 95  
Method : SSH  
Type : general-purpose  
Fingerprint : SSH:SSH-2.0-OpenSSH\_4.7p1 Debian-8ubuntu1

Remote operating system : Linux Kernel 2.6  
Confidence level : 55  
Method : FTP  
Type : general-purpose  
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)  
Confidence level : 95  
Method : HTTP  
Type : general-purpose  
Fingerprint : unknown

Remote operating system : Unix  
Confidence level : 70

Method : smb  
Type : general-purpose  
Fingerprint : unknown

Remote operating system : Unix  
Confidence level : 45  
Method : MSRPC  
Type : general-purpose  
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6  
Palo Alto Networks PAN-OS  
Confidence level : 59  
Method : SinFP  
Type :

Fingerprint : SinFP:  
P1:B10113:F0x12:W5840:00204ffff:M1460:  
P2:B10113:F0x12:W5792:00204ffff0402080affffff4445414401030307:M1460:  
P3:B00000:F0x00:W0:00:M0  
P4:191800\_7\_p=2121

Following fingerprints could not be used to determine OS :  
SMTP:!:220 metasploitable.localdomain ESMTP Postfix (Ubuntu)  
SSLcert:!:i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple  
Affairss/CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple  
Affairs  
ed093088706603bfd5dc237399b498da2d4d31c6  
i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple Affairss/  
CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple Affairs  
ed093088706603bfd5dc237399b498da2d4d31c6

### Synopsis

It is possible to guess the remote operating system.

### Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

### Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
Confidence level : 95
Method : HTTP
```

Not all fingerprints could give a match. If you think that these signatures would help us improve OS fingerprinting, please submit them by visiting <https://www.tenable.com/research/submitsignatures>.

```
SSH:SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
```

```
SinFP:
```

```
P1:B10113:F0x12:W5840:00204ffff:M1460:
```

```
P2:B10113:F0x12:W5792:00204ffff0402080affffffff4445414401030307:M1460:
```

```
P3:B00000:F0x00:W0:00:M0
```

```
P4:191800_7_p=2121
```

```
SMTP:!:220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
```

```
SSLcert:!:i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple
Affairss/CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple
Affairs
```

```
ed093088706603bfd5dc237399b498da2d4d31c6
```

```
i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple Affairs/
CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple Affairs
```

```
ed093088706603bfd5dc237399b498da2d4d31c6
```

The remote host is running Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)

## 117886 - OS Security Patch Assessment Not Available

### Synopsis

OS Security Patch Assessment is not available.

### Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVB:0001-B-0515

### Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

### Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SSH service.
```

## 181418 - OpenSSH Detection

### Synopsis

An OpenSSH-based SSH server was detected on the remote host.

### Description

An OpenSSH-based SSH server was detected on the remote host.

### See Also

<https://www.openssh.com/>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2023/09/14, Modified: 2026/05/05

### Plugin Output

tcp/22/ssh

```
Service      : ssh
Version      : 4.7p1
Banner       : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
backported   : 1
```



## 50845 - OpenSSL Detection

### Synopsis

---

The remote service appears to use OpenSSL to encrypt traffic.

### Description

---

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

### See Also

---

<https://www.openssl.org/>

### Solution

---

n/a

### Risk Factor

---

None

### Plugin Information

---

Published: 2010/11/30, Modified: 2020/06/12

### Plugin Output

---

tcp/25/smtp

## 50845 - OpenSSL Detection

### Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

### Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

### See Also

<https://www.openssl.org/>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

### Plugin Output

tcp/5432/postgresql

## 48243 - PHP Version Detection

### Synopsis

It was possible to obtain the version number of the remote PHP installation.

### Description

Nessus was able to determine the version of PHP available on the remote web server.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0936

### Plugin Information

Published: 2010/08/04, Modified: 2026/01/22

### Plugin Output

tcp/80/www

```
Nessus was able to identify the following PHP version information :
```

```
Version : 5.2.4-2ubuntu5.10  
Source  : X-Powered-By: PHP/5.2.4-2ubuntu5.10  
Backported : 1
```

### Synopsis

The remote host is missing several patches.

### Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

### Solution

Install the patches listed below.

### Risk Factor

None

### Plugin Information

Published: 2013/07/08, Modified: 2026/05/12

### Plugin Output

tcp/0

```
. You need to take the following 3 actions :
```

```
[ ISC BIND 9.x < 9.11.22, 9.12.x < 9.16.6, 9.17.x < 9.17.4 DoS (139915) ]
```

```
+ Action to take : Upgrade to BIND 9.11.22, 9.16.6, 9.17.4 or later.
```

```
+Impact : Taking this action will resolve 3 different vulnerabilities (CVEs).
```

```
[ Samba Badlock Vulnerability (90509) ]
```

```
+ Action to take : Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.
```

```
[ UnrealIRCd Backdoor Detection (46882) ]
```

```
+ Action to take : Re-download the software, verify it using the published MD5 / SHA1 checksums, and re-install it.
```

## 118224 - PostgreSQL STARTTLS Support

### Synopsis

The remote service supports encrypting traffic.

### Description

The remote PostgreSQL server supports the use of encryption initiated during pre-login to switch from a cleartext to an encrypted communications channel.

### See Also

<https://www.postgresql.org/docs/9.2/protocol-flow.html#AEN96066>

<https://www.postgresql.org/docs/9.2/protocol-message-formats.html>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2018/10/19, Modified: 2022/04/11

### Plugin Output

tcp/5432/postgresql

```
Here is the PostgreSQL's SSL certificate that Nessus
was able to collect after sending a pre-login packet :
```

```
----- snip -----
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
```

```
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
             7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
             73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
             D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
             8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
             98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
             00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
           0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
           1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
           68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
           83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
           A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
           15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]
```

## 26024 - PostgreSQL Server Detection

### Synopsis

A database service is listening on the remote host.

### Description

The remote service is a PostgreSQL database server, or a derivative such as EnterpriseDB.

### See Also

<https://www.postgresql.org/>

### Solution

Limit incoming traffic to this port if desired.

### Risk Factor

None

### Plugin Information

Published: 2007/09/14, Modified: 2025/09/24

### Plugin Output

tcp/5432/postgresql

```
Service : postgresql
Version : unknown
```

## 22227 - RMI Registry Detection

### Synopsis

An RMI registry is listening on the remote host.

### Description

The remote host is running an RMI registry, which acts as a bootstrap naming service for registering and retrieving remote objects with simple names in the Java Remote Method Invocation (RMI) system.

### See Also

<https://docs.oracle.com/javase/1.5.0/docs/guide/rmi/spec/rmiTOC.html>

<http://www.nessus.org/u?b6fd7659>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2006/08/16, Modified: 2025/03/19

### Plugin Output

tcp/1099/rmi\_registry  
tcp/1099/rmi\_registry

```
Valid response received for port 1099:
0x00:  51 AC ED 00 05 77 0F 01 A4 CE 42 63 00 00 01 9E   Q....w....Bc....
0x10:  29 04 51 18 80 02 75 72 00 13 5B 4C 6A 61 76 61   ).Q...ur..[Ljava
0x20:  2E 6C 61 6E 67 2E 53 74 72 69 6E 67 3B AD D2 56   .lang.String;..V
0x30:  E7 E9 1D 7B 47 02 00 00 70 78 70 00 00 00 00     ...{G...xp....
```



## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

tcp/111/rpc-portmapper

```
The following RPC services are available on TCP port 111 :  
- program: 100000 (portmapper), version: 2
```

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

udp/111/rpc-portmapper

```
The following RPC services are available on UDP port 111 :  
- program: 100000 (portmapper), version: 2
```

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

tcp/2049/rpc-nfs

```
The following RPC services are available on TCP port 2049 :
```

- program: 100003 (nfs), version: 2
- program: 100003 (nfs), version: 3
- program: 100003 (nfs), version: 4

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

udp/2049/rpc-nfs

```
The following RPC services are available on UDP port 2049 :
```

- program: 100003 (nfs), version: 2
- program: 100003 (nfs), version: 3
- program: 100003 (nfs), version: 4

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

tcp/37121/rpc-status

```
The following RPC services are available on TCP port 37121 :  
- program: 100024 (status), version: 1
```

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

udp/38454/rpc-status

```
The following RPC services are available on UDP port 38454 :  
- program: 100024 (status), version: 1
```

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

tcp/39810/rpc-mountd

```
The following RPC services are available on TCP port 39810 :
```

- program: 100005 (mountd), version: 1
- program: 100005 (mountd), version: 2
- program: 100005 (mountd), version: 3

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

udp/49002/rpc-nlockmgr

```
The following RPC services are available on UDP port 49002 :
```

- program: 100021 (nlockmgr), version: 1
- program: 100021 (nlockmgr), version: 3
- program: 100021 (nlockmgr), version: 4



## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

tcp/51558/rpc-nlockmgr

```
The following RPC services are available on TCP port 51558 :
```

- program: 100021 (nlockmgr), version: 1
- program: 100021 (nlockmgr), version: 3
- program: 100021 (nlockmgr), version: 4

## 11111 - RPC Services Enumeration

### Synopsis

An ONC RPC service is running on the remote host.

### Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

### Plugin Output

udp/58099/rpc-mountd

```
The following RPC services are available on UDP port 58099 :
```

- program: 100005 (mountd), version: 1
- program: 100005 (mountd), version: 2
- program: 100005 (mountd), version: 3

## 53335 - RPC portmapper (TCP)

### Synopsis

An ONC RPC portmapper is running on the remote host.

### Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/04/08, Modified: 2011/08/29

### Plugin Output

tcp/111/rpc-portmapper

## 10223 - RPC portmapper Service Detection

### Synopsis

An ONC RPC portmapper is running on the remote host.

### Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

### Solution

n/a

### Risk Factor

None

### CVSS v3.0 Base Score

0.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N)

### CVSS v2.0 Base Score

0.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:N)

### References

CVE CVE-1999-0632

### Plugin Information

Published: 1999/08/19, Modified: 2019/10/04

### Plugin Output

udp/111/rpc-portmapper

## 277650 - Remote Services Not Using Post-Quantum Ciphers

### Synopsis

Reports remote services that do not offer post-quantum ciphers.

### Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

### See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

### Plugin Output

tcp/22/ssh

```
The target SSH server offers no post-quantum ciphers.
```

## 277650 - Remote Services Not Using Post-Quantum Ciphers

### Synopsis

Reports remote services that do not offer post-quantum ciphers.

### Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

### See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

### Plugin Output

tcp/25/smtp

```
The target TLS server offers no post-quantum ciphers.
```

## 277650 - Remote Services Not Using Post-Quantum Ciphers

### Synopsis

Reports remote services that do not offer post-quantum ciphers.

### Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

### See Also

<http://www.nessus.org/u?7a390f87>  
<http://www.nessus.org/u?ad7d6b3b>  
<http://www.nessus.org/u?1c0c61e0>  
<http://www.nessus.org/u?5eec4b28>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

### Plugin Output

tcp/5432/postgresql

```
The target TLS server offers no post-quantum ciphers.
```

## 10263 - SMTP Server Detection

### Synopsis

An SMTP server is listening on the remote port.

### Description

The remote host is running a mail (SMTP) server on this port.

Since SMTP servers are the targets of spammers, it is recommended you disable it if you do not use it.

### Solution

Disable this service if you do not use it, or filter incoming traffic to this port.

### Risk Factor

None

### References

XREF IAVT:0001-T-0932

### Plugin Information

Published: 1999/10/12, Modified: 2020/09/22

### Plugin Output

tcp/25/smtp

```
Remote SMTP server banner :  
220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
```



## 42088 - SMTP Service STARTTLS Command Support

### Synopsis

The remote mail service supports encrypting traffic.

### Description

The remote SMTP service supports the use of the 'STARTTLS' command to switch from a cleartext to an encrypted communications channel.

### See Also

<https://en.wikipedia.org/wiki/STARTTLS>

<https://tools.ietf.org/html/rfc2487>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2009/10/09, Modified: 2019/03/20

### Plugin Output

tcp/25/smtp

```
Here is the SMTP service's SSL certificate that Nessus was able to
collect after sending a 'STARTTLS' command :
```

```
----- snip -----
```

```
Subject Name:
```

```
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain
```

```
Issuer Name:
```

```
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
```

```
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
             7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
             73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
             D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
             8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
             98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
             00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
           0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
           1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
           68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
           83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
           A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
           15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]
```

## 70657 - SSH Algorithms and Languages Supported

### Synopsis

An SSH server is listening on this port.

### Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

### Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ssh-dss
ssh-rsa
```

```
The server supports the following options for encryption_algorithms_client_to_server :
```

```
3des-cbc
aes128-cbc
```

```
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The server supports the following options for `mac_algorithms_server_to_client` :

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

The server supports the following options for `kex_algorithms` :

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
```

The server supports the following options for `compression_algorithms_client_to_server` :

```
none
zlib@openssh.com
```

The server supports the following options for `encryption_algorithms_server_to_client` :

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

## 149334 - SSH Password Authentication Accepted

### Synopsis

The SSH server on the remote host accepts password authentication.

### Description

The SSH server on the remote host accepts password authentication.

### See Also

<https://tools.ietf.org/html/rfc4252#section-8>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

### Plugin Output

tcp/22/ssh

## 10881 - SSH Protocol Versions Supported

### Synopsis

A SSH server is running on the remote host.

### Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

### Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :
```

- 1.99
- 2.0

## 153588 - SSH SHA-1 HMAC Algorithms Enabled

### Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

### Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

### Plugin Output

tcp/22/ssh

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
    hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

```
The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
    hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

## 10267 - SSH Server Type and Version Information

### Synopsis

An SSH server is listening on this port.

### Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0933

### Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

### Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
SSH supported authentication : publickey,password
```



## 56984 - SSL / TLS Versions Supported

### Synopsis

The remote service encrypts communications.

### Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

### Plugin Output

tcp/25/smtp

```
This port supports SSLv2/SSLv3/TLSv1.0.
```

## 56984 - SSL / TLS Versions Supported

### Synopsis

The remote service encrypts communications.

### Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

### Plugin Output

tcp/5432/postgresql

```
This port supports SSLv3/TLSv1.0.
```

## 45410 - SSL Certificate 'commonName' Mismatch

### Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

### Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

### Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

### Risk Factor

None

### Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

### Plugin Output

tcp/25/smtp

```
The host name known by Nessus is :
```

```
metasploitable
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

## 45410 - SSL Certificate 'commonName' Mismatch

### Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

### Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

### Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

### Risk Factor

None

### Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

### Plugin Output

tcp/5432/postgresql

```
The host name known by Nessus is :
```

```
metasploitable
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

## 10863 - SSL Certificate Information

### Synopsis

This plugin displays the SSL certificate.

### Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

### Plugin Output

tcp/25/smtp

```
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
```

```
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
            7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
            73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
            D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
            8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
            98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
            00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
            0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
            1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
            68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
            83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
            A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
            15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
                    83 0C 7A F1 E3 2D EE 43 6D E8 13 CC
SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]
```

## 10863 - SSL Certificate Information

### Synopsis

This plugin displays the SSL certificate.

### Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

### Plugin Output

tcp/5432/postgresql

```
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
```

```
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
            7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
            73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
            D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
            8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
            98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
            00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
            0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
            1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
            68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
            83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
            A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
            15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
                    83 0C 7A F1 E3 2D EE 43 6D E8 13 CC
SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]
```



## 70544 - SSL Cipher Block Chaining Cipher Suites Supported

### Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

### Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

### See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

### Plugin Output

tcp/25/smtp

Here is the list of SSL CBC ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

| Name                    | Code             | KEX | Auth | Encryption  | MAC |
|-------------------------|------------------|-----|------|-------------|-----|
| -----                   | -----            | --- | ---- | -----       | --- |
| EXP-RC2-CBC-MD5         | 0x04, 0x00, 0x80 | RSA | RSA  | RC2-CBC(40) | MD5 |
| export                  |                  |     |      |             |     |
| EXP-EDH-RSA-DES-CBC-SHA | 0x00, 0x14       | DHE | RSA  | DES-CBC(40) |     |
| SHA1 export             |                  |     |      |             |     |
| EDH-RSA-DES-CBC-SHA     | 0x00, 0x15       | DHE | RSA  | DES-CBC(56) |     |
| SHA1                    |                  |     |      |             |     |
| EXP-ADH-DES-CBC-SHA     | 0x00, 0x19       | DH  | None | DES-CBC(40) |     |
| SHA1 export             |                  |     |      |             |     |
| ADH-DES-CBC-SHA         | 0x00, 0x1A       | DH  | None | DES-CBC(56) |     |
| SHA1                    |                  |     |      |             |     |

|                           |            |     |     |             |     |
|---------------------------|------------|-----|-----|-------------|-----|
| EXP-DES-CBC-SHA<br>SHA1   | 0x00, 0x08 | RSA | RSA | DES-CBC(40) |     |
| export                    |            |     |     |             |     |
| EXP-RC2-CBC-MD5<br>export | 0x00, 0x06 | RSA | RSA | RC2-CBC(40) | MD5 |
| DES-CBC-SHA<br>SHA1       | 0x00, 0x09 | RSA | RSA | DES-CBC(56) |     |

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                         | Code             | KEX | Auth | Encryption    | MAC |
|------------------------------|------------------|-----|------|---------------|-----|
| -----                        | -----            | --- | ---- | -----         | --- |
| DES-CBC3-MD5                 | 0x07, 0x00, 0xC0 | RSA | RSA  | 3DES-CBC(168) | MD5 |
| EDH-RSA-DES-CBC3-SHA<br>SHA1 | 0x00, 0x16       | DHE | RSA  | 3DES-CBC(168) |     |
| ADH-DES-CBC3-SHA<br>SHA1     | 0x00, 0x1B       | DH  | None | 3DES-CBC(168) |     |
| DES-CBC3-SHA<br>SHA1         | 0x00, 0x0A       | RSA | RSA  | 3DES-CBC(168) |     |

High Strength Ciphers (>= 112-bit key)

| Name  | Code        | KEX | Auth | Encryption | MAC |
|-------|-------------|-----|------|------------|-----|
| ----- | ----- [...] |     |      |            |     |

## 70544 - SSL Cipher Block Chaining Cipher Suites Supported

### Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

### Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

### See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

### Plugin Output

tcp/5432/postgresql

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                 | Code       | KEX | Auth | Encryption     | MAC |
|----------------------|------------|-----|------|----------------|-----|
| -----                | -----      | --- | ---- | -----          | --- |
| EDH-RSA-DES-CBC3-SHA | 0x00, 0x16 | DHE | RSA  | 3DES-CBC (168) |     |
| SHA1                 |            |     |      |                |     |
| DES-CBC3-SHA         | 0x00, 0x0A | RSA | RSA  | 3DES-CBC (168) |     |
| SHA1                 |            |     |      |                |     |

High Strength Ciphers (>= 112-bit key)

| Name               | Code       | KEX | Auth | Encryption    | MAC |
|--------------------|------------|-----|------|---------------|-----|
| -----              | -----      | --- | ---- | -----         | --- |
| DHE-RSA-AES128-SHA | 0x00, 0x33 | DHE | RSA  | AES-CBC (128) |     |
| SHA1               |            |     |      |               |     |

|                    |            |     |     |              |
|--------------------|------------|-----|-----|--------------|
| DHE-RSA-AES256-SHA | 0x00, 0x39 | DHE | RSA | AES-CBC(256) |
| SHA1               |            |     |     |              |
| AES128-SHA         | 0x00, 0x2F | RSA | RSA | AES-CBC(128) |
| SHA1               |            |     |     |              |
| AES256-SHA         | 0x00, 0x35 | RSA | RSA | AES-CBC(256) |
| SHA1               |            |     |     |              |

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

## 21643 - SSL Cipher Suites Supported

### Synopsis

The remote service encrypts communications using SSL.

### Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

### See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

### Plugin Output

tcp/25/smtp

```
Here is the list of SSL ciphers supported by the remote server :  
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1
```

```
Low Strength Ciphers (<= 64-bit key)
```

| Name                    | Code       | KEX | Auth | Encryption   | MAC |
|-------------------------|------------|-----|------|--------------|-----|
| EXP-EDH-RSA-DES-CBC-SHA | 0x00, 0x14 | DHE | RSA  | DES-CBC (40) |     |
| SHA1 export             |            |     |      |              |     |
| EDH-RSA-DES-CBC-SHA     | 0x00, 0x15 | DHE | RSA  | DES-CBC (56) |     |
| SHA1                    |            |     |      |              |     |
| EXP-ADH-DES-CBC-SHA     | 0x00, 0x19 | DH  | None | DES-CBC (40) |     |
| SHA1 export             |            |     |      |              |     |
| EXP-ADH-RC4-MD5         | 0x00, 0x17 | DH  | None | RC4 (40)     | MD5 |
| export                  |            |     |      |              |     |
| ADH-DES-CBC-SHA         | 0x00, 0x1A | DH  | None | DES-CBC (56) |     |
| SHA1                    |            |     |      |              |     |
| EXP-DES-CBC-SHA         | 0x00, 0x08 | RSA | RSA  | DES-CBC (40) |     |
| SHA1 export             |            |     |      |              |     |
| EXP-RC2-CBC-MD5         | 0x00, 0x06 | RSA | RSA  | RC2-CBC (40) | MD5 |
| export                  |            |     |      |              |     |

|                       |            |     |     |              |     |
|-----------------------|------------|-----|-----|--------------|-----|
| EXP-RC4-MD5<br>export | 0x00, 0x03 | RSA | RSA | RC4 (40)     | MD5 |
| DES-CBC-SHA<br>SHA1   | 0x00, 0x09 | RSA | RSA | DES-CBC (56) |     |

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                         | Code       | KEX | Auth | Encryption     | MAC |
|------------------------------|------------|-----|------|----------------|-----|
| -----                        | -----      | --- | ---- | -----          | --- |
| EDH-RSA-DES-CBC3-SHA<br>SHA1 | 0x00, 0x16 | DHE | RSA  | 3DES-CBC (168) |     |
| ADH-DES-CBC3-SHA<br>SHA1     | 0x00, 0x1B | DH  | None | 3DES-CBC (168) |     |
| DES-CBC3-SHA<br>SHA1         | 0x00, 0x0A | RSA | RSA  | 3DES-CBC (168) |     |

High Strength Ciphers (>= 112-bit key)

| Name | Code | KEX | Auth | [...] |
|------|------|-----|------|-------|
|------|------|-----|------|-------|

## 21643 - SSL Cipher Suites Supported

### Synopsis

The remote service encrypts communications using SSL.

### Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

### See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffcd>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

### Plugin Output

tcp/5432/postgresql

```
Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1
```

```
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)
```

| Name                 | Code       | KEX | Auth | Encryption     | MAC |
|----------------------|------------|-----|------|----------------|-----|
| -----                | -----      | --- | ---  | -----          | --- |
| EDH-RSA-DES-CBC3-SHA | 0x00, 0x16 | DHE | RSA  | 3DES-CBC (168) |     |
| SHA1                 |            |     |      |                |     |
| DES-CBC3-SHA         | 0x00, 0x0A | RSA | RSA  | 3DES-CBC (168) |     |
| SHA1                 |            |     |      |                |     |

```
High Strength Ciphers (>= 112-bit key)
```

| Name               | Code       | KEX | Auth | Encryption    | MAC |
|--------------------|------------|-----|------|---------------|-----|
| -----              | -----      | --- | ---  | -----         | --- |
| DHE-RSA-AES128-SHA | 0x00, 0x33 | DHE | RSA  | AES-CBC (128) |     |
| SHA1               |            |     |      |               |     |
| DHE-RSA-AES256-SHA | 0x00, 0x39 | DHE | RSA  | AES-CBC (256) |     |
| SHA1               |            |     |      |               |     |
| AES128-SHA         | 0x00, 0x2F | RSA | RSA  | AES-CBC (128) |     |
| SHA1               |            |     |      |               |     |

|            |            |     |     |              |
|------------|------------|-----|-----|--------------|
| AES256-SHA | 0x00, 0x35 | RSA | RSA | AES-CBC(256) |
| SHA1       |            |     |     |              |
| RC4-SHA    | 0x00, 0x05 | RSA | RSA | RC4(128)     |
| SHA1       |            |     |     |              |

SSL Version : SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                 | Code       | KEX | Auth | Encryption    | MAC |
|----------------------|------------|-----|------|---------------|-----|
| -----                | -----      | --- | ---- | -----         | --- |
| EDH-RSA-DES-CBC3-SHA | 0x00, 0x16 | DHE | RSA  | 3DES-CBC(168) |     |
| SHA1                 |            |     |      |               |     |
| DES-CBC3-SHA         | 0x00, 0x0A | RSA | RSA  | 3DES-CBC(168) |     |
| SHA1                 |            |     |      |               |     |

High Strength Ciphers (>= 112-bit key)

| Name  | Code  | KEX | Auth  | Encryption | MAC |
|-------|-------|-----|-------|------------|-----|
| ----- | ----- | --- | [...] |            |     |



## 62563 - SSL Compression Methods Supported

### Synopsis

The remote service supports one or more compression methods for SSL connections.

### Description

This script detects which compression methods are supported by the remote service for SSL connections.

### See Also

<http://www.iana.org/assignments/comp-meth-ids/comp-meth-ids.xml>

<https://tools.ietf.org/html/rfc3749>

<https://tools.ietf.org/html/rfc3943>

<https://tools.ietf.org/html/rfc5246>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2012/10/16, Modified: 2022/04/11

### Plugin Output

tcp/25/smtp

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
DEFLATE (0x01)
```

## 62563 - SSL Compression Methods Supported

### Synopsis

The remote service supports one or more compression methods for SSL connections.

### Description

This script detects which compression methods are supported by the remote service for SSL connections.

### See Also

<http://www.iana.org/assignments/comp-meth-ids/comp-meth-ids.xml>

<https://tools.ietf.org/html/rfc3749>

<https://tools.ietf.org/html/rfc3943>

<https://tools.ietf.org/html/rfc5246>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2012/10/16, Modified: 2022/04/11

### Plugin Output

tcp/5432/postgresql

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
DEFLATE (0x01)
```

## 57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

### Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

### Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

### See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

[https://en.wikipedia.org/wiki/Diffie-Hellman\\_key\\_exchange](https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange)

[https://en.wikipedia.org/wiki/Perfect\\_forward\\_secrecy](https://en.wikipedia.org/wiki/Perfect_forward_secrecy)

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

### Plugin Output

tcp/25/smtp

Here is the list of SSL PFS ciphers supported by the remote server :

#### Low Strength Ciphers (<= 64-bit key)

| Name                    | Code       | KEX | Auth | Encryption  | MAC |
|-------------------------|------------|-----|------|-------------|-----|
| -----                   | -----      | --- | ---- | -----       | --- |
| EXP-EDH-RSA-DES-CBC-SHA | 0x00, 0x14 | DHE | RSA  | DES-CBC(40) |     |
| SHA1 export             |            |     |      |             |     |
| EDH-RSA-DES-CBC-SHA     | 0x00, 0x15 | DHE | RSA  | DES-CBC(56) |     |
| SHA1                    |            |     |      |             |     |

#### Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                 | Code       | KEX | Auth | Encryption    | MAC |
|----------------------|------------|-----|------|---------------|-----|
| -----                | -----      | --- | ---- | -----         | --- |
| EDH-RSA-DES-CBC3-SHA | 0x00, 0x16 | DHE | RSA  | 3DES-CBC(168) |     |
| SHA1                 |            |     |      |               |     |

#### High Strength Ciphers (>= 112-bit key)

| Name                       | Code       | KEX | Auth | Encryption   | MAC |
|----------------------------|------------|-----|------|--------------|-----|
| -----                      | -----      | --- | ---- | -----        | --- |
| DHE-RSA-AES128-SHA<br>SHA1 | 0x00, 0x33 | DHE | RSA  | AES-CBC(128) |     |
| DHE-RSA-AES256-SHA<br>SHA1 | 0x00, 0x39 | DHE | RSA  | AES-CBC(256) |     |

The fields above are :

{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}

## 57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

### Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

### Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

### See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

[https://en.wikipedia.org/wiki/Diffie-Hellman\\_key\\_exchange](https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange)

[https://en.wikipedia.org/wiki/Perfect\\_forward\\_secrecy](https://en.wikipedia.org/wiki/Perfect_forward_secrecy)

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

### Plugin Output

tcp/5432/postgresql

Here is the list of SSL PFS ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                         | Code       | KEX | Auth | Encryption    | MAC |
|------------------------------|------------|-----|------|---------------|-----|
| -----                        | -----      | --- | ---- | -----         | --- |
| EDH-RSA-DES-CBC3-SHA<br>SHA1 | 0x00, 0x16 | DHE | RSA  | 3DES-CBC(168) |     |

High Strength Ciphers (>= 112-bit key)

| Name                       | Code       | KEX | Auth | Encryption   | MAC |
|----------------------------|------------|-----|------|--------------|-----|
| -----                      | -----      | --- | ---- | -----        | --- |
| DHE-RSA-AES128-SHA<br>SHA1 | 0x00, 0x33 | DHE | RSA  | AES-CBC(128) |     |
| DHE-RSA-AES256-SHA<br>SHA1 | 0x00, 0x39 | DHE | RSA  | AES-CBC(256) |     |

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

## 51891 - SSL Session Resume Supported

### Synopsis

The remote host allows resuming SSL sessions.

### Description

This script detects whether a host allows resuming SSL sessions by performing a full SSL handshake to receive a session ID, and then reconnecting with the previously used session ID. If the server accepts the session ID in the second connection, the server maintains a cache of sessions that can be resumed.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/02/07, Modified: 2026/04/13

### Plugin Output

tcp/25/smtp

```
This port supports resuming SSLv3 sessions.
```

## 156899 - SSL/TLS Recommended Cipher Suites

### Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

### Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13\_AES\_128\_GCM\_SHA256
- 0x13,0x02 TLS13\_AES\_256\_GCM\_SHA384
- 0x13,0x03 TLS13\_CHACHA20\_POLY1305\_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

### See Also

[https://wiki.mozilla.org/Security/Server\\_Side\\_TLS](https://wiki.mozilla.org/Security/Server_Side_TLS)

<https://ssl-config.mozilla.org/>

### Solution

Only enable support for recommended cipher suites.

### Risk Factor

None

### Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

### Plugin Output

tcp/25/smtp



The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

#### Low Strength Ciphers (<= 64-bit key)

| Name                                   | Code             | KEX | Auth | Encryption  | MAC |
|----------------------------------------|------------------|-----|------|-------------|-----|
| -----                                  | -----            | --- | ---- | -----       | --- |
| EXP-RC2-CBC-MD5<br>export              | 0x04, 0x00, 0x80 | RSA | RSA  | RC2-CBC(40) | MD5 |
| EXP-RC4-MD5<br>export                  | 0x02, 0x00, 0x80 | RSA | RSA  | RC4(40)     | MD5 |
| EXP-EDH-RSA-DES-CBC-SHA<br>SHA1 export | 0x00, 0x14       | DHE | RSA  | DES-CBC(40) |     |
| EDH-RSA-DES-CBC-SHA<br>SHA1            | 0x00, 0x15       | DHE | RSA  | DES-CBC(56) |     |
| EXP-ADH-DES-CBC-SHA<br>SHA1 export     | 0x00, 0x19       | DH  | None | DES-CBC(40) |     |
| EXP-ADH-RC4-MD5<br>export              | 0x00, 0x17       | DH  | None | RC4(40)     | MD5 |
| ADH-DES-CBC-SHA<br>SHA1                | 0x00, 0x1A       | DH  | None | DES-CBC(56) |     |
| EXP-DES-CBC-SHA<br>SHA1 export         | 0x00, 0x08       | RSA | RSA  | DES-CBC(40) |     |
| EXP-RC2-CBC-MD5<br>export              | 0x00, 0x06       | RSA | RSA  | RC2-CBC(40) | MD5 |
| EXP-RC4-MD5<br>export                  | 0x00, 0x03       | RSA | RSA  | RC4(40)     | MD5 |
| DES-CBC-SHA<br>SHA1                    | 0x00, 0x09       | RSA | RSA  | DES-CBC(56) |     |

#### Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                         | Code             | KEX | Auth | Encryption    | MAC |
|------------------------------|------------------|-----|------|---------------|-----|
| -----                        | -----            | --- | ---- | -----         | --- |
| DES-CBC3-MD5                 | 0x07, 0x00, 0xC0 | RSA | RSA  | 3DES-CBC(168) | MD5 |
| EDH-RSA-DES-CBC3-SHA<br>SHA1 | 0x00, 0x16       | DHE | RSA  | 3DES-CBC(168) |     |
| ADH-DE [...]                 |                  |     |      |               |     |

## 156899 - SSL/TLS Recommended Cipher Suites

### Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

### Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13\_AES\_128\_GCM\_SHA256
- 0x13,0x02 TLS13\_AES\_256\_GCM\_SHA384
- 0x13,0x03 TLS13\_CHACHA20\_POLY1305\_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

### See Also

[https://wiki.mozilla.org/Security/Server\\_Side\\_TLS](https://wiki.mozilla.org/Security/Server_Side_TLS)

<https://ssl-config.mozilla.org/>

### Solution

Only enable support for recommended cipher suites.

### Risk Factor

None

### Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

### Plugin Output

tcp/5432/postgresql

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

| Name                 | Code       | KEX | Auth | Encryption    | MAC |
|----------------------|------------|-----|------|---------------|-----|
| -----                | -----      | --- | ---- | -----         | --- |
| EDH-RSA-DES-CBC3-SHA | 0x00, 0x16 | DHE | RSA  | 3DES-CBC(168) |     |
| SHA1                 |            |     |      |               |     |
| DES-CBC3-SHA         | 0x00, 0x0A | RSA | RSA  | 3DES-CBC(168) |     |
| SHA1                 |            |     |      |               |     |

High Strength Ciphers (>= 112-bit key)

| Name               | Code       | KEX | Auth | Encryption   | MAC |
|--------------------|------------|-----|------|--------------|-----|
| -----              | -----      | --- | ---- | -----        | --- |
| DHE-RSA-AES128-SHA | 0x00, 0x33 | DHE | RSA  | AES-CBC(128) |     |
| SHA1               |            |     |      |              |     |
| DHE-RSA-AES256-SHA | 0x00, 0x39 | DHE | RSA  | AES-CBC(256) |     |
| SHA1               |            |     |      |              |     |
| AES128-SHA         | 0x00, 0x2F | RSA | RSA  | AES-CBC(128) |     |
| SHA1               |            |     |      |              |     |
| AES256-SHA         | 0x00, 0x35 | RSA | RSA  | AES-CBC(256) |     |
| SHA1               |            |     |      |              |     |
| RC4-SHA            | 0x00, 0x05 | RSA | RSA  | RC4(128)     |     |
| SHA1               |            |     |      |              |     |

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

## 25240 - Samba Server Detection

### Synopsis

An SMB server is running on the remote host.

### Description

The remote host is running Samba, a CIFS/SMB server for Linux and Unix.

### See Also

<https://www.samba.org/>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/05/16, Modified: 2022/10/12

### Plugin Output

tcp/445/cifs

## 104887 - Samba Version

### Synopsis

It was possible to obtain the samba version from the remote operating system.

### Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

### Plugin Output

tcp/445/cifs

```
The remote Samba Version is : Samba 3.0.20-Debian
```

## 96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

### Synopsis

The remote host supports the SMBv1 protocol.

### Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

### See Also

<http://www.nessus.org/u?59bfc3ef>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

### Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

### Risk Factor

None

### References

XREF IAVT:0001-T-0710

### Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

### Plugin Output

tcp/445/cifs

```
The remote host supports SMBv1.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```



## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/25/smtp

```
An SMTP server is running on this port.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/80/www

```
A web server is running on this port.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/1524/wild\_shell

```
A shell server (Metasploitable) is running on this port.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/2121/ftp

```
An FTP server is running on this port.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/5900/vnc

```
A vnc server is running on this port.
```

## 22964 - Service Detection

### Synopsis

The remote service could be identified.

### Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

### Plugin Output

tcp/8180/www

```
A web server is running on this port.
```

## 17975 - Service Detection (GET request)

### Synopsis

The remote service could be identified.

### Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVT:0001-T-0935

### Plugin Information

Published: 2005/04/06, Modified: 2021/10/27

### Plugin Output

tcp/6667/irc

```
An IRC daemon is listening on this port.
```

## 11153 - Service Detection (HELP Request)

### Synopsis

The remote service could be identified.

### Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives a 'HELP' request.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/11/18, Modified: 2024/11/19

### Plugin Output

tcp/3306/mysql

```
A MySQL server is running on this port.
```



### Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

### Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

### See Also

<http://www.nessus.org/u?54fba2c1>

### Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

### Risk Factor

None

### Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

### Plugin Output

tcp/0

```
The TLS service on port 5432/TLSv1 offers these ciphers vulnerable to Shor's:
TLS_RSA_WITH_3DES_EDE_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_RC4_128_SHA
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
```

The SSH service on port 22 offers these ciphers vulnerable to Shor's:

- diffie-hellman-group14-sha1
- diffie-hellman-group-exchange-sha1
- diffie-hellman-group1-sha1
- diffie-hellman-group-exchange-sha256

The TLS service on port 25/SSLv3 offers these ciphers vulnerable to Shor's:

- TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA
- TLS\_DH\_anon\_EXPORT\_WITH\_DES40\_CBC\_SHA
- TLS\_DH\_anon\_WITH\_DES\_CBC\_SHA
- TLS\_DH\_anon\_WITH\_3DES\_EDE\_CBC\_SHA
- TLS\_RSA\_WITH\_RC4\_128\_SHA
- TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA
- TLS\_RSA\_EXPORT\_WITH\_RC2\_CBC\_40\_MD5
- TLS\_RSA\_EXPORT\_WITH\_RC4\_40\_MD5
- TLS\_DHE\_RSA\_WITH\_AES\_128\_CBC\_SHA
- TLS\_DHE\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA
- TLS\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA
- TLS\_DH\_anon\_WITH\_AES\_256\_CBC\_SHA
- TLS\_RSA\_WITH\_RC4\_128\_MD5
- TLS\_RSA\_WITH\_DES\_CBC\_SHA
- TLS\_DH\_anon\_WITH\_RC4\_128\_MD5
- TLS\_DH\_anon\_WITH\_AES\_128\_CBC\_SHA
- TLS\_DHE\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA
- TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA
- TLS\_DHE\_RSA\_WITH\_DES\_CBC\_SHA
- TLS\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA
- TLS\_DH\_anon\_EXPORT\_WITH\_RC4\_40\_MD5

The TLS service on port 25/SSLv2 offers these ciphers vulnerable to Shor's:

- SSL2\_RC4\_128\_WITH\_MD5
- SSL2\_RC2\_128\_CBC\_EXPORT40\_WITH\_MD5
- SSL2\_RC4\_128\_EXPORT40\_WITH\_MD5
- SSL2\_DES\_192\_EDE3\_CBC\_WITH\_MD5

The TLS service on port 5432/SSLv3 offers these ciphers vulnerable to Shor's:

- TLS\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA
- TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA
- TLS\_RSA\_WITH\_RC4\_128\_SHA
- TLS\_DHE\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA
- TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA
- TLS\_DHE\_RSA\_WITH\_AES\_128\_CBC\_SHA
- TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA

The TLS service on port 25/TLSv1 offers these ciphers vulnerable to Shor's:

- TLS\_DHE\_RSA\_WITH\_AES\_256\_CBC\_SHA
- TLS\_DH\_anon\_EXPORT\_WITH\_DES40\_CBC\_SHA
- TLS\_DH\_anon\_WITH\_DES\_CBC\_SHA
- TLS\_DH\_anon\_WITH\_3DES\_EDE\_CBC\_SHA
- TLS\_RSA\_WITH\_RC4\_128\_SHA
- TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA
- TLS\_RSA\_EXPORT\_WITH [...]

## 25220 - TCP/IP Timestamps Supported

### Synopsis

---

The remote service implements TCP timestamps.

### Description

---

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

### See Also

---

<http://www.ietf.org/rfc/rfc1323.txt>

### Solution

---

n/a

### Risk Factor

---

None

### Plugin Information

---

Published: 2007/05/16, Modified: 2023/10/17

### Plugin Output

---

tcp/0

## 11819 - TFTP Daemon Detection

### Synopsis

A TFTP server is listening on the remote port.

### Description

The remote host is running a TFTP (Trivial File Transfer Protocol) daemon. TFTP is often used by routers and diskless hosts to retrieve their configuration. It can also be used by worms to propagate.

### Solution

Disable this service if you do not use it.

### Risk Factor

None

### Plugin Information

Published: 2003/08/13, Modified: 2022/12/28

### Plugin Output

udp/69/tftp

## 110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

### Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

### Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

### Solution

n/a

### Risk Factor

None

### References

XREF IAVB:0001-B-0504

### Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

### Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.  
SSH local checks were not enabled.
```



## 10281 - Telnet Server Detection

## Synopsis

A Telnet server is listening on the remote port.

| Description |                                                                                                                                                   |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| 1           | 1. The first row of the table contains the header information, including the title of the document and the date of the report.                    |
| 2           | 2. The second row of the table contains the first column of data, which is the name of the person who provided the information.                   |
| 3           | 3. The third row of the table contains the second column of data, which is the date when the information was provided.                            |
| 4           | 4. The fourth row of the table contains the third column of data, which is the location where the information was provided.                       |
| 5           | 5. The fifth row of the table contains the fourth column of data, which is the name of the person who received the information.                   |
| 6           | 6. The sixth row of the table contains the fifth column of data, which is the date when the information was received.                             |
| 7           | 7. The seventh row of the table contains the sixth column of data, which is the location where the information was received.                      |
| 8           | 8. The eighth row of the table contains the seventh column of data, which is the name of the person who provided the information.                 |
| 9           | 9. The ninth row of the table contains the eighth column of data, which is the date when the information was provided.                            |
| 10          | 10. The tenth row of the table contains the ninth column of data, which is the location where the information was provided.                       |
| 11          | 11. The eleventh row of the table contains the tenth column of data, which is the name of the person who received the information.                |
| 12          | 12. The twelfth row of the table contains the eleventh column of data, which is the date when the information was received.                       |
| 13          | 13. The thirteenth row of the table contains the twelfth column of data, which is the location where the information was received.                |
| 14          | 14. The fourteenth row of the table contains the thirteenth column of data, which is the name of the person who provided the information.         |
| 15          | 15. The fifteenth row of the table contains the fourteenth column of data, which is the date when the information was provided.                   |
| 16          | 16. The sixteenth row of the table contains the fifteenth column of data, which is the location where the information was provided.               |
| 17          | 17. The seventeenth row of the table contains the sixteenth column of data, which is the name of the person who received the information.         |
| 18          | 18. The eighteenth row of the table contains the seventeenth column of data, which is the date when the information was received.                 |
| 19          | 19. The nineteenth row of the table contains the eighteenth column of data, which is the location where the information was received.             |
| 20          | 20. The twentieth row of the table contains the nineteenth column of data, which is the name of the person who provided the information.          |
| 21          | 21. The twenty-first row of the table contains the twentieth column of data, which is the date when the information was provided.                 |
| 22          | 22. The twenty-second row of the table contains the twenty-first column of data, which is the location where the information was provided.        |
| 23          | 23. The twenty-third row of the table contains the twenty-second column of data, which is the name of the person who received the information.    |
| 24          | 24. The twenty-fourth row of the table contains the twenty-third column of data, which is the date when the information was received.             |
| 25          | 25. The twenty-fifth row of the table contains the twenty-fourth column of data, which is the location where the information was received.        |
| 26          | 26. The twenty-sixth row of the table contains the twenty-fifth column of data, which is the name of the person who provided the information.     |
| 27          | 27. The twenty-seventh row of the table contains the twenty-sixth column of data, which is the date when the information was provided.            |
| 28          | 28. The twenty-eighth row of the table contains the twenty-seventh column of data, which is the location where the information was provided.      |
| 29          | 29. The twenty-ninth row of the table contains the twenty-eighth column of data, which is the name of the person who received the information.    |
| 30          | 30. The thirtieth row of the table contains the twenty-ninth column of data, which is the date when the information was received.                 |
| 31          | 31. The thirty-first row of the table contains the thirtieth column of data, which is the location where the information was received.            |
| 32          | 32. The thirty-second row of the table contains the thirty-first column of data, which is the name of the person who provided the information.    |
| 33          | 33. The thirty-third row of the table contains the thirty-second column of data, which is the date when the information was provided.             |
| 34          | 34. The thirty-fourth row of the table contains the thirty-third column of data, which is the location where the information was provided.        |
| 35          | 35. The thirty-fifth row of the table contains the thirty-fourth column of data, which is the name of the person who received the information.    |
| 36          | 36. The thirty-sixth row of the table contains the thirty-fifth column of data, which is the date when the information was received.              |
| 37          | 37. The thirty-seventh row of the table contains the thirty-sixth column of data, which is the location where the information was received.       |
| 38          | 38. The thirty-eighth row of the table contains the thirty-seventh column of data, which is the name of the person who provided the information.  |
| 39          | 39. The thirty-ninth row of the table contains the thirty-eighth column of data, which is the date when the information was provided.             |
| 40          | 40. The fortieth row of the table contains the thirty-ninth column of data, which is the location where the information was provided.             |
| 41          | 41. The forty-first row of the table contains the fortieth column of data, which is the name of the person who received the information.          |
| 42          | 42. The forty-second row of the table contains the forty-first column of data, which is the date when the information was received.               |
| 43          | 43. The forty-third row of the table contains the forty-second column of data, which is the location where the information was received.          |
| 44          | 44. The forty-fourth row of the table contains the forty-third column of data, which is the name of the person who provided the information.      |
| 45          | 45. The forty-fifth row of the table contains the forty-fourth column of data, which is the date when the information was provided.               |
| 46          | 46. The forty-sixth row of the table contains the forty-fifth column of data, which is the location where the information was provided.           |
| 47          | 47. The forty-seventh row of the table contains the forty-sixth column of data, which is the name of the person who received the information.     |
| 48          | 48. The forty-eighth row of the table contains the forty-seventh column of data, which is the date when the information was received.             |
| 49          | 49. The forty-ninth row of the table contains the forty-eighth column of data, which is the location where the information was received.          |
| 50          | 50. The fiftieth row of the table contains the forty-ninth column of data, which is the name of the person who provided the information.          |
| 51          | 51. The fifty-first row of the table contains the fiftieth column of data, which is the date when the information was provided.                   |
| 52          | 52. The fifty-second row of the table contains the fifty-first column of data, which is the location where the information was provided.          |
| 53          | 53. The fifty-third row of the table contains the fifty-second column of data, which is the name of the person who received the information.      |
| 54          | 54. The fifty-fourth row of the table contains the fifty-third column of data, which is the date when the information was received.               |
| 55          | 55. The fifty-fifth row of the table contains the fifty-fourth column of data, which is the location where the information was received.          |
| 56          | 56. The fifty-sixth row of the table contains the fifty-fifth column of data, which is the name of the person who provided the information.       |
| 57          | 57. The fifty-seventh row of the table contains the fifty-sixth column of data, which is the date when the information was provided.              |
| 58          | 58. The fifty-eighth row of the table contains the fifty-seventh column of data, which is the location where the information was provided.        |
| 59          | 59. The fifty-ninth row of the table contains the fifty-eighth column of data, which is the name of the person who received the information.      |
| 60          | 60. The sixtieth row of the table contains the fifty-ninth column of data, which is the date when the information was received.                   |
| 61          | 61. The sixty-first row of the table contains the sixtieth column of data, which is the location where the information was received.              |
| 62          | 62. The sixty-second row of the table contains the sixty-first column of data, which is the name of the person who provided the information.      |
| 63          | 63. The sixty-third row of the table contains the sixty-second column of data, which is the date when the information was provided.               |
| 64          | 64. The sixty-fourth row of the table contains the sixty-third column of data, which is the location where the information was provided.          |
| 65          | 65. The sixty-fifth row of the table contains the sixty-fourth column of data, which is the name of the person who received the information.      |
| 66          | 66. The sixty-sixth row of the table contains the sixty-fifth column of data, which is the date when the information was received.                |
| 67          | 67. The sixty-seventh row of the table contains the sixty-sixth column of data, which is the location where the information was received.         |
| 68          | 68. The sixty-eighth row of the table contains the sixty-seventh column of data, which is the name of the person who provided the information.    |
| 69          | 69. The sixty-ninth row of the table contains the sixty-eighth column of data, which is the date when the information was provided.               |
| 70          | 70. The seventieth row of the table contains the sixty-ninth column of data, which is the location where the information was provided.            |
| 71          | 71. The seventy-first row of the table contains the seventieth column of data, which is the name of the person who received the information.      |
| 72          | 72. The seventy-second row of the table contains the seventy-first column of data, which is the date when the information was received.           |
| 73          | 73. The seventy-third row of the table contains the seventy-second column of data, which is the location where the information was received.      |
| 74          | 74. The seventy-fourth row of the table contains the seventy-third column of data, which is the name of the person who provided the information.  |
| 75          | 75. The seventy-fifth row of the table contains the seventy-fourth column of data, which is the date when the information was provided.           |
| 76          | 76. The seventy-sixth row of the table contains the seventy-fifth column of data, which is the location where the information was provided.       |
| 77          | 77. The seventy-seventh row of the table contains the seventy-sixth column of data, which is the name of the person who received the information. |
| 78          | 78. The seventy-eighth row of the table contains the seventy-seventh column of data, which is the date when the information was received.         |
| 79          | 79. The seventy-ninth row of the table contains the seventy-eighth column of data, which is the location where the information was received.      |
| 80          | 80. The eightieth row of the table contains the seventy-ninth column of data, which is the name of the person who provided the information.       |
| 81          | 81. The eighty-first row of the table contains the eightieth column of data, which is the date when the information was provided.                 |
| 82          | 82. The eighty-second row of the table contains the eighty-first column of data, which is the location where the information was provided.        |
| 83          | 83. The eighty-third row of the table contains the eighty-second column of                                                                        |

The remote host is running a Telnet server, a remote terminal server.

## Solution

Disable this service if you do not use it.

| Risk Factor |
|-------------|
|-------------|

None

## Plugin Information

Published: 1999/10/12, Modified: 2020/06/12

### Plugin Output

tcp/23/telnet

[illegible][illegible][illegible][illegible][illegible]

```
Here is the banner from the remote Telnet server :  
  
----- snip -----  
  
 _ _ _ _ _  
|_ _ _ \ / _ \ _ _ \ / _ \ | _ _ \ / _ \ | _ _ \ / _ \ |  
|_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_|  
|_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_|  
      |_|  
Warning: Never expose this VM to an untrusted network!  
Contact: msfdev[at]metasploit.com  
Login with msfadmin/msfadmin to get started  
metasploitable login:  
  
----- snip -----
```

[illegible]

## 10287 - Traceroute Information

### Synopsis

It was possible to obtain traceroute information.

### Description

Makes a traceroute to the remote host.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

### Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.2.100 to 172.30.2.101 :
172.30.2.100
172.30.2.101

Hop Count: 1
```



## 11154 - Unknown Service Detection: Banner Retrieval

### Synopsis

There is an unknown service running on the remote host.

### Description

Nessus was unable to identify a service on the remote host even though it returned a banner of some type.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/11/18, Modified: 2022/07/26

### Plugin Output

tcp/512

```
If you know what this service is and think the banner could be used to
identify it, please send a description of the service along with the
following output to svc-signatures@nessus.org :
```

```
Port      : 512
Type      : spontaneous
Banner    :
0x00:  01 57 68 65 72 65 20 61 72 65 20 79 6F 75 3F 0A    .Where are you?.
      0x10:
```

## 11154 - Unknown Service Detection: Banner Retrieval

### Synopsis

There is an unknown service running on the remote host.

### Description

Nessus was unable to identify a service on the remote host even though it returned a banner of some type.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2002/11/18, Modified: 2022/07/26

### Plugin Output

tcp/8787

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to [svc-signatures@nessus.org](mailto:svc-signatures@nessus.org) :

```
Port      : 8787
Type      : get_http
Banner    :
0x0000:  00 00 00 03 04 08 46 00 00 03 A1 04 08 6F 3A 16  .....F.....O:..
0x0010:  44 52 62 3A 3A 44 52 62 43 6F 6E 6E 45 72 72 6F  DRb::DRbConnErro
0x0020:  72 07 3A 07 62 74 5B 17 22 2F 2F 75 73 72 2F 6C  r..bt[."//usr/l
0x0030:  69 62 2F 72 75 62 79 2F 31 2E 38 2F 64 72 62 2F  ib/ruby/1.8/drb/
0x0040:  64 72 62 2E 72 62 3A 35 37 33 3A 69 6E 20 60 6C  drb.rb:573:in `l
0x0050:  6F 61 64 27 22 37 2F 75 73 72 2F 6C 69 62 2F 72  oad'"7/usr/lib/r
0x0060:  75 62 79 2F 31 2E 38 2F 64 72 62 2F 64 72 62 2E  uby/1.8/drb/drb.
0x0070:  72 62 3A 36 31 32 3A 69 6E 20 60 72 65 63 76 5F  rb:612:in `recv_
0x0080:  72 65 71 75 65 73 74 27 22 37 2F 75 73 72 2F 6C  request'"7/usr/l
0x0090:  69 62 2F 72 75 62 79 2F 31 2E 38 2F 64 72 62 2F  ib/ruby/1.8/drb/
0x00A0:  64 72 62 2E 72 62 3A 39 31 31 3A 69 6E 20 60 72  drb.rb:911:in `r
0x00B0:  65 63 76 5F 72 65 71 75 65 73 74 27 22 3C 2F 75  ecv_request'"</u
0x00C0:  73 72 2F 6C 69 62 2F 72 75 62 79 2F 31 2E 38 2F  sr/lib/ruby/1.8/
0x00D0:  64 72 62 2F 64 72 62 2E 72 62 3A 31 35 33 30 3A  drb/drb.rb:1530:
0x00E0:  69 6E 20 60 69 6E 69 74 5F 77 69 74 68 5F 63 6C  in `init_with_cl
0x00F0:  69 65 6E 74 27 22 39 2F 75 73 72 2F 6C 69 62 2F  ient'"9/usr/lib/
0x0100:  72 75 62 79 2F 31 2E 38 2F 64 72 62 2F 64 72 62  ruby/1.8/drb/drb
0x0110:  2E 72 62 3A 31 35 34 32 3A 69 6E 20 60 73 65 74  .rb:1542:in `set
0x0120:  75 70 5F 6D 65 73 73 61 67 65 27 22 33 2F 75 73  up_message'"3/us
0x0130:  72 2F 6C 69 62 2F 72 75 62 79 2F 31 2E 38 2F 64  r/lib/ruby/1.8/d
0x0140:  72 62 2F 64 72 62 2E 72 62 3A 31 34 39 34  [...]

```

## 19288 - VNC Server Security Type Detection

### Synopsis

A VNC server is running on the remote host.

### Description

This script checks the remote VNC server protocol version and the available 'security types'.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2005/07/22, Modified: 2021/07/13

### Plugin Output

tcp/5900/vnc

```
\n\nThe remote VNC server chose security type #2 (VNC authentication)
```

## 65792 - VNC Server Unencrypted Communication Detection

### Synopsis

A VNC server with one or more unencrypted 'security-types' is running on the remote host.

### Description

This script checks the remote VNC server protocol version and the available 'security types' to determine if any unencrypted 'security-types' are in use or available.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2013/04/03, Modified: 2014/03/12

### Plugin Output

tcp/5900/vnc

```
The remote VNC server supports the following security type  
which does not perform full data communication encryption :
```

```
  2 (VNC authentication)
```

## 10342 - VNC Software Detection

### Synopsis

The remote host is running a remote display software (VNC).

### Description

The remote host is running VNC (Virtual Network Computing), which uses the RFB (Remote Framebuffer) protocol to provide remote access to graphical user interfaces and thus permits a console on the remote host to be displayed on another.

### See Also

<https://en.wikipedia.org/wiki/Vnc>

### Solution

Make sure use of this software is done in accordance with your organization's security policy and filter incoming traffic to this port.

### Risk Factor

None

### Plugin Information

Published: 2000/03/07, Modified: 2017/06/12

### Plugin Output

tcp/5900/vnc

```
The highest RFB protocol version supported by the server is :
```

```
3.3
```

### Synopsis

The remote web server contains a graphic image that is prone to information disclosure.

### Description

The 'favicon.ico' file found on the remote web server belongs to a popular web server. This may be used to fingerprint the web server.

### Solution

Remove the 'favicon.ico' file or create a custom one for your site.

### Risk Factor

None

### Plugin Information

Published: 2005/10/28, Modified: 2020/06/12

### Plugin Output

tcp/8180/www

```
MD5 fingerprint : 4644f2d45601037b8423d45e13194c93
Web server      : Apache Tomcat or Alfresco Community
```

## 11422 - Web Server Unconfigured - Default Install Page Present

### Synopsis

The remote web server is not configured or is improperly configured.

### Description

The remote web server uses its default welcome page. Therefore, it's probable that this server is not used at all or is serving content that is meant to be hidden.

### Solution

Disable this service if you do not use it.

### Risk Factor

None

### Plugin Information

Published: 2003/03/20, Modified: 2018/08/15

### Plugin Output

tcp/8180/www

```
The default welcome page is from Tomcat.
```

## 11424 - WebDAV Detection

### Synopsis

---

The remote server is running with WebDAV enabled.

### Description

---

WebDAV is an industry standard extension to the HTTP specification.

It adds a capability for authorized users to remotely add and manage the content of a web server.

If you do not use this extension, you should disable it.

### Solution

---

<http://support.microsoft.com/default.aspx?kbid=241520>

### Risk Factor

---

None

### Plugin Information

---

Published: 2003/03/20, Modified: 2011/03/14

### Plugin Output

---

tcp/80/www



### Synopsis

It was possible to obtain the network name of the remote host.

### Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

### Plugin Output

udp/137/netbios-ns

```
The following 7 NetBIOS names have been gathered :
```

```
METASPLOITABLE = Computer name
METASPLOITABLE = Messenger Service
METASPLOITABLE = File Server Service
__MSBROWSE__    = Master Browser
WORKGROUP       = Workgroup / Domain name
WORKGROUP       = Master Browser
WORKGROUP       = Browser Service Elections
```

```
This SMB server seems to be a Samba server - its MAC address is NULL.
```

## 52703 - vsftpd Detection

### Synopsis

An FTP server is listening on the remote port.

### Description

The remote host is running vsftpd, an FTP server for UNIX-like systems written in C.

### See Also

<http://vsftpd.beasts.org/>

### Solution

n/a

### Risk Factor

None

### Plugin Information

Published: 2011/03/17, Modified: 2019/11/22

### Plugin Output

tcp/21/ftp

```
Source  : 220 (vsFTPd 2.3.4)
Version : 2.3.4
```