



Metasploitable3 Vulnerability Scan

Report generated by Tenable Nessus™

Thu, 14 May 2026 21:05:47 EDT

TABLE OF CONTENTS

Vulnerabilities by Host

- 172.30.2.102..... 4

Vulnerabilities by Host

172.30.2.102

21

CRITICAL

28

HIGH

33

MEDIUM

4

LOW

117

INFO

Scan Information

Start time: Thu May 14 20:49:47 2026

End time: Thu May 14 21:05:47 2026

Host Information

Netbios Name: VAGRANT-2008R2

IP: 172.30.2.102

MAC Address: 08:00:27:D7:CC:D8 5C:6D:20:52:41:53

OS: Microsoft Windows Server 2008 R2 Standard Service Pack 1

Vulnerabilities

100995 - Apache 2.2.x < 2.2.33-dev / 2.4.x < 2.4.26 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache running on the remote host is 2.2.x prior to 2.2.33-dev or 2.4.x prior to 2.4.26. It is, therefore, affected by the following vulnerabilities :

- An authentication bypass vulnerability exists due to third-party modules using the ap_get_basic_auth_pw() function outside of the authentication phase. An unauthenticated, remote attacker can exploit this to bypass authentication requirements. (CVE-2017-3167)

- A NULL pointer dereference flaw exists due to third-party module calls to the mod_ssl ap_hook_process_connection() function during an HTTP request to an HTTPS port. An unauthenticated, remote attacker can exploit this to cause a denial of service condition. (CVE-2017-3169)

- A NULL pointer dereference flaw exists in mod_http2 that is triggered when handling a specially crafted HTTP/2 request. An unauthenticated, remote attacker can exploit this to cause a denial of service condition. Note that this vulnerability does not affect 2.2.x.

(CVE-2017-7659)

- An out-of-bounds read error exists in the ap_find_token() function due to improper handling of header sequences. An unauthenticated, remote attacker can exploit this, via a specially crafted header sequence, to cause a denial of service condition.

(CVE-2017-7668)

- An out-of-bounds read error exists in mod_mime due to improper handling of Content-Type response headers. An unauthenticated, remote attacker can exploit this, via a specially crafted Content-Type response header, to cause a denial of service condition or the disclosure of sensitive information.
(CVE-2017-7679)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.32

https://archive.apache.org/dist/httpd/CHANGES_2.4.26

https://httpd.apache.org/security/vulnerabilities_22.html

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.2.33-dev / 2.4.26 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6278

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	99132
BID	99134
BID	99135
BID	99137
BID	99170
CVE	CVE-2017-3167
CVE	CVE-2017-3169
CVE	CVE-2017-7659
CVE	CVE-2017-7668
CVE	CVE-2017-7679

Plugin Information

Published: 2017/06/22, Modified: 2025/12/15

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version  : 2.2.33
```

101787 - Apache 2.2.x < 2.2.34 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache running on the remote host is 2.2.x prior to 2.2.34. It is, therefore, affected by the following vulnerabilities :

- An authentication bypass vulnerability exists in httpd due to third-party modules using the `ap_get_basic_auth_pw()` function outside of the authentication phase. An unauthenticated, remote attacker can exploit this to bypass authentication requirements. (CVE-2017-3167)
- A denial of service vulnerability exists in httpd due to a NULL pointer dereference flaw that is triggered when a third-party module calls the `mod_ssl ap_hook_process_connection()` function during an HTTP request to an HTTPS port. An unauthenticated, remote attacker can exploit this to cause a denial of service condition. (CVE-2017-3169)
- A denial of service vulnerability exists in httpd due to an out-of-bounds read error in the `ap_find_token()` function that is triggered when handling a specially crafted request header sequence. An unauthenticated, remote attacker can exploit this to crash the service or force `ap_find_token()` to return an incorrect value. (CVE-2017-7668)
- A denial of service vulnerability exists in httpd due to an out-of-bounds read error in the `mod_mime` that is triggered when handling a specially crafted Content-Type response header. An unauthenticated, remote attacker can exploit this to disclose sensitive information or cause a denial of service condition. (CVE-2017-7679)
- A denial of service vulnerability exists in httpd due to a failure to initialize or reset the value placeholder in [Proxy-]Authorization headers of type 'Digest' before or between successive key=value assignments by `mod_auth_digest`. An unauthenticated, remote attacker can exploit this, by providing an initial key with no '=' assignment, to disclose sensitive information or cause a denial of service condition. (CVE-2017-9788)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.34

https://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.34 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6278

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	99134
BID	99135
BID	99137
BID	99170
BID	99569
CVE	CVE-2017-3167
CVE	CVE-2017-3169
CVE	CVE-2017-7668
CVE	CVE-2017-7679
CVE	CVE-2017-9788

Plugin Information

Published: 2017/07/18, Modified: 2025/12/10

Plugin Output

tcp/8585/www

Source : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version : 2.2.21

Fixed version : 2.2.34

158900 - Apache 2.4.x < 2.4.53 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.53. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.53 advisory.

- mod_lua Use of uninitialized value of in r:parsebody: A carefully crafted request body can cause a read to a random memory area which could cause the process to crash. This issue affects Apache HTTP Server 2.4.52 and earlier. Acknowledgements: Chamal De Silva (CVE-2022-22719)
- HTTP request smuggling: Apache HTTP Server 2.4.52 and earlier fails to close inbound connection when errors are encountered discarding the request body, exposing the server to HTTP Request Smuggling Acknowledgements: James Kettle <james.kettle portswigger.net> (CVE-2022-22720)
- Possible buffer overflow with very large or unlimited LimitXMLRequestBody in core: If LimitXMLRequestBody is set to allow request bodies larger than 350MB (defaults to 1M) on 32 bit systems an integer overflow happens which later causes out of bounds writes. This issue affects Apache HTTP Server 2.4.52 and earlier. Acknowledgements: Anonymous working with Trend Micro Zero Day Initiative (CVE-2022-22721)
- Read/write beyond bounds in mod_sed: Out-of-bounds Write vulnerability in mod_sed of Apache HTTP Server allows an attacker to overwrite heap memory with possibly attacker provided data. This issue affects Apache HTTP Server 2.4 version 2.4.52 and prior versions. Acknowledgements: Ronald Crane (Zippenhop LLC) (CVE-2022-23943)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.apache.org/dist/httpd/Announcement2.4.html>

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.53 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6055

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-22719
CVE	CVE-2022-22720
CVE	CVE-2022-22721
CVE	CVE-2022-23943
XREF	IAVA:2022-A-0124-S

Plugin Information

Published: 2022/03/14, Modified: 2023/11/06

Plugin Output

tcp/8585/www

```
URL          : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version  : 2.4.53
```

193421 - Apache 2.4.x < 2.4.54 Authentication Bypass

Synopsis

The remote web server is affected by an authentication bypass vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by an authentication bypass vulnerability as referenced in the 2.4.54 advisory.

- X-Forwarded-For dropped by hop-by-hop mechanism in mod_proxy: Apache HTTP Server 2.4.53 and earlier may not send the X-Forwarded-* headers to the origin server based on client side Connection header hop-by-hop mechanism. This may be used to bypass IP based authentication on the origin server/application.

Acknowledgements: The Apache HTTP Server project would like to thank Gaetan Ferry (Synacktiv) for reporting this issue

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0004

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-31813
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version  : 2.4.54
```

161948 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Read beyond bounds via ap_rwrite(): The ap_rwrite() function in Apache HTTP Server 2.4.53 and earlier may read unintended memory if an attacker can cause the server to reflect very large input using ap_rwrite() or ap_rputs(), such as with mod_lua's r:puts() function. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-28614)

- Read beyond bounds in ap_strcmp_match(): Apache HTTP Server 2.4.53 and earlier may crash or disclose information due to a read beyond bounds in ap_strcmp_match() when provided with an extremely large input buffer. While no code distributed with the server can be coerced into such a call, third-party modules or lua scripts that use ap_strcmp_match() may hypothetically be affected. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-28615)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:H)

CVSS v3.0 Temporal Score

7.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.0

EPSS Score

0.0103

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:P)

CVSS v2.0 Temporal Score

4.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-28614
CVE CVE-2022-28615
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2022/06/08, Modified: 2024/04/18

Plugin Output

tcp/8585/www

```
URL : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version : 2.4.54
```

170113 - Apache 2.4.x < 2.4.55 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.55. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.55 advisory.

- A carefully crafted If: request header can cause a memory read, or write of a single zero byte, in a pool (heap) memory location beyond the header value sent. This could cause the process to crash. This issue affects Apache HTTP Server 2.4.54 and earlier. (CVE-2006-20001)

- Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') vulnerability in mod_proxy_ajp of Apache HTTP Server allows an attacker to smuggle requests to the AJP server it forwards requests to. This issue affects Apache HTTP Server Apache HTTP Server 2.4 version 2.4.54 and prior versions. (CVE-2022-36760)

- Prior to Apache HTTP Server 2.4.55, a malicious backend can cause the response headers to be truncated early, resulting in some headers being incorporated into the response body. If the later headers have any security purpose, they will not be interpreted by the client. (CVE-2022-37436)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.55 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.8 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

7.3

EPSS Score

0.2314

CVSS v2.0 Base Score

7.6 (CVSS2#AV:N/AC:H/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2006-20001
CVE	CVE-2022-36760
CVE	CVE-2022-37436
XREF	IAVA:2023-A-0047-S

Plugin Information

Published: 2023/01/18, Modified: 2023/03/10

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version   : 2.4.55
```

172186 - Apache 2.4.x < 2.4.56 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.56. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.56 advisory.

- HTTP request splitting with mod_rewrite and mod_proxy: Some mod_proxy configurations on Apache HTTP Server versions 2.4.0 through 2.4.55 allow a HTTP Request Smuggling attack. Configurations are affected when mod_proxy is enabled along with some form of RewriteRule or ProxyPassMatch in which a non-specific pattern matches some portion of the user-supplied request-target (URL) data and is then re-inserted into the proxied request-target using variable substitution. For example, something like: RewriteEngine on RewriteRule ^/here/(.*) http://example.com:8080/elsewhere?\$1 http://example.com:8080/elsewhere ; [P] ProxyPassReverse /here/ http://example.com:8080/ http://example.com:8080/ Request splitting/smuggling could result in bypass of access controls in the proxy server, proxying unintended URLs to existing origin servers, and cache poisoning. Acknowledgements: finder: Lars Krapf of Adobe (CVE-2023-25690)

- Apache HTTP Server: mod_proxy_uwsgi HTTP response splitting: HTTP Response Smuggling vulnerability in Apache HTTP Server via mod_proxy_uwsgi. This issue affects Apache HTTP Server: from 2.4.30 through 2.4.55.

Special characters in the origin response header can truncate/split the response forwarded to the client.

Acknowledgements: finder: Dimas Fariski Setyawan Putra (nyxsorcerer) (CVE-2023-27522)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.56 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6818

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-25690
CVE	CVE-2023-27522
XREF	IAVA:2023-A-0124-S

Plugin Information

Published: 2023/03/07, Modified: 2023/10/21

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version   : 2.4.56
```

153583 - Apache < 2.4.49 Multiple Vulnerabilities

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.49. It is, therefore, affected by a vulnerability as referenced in the 2.4.49 changelog.

- A crafted request uri-path can cause mod_proxy to forward the request to an origin server chosen by the remote user. (CVE-2021-40438)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.3 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

8.1

EPSS Score

0.9443

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-40438
XREF	IAVA:2021-A-0440-S
XREF	CISA-KNOWN-EXPLOITED:2021/12/15

Plugin Information

Published: 2021/09/23, Modified: 2023/04/25

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version   : 2.4.49
```

153584 - Apache < 2.4.49 Multiple Vulnerabilities

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.49. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.49 changelog.

- ap_escape_quotes() may write beyond the end of a buffer when given malicious input. No included modules pass untrusted data to these functions, but third-party / external modules may. (CVE-2021-39275)
- Malformed requests may cause the server to dereference a NULL pointer. (CVE-2021-34798)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.3767

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-34798
CVE	CVE-2021-39275
XREF	IAVA:2021-A-0440-S

Plugin Information

Published: 2021/09/23, Modified: 2022/04/11

Plugin Output

tcp/8585/www

```
URL          : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version  : 2.4.49
```

171356 - Apache HTTP Server SEoL (2.1.x <= x <= 2.2.x)

Synopsis

An unsupported version of Apache HTTP Server is installed on the remote host.

Description

According to its version, Apache HTTP Server is between 2.1.x and 2.2.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://archive.apache.org/dist/httpd/Announcement2.2.txt>

Solution

Upgrade to a version of Apache HTTP Server that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2023/02/10, Modified: 2024/04/02

Plugin Output

tcp/8585/www

```
URL : http://172.30.2.102:8585/
Installed version : 2.2.21
Security End of Life : July 11, 2017
Time since Security End of Life (Est.) : >= 8 years
```


197850 - Apache Tomcat 8.0.0.RC1 < 8.0.37 multiple vulnerabilities

Synopsis

The remote Apache Tomcat server is affected by multiple vulnerabilities

Description

The version of Tomcat installed on the remote host is prior to 8.0.37. It is, therefore, affected by multiple vulnerabilities as referenced in the `fixed_in_apache_tomcat_8.5.5_and_8.0.37_security-8` advisory.

- The ResourceLinkFactory implementation in Apache Tomcat 9.0.0.M1 to 9.0.0.M9, 8.5.0 to 8.5.4, 8.0.0.RC1 to 8.0.36, 7.0.0 to 7.0.70 and 6.0.0 to 6.0.45 did not limit web application access to global JNDI resources to those resources explicitly linked to the web application. Therefore, it was possible for a web application to access any global JNDI resource whether an explicit ResourceLink had been configured or not. (CVE-2016-6797)
- A malicious web application running on Apache Tomcat 9.0.0.M1 to 9.0.0.M9, 8.5.0 to 8.5.4, 8.0.0.RC1 to 8.0.36, 7.0.0 to 7.0.70 and 6.0.0 to 6.0.45 was able to bypass a configured SecurityManager via manipulation of the configuration parameters for the JSP Servlet. (CVE-2016-6796)
- When a SecurityManager is configured, a web application's ability to read system properties should be controlled by the SecurityManager. In Apache Tomcat 9.0.0.M1 to 9.0.0.M9, 8.5.0 to 8.5.4, 8.0.0.RC1 to 8.0.36, 7.0.0 to 7.0.70, 6.0.0 to 6.0.45 the system property replacement feature for configuration files could be used by a malicious web application to bypass the SecurityManager and read system properties that should not be visible. (CVE-2016-6794)
- In Apache Tomcat 9.0.0.M1 to 9.0.0.M9, 8.5.0 to 8.5.4, 8.0.0.RC1 to 8.0.36, 7.0.0 to 7.0.70 and 6.0.0 to 6.0.45 a malicious web application was able to bypass a configured SecurityManager via a Tomcat utility method that was accessible to web applications. (CVE-2016-5018)
- The Realm implementations in Apache Tomcat versions 9.0.0.M1 to 9.0.0.M9, 8.5.0 to 8.5.4, 8.0.0.RC1 to 8.0.36, 7.0.0 to 7.0.70 and 6.0.0 to 6.0.45 did not process the supplied password if the supplied user name did not exist. This made a timing attack possible to determine valid user names. Note that the default configuration includes the LockOutRealm which makes exploitation of this vulnerability harder. (CVE-2016-0762)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://svn.apache.org/viewvc?view=rev&rev=1757272>
<https://svn.apache.org/viewvc?view=rev&rev=1757273>
<https://svn.apache.org/viewvc?view=rev&rev=1758493>
<https://svn.apache.org/viewvc?view=rev&rev=1763233>
<https://svn.apache.org/viewvc?view=rev&rev=1758494>
<https://svn.apache.org/viewvc?view=rev&rev=1763234>
<https://svn.apache.org/viewvc?view=rev&rev=1754726>
<https://svn.apache.org/viewvc?view=rev&rev=1754727>

<https://svn.apache.org/viewvc?view=rev&rev=1754900>
<https://svn.apache.org/viewvc?view=rev&rev=1760305>
<https://svn.apache.org/viewvc?view=rev&rev=1754901>
<https://svn.apache.org/viewvc?view=rev&rev=1760307>
<https://svn.apache.org/viewvc?view=rev&rev=1758500>
<https://svn.apache.org/viewvc?view=rev&rev=1758501>
<http://www.nessus.org/u?47795ca8>

Solution

Upgrade to Apache Tomcat version 8.0.37 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N)

CVSS v3.0 Temporal Score

8.2 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.0

EPSS Score

0.0105

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE	CVE-2016-0762
CVE	CVE-2016-5018
CVE	CVE-2016-6794
CVE	CVE-2016-6796
CVE	CVE-2016-6797

Plugin Information

Published: 2024/05/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/  
Installed version : 8.0.33  
Fixed version   : 8.0.37
```

197839 - Apache Tomcat 8.0.0.RC1 < 8.0.39 multiple vulnerabilities

Synopsis

The remote Apache Tomcat server is affected by multiple vulnerabilities

Description

The version of Tomcat installed on the remote host is prior to 8.0.39. It is, therefore, affected by multiple vulnerabilities as referenced in the fixed_in_apache_tomcat_8.0.39_security-8 advisory.

- Remote code execution is possible with Apache Tomcat before 6.0.48, 7.x before 7.0.73, 8.x before 8.0.39, 8.5.x before 8.5.7, and 9.x before 9.0.0.M12 if JmxRemoteLifecycleListener is used and an attacker can reach JMX ports. The issue exists because this listener wasn't updated for consistency with the CVE-2016-3427 Oracle patch that affected credential types. (CVE-2016-8735)

- The code in Apache Tomcat 9.0.0.M1 to 9.0.0.M11, 8.5.0 to 8.5.6, 8.0.0.RC1 to 8.0.38, 7.0.0 to 7.0.72, and 6.0.0 to 6.0.47 that parsed the HTTP request line permitted invalid characters. This could be exploited, in conjunction with a proxy that also permitted the invalid characters but with a different interpretation, to inject data into the HTTP response. By manipulating the HTTP response the attacker could poison a web-cache, perform an XSS attack and/or obtain sensitive information from requests other than their own. (CVE-2016-6816)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://svn.apache.org/viewvc?view=rev&rev=1767656>

<https://svn.apache.org/viewvc?view=rev&rev=1767653>

<http://www.nessus.org/u?833cb56a>

Solution

Upgrade to Apache Tomcat version 8.0.39 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.9388

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

CVE	CVE-2016-6816
CVE	CVE-2016-8735
CVE	CVE-2016-8735
XREF	CISA-KNOWN-EXPLOITED:2023/06/02

Plugin Information

Published: 2024/05/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL          : http://172.30.2.102:8282/
Installed version : 8.0.33
Fixed version  : 8.0.39
```

197857 - Apache Tomcat 8.0.0.RC1 < 8.0.42

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.42. It is, therefore, affected by a vulnerability as referenced in the `fixed_in_apache_tomcat_8.0.42_security-8` advisory.

- While investigating bug 60718, it was noticed that some calls to application listeners in Apache Tomcat 9.0.0.M1 to 9.0.0.M17, 8.5.0 to 8.5.11, 8.0.0.RC1 to 8.0.41, and 7.0.0 to 7.0.75 did not use the appropriate facade object. When running an untrusted application under a `SecurityManager`, it was therefore possible for that untrusted application to retain a reference to the request or response object and thereby access and/or modify information associated with another web application. (CVE-2017-5648)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://svn.apache.org/viewvc?view=rev&rev=1785776>

<http://www.nessus.org/u?698d011e>

Solution

Upgrade to Apache Tomcat version 8.0.42 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N)

CVSS v3.0 Temporal Score

7.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.2

EPSS Score

0.19

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

4.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2017-5648

Plugin Information

Published: 2024/05/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/  
Installed version : 8.0.33  
Fixed version  : 8.0.42
```

111067 - Apache Tomcat 8.0.0.RC1 < 8.0.53 multiple vulnerabilities

Synopsis

The remote Apache Tomcat server is affected by multiple vulnerabilities

Description

The version of Tomcat installed on the remote host is prior to 8.0.53. It is, therefore, affected by multiple vulnerabilities as referenced in the fixed_in_apache_tomcat_8.0.53_security-8 advisory.

- The host name verification when using TLS with the WebSocket client was missing. It is now enabled by default. Versions Affected: Apache Tomcat 9.0.0.M1 to 9.0.9, 8.5.0 to 8.5.31, 8.0.0.RC1 to 8.0.52, and 7.0.35 to 7.0.88. (CVE-2018-8034)

- The defaults settings for the CORS filter provided in Apache Tomcat 9.0.0.M1 to 9.0.8, 8.5.0 to 8.5.31, 8.0.0.RC1 to 8.0.52, 7.0.41 to 7.0.88 are insecure and enable 'supportsCredentials' for all origins. It is expected that users of the CORS filter will have configured it appropriately for their environment rather than using it in the default configuration. Therefore, it is expected that most users will not be impacted by this issue. (CVE-2018-8014)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?6a9165b5>

<https://svn.apache.org/viewvc?view=rev&rev=1831729>

<https://svn.apache.org/viewvc?view=rev&rev=1833759>

Solution

Upgrade to Apache Tomcat version 8.0.53 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6118

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	104203
CVE	CVE-2018-8014
CVE	CVE-2018-8034

Plugin Information

Published: 2018/07/13, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/
Installed version : 8.0.33
Fixed version  : 8.0.53
```

134862 - Apache Tomcat AJP Connector Request Injection (Ghostcat)

Synopsis

There is a vulnerable AJP connector listening on the remote host.

Description

A file read/inclusion vulnerability was found in AJP connector. A remote, unauthenticated attacker could exploit this vulnerability to read web application files from a vulnerable server. In instances where the vulnerable server allows file uploads, an attacker could upload malicious JavaServer Pages (JSP) code within a variety of file types and gain remote code execution (RCE).

See Also

<http://www.nessus.org/u?8ebe6246>
<http://www.nessus.org/u?4e287adb>
<http://www.nessus.org/u?cbc3d54e>
<https://access.redhat.com/security/cve/CVE-2020-1745>
<https://access.redhat.com/solutions/4851251>
<http://www.nessus.org/u?dd218234>
<http://www.nessus.org/u?dd772531>
<http://www.nessus.org/u?2a01d6bf>
<http://www.nessus.org/u?3b5af27e>
<http://www.nessus.org/u?9dab109f>
<http://www.nessus.org/u?5eafc70>

Solution

Update the AJP configuration to require authorization and/or upgrade the Tomcat server to 7.0.100, 8.5.51, 9.0.31 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

8.9

EPSS Score

0.9447

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.5 (CVSS2#E:H/RL:OF/RC:C)

References

CVE	CVE-2020-1745
CVE	CVE-2020-1938
XREF	CISA-KNOWN-EXPLOITED:2022/03/17
XREF	CEA-ID:CEA-2020-0021

Plugin Information

Published: 2020/03/24, Modified: 2026/03/23

Plugin Output

tcp/8009/ajp13

Nessus was able to exploit the issue using the following request :

```
0x0000: 02 02 00 08 48 54 54 50 2F 31 2E 31 00 00 0F 2F    ....HTTP/1.1.../
0x0010: 61 73 64 66 2F 78 78 78 78 2E 6A 73 70 00 00    asdf/xxxxx.jsp..
0x0020: 09 6C 6F 63 61 6C 68 6F 73 74 00 FF FF 00 09 6C    .localhost.....l
0x0030: 6F 63 61 6C 68 6F 73 74 00 00 50 00 00 09 A0 06    ocalhost..P.....
0x0040: 00 0A 6B 65 65 70 2D 61 6C 69 76 65 00 00 0F 41    ..keep-alive...A
0x0050: 63 63 65 70 74 2D 4C 61 6E 67 75 61 67 65 00 00    ccept-Language..
0x0060: 0E 65 6E 2D 55 53 2C 65 6E 3B 71 3D 30 2E 35 00    .en-US,en;q=0.5.
0x0070: A0 08 00 01 30 00 00 0F 41 63 63 65 70 74 2D 45    ....0...Accept-E
0x0080: 6E 63 6F 64 69 6E 67 00 00 13 67 7A 69 70 2C 20    ncoding...gzip,
0x0090: 64 65 66 6C 61 74 65 2C 20 73 64 63 68 00 00 0D    deflate, sdch...
0x00A0: 43 61 63 68 65 2D 43 6F 6E 74 72 6F 6C 00 00 09    Cache-Control...
0x00B0: 6D 61 78 2D 61 67 65 3D 30 00 A0 0E 00 07 4D 6F    max-age=0.....Mo
0x00C0: 7A 69 6C 6C 61 00 00 19 55 70 67 72 61 64 65 2D    zilla...Upgrade-
0x00D0: 49 6E 73 65 63 75 72 65 2D 52 65 71 75 65 73 74    Insecure-Request
0x00E0: 73 00 00 01 31 00 A0 01 00 09 74 65 78 74 2F 68    s...1.....text/h
0x00F0: 74 6D 6C 00 A0 0B 00 09 6C 6F 63 61 6C 68 6F 73    tml.....localhos
0x0100: 74 00 0A 00 21 6A 61 76 61 78 2E 73 65 72 76 6C    t...!javax.servl
0x0110: 65 74 2E 69 6E 63 6C 75 64 65 2E 72 65 71 75 65    et.include.reque
0x0120: 73 74 5F 75 72 69 00 00 01 31 00 0A 00 1F 6A 61    st_uri...1....ja
0x0130: 76 61 78 2E 73 65 72 76 6C 65 74 2E 69 6E 63 6C    vax.servlet.incl
0x0140: 75 64 65 2E 70 61 74 68 5F 69 6E 66 6F 00 00 10    ude.path_info...
0x0150: 2F 57 45 42 2D 49 4E 46 2F 77 65 62 2E 78 6D 6C    /WEB-INF/web.xml
0x0160: 00 0A 00 22 6A 61 76 61 78 2E 73 65 72 76 6C 65    ..."javax.servle
0x0170: 74 2E 69 6E 63 6C 75 64 65 2E 73 65 72 76 6C 65    t.include.servle
0x0180: 74 5F 70 61 74 68 00 00 00 00 00 FF              t_path.....
```

This produced the following truncated output (limite [...])

171342 - Apache Tomcat SEoL (8.0.x)

Synopsis

An unsupported version of Apache Tomcat is installed on the remote host.

Description

According to its version, Apache Tomcat is 8.0.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://tomcat.apache.org/tomcat-80-eol.html>

Solution

Upgrade to a version of Apache Tomcat that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2023/02/10, Modified: 2024/05/06

Plugin Output

tcp/8282/www

```
URL : http://172.30.2.102:8282/
Installed version : 8.0.33
Security End of Life : June 30, 2018
Time since Security End of Life (Est.) : >= 7 years
```

53514 - MS11-030: Vulnerability in DNS Resolution Could Allow Remote Code Execution (2509553) (remote check)

Synopsis

Arbitrary code can be executed on the remote host through the installed Windows DNS client.

Description

A flaw in the way the installed Windows DNS client processes Link- local Multicast Name Resolution (LLMNR) queries can be exploited to execute arbitrary code in the context of the NetworkService account.

Note that Windows XP and 2003 do not support LLMNR and successful exploitation on those platforms requires local access and the ability to run a special application. On Windows Vista, 2008, 7, and 2008 R2, however, the issue can be exploited remotely.

See Also

<https://www.nessus.org/u?361871b1>

Solution

Microsoft has released a set of patches for Windows XP, 2003, Vista, 2008, 7, and 2008 R2.

Risk Factor

Critical

VPR Score

7.3

EPSS Score

0.4693

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

BID	47242
CVE	CVE-2011-0657
MSKB	2509553
XREF	IAVA:2011-A-0039-S
XREF	MSFT:MS11-030

Exploitable With

Core Impact (true) Metasploit (true)

Plugin Information

Published: 2011/04/21, Modified: 2023/10/17

Plugin Output

udp/5355/llmnr

125313 - Microsoft RDP RCE (CVE-2019-0708) (BlueKeep) (unauthenticated check)

Synopsis

The remote host is affected by a remote code execution vulnerability.

Description

The remote host is affected by a remote code execution vulnerability in Remote Desktop Protocol (RDP). An unauthenticated, remote attacker can exploit this, via a series of specially crafted requests, to execute arbitrary code.

See Also

<http://www.nessus.org/u?577af692>

<http://www.nessus.org/u?8e4e0b74>

Solution

Microsoft has released a set of patches for Windows XP, 2003, 2008, 7, and 2008 R2.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

9.5

EPSS Score

0.9445

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.7 (CVSS2#E:H/RL:OF/RC:C)

References

BID	108273
CVE	CVE-2019-0708
XREF	CISA-KNOWN-EXPLOITED:2022/05/03
XREF	CEA-ID:CEA-2020-0129
XREF	CEA-ID:CEA-2019-0326
XREF	CEA-ID:CEA-2019-0700

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2019/05/22, Modified: 2025/09/29

Plugin Output

tcp/3389/msrdp

60085 - PHP 5.3.x < 5.3.15 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is 5.3.x earlier than 5.3.15, and is, therefore, potentially affected by the following vulnerabilities :

- An unspecified overflow vulnerability exists in the function '_php_stream_scandir' in the file 'main/streams/streams.c'. (CVE-2012-2688)
- An unspecified error exists that can allow the 'open_basedir' constraint to be bypassed. (CVE-2012-3365)

See Also

<http://www.php.net/ChangeLog-5.php#5.3.15>

Solution

Upgrade to PHP version 5.3.15 or later.

Risk Factor

Critical

VPR Score

5.9

EPSS Score

0.3268

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.4 (CVSS2#E:U/RL:OF/RC:C)

References

BID	54612
BID	54638

CVE	CVE-2012-2688
CVE	CVE-2012-3365

Plugin Information

Published: 2012/07/20, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.15
```

58987 - PHP Unsupported Version Detection

Synopsis

The remote host contains an unsupported version of a web application scripting language.

Description

According to its version, the installation of PHP on the remote host is no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

See Also

<http://php.net/eol.php>

<https://wiki.php.net/rfc/releaseprocess>

Solution

Upgrade to a version of PHP that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0581

Plugin Information

Published: 2012/05/04, Modified: 2025/10/29

Plugin Output

tcp/8585/www

```
Source          : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version : 5.3.10
```

End of support date : 2014/08/14
Announcement : <http://php.net/eol.php>
Supported versions : 8.1.x / 8.2.x / 8.3.x / 8.4.x

108797 - Unsupported Windows OS (remote)

Synopsis

The remote OS or service pack is no longer supported.

Description

The remote version of Microsoft Windows is either missing a service pack or is no longer supported. As a result, it is likely to contain security vulnerabilities.

See Also

<https://support.microsoft.com/en-us/lifecycle>

Solution

Upgrade to a supported service pack or operating system

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0501

Plugin Information

Published: 2018/04/03, Modified: 2025/10/21

Plugin Output

tcp/0

The following Windows version is installed and not supported:

Microsoft Windows Server 2008 R2 Standard Service Pack 1

62101 - Apache 2.2.x < 2.2.23 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.23. It is, therefore, potentially affected by the following vulnerabilities :

- The utility 'apachectl' can receive a zero-length directory name in the LD_LIBRARY_PATH via the 'envvars' file. A local attacker with access to that utility could exploit this to load a malicious Dynamic Shared Object (DSO), leading to arbitrary code execution.

(CVE-2012-0883)

- An input validation error exists related to 'mod_negotiation', 'Multiviews' and untrusted uploads that can allow cross-site scripting attacks.

(CVE-2012-2687)

Note that Nessus has not tested for these flaws but has instead relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.23

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.23 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.0 (CVSS:3.0/AV:L/AC:H/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.1 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.0732

CVSS v2.0 Base Score

6.9 (CVSS2#AV:L/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.1 (CVSS2#E:U/RL:OF/RC:C)

References

BID	53046
BID	55131
CVE	CVE-2012-0883
CVE	CVE-2012-2687
XREF	CWE:20
XREF	CWE:74
XREF	CWE:79
XREF	CWE:442
XREF	CWE:629
XREF	CWE:711
XREF	CWE:712
XREF	CWE:722
XREF	CWE:725
XREF	CWE:750
XREF	CWE:751
XREF	CWE:800
XREF	CWE:801
XREF	CWE:809
XREF	CWE:811
XREF	CWE:864
XREF	CWE:900
XREF	CWE:928
XREF	CWE:931
XREF	CWE:990

Plugin Information

Published: 2012/09/14, Modified: 2018/06/29

Plugin Output

tcp/8585/www


```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version   : 2.2.21
Fixed version       : 2.2.23
```

77531 - Apache 2.2.x < 2.2.28 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.28. It is, therefore, affected by the following vulnerabilities :

- A flaw exists within the 'mod_headers' module which allows a remote attacker to inject arbitrary headers. This is done by placing a header in the trailer portion of data being sent using chunked transfer encoding. (CVE-2013-5704)
- A flaw exists within the 'mod_deflate' module when handling highly compressed bodies. Using a specially crafted request, a remote attacker can exploit this to cause a denial of service by exhausting memory and CPU resources. (CVE-2014-0118)
- The 'mod_status' module contains a race condition that can be triggered when handling the scoreboard. A remote attacker can exploit this to cause a denial of service, execute arbitrary code, or obtain sensitive credential information. (CVE-2014-0226)
- The 'mod_cgid' module lacks a time out mechanism. Using a specially crafted request, a remote attacker can use this flaw to cause a denial of service by causing child processes to linger indefinitely, eventually filling up the scoreboard. (CVE-2014-0231)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.zerodayinitiative.com/advisories/ZDI-14-236/>
https://archive.apache.org/dist/httpd/CHANGES_2.2.29
http://httpd.apache.org/security/vulnerabilities_22.html
<http://swende.se/blog/HTTPChunked.html>

Solution

Upgrade to Apache version 2.2.29 or later.

Note that version 2.2.28 was never officially released.

Risk Factor

Medium

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.6 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.7544

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	66550
BID	68678
BID	68742
BID	68745
CVE	CVE-2013-5704
CVE	CVE-2014-0118
CVE	CVE-2014-0226
CVE	CVE-2014-0231
XREF	EDB-ID:34133

Plugin Information

Published: 2014/09/04, Modified: 2020/04/27

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version   : 2.2.21
Fixed version       : 2.2.29
```

193422 - Apache 2.4.x < 2.4.54 HTTP Request Smuggling Vulnerability

Synopsis

The remote web server is affected by a HTTP request smuggling vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by a http request smuggling vulnerability as referenced in the 2.4.54 advisory.

- Possible request smuggling in mod_proxy_ajp: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') vulnerability in mod_proxy_ajp of Apache HTTP Server allows an attacker to smuggle requests to the AJP server it forwards requests to. This issue affects Apache HTTP Server Apache HTTP Server 2.4 version 2.4.53 and prior versions. Acknowledgements: Richter Z @ 360 Noah Lab

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.3867

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-26377
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/8585/www

```
URL : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version : 2.4.54
```

193423 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Denial of Service mod_sed: If Apache HTTP Server 2.4.53 is configured to do transformations with mod_sed in contexts where the input to mod_sed may be very large, mod_sed may make excessively large memory allocations and trigger an abort. Acknowledgements: This issue was found by Brian Moussalli from the JFrog Security Research team

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.1194

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-30522
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/8585/www

```
URL : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version : 2.4.54
```

193424 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities (mod_lua)

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Denial of service in mod_lua r:parsebody: In Apache HTTP Server 2.4.53 and earlier, a malicious request to a lua script that calls r:parsebody(0) may cause a denial of service due to no default limit on possible input size. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-29404)

- Information Disclosure in mod_lua with websockets: Apache HTTP Server 2.4.53 and earlier may return lengths to applications calling r:wsread() that point past the end of the storage allocated for the buffer.

Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-30556)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0215

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-29404
CVE	CVE-2022-30556
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version   : 2.4.54
```

183391 - Apache 2.4.x < 2.4.58 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.58. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.58 advisory.

- Apache HTTP Server: DoS in HTTP/2 with initial windows size 0: An attacker, opening a HTTP/2 connection with an initial window size of 0, was able to block handling of that connection indefinitely in Apache HTTP Server. This could be used to exhaust worker resources in the server, similar to the well known slow loris attack pattern. This has been fixed in version 2.4.58, so that such connection are terminated properly after the configured connection timeout. This issue affects Apache HTTP Server: from 2.4.55 through 2.4.57. Users are recommended to upgrade to version 2.4.58, which fixes the issue.

Acknowledgements: (CVE-2023-43622)

- Apache HTTP Server: HTTP/2 stream memory not reclaimed right away on RST: When a HTTP/2 stream was reset (RST frame) by a client, there was a time window where the request's memory resources were not reclaimed immediately. Instead, de-allocation was deferred to connection close. A client could send new requests and resets, keeping the connection busy and open and causing the memory footprint to keep on growing. On connection close, all resources were reclaimed, but the process might run out of memory before that. This was found by the reporter during testing of CVE-2023-44487 (HTTP/2 Rapid Reset Exploit) with their own test client. During normal HTTP/2 use, the probability to hit this bug is very low. The kept memory would not become noticeable before the connection closes or times out. Users are recommended to upgrade to version 2.4.58, which fixes the issue. Acknowledgements: (CVE-2023-45802)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.58 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.6126

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2023-43622
CVE CVE-2023-45802
XREF IAVA:2023-A-0572-S

Plugin Information

Published: 2023/10/19, Modified: 2024/04/29

Plugin Output

tcp/8585/www

```
URL : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version : 2.4.58
```

193419 - Apache 2.4.x < 2.4.58 Out-of-Bounds Read (CVE-2023-31122)

Synopsis

The remote web server is affected by an out-of-bounds read vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.58. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.58 advisory.

- mod_macro buffer over-read: Out-of-bounds Read vulnerability in mod_macro of Apache HTTP Server. This issue affects Apache HTTP Server: through 2.4.57.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.58 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0035

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-31122
XREF	IAVA:2023-A-0572-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/29

Plugin Output

tcp/8585/www

```
URL          : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version  : 2.4.58
```

192923 - Apache 2.4.x < 2.4.59 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.59. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.59 advisory.

- Apache HTTP Server: HTTP Response Splitting in multiple modules: HTTP Response splitting in multiple modules in Apache HTTP Server allows an attacker that can inject malicious response headers into backend applications to cause an HTTP desynchronization attack. Users are recommended to upgrade to version 2.4.59, which fixes this issue. Acknowledgements: (CVE-2024-24795)

- Apache HTTP Server: HTTP/2 DoS by memory exhaustion on endless continuation frames: HTTP/2 incoming headers exceeding the limit are temporarily buffered in nghttp2 in order to generate an informative HTTP 413 response. If a client does not stop sending headers, this leads to memory exhaustion.

Acknowledgements: finder: Bartek Nowotarski (<https://nowotarski.info/>) (CVE-2024-27316)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.59 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.8941

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-38709
CVE	CVE-2024-24795
CVE	CVE-2024-27316
XREF	IAVA:2024-A-0202-S

Plugin Information

Published: 2024/04/04, Modified: 2024/07/12

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/
Installed version : 2.2.21
Fixed version   : 2.4.59
```

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.36. It is, therefore, affected by a vulnerability as referenced in the `fixed_in_apache_tomcat_8.5.3_and_8.0.36_security-8` advisory.

- The MultipartStream class in Apache Commons Fileupload before 1.3.2, as used in Apache Tomcat 7.x before 7.0.70, 8.x before 8.0.36, 8.5.x before 8.5.3, and 9.x before 9.0.0.M7 and other products, allows remote attackers to cause a denial of service (CPU consumption) via a long boundary string. (CVE-2016-3092)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://svn.apache.org/viewvc?view=rev&rev=1743722>

<https://svn.apache.org/viewvc?view=rev&rev=1743738>

<http://www.nessus.org/u?902a830c>

Solution

Upgrade to Apache Tomcat version 8.0.36 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.4025

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2016-3092

Plugin Information

Published: 2024/05/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/  
Installed version : 8.0.33  
Fixed version   : 8.0.36
```

197846 - Apache Tomcat 8.0.0.RC1 < 8.0.41

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.41. It is, therefore, affected by a vulnerability as referenced in the `fixed_in_apache_tomcat_8.0.41_security-8` advisory.

- A bug in the error handling of the send file code for the NIO HTTP connector in Apache Tomcat 9.0.0.M1 to 9.0.0.M13, 8.5.0 to 8.5.8, 8.0.0.RC1 to 8.0.39, 7.0.0 to 7.0.73 and 6.0.16 to 6.0.48 resulted in the current Processor object being added to the Processor cache multiple times. This in turn meant that the same Processor could be used for concurrent requests. Sharing a Processor can result in information leakage between requests including, not not limited to, session ID and the response body. The bug was first noticed in 8.5.x onwards where it appears the refactoring of the Connector code for 8.5.x onwards made it more likely that the bug was observed. Initially it was thought that the 8.5.x refactoring introduced the bug but further investigation has shown that the bug is present in all currently supported Tomcat versions. (CVE-2016-8745)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://svn.apache.org/viewvc?view=rev&rev=1777469>

<http://www.nessus.org/u?746a5afe>

Solution

Upgrade to Apache Tomcat version 8.0.41 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.171

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2016-8745

Plugin Information

Published: 2024/05/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/  
Installed version : 8.0.33  
Fixed version   : 8.0.41
```

99367 - Apache Tomcat 8.0.0.RC1 < 8.0.43

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.43. It is, therefore, affected by a vulnerability as referenced in the `fixed_in_apache_tomcat_8.0.43_security-8` advisory.

- A bug in the handling of the pipelined requests in Apache Tomcat 9.0.0.M1 to 9.0.0.M18, 8.5.0 to 8.5.12, 8.0.0.RC1 to 8.0.42, 7.0.0 to 7.0.76, and 6.0.0 to 6.0.52, when send file was used, results in the pipelined request being lost when send file processing of the previous request completed. This could result in responses appearing to be sent for the wrong request. For example, a user agent that sent requests A, B and C could see the correct response for request A, the response for request C for request B and no response for request C. (CVE-2017-5647)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?b3c8ea03>

<https://svn.apache.org/viewvc?view=rev&rev=1788999>

Solution

Upgrade to Apache Tomcat version 8.0.43 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0268

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID 97529

CVE CVE-2017-5647

Plugin Information

Published: 2017/04/14, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/
Installed version : 8.0.33
Fixed version   : 8.0.43
```

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.44. It is, therefore, affected by a vulnerability as referenced in the fixed_in_apache_tomcat_8.0.44_security-8 advisory.

- The error page mechanism of the Java Servlet Specification requires that, when an error occurs and an error page is configured for the error that occurred, the original request and response are forwarded to the error page. This means that the request is presented to the error page with the original HTTP method.

If the error page is a static file, expected behaviour is to serve content of the file as if processing a GET request, regardless of the actual HTTP method. The Default Servlet in Apache Tomcat 9.0.0.M1 to 9.0.0.M20, 8.5.0 to 8.5.14, 8.0.0.RC1 to 8.0.43 and 7.0.0 to 7.0.77 did not do this. Depending on the original request this could lead to unexpected and undesirable results for static error pages including, if the DefaultServlet is configured to permit writes, the replacement or removal of the custom error page.

Notes for other user provided error pages: (1) Unless explicitly coded otherwise, JSPs ignore the HTTP method. JSPs used as error pages must ensure that they handle any error dispatch as a GET request, regardless of the actual method. (2) By default, the response generated by a Servlet does depend on the HTTP method. Custom Servlets used as error pages must ensure that they handle any error dispatch as a GET request, regardless of the actual method. (CVE-2017-5664)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://svn.apache.org/viewvc?view=rev&rev=1793470>

<https://svn.apache.org/viewvc?view=rev&rev=1793489>

<http://www.nessus.org/u?cf8309f3>

Solution

Upgrade to Apache Tomcat version 8.0.44 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0957

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2017-5664

Plugin Information

Published: 2024/05/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/
Installed version : 8.0.33
Fixed version   : 8.0.44
```

103697 - Apache Tomcat 8.0.0.RC1 < 8.0.47

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.47. It is, therefore, affected by a vulnerability as referenced in the `fixed_in_apache_tomcat_8.0.47_security-8` advisory.

- When running Apache Tomcat versions 9.0.0.M1 to 9.0.0, 8.5.0 to 8.5.22, 8.0.0.RC1 to 8.0.46 and 7.0.0 to 7.0.81 with HTTP PUTs enabled (e.g. via setting the `readonly` initialisation parameter of the Default servlet to `false`) it was possible to upload a JSP file to the server via a specially crafted request. This JSP could then be requested and any code it contained would be executed by the server. (CVE-2017-12617)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?58d96e2d>

<https://svn.apache.org/viewvc?view=rev&rev=1809921>

Solution

Upgrade to Apache Tomcat version 8.0.47 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

8.1 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

9.0

EPSS Score

0.9438

CVSS v2.0 Base Score

172.30.2.102

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:H/RL:OF/RC:C)

References

BID	100954
CVE	CVE-2017-12617
XREF	CISA-KNOWN-EXPLOITED:2022/04/15
XREF	CEA-ID:CEA-2019-0240

Exploitable With

Core Impact (true) (true) Metasploit (true)

Plugin Information

Published: 2017/10/06, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/
Installed version : 8.0.33
Fixed version   : 8.0.47
```

121124 - Apache Tomcat 8.0.0.RC1 < 8.0.52

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.52. It is, therefore, affected by a vulnerability as referenced in the `fixed_in_apache_tomcat_8.0.52_security-8` advisory.

- An improper handling of overflow in the UTF-8 decoder with supplementary characters can lead to an infinite loop in the decoder causing a Denial of Service. Versions Affected: Apache Tomcat 9.0.0.M9 to 9.0.7, 8.5.0 to 8.5.30, 8.0.0.RC1 to 8.0.51, and 7.0.28 to 7.0.86. (CVE-2018-1336)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?bb2a802e>

<https://svn.apache.org/viewvc?view=rev&rev=1830375>

Solution

Upgrade to Apache Tomcat version 8.0.52 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.15

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2018-1336

Plugin Information

Published: 2019/01/11, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL          : http://172.30.2.102:8282/  
Installed version : 8.0.33  
Fixed version  : 8.0.52
```

58435 - MS12-020: Vulnerabilities in Remote Desktop Could Allow Remote Code Execution (2671387) (uncredentialed check)

Synopsis

The remote Windows host could allow arbitrary code execution.

Description

An arbitrary remote code vulnerability exists in the implementation of the Remote Desktop Protocol (RDP) on the remote Windows host. The vulnerability is due to the way that RDP accesses an object in memory that has been improperly initialized or has been deleted.

If RDP has been enabled on the affected system, an unauthenticated, remote attacker could leverage this vulnerability to cause the system to execute arbitrary code by sending a sequence of specially crafted RDP packets to it.

This plugin also checks for a denial of service vulnerability in Microsoft Terminal Server.

Note that this script does not detect the vulnerability if the 'Allow connections only from computers running Remote Desktop with Network Level Authentication' setting is enabled or the security layer is set to 'SSL (TLS 1.0)' on the remote host.

See Also

<https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2012/ms12-020>

Solution

Microsoft has released a set of patches for Windows XP, 2003, Vista, 2008, 7, and 2008 R2.

Note that an extended support contract with Microsoft is required to obtain the patch for this vulnerability for Windows 2000.

Risk Factor

High

VPR Score

9.2

EPSS Score

0.8738

CVSS v2.0 Base Score

9.3 (CVSS2#AV:N/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.3 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

BID	52353
BID	52354
CVE	CVE-2012-0002
CVE	CVE-2012-0152
MSKB	2621440
MSKB	2667402
XREF	EDB-ID:18606
XREF	MSFT:MS12-020
XREF	IAVA:2012-A-0039

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2012/03/22, Modified: 2025/09/29

Plugin Output

tcp/3389/msrdp

97833 - MS17-010: Security Update for Microsoft Windows SMB Server (4013389) (ETERNALBLUE) (ETERNALCHAMPION) (ETERNALROMANCE) (ETERNALSYNERGY) (WannaCry) (EternalRocks) (Petya) (uncredentialed check)

Synopsis

The remote Windows host is affected by multiple vulnerabilities.

Description

The remote Windows host is affected by the following vulnerabilities :

- Multiple remote code execution vulnerabilities exist in Microsoft Server Message Block 1.0 (SMBv1) due to improper handling of certain requests. An unauthenticated, remote attacker can exploit these vulnerabilities, via a specially crafted packet, to execute arbitrary code. (CVE-2017-0143, CVE-2017-0144, CVE-2017-0145, CVE-2017-0146, CVE-2017-0148)
- An information disclosure vulnerability exists in Microsoft Server Message Block 1.0 (SMBv1) due to improper handling of certain requests. An unauthenticated, remote attacker can exploit this, via a specially crafted packet, to disclose sensitive information. (CVE-2017-0147)

ETERNALBLUE, ETERNALCHAMPION, ETERNALROMANCE, and ETERNALSYNERGY are four of multiple Equation Group vulnerabilities and exploits disclosed on 2017/04/14 by a group known as the Shadow Brokers. WannaCry / WannaCrypt is a ransomware program utilizing the ETERNALBLUE exploit, and EternalRocks is a worm that utilizes seven Equation Group vulnerabilities. Petya is a ransomware program that first utilizes CVE-2017-0199, a vulnerability in Microsoft Office, and then spreads via ETERNALBLUE.

See Also

<http://www.nessus.org/u?68fc8eff>
<http://www.nessus.org/u?321523eb>
<http://www.nessus.org/u?065561d0>
<http://www.nessus.org/u?d9f569cf>
<https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/>
<http://www.nessus.org/u?b9d9ebf9>
<http://www.nessus.org/u?8dcab5e4>
<http://www.nessus.org/u?234f8ef8>
<http://www.nessus.org/u?4c7e0cf3>
<https://github.com/stamparm/EternalRocks/>
<http://www.nessus.org/u?59db5b5b>

Solution

Microsoft has released a set of patches for Windows Vista, 2008, 7, 2008 R2, 2012, 8.1, RT 8.1, 2012 R2, 10, and 2016. Microsoft has also released emergency patches for Windows operating systems that are no longer supported, including Windows XP, 2003, and 8.

For unsupported Windows operating systems, e.g. Windows XP, Microsoft recommends that users discontinue the use of SMBv1. SMBv1 lacks security features that were included in later SMB versions.

SMBv1 can be disabled by following the vendor instructions provided in Microsoft KB2696547. Additionally, US-CERT recommends that users block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

9.8

EPSS Score

0.9432

CVSS v2.0 Base Score

9.3 (CVSS2#AV:N/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.1 (CVSS2#E:H/RL:OF/RC:C)

STIG Severity

I

References

BID	96703
BID	96704
BID	96705
BID	96706
BID	96707
BID	96709
CVE	CVE-2017-0143
CVE	CVE-2017-0144
CVE	CVE-2017-0145

CVE	CVE-2017-0146
CVE	CVE-2017-0147
CVE	CVE-2017-0148
MSKB	4012212
MSKB	4012213
MSKB	4012214
MSKB	4012215
MSKB	4012216
MSKB	4012217
MSKB	4012606
MSKB	4013198
MSKB	4013429
MSKB	4012598
XREF	EDB-ID:41891
XREF	EDB-ID:41987
XREF	MSFT:MS17-010
XREF	IAVA:2017-A-0065
XREF	CISA-KNOWN-EXPLOITED:2022/05/03
XREF	CISA-KNOWN-EXPLOITED:2022/08/10
XREF	CISA-KNOWN-EXPLOITED:2022/04/15
XREF	CISA-KNOWN-EXPLOITED:2022/04/27
XREF	CISA-KNOWN-EXPLOITED:2022/06/14

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2017/03/20, Modified: 2025/12/29

Plugin Output

tcp/445/cifs

Sent:
00000054fff534d422500000001803c80000000000000000000000008bb800008000110000000
00ffffffffff000000000000000000000005400000054000200230000001100005c00500049005000
45005c00000000000

[illegible]

10547 - Microsoft Windows LAN Manager SNMP LanMan Services Disclosure

Synopsis

The list of LanMan services running on the remote host can be obtained via SNMP.

Description

It is possible to obtain the list of LanMan services on the remote host by sending SNMP requests with the OID 1.3.6.1.4.1.77.1.2.3.1.1

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

VPR Score

3.4

EPSS Score

0.04

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0499

Plugin Information

Published: 2000/11/10, Modified: 2024/03/22

Plugin Output

udp/161/snmp

jmx
Power
Server
jenkins
IP Helper
DNS Client
wampapache
wampmysqld
DHCP Client
Workstation
SNMP Service
Plug and Play
Print Spooler
OpenSSH Server
Task Scheduler
Windows Update
Remote Registry
Windows Firewall
COM+ Event System
Windows Event Log
IPsec Policy Agent
Group Policy Client
Network Connections
RPC Endpoint Mapper
Software Protection
Network List Service
User Profile Service
Base Filtering Engine
Microsoft FTP Service
TCP/IP NetBIOS Helper
Application Experience
Cryptographic Services
Diagnostic System Host
Certificate Propagation
Remote Desktop Services
Shell Hardware Detection
domain1 GlassFish Server
Apache Tomcat 8.0 Tomcat8
Diagnostic Policy Service
Security Accounts Manager
Network Location Awareness
Windows Font Cache Service
Remote Procedure Call (RPC)
DCOM Server Process Launcher
Remote Desktop Configuration
MEDC Server Component - Apache
Application Host Helper Service
Network Store Interface Service
Distributed Link Tracking Client
System Event Notification Service
World Wide Web Publishing Service
VirtualBox Guest Additions Service
Windows Management Instrumentation
Windows Process Activation Service
Distributed Transaction Coordinator
IKE and AuthIP IPsec Keying Modules
ManageEngine Desktop Central Server
Windows Licensing Monitoring Service
Desktop Window Manager Session Manager
Background Intelligent Transfer Service
WinHTTP Web Proxy Auto-Discovery Service
Windows Remote Management (WS-Management)
MEDC Server Component - Notification Server
Elasticsearch 1.1.1 (elasticsearch-service-x64)
Remote Desktop Services UserMode Port Redirector

59056 - PHP 5.3.x < 5.3.13 CGI Query String Code Execution

Synopsis

The remote web server uses a version of PHP that is affected by a remote code execution vulnerability.

Description

According to its banner, the version of PHP installed on the remote host is 5.3.x earlier than 5.3.13 and, as such, is potentially affected by a remote code execution and information disclosure vulnerability.

The fix for CVE-2012-1823 does not completely correct the CGI query vulnerability. Disclosure of PHP source code and code execution via query parameters are still possible.

Note that this vulnerability is exploitable only when PHP is used in CGI-based configurations. Apache with 'mod_php' is not an exploitable configuration.

See Also

<http://eindbazen.net/2012/05/php-cgi-advisory-cve-2012-1823/>

<https://bugs.php.net/bug.php?id=61910>

<http://www.php.net/archive/2012.php#id2012-05-08-1>

<http://www.php.net/ChangeLog-5.php#5.3.13>

Solution

Upgrade to PHP version 5.3.13 or later. A 'mod_rewrite' workaround is available as well.

Risk Factor

High

VPR Score

7.4

EPSS Score

0.7453

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	53388
CVE	CVE-2012-2311
CVE	CVE-2012-2335
CVE	CVE-2012-2336
XREF	CERT:520827

Exploitable With

Metasploit (true)

Plugin Information

Published: 2012/05/09, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.13
```

59529 - PHP 5.3.x < 5.3.14 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is 5.3.x earlier than 5.3.14, and is, therefore, potentially affected the following vulnerabilities :

- An integer overflow error exists in the function 'phar_parse_tarfile' in the file 'ext/phar/tar.c'. This error can lead to a heap-based buffer overflow when handling a maliciously crafted TAR file. Arbitrary code execution is possible due to this error. (CVE-2012-2386)
- A weakness exists in the 'crypt' function related to the DES implementation that can allow brute-force attacks. (CVE-2012-2143)
- Several design errors involving the incorrect parsing of PHP PDO prepared statements could lead to disclosure of sensitive information or denial of service. (CVE-2012-3450)
- A variable initialization error exists in the file 'ext/openssl/openssl.c' that can allow process memory contents to be disclosed when input data is of length zero. (CVE-2012-6113)

See Also

<http://www.nessus.org/u?ec6f812f>
<https://bugs.php.net/bug.php?id=61755>
<http://www.php.net/ChangeLog-5.php#5.3.14>
<http://www.nessus.org/u?99140286>
<http://www.nessus.org/u?a42ad63a>

Solution

Upgrade to PHP version 5.3.14 or later.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.1383

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	47545
BID	53729
BID	54777
BID	57462
CVE	CVE-2012-2143
CVE	CVE-2012-2386
CVE	CVE-2012-3450
CVE	CVE-2012-6113
XREF	EDB-ID:17201

Plugin Information

Published: 2012/06/15, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source   : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version : 5.3.10
Fixed version    : 5.3.14
```

64992 - PHP 5.3.x < 5.3.22 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is potentially affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP 5.3.x installed on the remote host is prior to 5.3.22. It is, therefore, potentially affected by the following vulnerabilities :

- An error exists in the file 'ext/soap/soap.c'

related to the 'soap.wsdl_cache_dir' configuration directive and writing cache files that could allow remote 'wsdl' files to be written to arbitrary locations. (CVE-2013-1635)

- An error exists in the file 'ext/soap/php_xml.c'

related to parsing SOAP 'wsdl' files and external entities that could cause PHP to parse remote XML documents defined by an attacker. This could allow access to arbitrary files. (CVE-2013-1643)

Note that this plugin does not attempt to exploit the vulnerabilities but, instead relies only on PHP's self-reported version number.

See Also

<http://www.nessus.org/u?2dcf53bd>

<http://www.nessus.org/u?889595b1>

<http://www.php.net/ChangeLog-5.php#5.3.22>

Solution

Upgrade to PHP version 5.3.22 or later.

Risk Factor

High

VPR Score

5.9

EPSS Score

0.0333

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	58224
BID	58766
CVE	CVE-2013-1635
CVE	CVE-2013-1643

Plugin Information

Published: 2013/03/04, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.22
```


66584 - PHP 5.3.x < 5.3.23 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is potentially affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP 5.3.x installed on the remote host is prior to 5.3.23. It is, therefore, potentially affected by multiple vulnerabilities:

- An error exists in the file 'ext/soap/soap.c'

related to the 'soap.wsdl_cache_dir' configuration directive and writing cache files that could allow remote 'wsdl' files to be written to arbitrary locations. (CVE-2013-1635)

- An error exists in the file 'ext/soap/php_xml.c'

related to parsing SOAP 'wsdl' files and external entities that could cause PHP to parse remote XML documents defined by an attacker. This could allow access to arbitrary files. (CVE-2013-1643)

- An information disclosure in the file 'ext/soap/php_xml.c' related to parsing SOAP 'wsdl'

files and external entities that could cause PHP to parse remote XML documents defined by an attacker. This could allow access to arbitrary files. (CVE-2013-1824)

Note that this plugin does not attempt to exploit the vulnerability, but instead relies only on PHP's self-reported version number.

See Also

<http://www.nessus.org/u?7c770707>

<http://www.php.net/ChangeLog-5.php#5.3.23>

Solution

Upgrade to PHP version 5.3.23 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.4 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.0333

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	58224
BID	58766
BID	62373
CVE	CVE-2013-1635
CVE	CVE-2013-1643
CVE	CVE-2013-1824

Plugin Information

Published: 2013/05/24, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.23
```

71426 - PHP 5.3.x < 5.3.28 Multiple OpenSSL Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is potentially affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is 5.3.x prior to 5.3.28. It is, therefore, potentially affected by the following vulnerabilities :

- A flaw exists in the PHP OpenSSL extension's hostname identity check when handling certificates that contain hostnames with NULL bytes. An attacker could potentially exploit this flaw to conduct man-in-the-middle attacks to spoof SSL servers. Note that to exploit this issue, an attacker would need to obtain a carefully-crafted certificate signed by an authority that the client trusts. (CVE-2013-4073, CVE-2013-4248)
- A memory corruption flaw exists in the way the openssl_x509_parse() function of the PHP OpenSSL extension parsed X.509 certificates. A remote attacker could use this flaw to provide a malicious, self-signed certificate or a certificate signed by a trusted authority to a PHP application using the aforementioned function. This could cause the application to crash or possibly allow the attacker to execute arbitrary code with the privileges of the user running the PHP interpreter. (CVE-2013-6420)

Note that this plugin does not attempt to exploit these vulnerabilities, but instead relies only on PHP's self-reported version number.

See Also

<https://seclists.org/fulldisclosure/2013/Dec/96>

https://bugzilla.redhat.com/show_bug.cgi?id=1036830

<http://www.nessus.org/u?b6ec9ef9>

<http://www.php.net/ChangeLog-5.php#5.3.28>

Solution

Upgrade to PHP version 5.3.28 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.6 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

4.2

EPSS Score

0.4022

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	60843
BID	61776
BID	64225
CVE	CVE-2013-4073
CVE	CVE-2013-4248
CVE	CVE-2013-6420
XREF	EDB-ID:30395

Plugin Information

Published: 2013/12/14, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.28
```

77285 - PHP 5.3.x < 5.3.29 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is 5.3.x prior to 5.3.29. It is, therefore, affected by the following vulnerabilities :

- A heap-based buffer overflow error exists in the file 'ext/date/lib/parse_iso_intervals.c' related to handling DateInterval objects that allows denial of service attacks. (CVE-2013-6712)
- A boundary checking error exists related to the Fileinfo extension, Composite Document Format (CDF) handling, and the function 'cdf_read_short_sector'. (CVE-2014-0207)
- A flaw exists with the 'cdf_unpack_summary_info()' function within 'src/cdf.c' where multiple file_printf calls occur when handling specially crafted CDF files. This could allow a context dependent attacker to crash the web application using PHP. (CVE-2014-0237)
- A flaw exists with the 'cdf_read_property_info()' function within 'src/cdf.c' where an infinite loop occurs when handling specially crafted CDF files. This could allow a context dependent attacker to crash the web application using PHP. (CVE-2014-0238)
- A type-confusion error exists related to the Standard PHP Library (SPL) extension and the function 'unserialize'. (CVE-2014-3515)
- An error exists related to configuration scripts and temporary file handling that could allow insecure file usage. (CVE-2014-3981)
- A heap-based buffer overflow error exists related to the function 'dns_get_record' that could allow execution of arbitrary code. (CVE-2014-4049)
- An out-of-bounds read exists in printf. (Bug #67249)

Note that Nessus has not attempted to exploit these issues, but has instead relied only on the application's self-reported version number.

Additionally, note that version 5.3.29 marks the end of support for the PHP 5.3.x branch.

See Also

<http://php.net/archive/2014.php#id2014-08-14-1>

<http://www.php.net/ChangeLog-5.php#5.3.29>

Solution

Upgrade to PHP version 5.3.29 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.4 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.4866

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	64018
BID	67759
BID	67765
BID	67837
BID	68007
BID	68120
BID	68237
BID	68238
BID	68239
BID	68241
BID	68243
BID	68423
BID	69271
BID	73385
CVE	CVE-2013-6712
CVE	CVE-2014-0207
CVE	CVE-2014-0237
CVE	CVE-2014-0238
CVE	CVE-2014-3478

CVE	CVE-2014-3479
CVE	CVE-2014-3480
CVE	CVE-2014-3487
CVE	CVE-2014-3515
CVE	CVE-2014-3981
CVE	CVE-2014-4049
CVE	CVE-2014-4721

Plugin Information

Published: 2014/08/20, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.29
```

58988 - PHP < 5.3.12 / 5.4.2 CGI Query String Code Execution

Synopsis

The remote web server uses a version of PHP that is affected by a remote code execution vulnerability.

Description

According to its banner, the version of PHP installed on the remote host is earlier than 5.3.12 / 5.4.2, and as such is potentially affected by a remote code execution and information disclosure vulnerability.

An error in the file 'sapi/cgi/cgi_main.c' can allow a remote attacker to obtain PHP source code from the web server or to potentially execute arbitrary code. In vulnerable configurations, PHP treats certain query string parameters as command line arguments including switches such as '-s', '-d', and '-c'.

Note that this vulnerability is exploitable only when PHP is used in CGI-based configurations. Apache with 'mod_php' is not an exploitable configuration.

See Also

<http://eindbazen.net/2012/05/php-cgi-advisory-cve-2012-1823/>

<https://bugs.php.net/bug.php?id=61910>

<http://www.php.net/archive/2012.php#id2012-05-03-1>

<http://www.php.net/ChangeLog-5.php#5.3.12>

<http://www.php.net/ChangeLog-5.php#5.4.2>

Solution

Upgrade to PHP version 5.3.12 / 5.4.2 or later. A 'mod_rewrite' workaround is available as well.

Risk Factor

High

VPR Score

9.0

EPSS Score

0.9436

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.5 (CVSS2#E:H/RL:OF/RC:C)

References

BID	53388
CVE	CVE-2012-1823
XREF	CERT:520827
XREF	CISA-KNOWN-EXPLOITED:2022/04/15

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2012/05/04, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.12 / 5.4.2
```

142591 - PHP < 7.3.24 Multiple Vulnerabilities

Synopsis

The version of PHP running on the remote web server is affected by multiple vulnerabilities.

Description

According to its self-reported version number, the version of PHP running on the remote web server is prior to 7.3.24. It is, therefore affected by multiple vulnerabilities

See Also

<https://www.php.net/ChangeLog-7.php#7.3.24>

Solution

Upgrade to PHP version 7.3.24 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

STIG Severity

I

References

XREF IAVA:2020-A-0510-S

Plugin Information

Published: 2020/11/06, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
URL      : http://172.30.2.102:8585/ (5.3.10 under Server: Apache/2.2.21 (Win64)
PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10)
Installed version : 5.3.10
Fixed version    : 7.3.24
```

41028 - SNMP Agent Default Community Name (public)

Synopsis

The community name of the remote SNMP server can be guessed.

Description

It is possible to obtain the default community name of the remote SNMP server.

An attacker may use this information to gain more knowledge about the remote host, or to change the configuration of the remote system (if the default community allows such modifications).

Solution

Disable the SNMP service on the remote host if you do not use it.

Either filter incoming UDP packets going to this port, or change the default community string.

Risk Factor

High

VPR Score

5.2

EPSS Score

0.92

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	2112
CVE	CVE-1999-0517

Plugin Information

Published: 2002/11/25, Modified: 2022/06/01

Plugin Output

172.30.2.102

udp/161/snmp

```
The remote SNMP server replies to the following default community  
string :
```

```
public
```

42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

VPR Score

6.1

EPSS Score

0.3775

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/3389/msrdp

```
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name          Code          KEX          Auth          Encryption          MAC
-----
DES-CBC3-SHA  0x00, 0x0A      RSA          RSA          3DES-CBC (168)
SHA1

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

VPR Score

6.1

EPSS Score

0.3775

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/8383/www

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
SHA1					
ECDHE-RSA-DES-CBC3-SHA	0xC0, 0x12	ECDHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

The fields above are :

{Tenable ciphername}

{Cipher ID code}

Kex={key exchange}

Auth={authentication}

Encrypt={symmetric encryption method}

MAC={message authentication code}

{export flag}

57791 - Apache 2.2.x < 2.2.22 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x installed on the remote host is prior to 2.2.22. It is, therefore, potentially affected by the following vulnerabilities :

- When configured as a reverse proxy, improper use of the RewriteRule and ProxyPassMatch directives could cause the web server to proxy requests to arbitrary hosts.

This could allow a remote attacker to indirectly send requests to intranet servers.

(CVE-2011-3368, CVE-2011-4317)

- A heap-based buffer overflow exists when mod_setenvif module is enabled and both a maliciously crafted 'SetEnvIf' directive and a maliciously crafted HTTP request header are used. (CVE-2011-3607)

- A format string handling error can allow the server to be crashed via maliciously crafted cookies.

(CVE-2012-0021)

- An error exists in 'scoreboard.c' that can allow local attackers to crash the server during shutdown.

(CVE-2012-0031)

- An error exists in 'protocol.c' that can allow 'HTTPOnly' cookies to be exposed to attackers through the malicious use of either long or malformed HTTP headers. (CVE-2012-0053)

- An error in the mod_proxy_ajp module when used to connect to a backend server that takes an overly long time to respond could lead to a temporary denial of service. (CVE-2012-4557)

Note that Nessus did not actually test for these flaws, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.22

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.22 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.8192

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	49957
BID	50494
BID	50802
BID	51407
BID	51705
BID	51706
BID	56753
CVE	CVE-2011-3368
CVE	CVE-2011-3607
CVE	CVE-2011-4317
CVE	CVE-2012-0021
CVE	CVE-2012-0031
CVE	CVE-2012-0053
CVE	CVE-2012-4557

Plugin Information

Published: 2012/02/02, Modified: 2018/06/29

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version   : 2.2.21
```

Fixed version : 2.2.22

64912 - Apache 2.2.x < 2.2.24 Multiple XSS Vulnerabilities

Synopsis

The remote web server is affected by multiple cross-site scripting vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.24. It is, therefore, potentially affected by the following cross-site scripting vulnerabilities :

- Errors exist related to the modules mod_info, mod_status, mod_imagemap, mod_ldap, and mod_proxy_ftp and unescaped hostnames and URIs that could allow cross-site scripting attacks. (CVE-2012-3499)
- An error exists related to the mod_proxy_balancer module's manager interface that could allow cross-site scripting attacks. (CVE-2012-4558)

Note that Nessus did not actually test for these issues, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.24
http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.24 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.0

EPSS Score

0.5822

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	58165
CVE	CVE-2012-3499
CVE	CVE-2012-4558
XREF	CWE:20
XREF	CWE:74
XREF	CWE:79
XREF	CWE:442
XREF	CWE:629
XREF	CWE:711
XREF	CWE:712
XREF	CWE:722
XREF	CWE:725
XREF	CWE:750
XREF	CWE:751
XREF	CWE:800
XREF	CWE:801
XREF	CWE:809
XREF	CWE:811
XREF	CWE:864
XREF	CWE:900
XREF	CWE:928
XREF	CWE:931
XREF	CWE:990

Plugin Information

Published: 2013/02/27, Modified: 2018/06/29

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version   : 2.2.21
Fixed version       : 2.2.24
```


68915 - Apache 2.2.x < 2.2.25 Multiple Vulnerabilities

Synopsis

The remote web server may be affected by multiple cross-site scripting vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.25. It is, therefore, potentially affected by the following vulnerabilities :

- A flaw exists in the 'RewriteLog' function where it fails to sanitize escape sequences from being written to log files, making it potentially vulnerable to arbitrary command execution. (CVE-2013-1862)
- A denial of service vulnerability exists relating to the 'mod_dav' module as it relates to MERGE requests. (CVE-2013-1896)

Note that Nessus did not actually test for these issues, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.25
http://httpd.apache.org/security/vulnerabilities_22.html
<http://www.nessus.org/u?f050c342>

Solution

Upgrade to Apache version 2.2.25 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.6 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

4.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.524

CVSS v2.0 Base Score

5.1 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	59826
BID	61129
CVE	CVE-2013-1862
CVE	CVE-2013-1896

Plugin Information

Published: 2013/07/16, Modified: 2018/06/29

Plugin Output

tcp/8585/www

```
Version source   : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version : 2.2.21
Fixed version    : 2.2.25
```

73405 - Apache 2.2.x < 2.2.27 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is a version prior to 2.2.27. It is, therefore, potentially affected by the following vulnerabilities :

- A flaw exists with the 'mod_dav' module that is caused when tracking the length of CDATA that has leading white space. A remote attacker with a specially crafted DAV WRITE request can cause the service to stop responding.

(CVE-2013-6438)

- A flaw exists in 'mod_log_config' module that is caused when logging a cookie that has an unassigned value. A remote attacker with a specially crafted request can cause the service to crash. (CVE-2014-0098)

Note that Nessus did not actually test for these issues, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.27

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.27 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.5079

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	66303
CVE	CVE-2013-6438
CVE	CVE-2014-0098

Plugin Information

Published: 2014/04/08, Modified: 2018/09/17

Plugin Output

tcp/8585/www

```
Version source   : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Installed version : 2.2.21
Fixed version    : 2.2.27
```

193420 - Apache 2.4.x < 2.4.54 Out-Of-Bounds Read (CVE-2022-28330)

Synopsis

The remote web server is affected by an out-of-bound read vulnerability

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by an out-of-bounds read vulnerability as referenced in the 2.4.54 advisory.

- Read beyond bounds in mod_isapi: Apache HTTP Server 2.4.53 and earlier on Windows may read beyond bounds when configured to process requests with the mod_isapi module. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.0019

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-28330
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/  
Installed version : 2.2.21  
Fixed version   : 2.4.54
```

102588 - Apache Tomcat 8.0.0.RC1 < 8.0.45

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Tomcat installed on the remote host is prior to 8.0.45. It is, therefore, affected by a vulnerability as referenced in the fixed_in_apache_tomcat_8.0.45_security-8 advisory.

- The CORS Filter in Apache Tomcat 9.0.0.M1 to 9.0.0.M21, 8.5.0 to 8.5.15, 8.0.0.RC1 to 8.0.44 and 7.0.41 to 7.0.78 did not add an HTTP Vary header indicating that the response varies depending on Origin. This permitted client and server side cache poisoning in some circumstances. (CVE-2017-7674)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?7af6643f>

https://bz.apache.org/bugzilla/show_bug.cgi?id=61101

<https://svn.apache.org/viewvc?view=rev&rev=1795815>

Solution

Upgrade to Apache Tomcat version 8.0.45 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

4.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:R/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.8 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.0539

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	100280
CVE	CVE-2017-7674

Plugin Information

Published: 2017/08/18, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/
Installed version : 8.0.33
Fixed version   : 8.0.45
```

106976 - Apache Tomcat 8.0.0.RC1 < 8.0.50 multiple vulnerabilities

Synopsis

The remote Apache Tomcat server is affected by multiple vulnerabilities

Description

The version of Tomcat installed on the remote host is prior to 8.0.50. It is, therefore, affected by multiple vulnerabilities as referenced in the fixed_in_apache_tomcat_8.0.50_security-8 advisory.

- Security constraints defined by annotations of Servlets in Apache Tomcat 9.0.0.M1 to 9.0.4, 8.5.0 to 8.5.27, 8.0.0.RC1 to 8.0.49 and 7.0.0 to 7.0.84 were only applied once a Servlet had been loaded. Because security constraints defined in this way apply to the URL pattern and any URLs below that point, it was possible - depending on the order Servlets were loaded - for some security constraints not to be applied.

This could have exposed resources to users who were not authorised to access them. (CVE-2018-1305)

- The URL pattern of (the empty string) which exactly maps to the context root was not correctly handled in Apache Tomcat 9.0.0.M1 to 9.0.4, 8.5.0 to 8.5.27, 8.0.0.RC1 to 8.0.49 and 7.0.0 to 7.0.84 when used as part of a security constraint definition. This caused the constraint to be ignored. It was, therefore, possible for unauthorised users to gain access to web application resources that should have been protected. Only security constraints with a URL pattern of the empty string were affected. (CVE-2018-1304)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?a15478b8>

https://bz.apache.org/bugzilla/show_bug.cgi?id=62067

<https://svn.apache.org/viewvc?view=rev&rev=1823308>

<https://svn.apache.org/viewvc?view=rev&rev=1823319>

<https://svn.apache.org/viewvc?view=rev&rev=1824359>

Solution

Upgrade to Apache Tomcat version 8.0.50 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.1958

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2018-1304

CVE CVE-2018-1305

Plugin Information

Published: 2018/02/23, Modified: 2024/05/23

Plugin Output

tcp/8282/www

```
URL           : http://172.30.2.102:8282/  
Installed version : 8.0.33  
Fixed version   : 8.0.50
```

12085 - Apache Tomcat Default Files

Synopsis

The remote web server contains default files.

Description

The default error page, default index page, example JSPs and/or example servlets are installed on the remote Apache Tomcat server. These files should be removed as they may help an attacker uncover information about the remote Tomcat install or host itself.

See Also

<http://www.nessus.org/u?4cb3b4dd>

https://www.owasp.org/index.php/Securing_tomcat

Solution

Delete the default index page and remove the example JSP and servlets. Follow the Tomcat or OWASP instructions to replace or modify the default error page.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2004/03/02, Modified: 2024/09/03

Plugin Output

tcp/8282/www

The following default files were found :

```
http://172.30.2.102:8282/docs/
http://172.30.2.102:8282/examples/servlets/index.html
http://172.30.2.102:8282/examples/jsp/index.html
http://172.30.2.102:8282/examples/websocket/index.xhtmll
```

The server is not configured to return a custom page in the event of a client requesting a non-existent resource.
This may result in a potential disclosure of sensitive information about the server to attackers.

11213 - HTTP TRACE / TRACK Methods Allowed

Synopsis

Debugging functions are enabled on the remote web server.

Description

The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods that are used to debug web server connections.

See Also

<http://www.nessus.org/u?e979b5cb>

<http://www.apacheweek.com/issues/03-01-24>

<https://download.oracle.com/sunalerts/1000718.1.html>

Solution

Disable these HTTP methods. Refer to the plugin output for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.0

EPSS Score

0.6899

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	9506
BID	9561
BID	11604
BID	33374
BID	37995
CVE	CVE-2003-1567
CVE	CVE-2004-2320
CVE	CVE-2010-0386
XREF	CERT:288308
XREF	CERT:867593
XREF	CWE:16
XREF	CWE:200

Plugin Information

Published: 2003/01/23, Modified: 2024/04/09

Plugin Output

tcp/8585/www

To disable these methods, add the following lines for each virtual host in your configuration file :

```
RewriteEngine on
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

Alternatively, note that Apache versions 1.3.34, 2.0.55, and 2.2 support disabling the TRACE method natively via the 'TraceEnable' directive.

Nessus sent the following TRACE request : \n\n----- snip
-----\nTRACE /Nessus2126298666.html HTTP/1.1

Connection: Close
Host: 172.30.2.102
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip ----- \n\nand received the
following response from the remote server : \n\n----- snip
-----\nHTTP/1.1 200 OK

Date: Fri, 15 May 2026 00:52:58 GMT
Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: message/http

TRACE /Nessus2126298666.html HTTP/1.1
Connection: Keep-Alive
Host: 172.30.2.102

```
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n
```

90510 - MS16-047: Security Update for SAM and LSAD Remote Protocols (3148527) (Badlock) (uncredentialed check)

Synopsis

The remote Windows host is affected by an elevation of privilege vulnerability.

Description

The remote Windows host is affected by an elevation of privilege vulnerability in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A man-in-the-middle attacker able to intercept communications between a client and a server hosting a SAM database can exploit this to force the authentication level to downgrade, allowing the attacker to impersonate an authenticated user and access the SAM database.

See Also

<http://www.nessus.org/u?52ade1e9>

Solution

Microsoft has released a set of patches for Windows Vista, 2008, 7, 2008 R2, 2012, 8.1, RT 8.1, 2012 R2, and 10.

Risk Factor

Medium

CVSS v3.0 Base Score

6.8 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:N)

CVSS v3.0 Temporal Score

5.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.0

EPSS Score

0.6027

CVSS v2.0 Base Score

5.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

4.3 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

BID	86002
CVE	CVE-2016-0128
MSKB	3148527
MSKB	3149090
MSKB	3147461
MSKB	3147458
XREF	MSFT:MS16-047
XREF	CERT:813296
XREF	IAVA:2016-A-0093

Plugin Information

Published: 2016/04/13, Modified: 2026/01/30

Plugin Output

tcp/49157/dce-rpc

10546 - Microsoft Windows LAN Manager SNMP LanMan Users Disclosure

Synopsis

The list of LanMan users of the remote host can be obtained via SNMP.

Description

It is possible to obtain the list of LanMan users on the remote host by sending SNMP requests with the OID 1.3.6.1.4.1.77.1.2.25.1.1

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

VPR Score

3.4

EPSS Score

0.04

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-1999-0499

Plugin Information

Published: 2000/11/10, Modified: 2023/11/08

Plugin Output

udp/161/snmp

```
sshd
Guest
greedo
vagrant
han_solo
kylo_ren
boba_fett
chewbacca
ben_kenobi
jabba_hutt
artoo_detoo
c_three_pio
darth_vader
leia_organa
sshd_server
jarjar_binks
Administrator
luke_skywalker
anakin_skywalker
lando_calrissian
```

66842 - PHP 5.3.x < 5.3.26 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is potentially affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP 5.3.x installed on the remote host is prior to 5.3.26. It is, therefore, potentially affected by the following vulnerabilities:

- An error exists in the function 'php_quot_print_encode' in the file 'ext/standard/quot_print.c' that could allow a heap-based buffer overflow when attempting to parse certain strings (Bug #64879)
- An integer overflow error exists related to the value of 'JEWISH_SDN_MAX' in the file 'ext/calendar/jewish.c' that could allow denial of service attacks. (Bug #64895)

Note that this plugin does not attempt to exploit these vulnerabilities, but instead relies only on PHP's self-reported version number.

See Also

<http://www.nessus.org/u?60cbc5f0>

<http://www.nessus.org/u?8456482e>

<http://www.php.net/ChangeLog-5.php#5.3.26>

Solution

Apply the vendor patch or upgrade to PHP version 5.3.26 or later.

Risk Factor

Medium

VPR Score

3.6

EPSS Score

0.1877

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	60411
BID	60731
CVE	CVE-2013-2110
CVE	CVE-2013-4635

Plugin Information

Published: 2013/06/07, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.26
```

67259 - PHP 5.3.x < 5.3.27 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is potentially affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP 5.3.x installed on the remote host is prior to 5.3.27. It is, therefore, potentially affected by the following vulnerabilities:

- A buffer overflow error exists in the function '_pdo_pgsql_error'. (Bug #64949)
- A heap corruption error exists in numerous functions in the file 'ext/xml/xml.c'. (CVE-2013-4113 / Bug #65236)

Note that this plugin does not attempt to exploit these vulnerabilities, but instead relies only on PHP's self-reported version number.

See Also

<https://bugs.php.net/bug.php?id=64949>

<https://bugs.php.net/bug.php?id=65236>

<http://www.php.net/ChangeLog-5.php#5.3.27>

Solution

Apply the vendor patch or upgrade to PHP version 5.3.27 or later.

Risk Factor

Medium

VPR Score

3.4

EPSS Score

0.1902

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID 61128
CVE CVE-2013-4113

Plugin Information

Published: 2013/07/12, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.27
```

58966 - PHP < 5.3.11 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is earlier than 5.3.11, and as such is potentially affected by multiple vulnerabilities :

- During the import of environment variables, temporary changes to the 'magic_quotes_gpc' directive are not handled properly. This can lower the difficulty for SQL injection attacks. (CVE-2012-0831)
- The '\$_FILES' variable can be corrupted because the names of uploaded files are not properly validated. (CVE-2012-1172)
- The 'open_basedir' directive is not properly handled by the functions 'readline_write_history' and 'readline_read_history'.
- The 'header()' function does not detect multi-line headers with a CR. (Bug #60227 / CVE-2011-1398)

See Also

<http://www.nessus.org/u?e81d4026>
<https://bugs.php.net/bug.php?id=61043>
<https://bugs.php.net/bug.php?id=54374>
<https://bugs.php.net/bug.php?id=60227>
<https://marc.info/?l=oss-security&m=134626481806571&w=2>
<http://www.php.net/archive/2012.php#id2012-04-26-1>
<http://www.php.net/ChangeLog-5.php#5.3.11>

Solution

Upgrade to PHP version 5.3.11 or later.

Risk Factor

Medium

VPR Score

6.7

EPSS Score

0.1605

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	51954
BID	53403
BID	55297
CVE	CVE-2011-1398
CVE	CVE-2012-0831
CVE	CVE-2012-1172

Plugin Information

Published: 2012/05/02, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.11
```


152853 - PHP < 7.3.28 Email Header Injection

Synopsis

The version of PHP running on the remote web server is affected by an email header injection vulnerability.

Description

According to its self-reported version number, the version of PHP running on the remote web server is prior to 7.3.28.

It is, therefore affected by an email header injection vulnerability, due to a failure to properly handle CR-LF sequences in header fields. An unauthenticated, remote attacker can exploit this, by inserting line feed characters into email headers, to gain full control of email header content.

See Also

<https://www.php.net/ChangeLog-7.php#7.3.28>

Solution

Upgrade to PHP version 7.3.28 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2021/08/26, Modified: 2025/05/26

Plugin Output

tcp/8585/www

```
URL           : http://172.30.2.102:8585/ (5.3.10 under Server: Apache/2.2.21 (Win64)
PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10)
Installed version : 5.3.10
Fixed version    : 7.3.28
```

73289 - PHP PHP_RSHUTDOWN_FUNCTION Security Bypass

Synopsis

The remote web server uses a version of PHP that is potentially affected by a security bypass vulnerability.

Description

According to its banner, the version of PHP 5.x installed on the remote host is 5.x prior to 5.3.11 or 5.4.x prior to 5.4.1 and thus, is potentially affected by a security bypass vulnerability.

An error exists related to the function 'PHP_RSHUTDOWN_FUNCTION' in the libxml extension and the 'stream_close' method that could allow a remote attacker to bypass 'open_basedir' protections and obtain sensitive information.

Note that this plugin has not attempted to exploit this issue, but has instead relied only on PHP's self-reported version number.

See Also

<http://www.nessus.org/u?bcc428c2>

<https://bugs.php.net/bug.php?id=61367>

Solution

Upgrade to PHP version 5.3.11 / 5.4.1 or later.

Risk Factor

Medium

VPR Score

3.4

EPSS Score

0.0016

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID 65673
CVE CVE-2012-1171

Plugin Information

Published: 2014/04/01, Modified: 2024/11/22

Plugin Output

tcp/8585/www

```
Version source      : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2, X-Powered-By: PHP/5.3.10
Installed version   : 5.3.10
Fixed version       : 5.3.11 / 5.4.1
```

18405 - Remote Desktop Protocol Server Man-in-the-Middle Weakness

Synopsis

It may be possible to get access to the remote host.

Description

The remote version of the Remote Desktop Protocol Server (Terminal Service) is vulnerable to a man-in-the-middle (MiTM) attack. The RDP client makes no effort to validate the identity of the server when setting up encryption. An attacker with the ability to intercept traffic from the RDP server can establish encryption with the client and server without being detected. A MiTM attack of this nature would allow the attacker to obtain any sensitive information transmitted, including authentication credentials.

This flaw exists because the RDP server stores a publicly known hard-coded RSA private key. Any attacker in a privileged network location can use the key for this attack.

See Also

<http://www.nessus.org/u?8033da0d>

Solution

- Force the use of SSL as a transport layer for this service if supported, or/and
- On Microsoft Windows operating systems, select the 'Allow connections only from computers running Remote Desktop with Network Level Authentication' setting if it is available.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

VPR Score

2.5

EPSS Score

0.0427

CVSS v2.0 Base Score

5.1 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	13818
CVE	CVE-2005-1794

Plugin Information

Published: 2005/06/01, Modified: 2022/08/24

Plugin Output

tcp/3389/msrdp

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

187315 - SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795)

Synopsis

The remote SSH server is vulnerable to a mitm prefix truncation attack.

Description

The remote SSH server is vulnerable to a man-in-the-middle prefix truncation weakness known as Terrapin. This can allow a remote, man-in-the-middle attacker to bypass integrity checks and downgrade the connection's security.

Note that this plugin only checks for remote SSH servers that support either ChaCha20-Poly1305 or CBC with Encrypt-then-MAC and do not support the strict key exchange countermeasures. It does not check for vulnerable software versions.

See Also

<https://terrapin-attack.com/>

Solution

Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.5261

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE CVE-2023-48795

Plugin Information

Published: 2023/12/27, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Supports following ChaCha20-Poly1305 Client to Server algorithm : chacha20-  
poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com  
Supports following Encrypt-then-MAC Client to Server algorithm : umac-64-etm@openssh.com,umac-128-  
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-  
etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1  
Supports following ChaCha20-Poly1305 Server to Client algorithm : chacha20-  
poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openssh.com,aes256-gcm@openssh.com  
Supports following Encrypt-then-MAC Server to Client algorithm : umac-64-etm@openssh.com,umac-128-  
etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-  
etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/3389/msrdp

```
The following certificate was at the top of the certificate
chain sent by the remote host, but it is signed by an unknown
certificate authority :
```

```
| -Subject : CN=vagrant-2008R2
| -Issuer  : CN=vagrant-2008R2
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/8383/www

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject      : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop Central/  
E=support@desktopcentral.com  
| -Not After   : Sep 05 12:24:44 2020 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop Central/  
E=support@desktopcentral.com  
| -Issuer  : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop Central/  
E=support@desktopcentral.com
```

15901 - SSL Certificate Expiry

Synopsis

The remote server's SSL certificate has already expired.

Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

Solution

Purchase or generate a new SSL certificate to replace the existing one.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2004/12/03, Modified: 2025/12/08

Plugin Output

tcp/8383/www

The SSL certificate has already expired :

```
Subject      : C=US, ST=CA, L=Pleasanton, O=Zoho Corporation, OU=ManageEngine, CN=Desktop
Central, emailAddress=support@desktopcentral.com
Issuer       : C=US, ST=CA, L=Pleasanton, O=Zoho Corporation, OU=ManageEngine, CN=Desktop
Central, emailAddress=support@desktopcentral.com
Not valid before : Sep  8 12:24:44 2010 GMT
Not valid after  : Sep  5 12:24:44 2020 GMT
```

35291 - SSL Certificate Signed Using Weak Hashing Algorithm

Synopsis

An SSL certificate in the certificate chain has been signed using a weak hash algorithm.

Description

The remote service uses an SSL certificate chain that has been signed using a cryptographically weak hashing algorithm (e.g. MD2, MD4, MD5, or SHA1). These signature algorithms are known to be vulnerable to collision attacks. An attacker can exploit this to generate another certificate with the same digital signature, allowing an attacker to masquerade as the affected service.

Note that this plugin reports all SSL certificate chains signed with SHA-1 that expire after January 1, 2017 as vulnerable. This is in accordance with Google's gradual sunsetting of the SHA-1 cryptographic hash algorithm.

Note that certificates in the chain that are contained in the Nessus CA database (known_CA.inc) have been ignored.

See Also

<https://tools.ietf.org/html/rfc3279>
<http://www.nessus.org/u?9bb87bf2>
<http://www.nessus.org/u?e120eea1>
<http://www.nessus.org/u?5d894816>
<http://www.nessus.org/u?51db68aa>
<http://www.nessus.org/u?9dc7bfba>

Solution

Contact the Certificate Authority to have the SSL certificate reissued.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

4.2

0.0815

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

3.9 (CVSS2#E:POC/RL:OF/RC:C)

BID	11849
BID	33065
CVE	CVE-2004-2761
CVE	CVE-2005-4900
XREF	CERT:836068
XREF	CWE:310

Published: 2009/01/05, Modified: 2025/04/09

tcp/3389/msrdp

[illegible]

35291 - SSL Certificate Signed Using Weak Hashing Algorithm

Synopsis

An SSL certificate in the certificate chain has been signed using a weak hash algorithm.

Description

The remote service uses an SSL certificate chain that has been signed using a cryptographically weak hashing algorithm (e.g. MD2, MD4, MD5, or SHA1). These signature algorithms are known to be vulnerable to collision attacks. An attacker can exploit this to generate another certificate with the same digital signature, allowing an attacker to masquerade as the affected service.

Note that this plugin reports all SSL certificate chains signed with SHA-1 that expire after January 1, 2017 as vulnerable. This is in accordance with Google's gradual sunsetting of the SHA-1 cryptographic hash algorithm.

Note that certificates in the chain that are contained in the Nessus CA database (known_CA.inc) have been ignored.

See Also

<https://tools.ietf.org/html/rfc3279>
<http://www.nessus.org/u?9bb87bf2>
<http://www.nessus.org/u?e120eea1>
<http://www.nessus.org/u?5d894816>
<http://www.nessus.org/u?51db68aa>
<http://www.nessus.org/u?9dc7bfba>

Solution

Contact the Certificate Authority to have the SSL certificate reissued.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

4.2

EPSS Score

0.0815

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	11849
BID	33065
CVE	CVE-2004-2761
CVE	CVE-2005-4900
XREF	CERT:836068
XREF	CWE:310

Plugin Information

Published: 2009/01/05, Modified: 2025/04/09

Plugin Output

tcp/8383/www

The following certificates were part of the certificate chain sent by the remote host, but contain hashes that are considered to be weak.

```
Subject          : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop Central/
E=support@desktopcentral.com
Signature Algorithm : SHA-1 With RSA Encryption
Valid From       : Sep 08 12:24:44 2010 GMT
Valid To        : Sep 05 12:24:44 2020 GMT
Raw PEM certificate :
-----BEGIN CERTIFICATE-----
MIID3TCCA0agAwIBAgIJAPWc73Hm23K1MA0GCSqGSIb3DQEBBQUAMIGmMQswCQYDVQQGEwJVUzELMAkGA1UECBMCQ0ExEzARBgNVBAcTC1BsZWZzYW
+WAUuldwD3YKmlgJIoyFB0SuCkOngoUmkVmsPS/
+LvKN09bPCa1BR0IXCKOSz2k0AayLsx0vMs2X9Jt74gk3WQIg59WYwtpKKried63w86mMWRayHe2uEGFArzNIKseZ0PpcNSqGPwgwKGTfrDuyCeFpL
+f8zyBAnYqkN5OrIXXY5S4Eu/HjCB2wYDVR0jBIHTMIHQgBT+f8zyBAnYqkN5OrIXXY5S4Eu/
HqGBrKsBqTCBpjELMAkGA1UEBhMCVVMxCzAJBgNVBAGTAkNBMRMwEQYDVQQHEwpQbGVhc2FudG9uMRkwFwYDVQQKEXBab2hvIENvcnBvcmlF0aW9uMR
MA0GCSqGSIb3DQEBBQUAA4GBAEXoUjGeAGFqUEmrwcwKyJ3um3Yw+ViJWnuCtsiSipqlcj1Ip+/
P5SN7RRR2MUUiijiIZjnEguG7qr95qTuahPl8w+0nyfZVXm2yxkAwDSjuRP3pxAPUhkcxIA11jTnpeK3TCgX/Na
+eBNQCGT2LosP5A8aFT5yXOF7T/hxnZybr1
-----END CERTIFICATE-----
```

45411 - SSL Certificate with Wrong Hostname

Synopsis

The SSL certificate for this service is for a different host.

Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

Plugin Output

tcp/8383/www

```
The identities known by Nessus are :
```

```
172.30.2.102
172.30.2.102
```

```
The Common Name in the certificate is :
```

```
Desktop Central
```

Synopsis

The remote service supports the use of the RC4 cipher.

Description

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

See Also

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf

Solution

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

VPR Score

7.3

EPSS Score

0.9076

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:U/RL:ND/RC:C)

References

BID 58796
BID 73684
CVE CVE-2013-2566
CVE CVE-2015-2808

Plugin Information

Published: 2013/04/05, Modified: 2025/05/09

Plugin Output

tcp/3389/msrdp

List of RC4 cipher suites supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
RC4-MD5	0x00, 0x04	RSA	RSA	RC4 (128)	MD5
RC4-SHA	0x00, 0x05	RSA	RSA	RC4 (128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/3389/msrdp

```
The following certificate was found at the top of the certificate
chain sent by the remote host, but is self-signed and was not
found in the list of known certificate authorities :
```

```
| -Subject : CN=vagrant-2008R2
```

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/8383/www

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

```
| -Subject : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop Central/  
E=support@desktopcentral.com
```

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2026/04/13

Plugin Output

tcp/3389/msrdp

TLsv1 is enabled and the server supports at least one cipher.

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2026/04/13

Plugin Output

tcp/8383/www

TLsv1 is enabled and the server supports at least one cipher.

157288 - TLS Version 1.1 Deprecated Protocol

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://datatracker.ietf.org/doc/html/rfc8996>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2022/04/04, Modified: 2026/04/13

Plugin Output

tcp/8383/www

TLSv1.1 is enabled and the server supports at least one cipher.

58453 - Terminal Services Doesn't Use Network Level Authentication (NLA) Only

Synopsis

The remote Terminal Services doesn't use Network Level Authentication only.

Description

The remote Terminal Services is not configured to use Network Level Authentication (NLA) only. NLA uses the Credential Security Support Provider (CredSSP) protocol to perform strong server authentication either through TLS/SSL or Kerberos mechanisms, which protect against man-in-the-middle attacks. In addition to improving authentication, NLA also helps protect the remote computer from malicious users and software by completing user authentication before a full RDP connection is established.

See Also

[https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc732713\(v=ws.11\)](https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc732713(v=ws.11))

<http://www.nessus.org/u?e2628096>

Solution

Enable Network Level Authentication (NLA) on the remote RDP server. This is generally done on the 'Remote' tab of the 'System' settings on Windows.

Risk Factor

Medium

CVSS v3.0 Base Score

4.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:L/I:N/A:N)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2012/03/23, Modified: 2025/09/29

Plugin Output

tcp/3389/msrdp

```
Nessus was able to negotiate non-NLA (Network Level Authentication) security.
```

57690 - Terminal Services Encryption Level is Medium or Low

Synopsis

The remote host is using weak cryptography.

Description

The remote Terminal Services service is not configured to use strong cryptography.

Using weak cryptography with this service may allow an attacker to eavesdrop on the communications more easily and obtain screenshots and/or keystrokes.

Solution

Change RDP encryption level to one of :

- 3. High
- 4. FIPS Compliant

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2012/01/25, Modified: 2026/01/05

Plugin Output

tcp/3389/msrdp

```
The terminal services encryption level is set to :  
  
2. Medium
```

Synopsis

The remote Apache Tomcat server is affected by a vulnerability

Description

The version of Apache Tomcat installed on the remote host is 8.x prior to 8.5.78.

- The simplified implementation of blocking reads and writes introduced in Tomcat 10 and back-ported to Tomcat 9.0.47 onwards exposed a long standing (but extremely hard to trigger) concurrency bug in Apache Tomcat 10.1.0 to 10.1.0-M12, 10.0.0-M1 to 10.0.18, 9.0.0-M1 to 9.0.60 and 8.5.0 to 8.5.77 that could cause client connections to share an Http11Processor instance resulting in responses, or part responses, to be received by the wrong client. (CVE-2021-43980)

Note : these changes are to mitigate the effects of CVE-2022-22965.

See Also

<http://www.nessus.org/u?c41b6749>

<http://www.nessus.org/u?72f4365d>

Solution

Upgrade to Apache Tomcat version 8.5.78 or later.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

2.2

EPSS Score

0.0009

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2021-43980

XREF IAVA:2023-A-0534-S

Plugin Information

Published: 2022/04/01, Modified: 2024/05/06

Plugin Output

tcp/8282/www

```
Installed version : 8.0.33
Fixed version    : 8.5.78
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
This host returns non-standard timestamps (high bit is set)
```

The ICMP timestamps might be in little endian format (not in network format)
The difference between the local and remote clocks is -61 seconds.

83875 - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

Synopsis

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits.

Description

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party may be able to find the shared secret in a short amount of time (depending on modulus size and attacker resources). This may allow an attacker to recover the plaintext or potentially violate the integrity of connections.

See Also

<https://weakdh.org/>

Solution

Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

2.9

EPSS Score

0.9374

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	74733
CVE	CVE-2015-4000
XREF	CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/05/28, Modified: 2025/12/15

Plugin Output

tcp/8383/www

Vulnerable connection combinations :

```
SSL/TLS version   : TLSv1.0
Cipher suite      : TLS1_DHE_RSA_WITH_3DES_EDE_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Warning - This is a known static Oakley Group2 modulus. This may make
the remote host more vulnerable to the Logjam attack.
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version   : TLSv1.0
Cipher suite      : TLS1_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Warning - This is a known static Oakley Group2 modulus. This may make
the remote host more vulnerable to the Logjam attack.
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version   : TLSv1.0
Cipher suite      : TLS1_DHE_RSA_WITH_AES_128_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Warning - This is a known static Oakley Group2 modulus. This may make
the remote host more vulnerable to the Logjam attack.
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version   : TLSv1.0
Cipher suite      : TLS1_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Warning - This is a known static Oakley Group2 modulus. This may make
the remote host more vulnerable to the Logjam attack.
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version   : TLSv1.0
Cipher suite      : TLS1_DHE_RSA_WITH_AES_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Warning - This is a known static Oakley Group2 modulus. This may make
the remote host more vulnerable to the Logjam attack.
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version   : TLSv1.0
Cipher suite      : TLS1_DHE_RSA_WITH_AES_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Warning - This is a known static Oakley Group2 modulus. This may make
the remote host more vulnerable to the Logjam attack.
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS ver [...]
```

30218 - Terminal Services Encryption Level is not FIPS-140 Compliant

Synopsis

The remote host is not FIPS-140 compliant.

Description

The encryption setting used by the remote Terminal Services service is not FIPS-140 compliant.

Solution

Change RDP encryption level to :

4. FIPS Compliant

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2008/02/11, Modified: 2026/01/05

Plugin Output

tcp/3389/msrdp

```
The terminal services encryption level is set to :  
2. Medium (Client Compatible)
```

21186 - AJP Connector Detection

Synopsis

There is an AJP connector listening on the remote host.

Description

The remote host is running an AJP (Apache JServ Protocol) connector, a service by which a standalone web server such as Apache communicates over TCP with a Java servlet container such as Tomcat.

See Also

<http://tomcat.apache.org/connectors-doc/>

<http://tomcat.apache.org/connectors-doc/ajp/ajpv13a.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/04/05, Modified: 2019/11/22

Plugin Output

tcp/8009/ajp13

The connector listing on this port supports the ajp13 protocol.

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/8585/www

```
URL      : http://172.30.2.102:8585/
Version  : 2.2.21
Source   : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
backported : 0
modules  : PHP/5.3.10 DAV/2
os       : Win64
```


39446 - Apache Tomcat Detection

Synopsis

The remote web server is an Apache Tomcat server.

Description

Nessus was able to detect a remote Apache Tomcat web server.

NOTE: When paranoia levels are elevated, this plugin will also consider versions obtained from responses with non-200 HTTP status codes.

See Also

<https://tomcat.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0535

Plugin Information

Published: 2009/06/18, Modified: 2026/01/22

Plugin Output

tcp/8282/www

```
URL      : http://172.30.2.102:8282/
Version  : 8.0.33
backported : 0
source    : Apache Tomcat/8.0.33
```

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

```
Give Nessus credentials to perform local checks.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :
```

```
cpe:/o:microsoft:windows_server_2008:r2:sp1 -> Microsoft Windows Server 2008
```

```
Following application CPE's matched on the remote system :
```

```
cpe:/a:apache:http_server:2.2.21 -> Apache Software Foundation Apache HTTP Server
```

```
cpe:/a:apache:tomcat:8.0.33 -> Apache Software Foundation Tomcat
```

```
cpe:/a:mysql:mysql -> MySQL MySQL
```

```
cpe:/a:openbsd:openssh:7.1 -> OpenBSD OpenSSH
```

```
cpe:/a:php:php:5.3.10 -> PHP PHP
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/135/epmap

The following DCERPC services are available locally :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WindowsShutdown

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WMsgKRpc037890

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WindowsShutdown

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WMsgKRpc037890

Object UUID : 6d726574-7273-0076-0000-000000000000
UUID : c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1.0

Description : Unknown RPC service
Annotation : Impl friendly name
Type : Local RPC service
Named pipe : LRPC-50e774b4d3fd4146b6

Object UUID : 52ef130c-08fd-4388-86b3-6edf00000001
UUID : 12e65dd8-887f-41ef-91bf-8d816c42c2e7, version 1.0
Description : Unknown RPC service
Annotation : Secure Desktop LRPC interface
Type : Local RPC service
Named pipe : WMsgKRpc03C5B1

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000001
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WMsgKRpc03C5B1

Object UUID : c994fbc7-49f0-4d12-8ed1-83bb0c2a7364
UUID : 906b0ce0-c70b-1067-b317-00dd010662da, version 1.0
Description : Distributed Transaction Coordinator
Windows process : msdtc.exe
Type : Local RPC service
Named pipe : LRPC-6ad93882809d808b97

Object UUID : 975bc5c1-4faa-4331-8018-da0e8cbb1e2b
UUID : 906b0ce0-c70b-1067-b317-00dd010662da, version 1.0
Description : Distributed Transaction Coordinator
Windows process : msdtc.exe
Type : Local RPC service
Named pipe : LRPC-6ad93882809d808b97

Object UUID : 3c608e97-e225-403d-93d7 [...]

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/445/cifs

The following DCERPC services are available remotely :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\InitShutdown
Netbios name : \\VAGRANT-2008R2

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\InitShutdown
Netbios name : \\VAGRANT-2008R2

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service
Named pipe : \pipe\lsass
Netbios name : \\VAGRANT-2008R2

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe

Type : Remote RPC service
Named pipe : \PIPE\protected_storage
Netbios name : \\VAGRANT-2008R2

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\VAGRANT-2008R2

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\VAGRANT-2008R2

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\VAGRANT-2008R2

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : a398e520-d59a-4bdd-aa7a-3c1e0303a511, version 1.0
Description : Unknown RPC service
Annotation : IKE/Authip API
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\VAGRANT-2008R2

Object U [...]

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49152/dce-rpc

The following DCERPC services are available on TCP port 49152 :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49152
IP : 172.30.2.102

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49153/dce-rpc

The following DCERPC services are available on TCP port 49153 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Event log TCPIP
Type : Remote RPC service
TCP Port : 49153
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 30adc50c-5cbc-46ce-9a0e-91914789e23c, version 1.0
Description : Unknown RPC service
Annotation : NRP server endpoint
Type : Remote RPC service
TCP Port : 49153
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d6, version 1.0
Description : Unknown RPC service
Annotation : DHCPv6 Client LRPC Endpoint
Type : Remote RPC service
TCP Port : 49153
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d5, version 1.0

Description : DHCP Client Service
Windows process : svchost.exe
Annotation : DHCP Client LRPC Endpoint
Type : Remote RPC service
TCP Port : 49153
IP : 172.30.2.102

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49154/dce-rpc

The following DCERPC services are available on TCP port 49154 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49154
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : a398e520-d59a-4bdd-aa7a-3c1e0303a511, version 1.0
Description : Unknown RPC service
Annotation : IKE/Authip API
Type : Remote RPC service
TCP Port : 49154
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 552d076a-cb29-4e44-8b6a-d15e59e2c0af, version 1.0
Description : Unknown RPC service
Annotation : IP Transition Configuration endpoint
Type : Remote RPC service
TCP Port : 49154
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 98716d03-89ac-44c7-bb8c-285824e51c4a, version 1.0
Description : Unknown RPC service

Annotation : XactSrv service
Type : Remote RPC service
TCP Port : 49154
IP : 172.30.2.102

Object UUID : 73736573-6f69-656e-6e76-000000000000
UUID : c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1.0
Description : Unknown RPC service
Annotation : Impl friendly name
Type : Remote RPC service
TCP Port : 49154
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 30b044a5-a225-43f0-b3a4-e060df91f9c1, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49154
IP : 172.30.2.102

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49157/dce-rpc

The following DCERPC services are available on TCP port 49157 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service
TCP Port : 49157
IP : 172.30.2.102
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49178/dce-rpc

The following DCERPC services are available on TCP port 49178 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 367abb81-9844-35f1-ad32-98f038001003, version 2.0
Description : Service Control Manager
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 49178
IP : 172.30.2.102

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49239/dce-rpc

The following DCERPC services are available on TCP port 49239 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 6b5bdd1e-528c-422c-af8c-a4079be4fe48, version 1.0
Description : Unknown RPC service
Annotation : Remote Fw APIs
Type : Remote RPC service
TCP Port : 49239
IP : 172.30.2.102

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345678-1234-abcd-ef00-0123456789ab, version 1.0
Description : IPsec Services (Windows XP & 2003)
Windows process : lsass.exe
Annotation : IPsec Policy agent endpoint
Type : Remote RPC service
TCP Port : 49239
IP : 172.30.2.102

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 99
```


35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

The following card manufacturers were identified :

08:00:27:D7:CC:D8 : PCS Systemtechnik GmbH

5C:6D:20:52:41:53 : Hon Hai Precision Ind. Co.,Ltd.

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 08:00:27:D7:CC:D8  
- 5C:6D:20:52:41:53
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8282/www

```
The remote web server type is :  
Apache-Coyote/1.1
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8585/www

```
The remote web server type is :  
Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8282/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : no

Options allowed : GET, HEAD, POST, PUT, DELETE, OPTIONS

Headers :

Server: Apache-Coyote/1.1

Content-Type: text/html; charset=UTF-8

Transfer-Encoding: chunked

Date: Fri, 15 May 2026 00:56:11 GMT

Response Body :

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
  <head>
```

```
    <meta charset="UTF-8" />
```

```
    <title>Apache Tomcat/8.0.33</title>
```

```
    <link href="favicon.ico" rel="icon" type="image/x-icon" />
```

```
    <link href="favicon.ico" rel="shortcut icon" type="image/x-icon" />
```

```
    <link href="tomcat.css" rel="stylesheet" type="text/css" />
```

```
  </head>
```

```
</body>
```

```

    <div id="wrapper">
      <div id="navigation" class="curved container">
        <span id="nav-home"><a href="http://tomcat.apache.org/">Home</a></span>
        <span id="nav-hosts"><a href="/docs/">Documentation</a></span>
        <span id="nav-config"><a href="/docs/config/">Configuration</a></span>
        <span id="nav-examples"><a href="/examples/">Examples</a></span>
        <span id="nav-wiki"><a href="http://wiki.apache.org/tomcat/FrontPage">Wiki</a></
span>
        <span id="nav-lists"><a href="http://tomcat.apache.org/lists.html">Mailing Lists</
a></span>
        <span id="nav-help"><a href="http://tomcat.apache.org/findhelp.html">Find Help</a></
span>
        <br class="separator" />
      </div>
      <div id="asf-box">
        <h1>Apache Tomcat/8.0.33</h1>
      </div>
      <div id="upper" class="curved container">
        <div id="congrats" class="curved container">
          <h2>If you're seeing this, you've successfully installed Tomcat.
Congratulations!</h2>
        </div>
        <div id="notice">
          
          <div id="tasks">
            [...]

```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8585/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Fri, 15 May 2026 00:56:11 GMT

Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2

X-Powered-By: PHP/5.3.10

Content-Length: 4462

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

```
<?xml version="1.0" encoding="iso-8859-1"?>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
```

```
"http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
```

```
<html lang="en" xml:lang="en">
```

```
<head>
```

```
<title>WAMPSEVER Homepage</title>
```

```
<meta http-equiv="Content-Type" content="text/html; charset=utf-8" />
```

```

<style type="text/css">
* {
margin: 0;
padding: 0;
}
html {
background: #ddd;
}
body {
margin: 1em 10%;
padding: 1em 3em;
font: 80%/1.4 tahoma, arial, helvetica, lucida sans, sans-serif;
border: 1px solid #999;
background: #eee;
position: relative;
}
#head {
margin-bottom: 1.8em;
margin-top: 1.8em;
padding-bottom: 0em;
border-bottom: 1px solid #999;
letter-spacing: -500em;
text-indent: -500em;
height: 125px;
background: url(index.php?img=gifLogo) 0 0 no-repeat;
}
.utility {
position: absolute;
right: 4em;
top: 145px;
font-size: 0.85em;
}
.utility li {
display: inline;
}
h2 {
margin: 0.8em 0 0 0;
}
ul {
list-style: none;
margin: 0;
padding: 0;
}
#head ul li, dl ul li, #foot li {
list-style: none;
display: inline;
margin: 0;
padding: 0 0.2em;
}
ul.vhosts, ul.aliases, ul.projects, ul.tools {
list-style: none;
line-height: 24px;
}
ul.vhosts a, ul.aliases a, ul.projects a, ul.tools a {
padding-left: 22px;
background: url(index.php?img=pngFolder) 0 100% no-repeat;
}
ul.tools a {
background: url(index.php?img=pngWrench) 0 100% no-repeat;
}
ul.aliases a {
background: url(index.php?img=pngFolderGo) 0 100% no-repeat;
}
ul.vhosts a {
background: url(index.php?img=pngFolderGo) 0 100% no-repeat;
}
dl {
ma [...]

```


53513 - Link-Local Multicast Name Resolution (LLMNR) Detection

Synopsis

The remote device supports LLMNR.

Description

The remote device answered to a Link-local Multicast Name Resolution (LLMNR) request. This protocol provides a name lookup service similar to NetBIOS or DNS. It is enabled by default on modern Windows versions.

See Also

<http://www.nessus.org/u?51eae65d>

<http://technet.microsoft.com/en-us/library/bb878128.aspx>

Solution

Make sure that use of this software conforms to your organization's acceptable use and security policies.

Risk Factor

None

Plugin Information

Published: 2011/04/21, Modified: 2023/10/17

Plugin Output

udp/5355/llmnr

```
According to LLMNR, the name of the remote host is 'vagrant-2008R2'.
```

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Windows Server 2008 R2 Standard 7601 Service Pack 1
The remote native LAN manager is : Windows Server 2008 R2 Standard 6.1
The remote SMB Domain Name is : VAGRANT-2008R2
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
  SMBv1  
  SMBv2
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host supports the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7

The remote host does NOT support the following SMB dialects :
_version_  _introduced in windows version_
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

Plugin Output

tcp/3306/mysql

```
Service : mysql  
Version : unknown
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/0

```
Nessus SNMP scanner was able to retrieve the open port list  
with the community name: p*****  
It found 17 open TCP ports and 9 open UDP ports.
```


14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/135/epmap

```
Port 135/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/137/netbios-ns

```
Port 137/udp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/138

```
Port 138/udp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/139/smb

```
Port 139/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/161/snmp

```
Port 161/udp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/500

```
Port 500/udp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```


14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/3389/msrdp

```
Port 3389/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/4500

```
Port 4500/udp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/5353

```
Port 5353/udp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/5355/llmnr

```
Port 5355/udp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/8009/ajp13

```
Port 8009/tcp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/8020/www

```
Port 8020/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/8027

```
Port 8027/tcp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/8282/www

```
Port 8282/tcp was found to be open
```


Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/8383/www

```
Port 8383/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/8585/www

```
Port 8585/tcp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/33848

```
Port 33848/udp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/49152/dce-rpc

```
Port 49152/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/49153/dce-rpc

```
Port 49153/tcp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/49154/dce-rpc

```
Port 49154/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/49157/dce-rpc

```
Port 49157/tcp was found to be open
```

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/49178/dce-rpc

```
Port 49178/tcp was found to be open
```


14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

tcp/49239/dce-rpc

```
Port 49239/tcp was found to be open
```

14274 - Nessus SNMP Scanner

Synopsis

SNMP information is enumerated to learn about other open ports.

Description

This plugin runs an SNMP scan against the remote machine to find open ports.

See the section 'plugins options' to configure it.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2023/11/08

Plugin Output

udp/54328

```
Port 54328/udp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.0
Nessus build : 20184
Plugin feed version : 202605141537
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : debian10-x86-64
Scan type : Normal
Scan name : Metasploitable3 Vulnerability Scan
```

```
Scan policy used : Basic Network Scan
Scanner IP : 172.30.2.100
Port scanner(s) : snmp_scanner
Port range : default
Ping RTT : 63.719 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/14 20:49 EDT (UTC -04:00)
Scan duration : 954 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Microsoft Windows Server 2012 R2
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Microsoft Windows 7
Microsoft Windows Server 2008 R2
Confidence level : 70
Method : Misc
Type : general-purpose
Fingerprint : unknown

Remote operating system : Microsoft Windows 7
Microsoft Windows Server 2008 R2
Confidence level : 75
Method : SNMP
Type : general-purpose
Fingerprint : SNMP:Hardware: AMD64 Family 25 Model 80 Stepping 0 AT/AT COMPATIBLE - Software:
Windows Version 6.1 (Build 7601 Multiprocessor Free)

Remote operating system : Microsoft Windows XP Professional
Microsoft Windows Server 2008 R2
Microsoft Windows 10
Confidence level : 66
Method : RDP

Type : general-purpose
Fingerprint : RDP:000000000f00000010000100080001000900000001001000100010

Remote operating system : Microsoft Windows
Confidence level : 70
Method : SinFP

Type : general-purpose
Fingerprint : SinFP:
P1:B11113:F0x12:W8192:00204ffff:M1460:
P2:B11113:F0x12:W8192:00204ffff010303080402080affffffff44454144:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191800_7_p=49239

Remote operating system : Windows 6.1
Confidence level : 70
Method : smb
Type : general-purpose
Fingerprint : unknown

Remote operating system : Microsoft Windows Server 2008 R2 Standard Service Pack 1
Confidence level : 99
Method : MSRPC
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :
SSH:!:SSH-2.0-OpenSSH_7.1
HTTP:!:Server: Apache

SSLcert:!:i/CN:Desktop Centrali/O:Zoho Corporationi/OU:ManageEngines/CN:Desktop Centrals/O:Zoho
Corporations/OU:ManageEngine
701e2e6df8854c4f0b298dff03a2c6f0bac7d315
i/CN:vagrant-2008R2s/CN:vagrant-2008R2
e37e2d46f2642e4b3459c4e9700cfb125ef3435c

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Microsoft Windows Server 2008 R2 Standard Service Pack 1
Confidence level : 99
Method : MSRPC
```

```
The remote host is running Microsoft Windows Server 2008 R2 Standard Service Pack 1
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SMB service.
```


181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/05/05

Plugin Output

tcp/22/ssh

```
Service      : ssh
Version      : 7.1
Banner       : SSH-2.0-OpenSSH_7.1
backported   : 1
```

50845 - OpenSSL Detection

Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

Plugin Output

tcp/8383/www

48243 - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2026/01/22

Plugin Output

tcp/8585/www

Nessus was able to identify the following PHP version information :

```
Version : 5.3.10
Source  : Server: Apache/2.2.21 (Win64) PHP/5.3.10 DAV/2
Source  : X-Powered-By: PHP/5.3.10
Backported : 0
```

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/05/12

Plugin Output

tcp/0

```
. You need to take the following 5 actions :
```

```
[ Apache 2.4.x < 2.4.59 Multiple Vulnerabilities (192923) ]
```

```
+ Action to take : Upgrade to Apache version 2.4.59 or later.
```

```
+Impact : Taking this action will resolve 51 different vulnerabilities (CVEs).
```

```
[ Apache Tomcat 8.x < 8.5.78 Spring4Shell CVE-2021-43980 (159462) ]
```

```
+ Action to take : Upgrade to Apache Tomcat version 8.5.78 or later.
```

```
+Impact : Taking this action will resolve 20 different vulnerabilities (CVEs).
```

```
[ Microsoft RDP RCE (CVE-2019-0708) (BlueKeep) (uncredentialed check) (125313) ]
```

```
+ Action to take : Microsoft has released a set of patches for Windows XP, 2003, 2008, 7, and 2008 R2.
```

```
+Impact : Taking this action will resolve 2 different vulnerabilities (CVEs).
```

[PHP 5.3.x < 5.3.29 Multiple Vulnerabilities (77285)]

+ Action to take : Upgrade to PHP version 5.3.29 or later.

+Impact : Taking this action will resolve 35 different vulnerabilities (CVEs).

[SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) (187315)]

+ Action to take : Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Synopsis

It is possible to take a screenshot of the remote login screen.

Description

This script attempts to connect to the remote host via RDP (Remote Desktop Protocol) and attempts to take a screenshot of the login screen.

While this is not a vulnerability by itself, some versions of Windows display the names of the users who can connect and which ones are connected already.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/04/22, Modified: 2026/04/22

Plugin Output

tcp/3389/msrdp

```
It was possible to gather the following screenshot of the remote login screen.
```

10940 - Remote Desktop Protocol Service Detection

Synopsis

The remote host has an remote desktop protocol service enabled.

Description

The Remote Desktop Protocol allows a user to remotely obtain a graphical login (and therefore act as a local user on the remote host).

If an attacker gains a valid login and password, this service could be used to gain further access on the remote host. An attacker may also use this service to mount a dictionary attack against the remote host to try to log in remotely.

Note that RDP (the Remote Desktop Protocol) is vulnerable to Man-in-the-middle attacks, making it easy for attackers to steal the credentials of legitimate users by impersonating the Windows server.

Solution

Disable the service if you do not use it, and do not allow this service to run across the Internet.

Risk Factor

None

Plugin Information

Published: 2002/04/20, Modified: 2023/08/21

Plugin Output

tcp/3389/msrdp

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

```
The target SSH server offers no post-quantum ciphers.
```


277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>
<http://www.nessus.org/u?ad7d6b3b>
<http://www.nessus.org/u?1c0c61e0>
<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/3389/msrdp

```
The target TLS server offers no post-quantum ciphers.
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

`tcp/8383/www`

```
The target TLS server offers no post-quantum ciphers.
```

35296 - SNMP Protocol Version Detection

Synopsis

This plugin reports the protocol version negotiated with the remote SNMP agent.

Description

By sending an SNMP 'get-next-request', it is possible to determine the protocol version of the remote SNMP agent.

See Also

https://en.wikipedia.org/wiki/Simple_Network_Management_Protocol

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2009/01/06, Modified: 2019/11/22

Plugin Output

udp/161/snmp

```
Nessus has negotiated SNMP communications at SNMPv2c.
```

19763 - SNMP Query Installed Software Disclosure

Synopsis

The list of software installed on the remote host can be obtained via SNMP.

Description

It is possible to obtain the list of installed software on the remote host by sending SNMP requests with the OID 1.3.6.1.2.1.25.6.3.1.2

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2005/09/20, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
7-Zip 22.01 (x64)
OpenSSH for Windows 7.1p1-1 (remove only)
Oracle VM VirtualBox Guest Additions 6.0.8
Microsoft .NET Framework 4.5.2
Java 8 Update 251 (64-bit)
Microsoft Visual C++ 2008 Redistributable - x64 9.0.30729.6161
Java SE Development Kit 8 Update 211 (64-bit)
Microsoft .NET Framework 4.5.2
```

34022 - SNMP Query Routing Information Disclosure

Synopsis

The list of IP routes on the remote host can be obtained via SNMP.

Description

It is possible to obtain the routing information on the remote host by sending SNMP requests with the OID 1.3.6.1.2.1.4.21

An attacker may use this information to gain more knowledge about the network topology.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2008/08/21, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
127.0.0.0/255.0.0.0
127.0.0.1/255.255.255.255
127.255.255.255/255.255.255.255
172.30.2.0/255.255.255.0
172.30.2.102/255.255.255.255
172.30.2.255/255.255.255.255
224.0.0.0/240.0.0.0
255.255.255.255/255.255.255.255
```

10550 - SNMP Query Running Process List Disclosure

Synopsis

The list of processes running on the remote host can be obtained via SNMP.

Description

It is possible to obtain the list of running processes on the remote host by sending SNMP requests with the OID 1.3.6.1.2.1.25.4.2.1.2

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2000/11/13, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
PID    CPU    MEM  COMMAND                ARGS
  1     813    24   System Idle Process
  4      16   300   System
128      0  17696 dcserverhttpd.exe -d C:/ManageEngine/DesktopCentral_Server/apache
204      0  16296 svchost.exe
252      0   1076 smss.exe
324      0   4184 csrss.exe      ObjectDirectory=\Windows SharedSection=1024,20480,768 Windows=On
SubSystemType=Windows ServerDll=basesrv,1 ServerDll=winsrv:User
376      0   4364 wininit.exe
388      0   4848 csrss.exe      ObjectDirectory=\Windows SharedSection=1024,20480,768 Windows=On
SubSystemType=Windows ServerDll=basesrv,1 ServerDll=winsrv:User
424      0   4896 winlogon.exe
472      0   8072 services.exe
480      0  11708 lsass.exe
488      0   5756 lsm.exe
572      0   4436 svchost.exe
584      0   8772 svchost.exe
600      0  10956 svchost.exe
620      0   7504 msdtc.exe
648      0   5480 VBoxService.exe
716      0   7056 svchost.exe
776      0  13324 svchost.exe
848      0  29924 svchost.exe
888      0   3508 dcrotatologs.exe -l C:/ManageEngine/DesktopCentral_Server/logs/apache_errorlog_%Y-
%m-%d-%H_%M.txt 5M
904      0  10052 svchost.exe
```

```

936      0  2700 conhost.exe
940      0  4296 dwm.exe
948      0 25924 explorer.exe
984      0 10432 svchost.exe
1176     0  2712 conhost.exe
1200     0  3528 dcrotatelog.exe -l C:/ManageEngine/DesktopCentral_Server/logs/apache_errorlog_%Y-
%Y-%m-%d-%H_%M.txt 5M
1220     0 10744 spoolsv.exe
1260     0  8940 svchost.exe
1300     0  7752 wrapper.exe
1364     0  2724 conhost.exe
1376     0 15008 domain1Service.exe
1436     4 230692 elasticsearch-service-x64.exe //RS//elasticsearch-service-x64
1444     0  2632 conhost.exe
1476     0  8852 svchost.exe
1500     3 50652 jenkins.exe
1512     0  2948 cmd.exe /c ""C:/glassfish/glassfish4/glassfish/lib/nadmin.bat" start-
domain --watchdog --domain C:\glassfish\glassfish4\glassfish
1520     0  2732 conh [...]

```

10800 - SNMP Query System Information Disclosure

Synopsis

The System Information of the remote host can be obtained via SNMP.

Description

It is possible to obtain the system information about the remote host by sending SNMP requests with the OID 1.3.6.1.2.1.1.1.

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2001/11/06, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
System information :
sysDescr      : Hardware: AMD64 Family 25 Model 80 Stepping 0 AT/AT COMPATIBLE - Software: Windows
Version 6.1 (Build 7601 Multiprocessor Free)
sysObjectID   : 1.3.6.1.4.1.311.1.1.3.1.2
sysUptime     : 0d 0h 0m 43s
sysContact    :
sysName       : vagrant-2008R2
sysLocation   :
sysServices   : 76
```


10551 - SNMP Request Network Interfaces Enumeration

Synopsis

The list of network interfaces cards of the remote host can be obtained via SNMP.

Description

It is possible to obtain the list of the network interfaces installed on the remote host by sending SNMP requests with the OID 1.3.6.1.2.1.2.1.0

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2000/11/13, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
Interface 1 information :  
ifIndex      : 1  
ifDescr      : Software Loopback Interface 1
```

185519 - SNMP Server Detection

Synopsis

An SNMP server is listening on the remote host.

Description

The remote service is an SNMP agent which provides management data about the device.

See Also

https://en.wikipedia.org/wiki/Simple_Network_Management_Protocol

Solution

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

Risk Factor

None

Plugin Information

Published: 2023/11/14, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
Nessus detected the following SNMP versions:  
- SNMPv1 (public community)  
- SNMPv1 (configured community)  
- SNMPv2c (public community)  
- SNMPv2c (configured community)
```

40448 - SNMP Supported Protocols Detection

Synopsis

This plugin reports all the protocol versions successfully negotiated with the remote SNMP agent.

Description

Extend the SNMP settings data already gathered by testing for\ SNMP versions other than the highest negotiated.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/07/31, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
Nessus detected the following SNMP versions:  
- SNMPv2c  
- SNMPv1
```

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ecdsa-sha2-nistp521
ssh-rsa
```

```
The server supports the following options for encryption_algorithms_client_to_server :
```

```
aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com
```

The server supports the following options for `mac_algorithms_server_to_client` :

```
hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

The server supports the following options for `kex_algorithms` :

```
curve25519-sha256@libssh.org
diffie-hellman-group-exchange-sha256
diffie-hellman-group14-sha1
ecdh-sha2-nistp256
ecdh-sha2-nistp384
ecdh-sha2-nistp521
```

The server supports the following options for `compression_algorithms_client_to_server` :

```
none
zlib@openssh.com
```

The server supports the following options for `encryption_algorithms_server_to_client` :

```
aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the  
SSH protocol :
```

- 1.99
- 2.0

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_7.1
SSH supported authentication : publickey,password,keyboard-interactive
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/3389/msrdp

```
This port supports TLSv1.0.
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/8383/www

```
This port supports TLSv1.0/TLSv1.1/TLSv1.2.
```

45410 - SSL Certificate 'commonName' Mismatch

Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

Risk Factor

None

Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

Plugin Output

tcp/8383/www

```
The host name known by Nessus is :
```

```
vagrant-2008r2
```

```
The Common Name in the certificate is :
```

```
desktop central
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/3389/msrdp

```
Subject Name:

Common Name: vagrant-2008R2

Issuer Name:

Common Name: vagrant-2008R2

Serial Number: 7B E3 C9 2E F7 4B B9 9B 45 24 52 DD 48 B9 43 3E

Version: 3

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: May 12 02:22:28 2026 GMT
Not Valid After: Nov 11 02:22:28 2026 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 B0 A6 24 17 10 39 F2 F3 76 FC 04 EE FE 6D C2 7D 5E AA F6
             EA 21 F6 28 36 42 63 1E 01 25 B0 CB 05 9A 47 9D A7 D9 70 6C
             FF E2 AB E4 A3 DE 67 C6 02 E5 FA 27 71 66 27 19 05 59 3D 2E
             06 B1 F7 82 A5 62 B4 72 6F 03 87 F0 62 02 FD 99 7C A4 1F 2D
             D0 DF 12 75 00 1B 6F 36 6E 76 A6 D8 87 D8 0D 10 FA B7 CA 32
             7D 50 86 49 16 B1 7B 15 40 07 23 4B A0 E2 84 D2 6D A7 28 D3
             55 75 CA B2 41 FC 2E 85 E3 D0 66 12 42 AB 99 21 6F E8 A6 62
             9C C9 22 B8 55 D1 3E 93 0C 3B 7B C1 0D 17 8B 45 59 CB 18 67
             D5 3A 7D 26 A8 4E DC D2 57 3B 81 4B A1 37 EC 3D 18 5C 32 9B
             08 D5 D5 32 DB 8F C4 41 4A 44 9F E5 ED 7F E8 F6 D8 52 3F 26
             EA 68 D3 0D 23 2B A2 AE 8E 85 87 3E AA C8 64 A2 A0 30 F0 DC
```

```
15 2B D8 3E 38 DB 40 D2 AC 05 9F 89 35 36 0F FB C5 01 AD C7
AD 19 8A 2C 35 DF 45 96 40 46 E8 61 5F CD 5A F9 D7
Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits
Signature: 00 21 28 75 4B 66 66 AC F3 84 8D 9C 85 7A 8D 71 0A FF EB 64
           CC A1 17 16 62 33 B5 F5 9B C9 F5 5D 4E 01 C3 8A 8A A0 7E 7F
           3F 2A 29 B5 97 26 8D 15 4F 0E EB 70 52 23 43 8E E1 8C C4 5B
           5E AF 14 7D DB EC B3 B5 D4 6C 57 21 3C 82 D1 37 C5 6D 47 E4
           CE 86 82 6E AA 5C 39 9D 5F 3A 23 B3 05 29 FD DA C7 9D 7B 1B
           C8 0E BC 67 22 BB 8E 76 6E 47 4E F1 59 C1 08 60 92 F6 2E 33
           EF 3C 2F 68 7B 1F 09 DF 6A 2D 6E 17 6F DB D1 57 EE 14 E0 33
           FE A5 F2 C1 12 74 91 86 74 F6 FD FB D0 06 B9 D7 CD 5F FD E8
           54 43 5F 8F F7 CA D1 E4 4B A5 5A D8 FA C2 68 0B A4 0F 36 8C
           B6 72 61 A9 55 A6 54 B [...]
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/8383/www

```
Subject Name:

Country: US
State/Province: CA
Locality: Pleasanton
Organization: Zoho Corporation
Organization Unit: ManageEngine
Common Name: Desktop Central
Email Address: support@desktopcentral.com

Issuer Name:

Country: US
State/Province: CA
Locality: Pleasanton
Organization: Zoho Corporation
Organization Unit: ManageEngine
Common Name: Desktop Central
Email Address: support@desktopcentral.com

Serial Number: 00 F5 9C EF 71 E6 DB 72 A5

Version: 3

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Sep 08 12:24:44 2010 GMT
Not Valid After: Sep 05 12:24:44 2020 GMT

Public Key Info:

Algorithm: RSA Encryption
```

```
Key Length: 1024 bits
Public Key: 00 F9 60 14 BA 57 70 0F 76 0A 9A 58 09 22 8C 85 07 44 AE 0A
            43 A7 82 85 26 91 59 AC 3D 2F FE 2E F2 8D D3 D6 CF 09 AD 41
            47 42 17 08 A3 92 CF 69 0E 01 AC 8B B3 1D 2F 32 CD 97 F4 9B
            7B E2 09 37 59 02 20 E7 D5 98 C2 DA 4A 2A B8 9E 77 AD F0 F3
            A9 8C 59 16 B2 1D ED AE 10 61 40 AF 33 48 2A C7 99 D0 FA 5C
            35 2A 86 3F 08 30 28 64 DF AC 3B B2 09 E1 69 0C 83 95 DB 81
            35 A5 48 B0 5E 06 0D 20 33
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 45 E8 52 31 9E 00 61 6A 50 49 AB C1 CC 0A C8 9D EE 9B 76
            30 F9 58 89 5A 7B 82 B6 C8 92 8A 9A A5 72 3D 48 A7 EF CF E5
            23 7B 45 14 76 31 45 22 8E 22 19 8E 71 20 B8 6E EA AF DE 6A
            4E E6 A1 3E 5F 30 FB 49 F2 7D 95 57 9B 6C B1 90 0C 03 4A 3B
            91 3F 7A 71 00 F5 21 91 C5 E2 03 5D 63 4E 7A 5E 2B 74 C2 81
            7F CD 6B E7 81 35 00 86 4F 62 E8 B0 FE 40 F1 A1 53 E7 25 CE
            17 B4 FF 87 19 D9 C9 BA F5

Extension: Subject Key Identifier(2.5.29.14)
Critical: 0
Subject Key Identifier: FE 7F CC F2 04 09 D8 AA 43 79 3A B2 17 5D 8E 52 E0 4B BF 1E

Extension: Authority Key Identifier(2.5.29.35)
Critical: 0
Key Identifier: FE 7F CC F2 04 09 D8 AA 43 79 3A B2 17 5D 8E 52 E0 4B BF 1E
Country: US
State/Province: CA
Locality: Pleasanton
Organization: Zoho Corporation
Organization [...]
```


70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/3389/msrdp

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

SHA1

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC (128)	
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC (256)	

SHA1

AES128-SHA SHA1	0x00, 0x2F	RSA	RSA	AES-CBC(128)
AES256-SHA SHA1	0x00, 0x35	RSA	RSA	AES-CBC(256)

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/8383/www

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC (168)	
SHA1					
ECDHE-RSA-DES-CBC3-SHA	0xC0, 0x12	ECDHE	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---

DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x67	DHE	RSA	AES-CBC(128)
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)
DHE-RSA-AES256-SHA256 SHA256	0x00, 0x6B	DHE	RSA	AES-CBC(256)
DHE-RSA-CAMELLIA128-SHA SHA1	0x00, 0x45	DHE	RSA	Camellia-CBC(128)
DHE-RSA-CAMELLIA256-SHA SHA1	0x00, 0x88	DHE	RSA	Camellia-CBC(256)
ECDHE-RSA-AES128-SHA SHA1	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES256-SHA SHA1	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x28	ECDHE	RSA	AES-CBC(256)
AES128-SHA SHA1	0x00, 0x2F	RSA	RSA	AES-CBC(128)
RSA-AES128-SHA256	[...]			

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/3389/msrdp

```
Here is the list of SSL ciphers supported by the remote server :  
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1
```

```
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)
```

Name	Code	KEX	Auth	Encryption	MAC
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

SHA1

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC (128)	
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC (256)	
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC (128)	
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC (256)	

SHA1

RC4-MD5	0x00, 0x04	RSA	RSA	RC4 (128)	MD5
RC4-SHA	0x00, 0x05	RSA	RSA	RC4 (128)	
SHA1					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

Note that this service does not encrypt traffic by default but does support upgrading to an encrypted connection using STARTTLS.

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffcd>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/8383/www

```
Here is the list of SSL ciphers supported by the remote server :  
Each group is reported per SSL Version.
```

```
SSL Version : TLSv1.2
```

```
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC (168)	
SHA1					
ECDHE-RSA-DES-CBC3-SHA	0xC0, 0x12	ECDHE	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
SHA1					

```
High Strength Ciphers (>= 112-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA256	0x00, 0x9E	DHE	RSA	AES-GCM (128)	
SHA256					
DHE-RSA-AES256-SHA384	0x00, 0x9F	DHE	RSA	AES-GCM (256)	
SHA384					

ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)
RSA-AES128-SHA256 SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)
RSA-AES256-SHA384 SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x67	DHE	RSA	AES-CBC(128)
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)
DHE-RSA-AES256-SHA256 SHA256	0x00, 0x6B	DHE	RSA	AES-CBC(256)
DHE-RSA-CAMELLIA128-SHA	0x00, 0x45	DHE	R [...]	

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/3389/msrdp

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					

The fields above are :

{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}

```
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/8383/www

Here is the list of SSL PFS ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC (168)	
SHA1					
ECDHE-RSA-DES-CBC3-SHA	0xC0, 0x12	ECDHE	RSA	3DES-CBC (168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA256	0x00, 0x9E	DHE	RSA	AES-GCM (128)	
SHA256					

DHE-RSA-AES256-SHA384 SHA384	0x00, 0x9F	DHE	RSA	AES-GCM(256)
ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x2F	ECDHE	RSA	AES-GCM(128)
ECDHE-RSA-AES256-SHA384 SHA384	0xC0, 0x30	ECDHE	RSA	AES-GCM(256)
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x67	DHE	RSA	AES-CBC(128)
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)
DHE-RSA-AES256-SHA256 SHA256	0x00, 0x6B	DHE	RSA	AES-CBC(256)
DHE-RSA-CAMELLIA128-SHA SHA1	0x00, 0x45	DHE	RSA	Camellia-CBC(128)
DHE-RSA-CAMELLIA256-SHA SHA1	0x00, 0x88	DHE	RSA	Camellia-CBC(256)
ECDHE-RSA-AES128-SHA SHA1	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES128-SHA256 SHA256	0xC0, 0x27	ECDHE	RSA	AES-CBC(128)
ECDHE-RSA-AES256-SHA [...]				

94761 - SSL Root Certification Authority Certificate Information

Synopsis

A root Certification Authority certificate was found at the top of the certificate chain.

Description

The remote service uses an SSL certificate chain that contains a self-signed root Certification Authority certificate at the top of the chain.

See Also

[https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2003/cc778623\(v=ws.10\)](https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2003/cc778623(v=ws.10))

Solution

Ensure that use of this root Certification Authority certificate complies with your organization's acceptable use and security policies.

Risk Factor

None

Plugin Information

Published: 2016/11/14, Modified: 2018/11/15

Plugin Output

tcp/8383/www

The following root Certification Authority certificate was found :

```
| -Subject          : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop  
Central/E=support@desktopcentral.com  
| -Issuer           : C=US/ST=CA/L=Pleasanton/O=Zoho Corporation/OU=ManageEngine/CN=Desktop  
Central/E=support@desktopcentral.com  
| -Valid From       : Sep 08 12:24:44 2010 GMT  
| -Valid To         : Sep 05 12:24:44 2020 GMT  
| -Signature Algorithm : SHA-1 With RSA Encryption
```

51891 - SSL Session Resume Supported

Synopsis

The remote host allows resuming SSL sessions.

Description

This script detects whether a host allows resuming SSL sessions by performing a full SSL handshake to receive a session ID, and then reconnecting with the previously used session ID. If the server accepts the session ID in the second connection, the server maintains a cache of sessions that can be resumed.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/02/07, Modified: 2026/04/13

Plugin Output

tcp/3389/msrdp

```
This port supports resuming TLSv1 sessions.
```

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/3389/msrdp

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	
SHA1					
ECDHE-RSA-AES256-SHA	0xC0, 0x14	ECDHE	RSA	AES-CBC(256)	
SHA1					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
RC4-MD5	0x00, 0x04	RSA	RSA	RC4(128)	MD5
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)	
SHA1					

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```


156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/8383/www

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
ECDHE-RSA-DES-CBC3-SHA SHA1	0xC0, 0x12	ECDHE	RSA	3DES-CBC(168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x9E	DHE	RSA	AES-GCM(128)	
DHE-RSA-AES256-SHA384 SHA384	0x00, 0x9F	DHE	RSA	AES-GCM(256)	
RSA-AES128-SHA256 SHA256	0x00, 0x9C	RSA	RSA	AES-GCM(128)	
RSA-AES256-SHA384 SHA384	0x00, 0x9D	RSA	RSA	AES-GCM(256)	
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)	
DHE-RSA-AES128-SHA256 SHA256	0x00, 0x67	DHE	RSA	AES-CBC(128)	
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)	
DHE-RSA-AES256-SHA256 SHA256	0x00, 0x6B	DHE	RSA	AES-CBC(256)	
DHE-RSA-CAMELLIA128-SHA SHA1	0x00, 0x45	DHE	RSA	Camellia-CBC(128)	
DHE-RSA-CAMELLIA256-SHA SHA1	0x00, 0x88	DHE	RSA	Camellia-CBC(256)	
ECDHE-RSA-AES128-SHA	0xC0, 0x13	ECDHE	RSA	AES-CBC(128)	[...]

96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

<http://www.nessus.org/u?59bfc3ef>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

tcp/445/cifs

```
The remote host supports SMBv1.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/8020/www

```
A web server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/8282/www

```
A web server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/8383/www

```
A TLSv1.2 server answered on this port.
```

tcp/8383/www

```
A web server is running on this port through TLSv1.2.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/8585/www

```
A web server is running on this port.
```


17975 - Service Detection (GET request)

Synopsis

The remote service could be identified.

Description

It was possible to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0935

Plugin Information

Published: 2005/04/06, Modified: 2021/10/27

Plugin Output

tcp/3306/mysql

```
A MySQL server seems to be running on this port but the Nessus scanner
IP has been blacklisted. Run 'mysqladmin flush-hosts' if you want
complete tests.
```

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

<http://www.nessus.org/u?54fba2c1>

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The TLS service on port 8383/TLSv1.2 offers these ciphers vulnerable to Shor's:
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA
```

```
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_3DES_EDE_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
```

The SSH service on port 22 offers these ciphers vulnerable to Shor's:

```
diffie-hellman-group-exchange-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
curve25519-sha256@libssh.org
ecdh-sha2-nistp384
diffie-hellman-group14-sha1
```

The TLS service on port 3389/TLSv1 offers these ciphers vulnerable to Shor's:

```
TLS_RSA_WITH_3DES_EDE_CBC_SHA
TLS_RSA_WITH_RC4_128_SHA
TLS_RSA_WITH_RC4_128_MD5
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
```

The TLS service on port 8383/TLSv1 offers these ciphers vulnerable to Shor's:

```
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA
TLS_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_DHE_RSA_WITH_CAMELLIA_256_CBC_SHA
TLS_RSA_WITH_3DES_EDE_CBC_SHA
```

The TLS service on port 8383/ [...]

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/3389/msrdp

These are the TLS supported groups offered by the remote server :

TLS supported groups :

Name	Code

secp256r1	0x0017
secp384r1	0x0018

277654 - TLS Supported Groups

Synopsis

The remote service negotiates TLS supported curve groups.

Description

This plugin detects which TLS supported groups entries are supported by the remote service.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/8383/www

```
These are the TLS supported groups offered by the remote server :
```

```
TLS supported groups :
```

Name	Code

secp256r1	0x0017

121010 - TLS Version 1.1 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1.

TLS 1.1 lacks support for current and recommended cipher suites.

Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

None

References

XREF CWE:327

Plugin Information

Published: 2019/01/08, Modified: 2026/04/13

Plugin Output

tcp/8383/www

```
TLSv1.1 is enabled and the server supports at least one cipher.
```

136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2026/04/13

Plugin Output

tcp/8383/www

```
TLSv1.2 is enabled and the server supports at least one cipher.
```


110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SMB was detected on port 445 but no credentials were provided.  
SMB local checks were not enabled.
```


64814 - Terminal Services Use SSL/TLS

Synopsis

The remote Terminal Services use SSL/TLS.

Description

The remote Terminal Services is configured to use SSL/TLS.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/02/22, Modified: 2023/07/10

Plugin Output

tcp/3389/msrdp

```
Subject Name:

Common Name: vagrant-2008R2

Issuer Name:

Common Name: vagrant-2008R2

Serial Number: 7B E3 C9 2E F7 4B B9 9B 45 24 52 DD 48 B9 43 3E

Version: 3

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: May 12 02:22:28 2026 GMT
Not Valid After: Nov 11 02:22:28 2026 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 B0 A6 24 17 10 39 F2 F3 76 FC 04 EE FE 6D C2 7D 5E AA F6
             EA 21 F6 28 36 42 63 1E 01 25 B0 CB 05 9A 47 9D A7 D9 70 6C
             FF E2 AB E4 A3 DE 67 C6 02 E5 FA 27 71 66 27 19 05 59 3D 2E
             06 B1 F7 82 A5 62 B4 72 6F 03 87 F0 62 02 FD 99 7C A4 1F 2D
             D0 DF 12 75 00 1B 6F 36 6E 76 A6 D8 87 D8 0D 10 FA B7 CA 32
             7D 50 86 49 16 B1 7B 15 40 07 23 4B A0 E2 84 D2 6D A7 28 D3
             55 75 CA B2 41 FC 2E 85 E3 D0 66 12 42 AB 99 21 6F E8 A6 62
             9C C9 22 B8 55 D1 3E 93 0C 3B 7B C1 0D 17 8B 45 59 CB 18 67
             D5 3A 7D 26 A8 4E DC D2 57 3B 81 4B A1 37 EC 3D 18 5C 32 9B
             08 D5 D5 32 DB 8F C4 41 4A 44 9F E5 ED 7F E8 F6 D8 52 3F 26
             EA 68 D3 0D 23 2B A2 AE 8E 85 87 3E AA C8 64 A2 A0 30 F0 DC
```

```
15 2B D8 3E 38 DB 40 D2 AC 05 9F 89 35 36 0F FB C5 01 AD C7
AD 19 8A 2C 35 DF 45 96 40 46 E8 61 5F CD 5A F9 D7
Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits
Signature: 00 21 28 75 4B 66 66 AC F3 84 8D 9C 85 7A 8D 71 0A FF EB 64
           CC A1 17 16 62 33 B5 F5 9B C9 F5 5D 4E 01 C3 8A 8A A0 7E 7F
           3F 2A 29 B5 97 26 8D 15 4F 0E EB 70 52 23 43 8E E1 8C C4 5B
           5E AF 14 7D DB EC B3 B5 D4 6C 57 21 3C 82 D1 37 C5 6D 47 E4
           CE 86 82 6E AA 5C 39 9D 5F 3A 23 B3 05 29 FD DA C7 9D 7B 1B
           C8 0E BC 67 22 BB 8E 76 6E 47 4E F1 59 C1 08 60 92 F6 2E 33
           EF 3C 2F 68 7B 1F 09 DF 6A 2D 6E 17 6F DB D1 57 EE 14 E0 33
           FE A5 F2 C1 12 74 91 86 74 F6 FD FB D0 06 B9 D7 CD 5F FD E8
           54 43 5F 8F F7 CA D1 E4 4B A5 5A D8 FA C2 68 0B A4 0F 36 8C
           B6 72 61 A9 55 A6 54 B [...]
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.2.100 to 172.30.2.102 :  
172.30.2.100  
172.30.2.102  
  
Hop Count: 1
```

Synopsis

The remote web server contains a graphic image that is prone to information disclosure.

Description

The 'favicon.ico' file found on the remote web server belongs to a popular web server. This may be used to fingerprint the web server.

Solution

Remove the 'favicon.ico' file or create a custom one for your site.

Risk Factor

None

Plugin Information

Published: 2005/10/28, Modified: 2020/06/12

Plugin Output

tcp/8282/www

```
MD5 fingerprint : 4644f2d45601037b8423d45e13194c93
Web server      : Apache Tomcat or Alfresco Community
```

11422 - Web Server Unconfigured - Default Install Page Present

Synopsis

The remote web server is not configured or is improperly configured.

Description

The remote web server uses its default welcome page. Therefore, it's probable that this server is not used at all or is serving content that is meant to be hidden.

Solution

Disable this service if you do not use it.

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2018/08/15

Plugin Output

tcp/8282/www

```
The default welcome page is from Tomcat.
```

11424 - WebDAV Detection

Synopsis

The remote server is running with WebDAV enabled.

Description

WebDAV is an industry standard extension to the HTTP specification.

It adds a capability for authorized users to remotely add and manage the content of a web server.

If you do not use this extension, you should disable it.

Solution

<http://support.microsoft.com/default.aspx?kbid=241520>

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2011/03/14

Plugin Output

tcp/8585/www

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

udp/137/netbios-ns

```
The following 3 NetBIOS names have been gathered :
```

```
VAGRANT-2008R2    = Computer name
WORKGROUP         = Workgroup / Domain name
VAGRANT-2008R2    = File Server Service
```

```
The remote host has the following MAC address on its adapter :
```

```
08:00:27:d7:cc:d8
```