

prepboi

Technical Deployment Guide

Version 1.0 | Multi-Location Kitchen Operations Platform

For: Franchise operators and technical administrators deploying PrepBoi across one or more locations. Estimated setup time: 20–40 minutes (Netlify) or 30–60 minutes (Docker).

Accounts You Will Need

Create accounts at each of the following services before beginning. All have free tiers that cover initial deployment.

Service	Purpose	URL
Supabase	Database, authentication, file storage, real-time notifications	supabase.com
Resend	Transactional email for submission notifications	resend.com
Anthropic	AI quiz generation from SOP and recipe content	console.anthropic.com
Netlify	Frontend hosting — automatic deploys from GitHub (Netlify path)	netlify.com
GitHub	Code repository — required if using Netlify deploy	github.com

Step 1 — Supabase Database Setup

Supabase is the backend. It handles user accounts, all data storage, file uploads (recipe PDFs), and real-time notifications. Everything else is built on top of it.

1a. Create Your Supabase Project

1. Go to supabase.com/dashboard and sign in or create an account.
2. Click New Project. Choose an organization (create one if prompted).
3. Name your project (e.g. "prepboi-production" or your brand name).
4. Set a strong database password and save it somewhere safe. You will need it if you ever connect directly to the database.
5. Choose a region geographically closest to your restaurant locations. US-East or US-West for continental US operators.

6. Click Create new project and wait approximately 90 seconds for provisioning.

1b. Apply the Database Schema

The schema file creates all tables, security policies, and automated triggers. It must be applied exactly once on a fresh project.

7. In your Supabase project dashboard, click SQL Editor in the left sidebar.
8. Click New Query.
9. Open the file supabase/migrations/001_schema.sql from the PrepBoi project folder.
10. Select all the text (Cmd+A or Ctrl+A), copy it, and paste it into the SQL Editor.
11. Click Run (or press Cmd+Enter / Ctrl+Enter).
12. You should see the message: Success. No rows returned. If you see any error in red, do not proceed — the error text will tell you what went wrong.

Critical: Run this only once

Running the schema migration a second time on the same database will produce errors because the tables already exist. If you need to reset, you must first drop all tables or create a brand-new Supabase project.

1c. Collect Your API Keys

These are the keys you will put into your environment variables file.

13. In your Supabase project, click Settings in the left sidebar.
14. Click API under the Configuration section.
15. Copy the Project URL — this becomes VITE_SUPABASE_URL in your .env file.
16. Copy the anon public key (under Project API keys) — this becomes VITE_SUPABASE_ANON_KEY.

Do not use the service_role key in your frontend .env file. The service_role key bypasses all security policies and should only ever be used in server-side environments (like the Edge Function).

1d. Disable Email Confirmation (Recommended for Internal Teams)

By default, Supabase requires new users to confirm their email before signing in. For internal kitchen staff apps, this creates unnecessary friction and support burden.

17. In Supabase, go to Authentication → Settings.
18. Under Email Auth, toggle off Enable email confirmations.
19. Click Save.

New staff accounts created through the Admin panel will be immediately usable without any email confirmation step.

1e. Seed Your First Organization and Location

PrepBoi uses a multi-location data model. Every piece of data belongs to an organization, which contains one or more locations. Before any user can sign in successfully, at least one organization and one location must exist.

In the SQL Editor, run the following — replacing the placeholder values with your actual business name:

```
-- Step 1: Create your organization
INSERT INTO organizations (name, slug)
VALUES ('Bake Tempe', 'bake-tempe')
RETURNING id;
```

Copy the UUID that is returned. Then run:

```
-- Step 2: Create your first location (use the org UUID from above)
INSERT INTO locations (org_id, name, address, timezone)
VALUES
  ('<paste-org-id-here>', 'Mill Ave', '123 Mill Ave, Tempe AZ',
  'America/Phoenix')
RETURNING id;
```

Save both UUIDs. You will need them to promote your first super user in Step 1f.

1f. Create and Promote Your First Super User

The first super user account cannot be created through the app because the app requires an existing super user to create accounts. You will sign up through the app, then promote yourself through SQL.

20. Deploy the app first (Step 2 or Step 3 below), then navigate to your deployed URL.
21. Click the sign in form. There is no public "sign up" link — enter your email and a password directly.
22. The account is created in Supabase Auth. Now go back to the SQL Editor.
23. Find your user ID: in Supabase, go to Authentication → Users and copy your user's UUID.
24. Run the following SQL to link your account to your org and elevate your role:

```
UPDATE profiles
SET
  role          = 'super_user',
  org_id        = '<your-org-id>',
  location_id   = '<your-location-id>'
WHERE id = '<your-auth-user-uuid>;'
```

25. Sign out and sign back in. You now have full super user access and can create all future accounts through the Admin panel in the app.

Step 2 — Email Notifications (Resend + Edge Function)

When a team member submits a checklist, super users and shift leaders at that location receive both an in-app notification and an email. This is handled by a Supabase Edge Function that calls the Resend API.

2a. Set Up Resend

26. Sign up at resend.com.
27. Go to Domains → Add Domain. Add and verify your sending domain (e.g. prepboi.yourbrand.com). This requires adding DNS records to your domain registrar — Resend provides exact instructions.
28. If you want to test before verifying a domain, Resend provides a sandbox mode that delivers to your verified email address only.
29. Go to API Keys → Create API Key. Give it a name like "prepboi-production". Copy the key — it starts with `re_`.

2b. Install the Supabase CLI

```
npm install -g supabase
supabase login
# Enter your Supabase access token when prompted
# Find your token at: supabase.com/dashboard/account/tokens

# Link to your project (find your ref in: Settings → General → Reference ID)
supabase link --project-ref <your-project-ref>
```

2c. Set Edge Function Secrets

These are environment variables for the server-side email function. They are stored securely in Supabase — never in your frontend code.

```
supabase secrets set RESEND_API_KEY=re_your_key_here
supabase secrets set FROM_EMAIL=noreply@yourdomain.com
supabase secrets set APP_URL=https://your-app.netlify.app
```

To verify secrets are set correctly:

```
supabase secrets list
```

2d. Deploy the Edge Function

```
supabase functions deploy notify-email
```

After deployment, note the function URL shown in the output. It will look like:

```
https://<your-project-ref>.supabase.co/functions/v1/notify-email
```

2e. Wire the Database Webhook

The webhook fires the Edge Function automatically whenever a new notification row is inserted into the database.

30. In Supabase, go to Database → Webhooks → Create a new hook.
31. Configure as follows:
 - Name: notify-email-on-insert
 - Table: notifications

- Events: check INSERT only
 - Type: HTTP Request
 - URL: paste your Edge Function URL from Step 2d
 - Headers: add Authorization with value Bearer <your-anon-key>
32. Click Create webhook.
33. Test it: submit a checklist through the app and verify the email arrives.

Step 3A — Netlify Deployment (Recommended)

3a. Push Code to GitHub

34. Create a new repository on github.com.
35. From the prepboi-prod project folder on your machine, run:

```
git init
git add .
git commit -m "Initial PrepBoi deployment"
git remote add origin https://github.com/your-org/prepboi.git
git push -u origin main
```

3b. Connect to Netlify

36. Go to app.netlify.com and click Add new site → Import an existing project.
37. Choose GitHub and authorize Netlify to access your repositories.
38. Select your prepboi repository.
39. Build settings are auto-detected from netlify.toml. Verify:
- Build command: npm ci && npm run build
 - Publish directory: dist
40. Do not click Deploy yet — add environment variables first.

3c. Set Environment Variables in Netlify

41. In your Netlify site settings, go to Environment variables.
42. Add each of the following variables:

Variable	Where to get it	Status	Bg
VITE_SUPABASE_URL	Supabase → Settings → API → Project URL	Required	
VITE_SUPABASE_ANON_KEY	Supabase → Settings → API → anon public key	Required	
VITE_ANTHROPIC_API_KEY	console.anthropic.com/keys	Required	
VITE_APP_URL	Your Netlify or custom domain URL	Required	
RESEND_API_KEY	resend.com/api-keys (Edge Function secret, not .env)	Email	

FROM_EMAIL	Your verified sender email (Edge Function secret)	Email
------------	---	-------

43. Click Deploy site. Netlify will build and publish your app. The first build takes 2–3 minutes.

3d. Custom Domain (Optional)

44. In Netlify, go to Domain management → Add custom domain.
45. Follow the DNS instructions. Netlify handles SSL automatically.
46. Update VITE_APP_URL in Netlify to match your new domain.
47. Update the APP_URL Edge Function secret: supabase secrets set APP_URL=https://yourcustomdomain.com
48. Trigger a new Netlify deploy to pick up the updated environment variable.

Step 3B — Docker / Self-Hosted Deployment

Use this path if you are running on your own server infrastructure (DigitalOcean Droplet, AWS EC2, Hetzner VPS, etc).

4a. Server Requirements

- Ubuntu 20.04 or 22.04 LTS (recommended)
- Minimum: 1 vCPU, 1 GB RAM, 20 GB SSD
- Docker and Docker Compose installed
- Ports 80 and 443 open in your firewall

4b. Install Docker (if not already installed)

```
curl -fsSL https://get.docker.com | sh
sudo usermod -aG docker $USER
# Log out and back in for group membership to take effect
```

4c. Deploy PrepBoi

49. Clone or upload the prepboi-prod project folder to your server.
50. Copy the environment variables template and fill in your values:

```
cp .env.example .env
nano .env # fill in all four VITE_ variables
```

51. Build and start the container:

```
docker compose up -d --build
```

52. Verify it is running:

```
docker compose ps
curl http://localhost/health # should return: ok
```

4d. SSL with Caddy (Recommended)

Caddy is the simplest way to add automatic HTTPS to your self-hosted deployment.

```
# Install Caddy
sudo apt install -y debian-keyring debian-archive-keyring apt-transport-https
curl -1sLf 'https://dl.cloudsmith.io/public/caddy/stable/gpg.key' | sudo gpg
--dearmor -o /usr/share/keyrings/caddy-stable-archive-keyring.gpg
curl -1sLf 'https://dl.cloudsmith.io/public/caddy/stable/debian.deb.txt' |
sudo tee /etc/apt/sources.list.d/caddy-stable.list
sudo apt update && sudo apt install caddy
```

Edit /etc/caddy/Caddyfile to add your domain:

```
yourdomain.com {
    reverse_proxy localhost:80
}
```

```
sudo systemctl reload caddy
```

Caddy automatically obtains and renews a Let's Encrypt certificate. Your app is now accessible over HTTPS.

4e. Updating PrepBoi

```
git pull # get latest code
docker compose up -d --build # rebuild and restart
```

Step 4 — Multi-Location Configuration

PrepBoi is designed for franchise and chain operators. Each organization can have unlimited locations. Checklists, SOPs, and recipes can be scoped to a specific location or shared across all locations in the org.

Adding Additional Locations

Run in the Supabase SQL Editor:

```
INSERT INTO locations (org_id, name, address, timezone)
VALUES
  ('<org_id>', 'Mill Ave', '123 Mill Ave, Tempe AZ',
  'America/Phoenix'),
  ('<org_id>', 'Downtown', '456 Central Ave, Phoenix AZ',
  'America/Phoenix'),
  ('<org_id>', 'Old Town', '789 Brown Ave, Scottsdale
  AZ', 'America/Phoenix');
```

How Location Scoping Works

- Checklist with no location set → visible to all staff at all locations in the org
- Checklist with a location set → visible only to staff assigned to that location

- The submission dashboard automatically filters by the viewer's location
- Super users see data from all locations
- Shift leaders see data from their assigned location only

Assigning Users to Locations

Through the Admin panel (once deployed): create each user and select their location from the dropdown. Users can also be reassigned at any time by a super user editing their profile.

Role Permission Reference

Permission	Employee	Shift Leader	Super User
Can complete checklists			
Can view recipes			
Can take quizzes			
Receives notifications			
Can view submission dash			
Can assign training			
Can create checklists/SOPs			
Can upload recipe PDFs			
Can manage users			
Can manage locations			

Environment Variable Reference

Variable	Where to get it	Status	Bg
VITE_SUPABASE_URL	Supabase → Settings → API → Project URL	Required	
VITE_SUPABASE_ANON_KEY	Supabase → Settings → API → anon public key	Required	
VITE_ANTHROPIC_API_KEY	console.anthropic.com/keys	Required	
VITE_APP_URL	Your Netlify or custom domain URL	Required	
RESEND_API_KEY	resend.com/api-keys (Edge Function secret, not .env)	Email	

FROM_EMAIL	Your verified sender email (Edge Function secret)	Email
------------	---	-------

Troubleshooting

"Missing Supabase env vars" Error on Startup

The app cannot connect to Supabase. Check that:

- Your .env file exists and has VITE_SUPABASE_URL and VITE_SUPABASE_ANON_KEY filled in
- For Netlify: the environment variables are set in Site Settings → Environment Variables and you triggered a new deploy after adding them
- For Docker: the .env file is in the project root and docker compose up -d --build was run after editing it
- The URL does not have a trailing slash

Users Cannot Sign In

- Go to Supabase → Authentication → Users and confirm the account exists
- If email confirmation is enabled and the user has not confirmed, they will be blocked — disable email confirmations (Step 1d)
- Check that the profile row exists: `SELECT * FROM profiles WHERE id = '<user-uuid>';`
- Check that org_id is set on the profile row

Notification Emails Not Arriving

- Check Supabase → Edge Functions → notify-email → Logs for errors
- Verify the webhook is configured (Database → Webhooks)
- Run: `supabase secrets list` to confirm RESEND_API_KEY is set
- Check Resend → Emails for delivery status and bounce information
- Confirm your sending domain is verified in Resend (unverified domains can only send to your own email in sandbox mode)

Quiz Generation Failing

- Confirm VITE_ANTHROPIC_API_KEY is set and the account has available credits
- SOPs and recipes with pre-built quiz_questions in the database never call the API — only content without them does
- Check browser Developer Tools → Console for API error messages

Data Not Appearing (RLS Policy Issues)

Row Level Security locks data by org_id and role. If a user can see nothing:

- Run in SQL Editor: `SELECT my_org_id(), my_role();` while the user is signed in to verify their profile is set up correctly
- For checklists: verify the user's role is in the checklist's `assigned_roles` array
- For location-scoped data: verify the user's `location_id` matches the data's `location_id`

Pre-Launch Checklist

Before going live with real staff, verify each of the following:

- Schema applied with no errors in SQL Editor
- First organization and location created
- First super user promoted and can sign in
- Email confirmation disabled (unless you want staff to confirm emails)
- At least one checklist created and assigned to the employee role
- Test submission: complete a checklist as an employee, verify notification appears in bell for a shift leader or super user
- Test email: verify notification email arrives from your Resend sending address
- Test employee account: confirm employee cannot see Admin panel
- Test shift leader account: confirm shift leader can see Dashboard but not Admin panel
- Custom domain configured and HTTPS active (if using a custom domain)