14K/16K LCD 3D Printer

AS Technology

Specially designed for high-quality jewelry production, this ultra-clear resolution LCD 3D printer boasts high precision, fast printing speed, and long-term stable ultra-large printing capability.

- Ultra clear resolution
- USB transmission / WiFi
- One click automatic generation of editable support
- Ultra large production capacity

Technical Information

Model	M.PR.VAN70-WAX	M.PR.VAN70-16K
Power Supply	110V/220V 50/60Hz 500W	110V/220V 50/60Hz 500W
Build Size	L223×W126×H180mm	L211×W118×H180mm
Pixel	13320×5120	15120×6230
Build Speed	10+mm/hr maximum 50mm/h	10+mm/hr maximum 50mm/h
Printing Layer Thickness	0.025–0.1mm	0.025–0.1mm
Light Source	COB Light Source / COB Light Source	COB Light Source / COB Light Source
Software	ChituBox	ChituBox
File Format	STL, OBJ	STL, OBJ
Connectivity	USB	USB
Curing wavelength	405nm	4405nm*
Material	Photosensitive Resin / Photosensitive Resin	Photosensitive Resin / Photosensitive Resin
Machine dimension	L337×W467×H795mm	L337×W467×H795mm
Net weight	43KG	43KG

Ultra high resolution and accuracy

Printing time	17 hours and 3 min
Printing Layer Thickness	50 microns
Build Speed	Build Speed 10mm/hour
Build size	223x126x180mm

16K LCD 3D Printer (Max)

AS Technology

Specially designed for the production of large-scale products such as Buddha statues and handicrafts, this ultra-clear resolution LCD 3D printer has high precision, fast printing speed, and long-term stable super large printing capacity.

- Ultra clear resolution
- USB transmission / WiFi
- One-click automatic generation of editable support
- Ultra large production capacity

Technical Information

Item	Specification
Model	M.P.R.VAN90-WAX
Power Supply	110V/220V 50/60Hz 700W
Build Size	L302 × W161 × H400 mm
Pixel	15120 × 6230
XY Resolution	20 × 26 μm
Build Speed	2–3 layers/sec
Printing Layer Thickness	0.025–0.1 mm
Projection Light Source	LCD
File Format	STL
Connectivity	USB / WiFi
Curing Wavelength	405 nm
Material	Photosensitive Resin
Machine Dimension	L650 × W385 × H1500 mm

Ultra High Resolution And Accuracy

Build Speed	302x161x400mm
Printing Layer Thickness	2-3 layer/s
Build size	50 microns
Printing time	33 hours

PRO DLP 3D Printer

AS Technology

A 3D printer specifically developed for the jewelry industry, used for making master molds, customized designs for customers, displaying models, direct precision casting, hot/cold pressing molds, and mass production in the jewelry industry.

Technical Information

Model	M.P.RL Pro100	M.P.RL Pro200	M.P.RL Pro150-wax
Power Supply	110V/220V 50/60Hz 500W	110V/220V 50/60Hz 500W	110V/220V 50/60Hz 500W
Pixel	1280×800	1920×1080	1920×1080
Build Size	L64×W40×H80mm	L144×W81×H170mm	L96×W54×H130mm
Build Speed	10+ mm/hr	10+ mm/hr	10–50 mm/hr
Printing Layer Thickness	25–50 μm	25–50 μm	10–50 μm
Light Source	Industrial UV LED 405nm	Industrial UV LED 405nm	Industrial UV LED 405nm
Software	3DPrint Slicer	3DPrint Slicer	V2.0 for Windows 7
File Format	YXP	YXP	SLC
Connectivity	USB / WiFi	USB / WiFi	USB / WiFi
Material	DLP Resin	DLP Resin	Wax Material
Machine Size	L337×W467× H795mm	L359×W467×H 956mm	L337×W467× H795mm
Net weight	45KG	58KG	45KG

Ultra high resolution and accuracy

Printing time	12 hour
Printing Layer Thickness	50 microns
Build Speed	10 mm/hour
Build size	144 × 81 × 170 mm

Smart Solutions for a Smarter Future

Curing Box

AS Technology

Technical Information

Model	M.P.RL PROP14-1
Curing Size	400 × 400 × 400 mm
Curing Wavelength	405 nm
Curing Power	120 W
Heating Power	80 W
Total Power	200 W
Input Power	100–240V AC, 50–60Hz
Product Size	445 × 445 × 515 mm
Product Weight	20 KG
Outer Dimensions of Packaging	520 × 520 × 615 mm

Technical Information

Model	M.P.RL PRO14
Curing Time	1–30 seconds / 1–30 minutes
Curing Light Source	Top-mounted 405 nm light board
Power	100 W
Input Voltage	100–240V 50/60Hz; DC 24V
Weight	6 KG
Lumen Size (Internal Light Area)	L180 × W180 × H100 mm
Machine Size	L220 × W220 × H325 mm

Rasin

Technical Information

Model	RS-ALBINO	RS-OBSIDIAN	RS-AURORA	RS-OLIVE
Density	1.06g–1.075g/cm³	1.07g–1.1g/cm³	1.07g–1.1g/cm³	1.07g–1.1g/cm³
Viscosity	450–550 cps	250 cps–350 cps	250 cps–350 cps	1500 cps–2000 cps
Exposure Time	5.5s–6.5s	3.5s–5.5s	3.5s–5.5s	5.5s–6.5s
Bottom Exposure Time	30s–40s	15s–25s	15s–25s	40s
Color	Yellow (after curing becomes white)	Semi-transparent black	Orange	Green

Suitable for jewelry, dentistry, education and scientific research, toy design, handicraft design, and industrial part design.

Jewelry 3D Scanner

AS Technology

Jewelry 3D scanner is tailor-made for scanning 5mm–80mm sized small objects to get their 3D models, such as jewelry, rings, gems, pendants, coin, miniature, watch part, small industrial parts etc., widely used for CAD/CNC/remodeling/digital archive/3D printing etc.

Advantages:
Manufacturer sells directly

- Full-automatic scanning
- Easy to use
- High Resolution & High Accuracy
- Get 3D models quickly
- Save designers precious design time
- Affordable price

Parameter	
Camera	Monochrome, 5mp
Raster	DLP 1280×1080
Lens	25mm lens
FOV	80*60mm
Resolution	0.0008mm
Software	Free update, Scan //Wrap / After process
Accuracy	<0.01mm
Scan Volume	5–80mm
Data Format	ASC/STL
Divided Model Scan	Yes
Suggest PC	Intel CPU + Nvidia as main GPU + Win 10/11
Certification	CE/FCC/WEEE
Public API	C++ interface
Shipping Info	11.65 Kg / 50cm*35cm*28cm
Packing List	Scanner / cables / U-disk / Adaptor / Calibration Plate / Clip
Value-add	Free Mesh Edit Software, open API interface