

Operating systems and concurrency B08

David Kendall

Northumbria University

- Semaphores can cause problems if not used carefully
- We will consider:
 - Deadlock
 - Starvation
 - Priority inversion (next time)

A mistake in the producer/consumer solution

Producer

```
1 while (true)
2
3   // produce an item
4
5   pend (bufMutex);
6   pend (emptySlot);
7
8   // add item to buffer
9
10  post (bufMutex);
11  post (fullSlot);
12 }
```

Consumer

```
1 while (true) {
2   pend (fullSlot);
3   pend (bufMutex);
4
5   // remove item from buffer
6
7   post (bufMutex);
8   post (emptySlot);
9
10  // consume the item
11
12 }
```

- Spot the difference with the correct solution!

A mistake in the producer/consumer solution

Producer

```
1 while (true)
2
3   // produce an item
4
5   pend (bufMutex);
6   pend (emptySlot);
7
8   // add item to buffer
9
10  post (bufMutex);
11  post (fullSlot);
12 }
```

Consumer

```
1 while (true) {
2   pend (fullSlot);
3   pend (bufMutex);
4
5   // remove item from buffer
6
7   post (bufMutex);
8   post (emptySlot);
9
10  // consume the item
11
12 }
```

- Spot the difference with the correct solution!
- Lines 5 and 6 in the producer are the wrong way round

What can go wrong?

- Imagine...
 - the buffer is full
 - a producer wants to add to the buffer
 - the producer acquires the `bufMutex`
 - the producer is suspended by `pend(emptySlot)`
 - a consumer tries to remove an item from the buffer
 - the consumer acquires `fullSlot` successfully
 - the consumer is suspended by `pend(bufMutex)`
- What now?

What can go wrong?

- The producer will be blocked until the `emptySlot` mutex is posted by the consumer
- The consumer will be blocked until the `bufMutex` mutex is posted by the producer
- The producer can't post `bufMutex` until the consumer posts `emptySlot`
- The consumer can't post `emptySlot` until the producer posts `bufMutex`
- **DEADLOCK**

Necessary conditions for deadlock

- 1 Mutual exclusion
 - some resources cannot be shared
- 2 Hold and wait
 - tasks can hold non-shareable resources while waiting to acquire other non-shareable resources
- 3 No pre-emption
 - once a task is holding a resource, the resource can't be taken away from it
- 4 Circular wait
 - task T_0 can wait for a resource held by task T_1 that is waiting for a resource held by task T_2, \dots , that is waiting for a resource held by task T_n that is waiting for a resource held by task T_0

A problem with the readers/writers solution

Writers

```
1 while (true) {  
2     pend(writeMutex);  
3  
4     // write the data  
5  
6     post(writeMutex);  
7  
8     // do non-critical stuff  
9 }
```

Readers

```
1 while (true) {  
2     pend(nReadersMutex);  
3     nReaders += 1;  
4     if (nReaders == 1) {  
5         pend(writeMutex);  
6     }  
7     post(nReadersMutex);  
8  
9     // read the data  
10  
11    pend(nReadersMutex);  
12    nReaders -= 1;  
13    if (nReaders == 0) {  
14        post(writeMutex);  
15    }  
16  
17    // do non-critical stuff  
18 }
```


A problem with the readers/writers solution

Writers

```
1 while (true) {  
2     pend(writeMutex);  
3  
4     // write the data  
5  
6     post(writeMutex);  
7  
8     // do non-critical stuff  
9 }
```

- What happens to writers if a reader always arrives before the last reader finishes?

Readers

```
1 while (true) {  
2     pend(nReadersMutex);  
3     nReaders += 1;  
4     if (nReaders == 1) {  
5         pend(writeMutex);  
6     }  
7     post(nReadersMutex);  
8  
9     // read the data  
10  
11    pend(nReadersMutex);  
12    nReaders -= 1;  
13    if (nReaders == 0) {  
14        post(writeMutex);  
15    }  
16  
17    // do non-critical stuff  
18 }
```

A problem with the readers/writers solution

Writers

```
1 while (true) {
2     pend(writeMutex);
3
4     // write the data
5
6     post(writeMutex);
7
8     // do non-critical stuff
9 }
```

- What happens to writers if a reader always arrives before the last reader finishes?
- **STARVATION**

Readers

```
1 while (true) {
2     pend(nReadersMutex);
3     nReaders += 1;
4     if (nReaders == 1) {
5         pend(writeMutex);
6     }
7     post(nReadersMutex);
8
9     // read the data
10
11    pend(nReadersMutex);
12    nReaders -= 1;
13    if (nReaders == 0) {
14        post(writeMutex);
15    }
16
17    // do non-critical stuff
18 }
```

Acknowledgements

- Silberschatz, Galvin, Gagne, *Operating System Concepts*, John Wiley, 2008