

SMALL WEB FORMAT ~ FLASH



HEADER

FIELDS	VALUES
signature	FWS
version	7
file size	140
rect nbits	15*
xmin, xmax, ymin, ymax	0 550 0 400*
frame rate	12.0
frame count	1

ACTION

extended length	0x63*
code	12 DoAction
length	109
action id	0x88 ActionConstantPool
length	0x2c
count	4
message	createTextField text Hello World!

CONSTANT POOL

action id	0x96 ActionPush
length	0x2a
params:	50 Int 100 Int 0.0 Double 0.0 Double 1 Int 0 Constant8 6 Int 1 Constant8

PUSH

CALL FUNCTION

action id	0x3d ActionCallFunction
action id	0x17 ActionPop
action id	0x96 ActionPush
length	2

POP

PUSH

GETVARIABLE

param: 0	Constant8
action id	0x1c ActionGetVariable
action id	0x96 ActionPush
length	4
2	Constant8
3	Constant8

SETMEMBER

action id	0x4f ActionSetMember
action id	0x00 ActionEndFlag

END

SHOW FRAME

length / code*	0 / 1 ShowFrame
----------------	-----------------

END

length / code*	0 / 0 End
----------------	-----------

*NON-ALIGNED ENCODING

JAVA CLASS

```
~$ java mini
```

```
~$
```

FIELDS

VALUES

magic	CAFEBABE
minor_version	0x0003
major_version	0x002D 45.3 → Java 1.0.2
constant_pool_count	0x0008

CONSTANT POOL DATA USED BY THE CODE

00: <always empty>	
01: class reference (name:#02)	reference to the "mini" class
02: "mini" UTF-8 literal (length:4)	
03: class reference (name:#04)	reference to the "java.lang.Object" class
04: "java/lang/Object" UTF-8 literal (length:16)	
05: "main" UTF-8 literal (length:4)	a literal containing "main" (used as method name)
06: "Code" UTF-8 literal (length:4)	a literal containing "Code" (used as attribute name)
07: "([Ljava/lang/String;)V" UTF-8 literal (length:22)	a literal which means, as a method type: takes an array of "java.lang.String" as parameter returns "void"

access_flags	0x0001 ACC_PUBLIC
this_class	0x0001 + "mini"
super_class	0x0003 + "java.lang.Object"
interfaces_count	0x0000
(no interfaces)	
fields_count	0x0000
(no fields)	

methods_count	0x0001
01: access_flags	0x0001 ACC_PUBLIC ACC_STATIC
name_index	0x0005 + class name "main"
descriptor_index	0x0007 → Return type void Parameters: java.lang.String[]
attributes_count	0x0001

01: attribute_name_index	0x0006 + "Code"
attribute_length	0x00000000 (13)
info	
max_stack	0x0000
max_locals	0x0001
code_length	0x00000001

BYTECODE	SOURCE CODE
return	return;

exception_table_length	0x0000
(no exception_table)	
attributes_count	0x0000
(no attributes)	

attributes_count	0x0000
(no attributes)	

METHODS

CONTAINS BYTECODE

```
0 1 2 3 4 5 6 7 8 9 A B C D E F
000: CA FE BA BE 00 03 00 2D 00 08 07 00 02 01 00 04
010: .m .i .n .i .e 07 00 04 01 00 10 .j .a .v .a . / . l
020: .a .n .g . / .o .b .j .e .c .t .e 01 00 04 .m .a .i
030: .n 01 00 04 .c .o .d .e 01 00 16 .( .[ .L .j .a
040: .v .a . / .l .a .n .g . / .S .t .r .i .n .g . ; .)
050: .V 00 01 00 01 00 03 00 00 00 00 00 01 00 09 00
060: 05 00 07 00 01 00 06 00 00 00 0D 00 00 00 01 00
070: 00 00 01 B1 00 00 00 00 00 00
```

```
public class mini {
  public static void main(String[])
  {
  }
}
```