[320] Graph Search

Department of Computer Sciences University of Wisconsin-Madison

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
```

A.find(D) =

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
return None
```

$$A.find(D) =$$

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
return None
```

```
A.find(D) = B.find(D) =
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath

return None
```

```
A.find(D) = B.find(D) =
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath

return None
```

```
A.find(D) = B.find(D) = None
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
```

```
A.find(D) = \otimes B.find(D) = None
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
        return (self.name,) + childpath

return None
```

A.find(D) =
$$\otimes$$
 B.find(D) = None

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
```

```
A.find(D) = \times B.find(D) = None C.find(D) =
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath

return None
```

```
A.find(D) = \times B.find(D) = None C.find(D) =
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
            return (self.name,) + childpath
return None
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
        return (self.name,) + childpath

return None
```

```
A.find(D) =

\times B.find(D) = None

C.find(D) =

D.find(D) =
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
        return (self.name,) + childpath

return None
```

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
        return (self.name,) + childpath
```

A.find(D) =

$$igotimes B.find(D) = None$$

C.find(D) = (C, D) where (C, D) = (C,) + (D,)

D.find(D) = (D,)

```
def find(self, dst):
    self.graph.visited.add(self)

if self == dst:
    return (self.name,)

for child in self.children:
    if not child in self.graph.visited:
        childpath = child.find(dst)
        if childpath:
        return (self.name,) + childpath
```

A.find(D) = (A, C, D) where (A, C, D) = (A,) + (C, D)

$$\otimes$$
 B.find(D) = None
C.find(D) = (C, D)
D.find(D) = (D,)