

MooViE

1.0

Generated by Doxygen 1.8.13

Contents

1	Namespace Index	1
1.1	Namespace List	1
2	Hierarchical Index	3
2.1	Class Hierarchy	3
3	Class Index	5
3.1	Class List	5
4	Namespace Documentation	7
4.1	angle_helper Namespace Reference	7
4.1.1	Detailed Description	7
4.1.2	Function Documentation	7
4.1.2.1	deg_to_rad()	7
4.1.2.2	rad_to_deg()	8
5	Class Documentation	9
5.1	Angle Class Reference	9
5.1.1	Detailed Description	10
5.1.2	Constructor & Destructor Documentation	10
5.1.2.1	Angle()	10
5.1.3	Member Function Documentation	10
5.1.3.1	center()	10
5.1.3.2	interpolate()	11
5.1.3.3	operator*()	11

5.1.3.4	<code>operator*=()</code>	11
5.1.3.5	<code>operator+()</code>	12
5.1.3.6	<code>operator+=()</code>	12
5.1.3.7	<code>operator-()</code>	13
5.1.3.8	<code>operator-=()</code>	13
5.1.3.9	<code>operator/()</code>	13
5.1.3.10	<code>operator/=()</code>	14
5.1.3.11	<code>operator<()</code>	14
5.1.3.12	<code>operator<=()</code>	14
5.1.3.13	<code>operator=()</code>	15
5.1.3.14	<code>operator==()</code>	15
5.1.3.15	<code>operator>()</code>	15
5.1.3.16	<code>operator>=()</code>	17
5.1.3.17	<code>value()</code>	17
5.2	CairoDrawer Class Reference	18
5.2.1	Detailed Description	19
5.2.2	Member Function Documentation	19
5.2.2.1	<code>change_surface()</code>	20
5.2.2.2	<code>draw_arc()</code>	20
5.2.2.3	<code>draw_arrow()</code>	20
5.2.2.4	<code>draw_connector()</code>	21
5.2.2.5	<code>draw_connector_segment()</code>	21
5.2.2.6	<code>draw_coord_point()</code>	22
5.2.2.7	<code>draw_histogram()</code>	22
5.2.2.8	<code>draw_input_axis()</code>	22
5.2.2.9	<code>draw_line()</code>	23
5.2.2.10	<code>draw_link()</code>	23
5.2.2.11	<code>draw_output_grid()</code>	24
5.2.2.12	<code>draw_output_label()</code>	24
5.2.2.13	<code>draw_relation_element()</code>	24

5.2.2.14	draw_ring_segment()	25
5.2.2.15	draw_segment_axis()	25
5.2.2.16	draw_text_orthogonal()	26
5.2.2.17	draw_text_parallel()	26
5.2.2.18	finish()	26
5.2.2.19	get_cairo_angle()	27
5.2.2.20	set_font_face()	27
5.2.2.21	set_surface()	27
5.3	Cartesian Class Reference	28
5.3.1	Detailed Description	28
5.3.2	Constructor & Destructor Documentation	28
5.3.2.1	Cartesian()	28
5.3.3	Member Function Documentation	29
5.3.3.1	center()	29
5.3.3.2	interpolate()	29
5.3.3.3	operator==()	30
5.3.3.4	x() [1/2]	30
5.3.3.5	x() [2/2]	30
5.3.3.6	y() [1/2]	31
5.3.3.7	y() [2/2]	31
5.4	DataSet< T >::Cell Struct Reference	31
5.4.1	Detailed Description	32
5.4.2	Constructor & Destructor Documentation	32
5.4.2.1	Cell() [1/2]	32
5.4.2.2	Cell() [2/2]	32
5.4.3	Member Data Documentation	32
5.4.3.1	null	32
5.4.3.2	value	32
5.5	Color Class Reference	33
5.5.1	Detailed Description	33

5.5.2	Constructor & Destructor Documentation	33
5.5.2.1	Color()	33
5.5.3	Member Function Documentation	34
5.5.3.1	a()	34
5.5.3.2	b()	34
5.5.3.3	g()	34
5.5.3.4	operator!=(())	34
5.5.3.5	operator==(())	35
5.5.3.6	r()	35
5.5.3.7	set_alpha()	35
5.5.3.8	set_blue()	36
5.5.3.9	set_green()	36
5.5.3.10	set_red()	36
5.5.4	Friends And Related Function Documentation	36
5.5.4.1	operator<<	37
5.5.5	Member Data Documentation	37
5.5.5.1	BLACK	37
5.6	Configuration Class Reference	37
5.6.1	Detailed Description	39
5.6.2	Member Function Documentation	39
5.6.2.1	get_connector_arc_ratio()	39
5.6.2.2	get_grid_size()	39
5.6.2.3	get_height()	40
5.6.2.4	get_histogram_background()	40
5.6.2.5	get_histogram_fill()	40
5.6.2.6	get_histogram_height()	40
5.6.2.7	get_input_file()	41
5.6.2.8	get_input_inner_radius()	41
5.6.2.9	get_input_separation_angle()	41
5.6.2.10	get_input_thickness()	41

5.6.2.11	get_instance()	41
5.6.2.12	get_num_histogram_classes()	42
5.6.2.13	get_num_major_sections_axis()	42
5.6.2.14	get_num_major_sections_grid()	42
5.6.2.15	get_num_minor_sections_axis()	42
5.6.2.16	get_num_minor_sections_grid()	43
5.6.2.17	get_output_angle_span()	43
5.6.2.18	get_output_file()	43
5.6.2.19	get_output_inner_radius()	43
5.6.2.20	get_output_thickness()	44
5.6.2.21	get_prop_axis_label()	44
5.6.2.22	get_prop_scale_label()	44
5.6.2.23	get_prop_thick()	44
5.6.2.24	get_prop_thin()	45
5.6.2.25	get_width()	45
5.6.2.26	initialize() [1/2]	45
5.6.2.27	initialize() [2/2]	45
5.6.2.28	is_histograms_enabled()	46
5.6.2.29	set_connector_arc_ratio()	46
5.6.2.30	set_grid_size()	46
5.6.2.31	set_height()	46
5.6.2.32	set_histogram_background()	47
5.6.2.33	set_histogram_fill()	47
5.6.2.34	set_histogram_height()	47
5.6.2.35	set_histograms_enabled()	48
5.6.2.36	set_input_inner_radius()	48
5.6.2.37	set_input_separation_angle()	48
5.6.2.38	set_input_thickness()	48
5.6.2.39	set_num_histogram_classes()	49
5.6.2.40	set_num_major_sections_axis()	49

5.6.2.41	set_num_major_sections_grid()	49
5.6.2.42	set_num_minor_sections_axis()	50
5.6.2.43	set_num_minor_sections_grid()	50
5.6.2.44	set_output_angle_span()	50
5.6.2.45	set_output_file()	50
5.6.2.46	set_output_inner_radius()	51
5.6.2.47	set_output_thickness()	51
5.6.2.48	set_prop_axis_label()	51
5.6.2.49	set_prop_scale_label()	52
5.6.2.50	set_prop_thick()	52
5.6.2.51	set_prop_thin()	52
5.6.2.52	set_width()	52
5.6.3	Member Data Documentation	53
5.6.3.1	GLOW_10	53
5.6.3.2	SET2_3_1	53
5.6.3.3	SET3	53
5.7	DataSet< T >::DataRow::const_iterator Class Reference	53
5.8	DataSet< T >::const_iterator Class Reference	54
5.9	CoordinateConverter Class Reference	54
5.9.1	Detailed Description	55
5.9.2	Constructor & Destructor Documentation	55
5.9.2.1	CoordinateConverter()	55
5.9.3	Member Function Documentation	55
5.9.3.1	convert() [1/2]	55
5.9.3.2	convert() [2/2]	56
5.9.3.3	get_center_x()	56
5.9.3.4	get_center_y()	56
5.10	DataSet< T >::DataColumn Struct Reference	57
5.10.1	Detailed Description	57
5.10.2	Constructor & Destructor Documentation	57

5.10.2.1	DataColumn()	57
5.10.3	Member Data Documentation	58
5.10.3.1	cells	58
5.10.3.2	type	58
5.10.3.3	var	58
5.11	DataSet< T >::DataRow Class Reference	58
5.11.1	Detailed Description	59
5.11.2	Constructor & Destructor Documentation	59
5.11.2.1	DataRow()	59
5.11.3	Member Function Documentation	59
5.11.3.1	begin()	59
5.11.3.2	end()	60
5.11.3.3	is_enabled()	60
5.11.3.4	operator[]()	60
5.11.3.5	set_enabled()	60
5.11.3.6	size()	61
5.12	DataSet< T > Class Template Reference	61
5.12.1	Detailed Description	62
5.12.2	Member Enumeration Documentation	62
5.12.2.1	ColumnType	62
5.12.3	Member Function Documentation	63
5.12.3.1	begin()	63
5.12.3.2	end()	63
5.12.3.3	get_num_cols()	63
5.12.3.4	get_num_inputs()	64
5.12.3.5	get_num_outputs()	64
5.12.3.6	get_num_rows()	64
5.12.3.7	input_variables()	64
5.12.3.8	operator[]()	65
5.12.3.9	output_variables()	65

5.12.3.10	<code>parse_from_csv()</code>	65
5.12.3.11	<code>restrict_column()</code>	66
5.12.3.12	<code>swap_columns()</code>	66
5.12.3.13	<code>toggle_column()</code>	67
5.13	Drawer Class Reference	67
5.13.1	Detailed Description	68
5.13.2	Constructor & Destructor Documentation	69
5.13.2.1	<code>Drawer()</code>	69
5.13.3	Member Function Documentation	69
5.13.3.1	<code>change_surface()</code>	69
5.13.3.2	<code>create_link_control_point()</code>	69
5.13.3.3	<code>draw_arc()</code>	70
5.13.3.4	<code>draw_arrow()</code>	70
5.13.3.5	<code>draw_connector()</code>	71
5.13.3.6	<code>draw_connector_segment()</code>	71
5.13.3.7	<code>draw_coord_point()</code>	71
5.13.3.8	<code>draw_histogram()</code>	72
5.13.3.9	<code>draw_input_axis()</code>	72
5.13.3.10	<code>draw_line()</code>	73
5.13.3.11	<code>draw_link()</code>	73
5.13.3.12	<code>draw_output_grid()</code>	73
5.13.3.13	<code>draw_output_label()</code>	74
5.13.3.14	<code>draw_relation_element()</code>	74
5.13.3.15	<code>draw_ring_segment()</code>	75
5.13.3.16	<code>draw_segment_axis()</code>	75
5.13.3.17	<code>draw_text_orthogonal()</code>	76
5.13.3.18	<code>draw_text_parallel()</code>	76
5.13.3.19	<code>finish()</code>	76
5.13.3.20	<code>get_connector_end()</code>	77
5.13.3.21	<code>get_connector_start()</code>	77

5.13.3.22 <code>set_surface()</code>	77
5.13.4 Member Data Documentation	78
5.13.4.1 <code>m_coord_converter</code>	78
5.13.4.2 <code>m_num_inputs</code>	78
5.14 <code>DrawerProperties< FillT ></code> Struct Template Reference	78
5.14.1 Detailed Description	79
5.14.2 Constructor & Destructor Documentation	79
5.14.2.1 <code>DrawerProperties()</code>	79
5.14.3 Member Data Documentation	79
5.14.3.1 <code>fill_color</code>	79
5.14.3.2 <code>line_color</code>	80
5.14.3.3 <code>line_width</code>	80
5.15 <code>InputAxis::Histogram</code> Class Reference	80
5.15.1 Constructor & Destructor Documentation	80
5.15.1.1 <code>Histogram()</code>	80
5.15.2 Member Function Documentation	81
5.15.2.1 <code>calculate()</code>	81
5.15.2.2 <code>get_num_intervals()</code>	81
5.15.2.3 <code>get_section_frequency()</code>	81
5.15.2.4 <code>set_num_intervals()</code>	82
5.16 <code>InputAxis</code> Class Reference	82
5.16.1 Detailed Description	83
5.16.2 Constructor & Destructor Documentation	83
5.16.2.1 <code>InputAxis()</code>	83
5.16.3 Member Function Documentation	83
5.16.3.1 <code>calculate_histogram()</code>	84
5.16.3.2 <code>get_end()</code>	84
5.16.3.3 <code>get_height()</code>	84
5.16.3.4 <code>get_histogram()</code>	84
5.16.3.5 <code>get_prop()</code>	85

5.16.3.6	get_radius()	85
5.16.3.7	get_scale()	85
5.16.3.8	get_start()	85
5.16.3.9	get_var()	86
5.16.3.10	make_label()	86
5.16.3.11	set_end()	86
5.16.3.12	set_height()	86
5.16.3.13	set_prop()	87
5.16.3.14	set_radius()	87
5.16.3.15	set_start()	87
5.17	IOVector Class Reference	87
5.17.1	Detailed Description	88
5.17.2	Member Function Documentation	88
5.17.2.1	emplace_back()	88
5.17.2.2	operator[]()	88
5.17.2.3	size()	89
5.18	IOVectorFactory Class Reference	89
5.18.1	Detailed Description	89
5.18.2	Constructor & Destructor Documentation	89
5.18.2.1	IOVectorFactory()	89
5.18.3	Member Function Documentation	90
5.18.3.1	create()	90
5.19	Label Class Reference	90
5.19.1	Detailed Description	91
5.19.2	Constructor & Destructor Documentation	91
5.19.2.1	Label()	91
5.19.3	Member Function Documentation	91
5.19.3.1	get_properties()	91
5.19.3.2	get_text()	92
5.20	Mapper Class Reference	92

5.20.1 Detailed Description	92
5.20.2 Constructor & Destructor Documentation	92
5.20.2.1 Mapper()	92
5.20.3 Member Function Documentation	93
5.20.3.1 inverse()	93
5.20.3.2 map()	93
5.21 DataSet< T >::MockColumn Class Reference	94
5.21.1 Detailed Description	94
5.21.2 Constructor & Destructor Documentation	94
5.21.2.1 MockColumn()	94
5.21.3 Member Function Documentation	95
5.21.3.1 get_type()	95
5.21.3.2 get_var()	95
5.21.3.3 is_enabled()	95
5.21.3.4 operator[]()	95
5.21.3.5 set_enabled()	96
5.21.3.6 size()	96
5.21.3.7 swap()	96
5.22 MultiScale Class Reference	97
5.22.1 Detailed Description	97
5.22.2 Constructor & Destructor Documentation	97
5.22.2.1 MultiScale()	97
5.22.3 Member Function Documentation	98
5.22.3.1 add_scale()	98
5.22.3.2 get_extremes()	98
5.22.3.3 get_scale_number()	98
5.22.3.4 make_labels()	99
5.23 OutputGrid Class Reference	99
5.23.1 Detailed Description	99
5.23.2 Constructor & Destructor Documentation	100

5.23.2.1	OutputGrid()	100
5.23.3	Member Function Documentation	100
5.23.3.1	get_direction()	100
5.23.3.2	get_end()	100
5.23.3.3	get_height()	101
5.23.3.4	get_num_outputs()	101
5.23.3.5	get_radius()	101
5.23.3.6	get_scale()	101
5.23.3.7	get_start()	102
5.23.3.8	get_var()	102
5.23.3.9	set_direction()	102
5.23.3.10	set_end()	102
5.23.3.11	set_height()	103
5.23.3.12	set_radius()	103
5.23.3.13	set_start()	103
5.24	Point Struct Reference	104
5.24.1	Detailed Description	104
5.24.2	Constructor & Destructor Documentation	104
5.24.2.1	Point()	104
5.24.3	Member Data Documentation	105
5.24.3.1	coord	105
5.24.3.2	prop	105
5.25	Polar Class Reference	105
5.25.1	Detailed Description	106
5.25.2	Constructor & Destructor Documentation	106
5.25.2.1	Polar()	106
5.25.3	Member Function Documentation	106
5.25.3.1	angle() [1/2]	106
5.25.3.2	angle() [2/2]	107
5.25.3.3	center()	107

5.25.3.4	interpolate()	107
5.25.3.5	operator==()	108
5.25.3.6	radius() [1/2]	108
5.25.3.7	radius() [2/2]	108
5.26	Scale Class Reference	109
5.26.1	Detailed Description	109
5.26.2	Constructor & Destructor Documentation	109
5.26.2.1	Scale()	109
5.26.3	Member Function Documentation	110
5.26.3.1	get_major_intersections()	110
5.26.3.2	get_minor_intersections()	110
5.27	Scene Class Reference	110
5.27.1	Detailed Description	111
5.27.2	Constructor & Destructor Documentation	111
5.27.2.1	Scene()	111
5.27.3	Member Function Documentation	111
5.27.3.1	get_input_variables()	111
5.27.3.2	get_output_variables()	112
5.27.3.3	restrict_input()	112
5.27.3.4	restrict_output()	112
5.27.3.5	swap_inputs()	113
5.27.3.6	swap_outputs()	113
5.27.3.7	toggle_input()	113
5.27.3.8	toggle_output()	114
5.27.3.9	update()	114
5.28	SimpleScale Class Reference	114
5.28.1	Detailed Description	115
5.28.2	Constructor & Destructor Documentation	115
5.28.2.1	SimpleScale()	115
5.28.3	Member Function Documentation	116

5.28.3.1	get_extremes()	116
5.28.3.2	make_labels()	116
5.29	Drawer::TextAlignment Struct Reference	116
5.29.1	Detailed Description	117
5.30	TextProperties Struct Reference	117
5.30.1	Detailed Description	117
5.30.2	Constructor & Destructor Documentation	118
5.30.2.1	TextProperties()	118
5.30.3	Member Data Documentation	118
5.30.3.1	bold	118
5.30.3.2	color	118
5.30.3.3	font_name	118
5.30.3.4	font_size	119
5.30.3.5	italic	119
5.31	Triangle< T, dim > Class Template Reference	119
5.31.1	Detailed Description	119
5.31.2	Constructor & Destructor Documentation	120
5.31.2.1	Triangle() [1/2]	120
5.31.2.2	Triangle() [2/2]	120
5.31.3	Member Function Documentation	120
5.31.3.1	at() [1/2]	120
5.31.3.2	at() [2/2]	121
5.32	DataSet< T >::Variable Struct Reference	121
5.32.1	Detailed Description	121
5.32.2	Constructor & Destructor Documentation	122
5.32.2.1	Variable()	122
5.32.3	Member Data Documentation	122
5.32.3.1	max	122
5.32.3.2	min	122
5.32.3.3	name	122
5.32.3.4	unit	123

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

angle_helper	7
--	---

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Angle	9
Cartesian	28
DataSet< T >::Cell	31
Color	33
Configuration	37
CoordinateConverter	54
DataSet< T >::DataColumn	57
DataSet< T >::DataRow	58
DataSet< T >	61
Drawer	67
CairoDrawer	18
DrawerProperties< FillT >	78
InputAxis::Histogram	80
InputAxis	82
IOVector	87
IOVectorFactory	89
iterator	
DataSet< T >::const_iterator	54
DataSet< T >::DataRow::const_iterator	53
Label	90
Mapper	92
DataSet< T >::MockColumn	94
OutputGrid	99
Point	104
Polar	105
Scale	109
MultiScale	97
SimpleScale	114
Scene	110
Drawer::TextAlignment	116
TextProperties	117
Triangle< T, dim >	119
Triangle< Color, 12 >	119
DataSet< T >::Variable	121

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Angle	Mathematical angle representation	9
CairoDrawer	SVG surface drawer for MooViE	18
Cartesian	The Cartesian class	28
DataSet< T >::Cell	Cell of a data table	31
Color	RGB color representation	33
Configuration	Configuration for a MooViE run	37
DataSet< T >::DataRow::const_iterator	53
DataSet< T >::const_iterator	54
CoordinateConverter	Converter between polar and cartesian coordinates	54
DataSet< T >::DataColumn	Column of a data table	57
DataSet< T >::DataRow	Row of a data table	58
DataSet< T >	Table of data	61
Drawer	Abstract Drawer for MooViE scenes	67
DrawerProperties< FiIT >	Properties to modify a MooViE drawers behavior	78
InputAxis::Histogram	80
InputAxis	InputAxis MooViE component representation	82
IOVector	IOVector MooViE component representation	87
IOVectorFactory	89
Label	Text label MooViE component representation	90
Mapper	Mapper is a bijective function $f: [a,b] \rightarrow [c,d]$	92

DataSet< T >::MockColumn	
Technical column for internal use	94
MultiScale	97
OutputGrid	
OutputGrid MooViE component representation	99
Point	
Styled polar coordinate	104
Polar	
Polar coordinate representation	105
Scale	
Ticked scale	109
Scene	
MooViE scene	110
SimpleScale	114
Drawer::TextAlignment	
Text alignment representation	116
TextProperties	
Properties to modify a MooViE Drawers text style	117
Triangle< T, dim >	
Triangular set storage	119
DataSet< T >::Variable	
Header description	121

Chapter 4

Namespace Documentation

4.1 angle_helper Namespace Reference

Functions

- double [deg_to_rad](#) (double deg)
- double [rad_to_deg](#) (double rad)
- double **rad_dist** (double rad0, double rad1)

4.1.1 Detailed Description

A namespace for converter functions.

4.1.2 Function Documentation

4.1.2.1 deg_to_rad()

```
double angle_helper::deg_to_rad (  
    double deg ) [inline]
```

Converts degree to radian value.

Parameters

<i>deg</i>	the degree value to be converted
------------	----------------------------------

Returns

the matching radian value

4.1.2.2 rad_to_deg()

```
double angle_helper::rad_to_deg (  
    double rad ) [inline]
```

Converts radian to degree value.

Parameters

<i>rad</i>	the radian value to be converted
------------	----------------------------------

Returns

the matching degree value

Chapter 5

Class Documentation

5.1 Angle Class Reference

Mathematical angle representation.

```
#include <Coordinates.h>
```

Public Member Functions

- [Angle](#) (double angle)
constructor
- double [value](#) () const
- double [operator=](#) (double angle)
- bool [operator==](#) (const [Angle](#) &rhs) const
- bool [operator<](#) (const [Angle](#) &rhs) const
- bool [operator<=](#) (const [Angle](#) &rhs) const
- bool [operator>](#) (const [Angle](#) &rhs) const
- bool [operator>=](#) (const [Angle](#) &rhs) const
- [Angle](#) & [operator+=](#) (const [Angle](#) &rhs)
- [Angle](#) [operator+](#) (const [Angle](#) &rhs) const
this + rhs
- [Angle](#) & [operator-=](#) (const [Angle](#) &rhs)
- [Angle](#) [operator-](#) (const [Angle](#) &rhs) const
this - rhs
- [Angle](#) & [operator*=](#) (double val)
- [Angle](#) [operator*](#) (double val) const
- [Angle](#) & [operator/=](#) (double val)
- [Angle](#) [operator/](#) (double val)

Static Public Member Functions

- static [Angle](#) [interpolate](#) (const [Angle](#) &a1, const [Angle](#) &a2, double p)
- static [Angle](#) [center](#) (const [Angle](#) &a1, const [Angle](#) &a2)

5.1.1 Detailed Description

Mathematical angle representation.

[Angle](#) is a wrapper class for angle values. Angles are stored as radian values. For consistence, its value needs to be in $[0, 2\pi]$.

Author

beyss

Date

03.07.2017

5.1.2 Constructor & Destructor Documentation

5.1.2.1 Angle()

```
Angle::Angle (  
    double angle )    [inline]
```

constructor

Creates a [Angle](#) from an angle value. If necessary, the value is corrected to be consistent.

Parameters

<i>angle</i>	the angle value
--------------	-----------------

5.1.3 Member Function Documentation

5.1.3.1 center()

```
static Angle Angle::center (  
    const Angle & a1,  
    const Angle & a2 )    [inline], [static]
```

Returns the [Angle](#) in the center of two given Angles.

Parameters

<i>a1</i>	the first Angle
<i>a2</i>	the second Angle

Returns

the centered [Angle](#)

5.1.3.2 interpolate()

```
static Angle Angle::interpolate (  
    const Angle & a1,  
    const Angle & a2,  
    double p ) [inline], [static]
```

Returns an [Angle](#) that is (1-p) percent of a1 and p percent of a2. To be consistent, p should be in [0,1].

Parameters

<i>a1</i>	the first angle
<i>a2</i>	the second angle
<i>p</i>	the percentage

Returns

the interpolated [Angle](#)

5.1.3.3 operator*()

```
Angle Angle::operator* (  
    double val ) const [inline]
```

Multiplication operator returning an [Angle](#) with the value of adjusted this * val.

Parameters

<i>val</i>	the factor
------------	------------

Returns

a new [Angle](#) equal to this * val

5.1.3.4 operator*=()

```
Angle& Angle::operator*= (  
    double val ) [inline]
```

Multiplication assignment operator multiplying this [Angle](#)'s value with the given double value. If necessary, the value is corrected to be consistent.

Parameters

<i>rhs</i>	the factor
------------	------------

Returns

a reference to this angle

5.1.3.5 operator+()

```
Angle Angle::operator+ (
    const Angle & rhs ) const [inline]
```

this + rhs

Friend addition operator returning an [Angle](#) equal to the return of this += rhs. It operates on a copy of lhs so that the original object is not changed.

Parameters

<i>rhs</i>	the right operand Angle
------------	---

Returns

a new [Angle](#) equal to this + rhs

5.1.3.6 operator+=()

```
Angle& Angle::operator+= (
    const Angle & rhs ) [inline]
```

Addition assignment operator increasing this [Angle](#)'s value by the other [Angle](#)'s value. If necessary, the value is corrected to be consistent.

Parameters

<i>rhs</i>	the other Angle
------------	---------------------------------

Returns

a reference to this angle

5.1.3.7 operator-()

```
Angle Angle::operator- (
    const Angle & rhs ) const [inline]
```

this - rhs

Friend addition operator returning an [Angle](#) equal to the return of this - rhs. It operates on a copy of lhs so that the original object is not changed.

Parameters

<i>rhs</i>	the right operand Angle
------------	---

Returns

a new [Angle](#) equal to this - rhs

5.1.3.8 operator-=()

```
Angle& Angle::operator-= (
    const Angle & rhs ) [inline]
```

Subtraction assignment operator decreasing this [Angle](#)'s value by the other [Angle](#)'s value. If necessary, the value is corrected to be consistent.

Parameters

<i>rhs</i>	the other angle
------------	-----------------

Returns

a reference to this angle

5.1.3.9 operator/()

```
Angle Angle::operator/ (
    double val ) [inline]
```

Division operator returning an [Angle](#) with the value of adjusted this / val.

Parameters

<i>val</i>	the dividend
------------	--------------

Returns

a new [Angle](#) equal to this / val

5.1.3.10 operator/=()

```
Angle& Angle::operator/= (
    double val ) [inline]
```

Division assignment operator divides this [Angle](#)'s value by the given double value. If necessary, the value is corrected to be consistent.

Parameters

<i>val</i>	the dividend
------------	--------------

Returns

a reference to this angle

5.1.3.11 operator<()

```
bool Angle::operator< (
    const Angle & rhs ) const [inline]
```

Smaller than operator checking whether this [Angle](#)'s value is smaller than the other [Angle](#)'s value.

Parameters

<i>rhs</i>	the other Angle
------------	---------------------------------

Returns

if smaller than or not

5.1.3.12 operator<=()

```
bool Angle::operator<= (
    const Angle & rhs ) const [inline]
```

Smaller than or equal to operator checking whether this [Angle](#)'s value is smaller than or equal to the other [Angle](#)'s value.

Parameters

<i>rhs</i>	the other Angle
------------	---------------------------------

Returns

if smaller than or equal or not

5.1.3.13 operator=()

```
double Angle::operator= (
    double angle ) [inline]
```

Assignment operator setting this [Angle](#)'s value. If necessary, the value is corrected to be consistent.

Parameters

<i>angle</i>	the angle value in radians
--------------	----------------------------

Returns

the adjusted angle value

5.1.3.14 operator==()

```
bool Angle::operator== (
    const Angle & rhs ) const [inline]
```

Equal to operator checking whether this [Angle](#)'s value is equal to the other [Angle](#)'s value.

Parameters

<i>rhs</i>	the other Angle
------------	---------------------------------

Returns

if equal or not

5.1.3.15 operator>()

```
bool Angle::operator> (
    const Angle & rhs ) const [inline]
```

Greater than operator checking whether this [Angle](#)'s value is greater than the other [Angle](#)'s value.

Parameters

<i>rhs</i>	the other Angle
------------	---------------------------------

Returns

if greater than or not

5.1.3.16 operator>=()

```
bool Angle::operator>= (
    const Angle & rhs ) const [inline]
```

Greater than or equal to operator checking whether this [Angle](#)'s value is smaller than or equal to the other [Angle](#)'s value.

Parameters

<i>rhs</i>	the other Angle
------------	---------------------------------

Returns

if greater than or equal or not

5.1.3.17 value()

```
double Angle::value ( ) const [inline]
```

Returns the value of this angle.

Returns

the angle value

The documentation for this class was generated from the following file:


- include/Coordinates.h

5.2 CairoDrawer Class Reference

SVG surface drawer for MooViE.

```
#include <CairoDrawer.h>
```

Inheritance diagram for CairoDrawer:



Public Member Functions

- **CairoDrawer** (const std::string &fpath, int width, int height, std::size_t num_inputs_)
- virtual void [change_surface](#) (const std::string &fpath, int width, int height, std::size_t num_inputs_)
- virtual void [draw_output_grid](#) (const [OutputGrid](#) &grid)
- virtual void [draw_input_axis](#) (const [InputAxis](#) &axis)
- virtual void [draw_relation_element](#) (const [IOVector](#) &link)
- virtual void [finish](#) ()

Static Public Attributes

- static const double **RADIAL_TEXT_FACTOR**
- static const double **COORDGRID_ADJUSTMENT**
- static const double **COORDPOINT_ANGLE**
- static const double **COORDGRID_DESCRIPTION_ANGLE**
- static const double **END_RADIUS_MAJOR_FACTOR**
- static const double **END_RADIUS_MINOR_FACTOR**
- static const double **RADIUS_TICK_LABEL_FACTOR**
- static const double **DATA_LINK_LINE_WIDTH**
- static const double **CONNECTOR_ARROW_HEIGHT**
- static const double **RADIUS_LABEL_DELTA**
- static const double **RADIUS_HISTOGRAM_DELTA**
- static const double **CONNECTOR_DELTA**
- static const double **TEXT_DELTA**
- static const double **ANGLE_DELTA_SMALL**
- static const double **ANGLE_DELTA_MEDIUM**
- static const double **ANGLE_DELTA_LARGE**
- static const double **RADIUS_DELTA**
- static const double **OUTPUT_EXTREME_RADIUS_DELTA**
- static const double **OUTPUT_LABEL_LINE_END_DELTA**
- static const double **OUTPUT_LABEL_RADIUS_DELTA**

Protected Member Functions

- virtual void [set_surface](#) (const std::string &fpath, int width, int height)
- virtual void [draw_histogram](#) (const [InputAxis::Histogram](#) &histogram, double radius, const [Angle](#) &start, const [Angle](#) &end)
- virtual void [draw_link](#) (const [Polar](#) &origin1, const [Polar](#) &origin2, const [Polar](#) &target1, const [Polar](#) &target2, const [DrawerProperties](#)<> &prop)
- virtual void [draw_connector](#) (const [Polar](#) &from, const [Polar](#) &to, const [DrawerProperties](#)<> &prop)
- virtual void [draw_segment_axis](#) (double inner_radius, double thickness, const [Angle](#) &start, const [Angle](#) &end, const [DrawerProperties](#)< std::array< [Color](#), 10 >> &prop, Direction dir)
- virtual void [draw_output_label](#) (const [Label](#) &output_label, double radius_label, double radius_output, const [Angle](#) &begin, const [Angle](#) &end)
- virtual void [draw_arrow](#) (const [Polar](#) &start, const [DrawerProperties](#)<> &prop)
- virtual void [draw_ring_segment](#) (double radius, double thickness, const [Angle](#) &begin, const [Angle](#) &end, const [DrawerProperties](#)<> &prop, Direction dir)
- virtual void [draw_connector_segment](#) (double begin_radius, double begin_angle, double end_radius, double end_angle, const [DrawerProperties](#)<> &prop)
- virtual void [draw_line](#) (const [Polar](#) &from, const [Polar](#) &to, const [DrawerProperties](#)<> &prop)
- virtual void [draw_arc](#) (double inner_radius, const [Angle](#) &start, const [Angle](#) &end, Direction dir)
- virtual void [draw_coord_point](#) (const [Polar](#) &coord, const [Angle](#) &width, double height, const [DrawerProperties](#)<> &prop)
- virtual void [draw_text_parallel](#) (const [Label](#) &label, const [Polar](#) &start, const [TextAlignment](#) &alignment=TextAlignment::CENTERED)
- virtual void [draw_text_orthogonal](#) (const [Label](#) &label, const [Polar](#) &start, const [TextAlignment](#) &alignment=TextAlignment::CENTERED)
- void [set_font_face](#) (const [Label](#) &label)
set font style
- Cairo::TextExtents [get_text_extents](#) (const [Label](#) &label) const
- [Angle](#) [get_cairo_angle](#) (const [Angle](#) &angle)

Additional Inherited Members

5.2.1 Detailed Description

SVG surface drawer for MooViE.

[CairoDrawer](#) is a wrapper class for MooViE's basic drawing abilities which are realized using Cairo.

Authors

beyss, stratmann

Date

05.07.2017

5.2.2 Member Function Documentation

5.2.2.1 `change_surface()`

```
virtual void CairoDrawer::change_surface (
    const std::string & fpath,
    int width,
    int height,
    std::size_t num_inputs ) [virtual]
```

Alters the surface of this [Drawer](#) in number of inputs, width, height and storage path. All unsafed changes will be stored and all kept resources freed correctly.

Parameters

<i>fpath</i>	a string containing an valid existing or accessible not existing path
<i>width</i>	an integer between 0 and MAX_INT
<i>height</i>	an integer between 0 and MAX_INT
<i>num_inputs</i>	the number of inputs

Implements [Drawer](#).

5.2.2.2 `draw_arc()`

```
virtual void CairoDrawer::draw_arc (
    double inner_radius,
    const Angle & start,
    const Angle & end,
    Direction dir ) [protected], [virtual]
```

Draws a simple edge segment around the center of its coordinate system between the two given Angles and with the given radius.

Parameters

<i>inner_radius</i>	the inner radius
<i>start</i>	the start Angle
<i>end</i>	the end Angle
<i>dir</i>	the direction

Implements [Drawer](#).

5.2.2.3 `draw_arrow()`

```
virtual void CairoDrawer::draw_arrow (
    const Polar & start,
    const DrawerProperties<> & prop ) [protected], [virtual]
```

Draws a arrow head from a given start pointing.

Parameters

<i>start</i>	the start of the arrow head
<i>prop</i>	DrawerProperties for the arrow head

Implements [Drawer](#).

5.2.2.4 draw_connector()

```
virtual void CairoDrawer::draw_connector (
    const Polar & from,
    const Polar & to,
    const DrawerProperties<> & prop ) [protected], [virtual]
```

Draws a connection between to given polar coordinates. The connection is a bezier curve which is controlled by automatically generated control points.

Parameters

<i>from</i>	the start Polar
<i>to</i>	the end Polar
<i>prop</i>	the DrawerProperties

Implements [Drawer](#).

5.2.2.5 draw_connector_segment()

```
virtual void CairoDrawer::draw_connector_segment (
    double start_radius,
    double start_angle,
    double end_radius,
    double end_angle,
    const DrawerProperties<> & prop ) [protected], [virtual]
```

Draws a Bezier curve from [Polar\(start_radius, start_angle\)](#) to [Polar\(end_radius, end_angle\)](#) which approximately behaves like Archimedean spiral. If the smaller difference angle between start_angle and end_angle is bigger than PI, the spiral will be approximated by two Bezier curves.

Parameters

<i>start_radius</i>	the radius of the starting point
<i>start_angle</i>	the angle of the starting point
<i>end_radius</i>	the radius of the end point
<i>end_angle</i>	the angle of the end point
<i>prop</i>	the DrawerProperties for the segment

Implements [Drawer](#).

5.2.2.6 draw_coord_point()

```
virtual void CairoDrawer::draw_coord_point (
    const Polar & coord,
    const Angle & width,
    double height,
    const DrawerProperties<> & prop ) [protected], [virtual]
```

Draws a coordinate point with given height and with.

Parameters

<i>coord</i>	the polar coordinate to draw
<i>width</i>	the width
<i>height</i>	the height
<i>prop</i>	the DrawerProperties

Implements [Drawer](#).

5.2.2.7 draw_histogram()

```
virtual void CairoDrawer::draw_histogram (
    const InputAxis::Histogram & histogram,
    double radius,
    const Angle & start,
    const Angle & end ) [protected], [virtual]
```

Draws a Histogram from the given radius, between begin and end [Angle](#). For the histogram height, thin or thick lines the properties given by the [Configuration](#) instance are used.

Parameters

<i>histogram</i>	the Histogram to draw
<i>radius</i>	the start radius of the Histogram
<i>start</i>	the starting angle of the Histogram
<i>end</i>	the end angle of the Histogram

Implements [Drawer](#).

5.2.2.8 draw_input_axis()

```
virtual void CairoDrawer::draw_input_axis (
    const InputAxis & axis ) [virtual]
```

Draws a [InputAxis](#) using its radius and angles. For thin or thick lines the properties given by the [Configuration](#) instance are used.

Parameters

<i>axis</i>	the InputAxis to draw
-------------	---------------------------------------

Implements [Drawer](#).

5.2.2.9 draw_line()

```
virtual void CairoDrawer::draw_line (
    const Polar & from,
    const Polar & to,
    const DrawerProperties<> & prop ) [protected], [virtual]
```

Draws a line from a given starting vertice to a given end vertice.

Parameters

<i>from</i>	the starting coordinates
<i>to</i>	the end coordinates
<i>prop</i>	the DrawerProperties to use

Implements [Drawer](#).

5.2.2.10 draw_link()

```
virtual void CairoDrawer::draw_link (
    const Polar & origin1,
    const Polar & origin2,
    const Polar & target1,
    const Polar & target2,
    const DrawerProperties<> & prop ) [protected], [virtual]
```

Draws a bold line between the lines origin1-origin2 and target1-target2. This is realized by drawing Bezier curves from origin1 to target1 and from origin2 to target2 and filling the so created surface.

Parameters

<i>origin1</i>	first origin coordinate
<i>origin2</i>	second origin coordinate
<i>target1</i>	first target coordinate
<i>target2</i>	second target coordinate
<i>prop</i>	DrawerProperties for the link

Implements [Drawer](#).

5.2.2.11 draw_output_grid()

```
virtual void CairoDrawer::draw_output_grid (
    const OutputGrid & grid ) [virtual]
```

Draws a [OutputGrid](#) using its radius and angles. For thin or thick lines the properties given by the [Configuration](#) instance are used.

Parameters

<i>grid</i>	the OutputGrid to draw
-------------	--

Implements [Drawer](#).

5.2.2.12 draw_output_label()

```
virtual void CairoDrawer::draw_output_label (
    const Label & output_label,
    double radius_label,
    double radius_output,
    const Angle & begin,
    const Angle & end ) [protected], [virtual]
```

Draws the given [Label](#) output_label with the radius radius_label and a descriptive path that connects the output label with the associated output. The path consists of an arc segment and a line.

Parameters

<i>output_label</i>	the output label to draw
<i>radius_label</i>	the radius of the output label
<i>radius_output</i>	the radius of the associated output
<i>begin</i>	the angle at which the output ends
<i>end</i>	the angle at which the arc ends

Implements [Drawer](#).

5.2.2.13 draw_relation_element()

```
virtual void CairoDrawer::draw_relation_element (
    const IOVector & elem ) [virtual]
```

Draws a [IOVector](#) using its coordinates.

Parameters

<i>elem</i>	the IOVector to draw
-------------	--------------------------------------

Implements [Drawer](#).

5.2.2.14 draw_ring_segment()

```
virtual void CairoDrawer::draw_ring_segment (
    double radius,
    double thickness,
    const Angle & start,
    const Angle & end,
    const DrawerProperties<> & prop,
    Direction dir ) [protected], [virtual]
```

Draws a filled ring segment around the center of its coordinate system between the two given Angles and with the given radius.

Parameters

<i>radius</i>	the radius
<i>thickness</i>	the thickness of the edge segment
<i>begin</i>	the begin Angle
<i>end</i>	the end Angle
<i>prop</i>	the CairoDrawer properties
<i>dir</i>	the direction

Implements [Drawer](#).

5.2.2.15 draw_segment_axis()

```
virtual void CairoDrawer::draw_segment_axis (
    double inner_radius,
    double thickness,
    const Angle & begin,
    const Angle & end,
    const DrawerProperties< std::array< Color, 10 >> & prop,
    Direction dir ) [protected], [virtual]
```

Draws a circle segment which is itself divided in colored segments.

Parameters

<i>inner_radius</i>	inner radius of the split axis
<i>thickness</i>	width of the split axis
<i>begin</i>	angle of the segments begin
<i>end</i>	angle of the segments end
<i>prop</i>	color
<i>dir</i>	direction of the split axis' colors

Implements [Drawer](#).

5.2.2.16 draw_text_orthogonal()

```
virtual void CairoDrawer::draw_text_orthogonal (
    const Label & label,
    const Polar & start,
    const TextAlignment & alignment = TextAlignment::CENTERED ) [protected], [virtual]
```

Draws the given label orthogonal to the angle of the given coordinate's angle.

Parameters

<i>label</i>	the label to draw
<i>start</i>	the coordinate to adjust to

Implements [Drawer](#).

5.2.2.17 draw_text_parallel()

```
virtual void CairoDrawer::draw_text_parallel (
    const Label & label,
    const Polar & start,
    const TextAlignment & alignment = TextAlignment::CENTERED ) [protected], [virtual]
```

Draws the given label with the same angle like the given coordinate.

Parameters

<i>label</i>	the label to draw
<i>start</i>	the coordinate to adjust to

Implements [Drawer](#).

5.2.2.18 finish()

```
virtual void CairoDrawer::finish ( ) [virtual]
```

Save the [Drawer](#)'s result to the given file.

Implements [Drawer](#).

5.2.2.19 `get_cairo_angle()`

```
Angle CairoDrawer::get_cairo_angle (
    const Angle & angle ) [inline], [protected]
```

Cairo uses an non-standard way to define angles. The angle of 0 is on the positive X axis, but the angle of $\pi/2$ or 90° is on the negative Y axis (the common model uses the positive Y axis).

Parameters

<i>angle</i>	
--------------	--

Returns

the cairo angle

5.2.2.20 `set_font_face()`

```
void CairoDrawer::set_font_face (
    const Label & label ) [protected]
```

set font style

Sets the font face according to the [TextProperties](#) of the given [Label](#).

Parameters

<i>label</i>	the Label whose properties to set
--------------	---

5.2.2.21 `set_surface()`

```
virtual void CairoDrawer::set_surface (
    const std::string & fpath,
    int width,
    int height ) [protected], [virtual]
```

Alters the surface of this [Drawer](#) in with, height and storage path.

Parameters

<i>fpath</i>	a string containing an valid or accessible path
<i>width</i>	an integer between 0 and MAX_INT
<i>height</i>	an integer between 0 and MAX_INT

Implements [Drawer](#).

The documentation for this class was generated from the following file:

- include/CairoDrawer.h

5.3 Cartesian Class Reference

The [Cartesian](#) class.

```
#include <Coordinates.h>
```

Public Member Functions

- [Cartesian](#) (double *x*=0, double *y*=0)
Cartesian.
- bool *operator==* (const [Cartesian](#) &rhs) const
operator ==
- const double & *x* () const
x
- double & *x* ()
x
- const double & *y* () const
y
- double & *y* ()
y

Static Public Member Functions

- static [Cartesian interpolate](#) (const [Cartesian](#) &p1, const [Cartesian](#) &p2, double p)
interpolate
- static [Cartesian center](#) (const [Cartesian](#) &p1, const [Cartesian](#) &p2)
center

5.3.1 Detailed Description

The [Cartesian](#) class.

[Cartesian](#) represents a tuple from the \mathbb{R}^2 as cartesian coordinate.

5.3.2 Constructor & Destructor Documentation

5.3.2.1 Cartesian()

```
Cartesian::Cartesian (
    double x = 0,
    double y = 0 ) [inline]
```

[Cartesian.](#)

Creates a cartesian coordinate from given x and y value.

Parameters

<i>x</i>	the x value
<i>y</i>	the y value

5.3.3 Member Function Documentation

5.3.3.1 center()

```
static Cartesian Cartesian::center (
    const Cartesian & p1,
    const Cartesian & p2 ) [inline], [static]
```

center

Returns a [Cartesian](#) centered between two given [Cartesian](#).

Parameters

<i>p1</i>	the first Cartesian
<i>p2</i>	the second Cartesian

Returns

the centered [Cartesian](#)

5.3.3.2 interpolate()

```
static Cartesian Cartesian::interpolate (
    const Cartesian & p1,
    const Cartesian & p2,
    double p ) [inline], [static]
```

interpolate

Returns an [Cartesian](#) whose radius and [Angle](#) are (1-p) percent of p1's and p percent of p2's radius and [Angle](#). To be consistent, p should be in [0,1].

Parameters

<i>p1</i>	the first Cartesian
<i>p2</i>	the second Cartesian
<i>p</i>	the percentage

Returns

the interpolated [Cartesian](#)

5.3.3.3 operator==()

```
bool Cartesian::operator== (
    const Cartesian & rhs ) const [inline]
```

operator ==

Equal to operator checking for equality of x and y.

Parameters

<i>rhs</i>	the other Cartesian
------------	-------------------------------------

Returns

if equal or not

5.3.3.4 x() [1/2]

```
const double& Cartesian::x ( ) const [inline]
```

x

Access function for this [Cartesian](#)'s x value as readonly.

Returns

a constant reference to this Cartesians x value

5.3.3.5 x() [2/2]

```
double& Cartesian::x ( ) [inline]
```

x

Access function for this [Cartesian](#)'s x value.

Returns

a reference to this Cartesians x value

5.3.3.6 y() [1/2]

```
const double& Cartesian::y ( ) const [inline]
```

y

Access function for this [Cartesian](#)'s y value as readonly.

Returns

a constant reference to this Cartesians y value

5.3.3.7 y() [2/2]

```
double& Cartesian::y ( ) [inline]
```

y

Access function for this [Cartesian](#)'s y value.

Returns

a reference to this Cartesians y value

The documentation for this class was generated from the following file:

- include/Coordinates.h

5.4 DataSet< T >::Cell Struct Reference

[Cell](#) of a data table.

```
#include <DataSet.h>
```

Public Member Functions

- [Cell](#) ()
- [Cell](#) (T value_)

Public Attributes

- const bool [null](#)
- const T [value](#)

5.4.1 Detailed Description

```
template<typename T>
struct DataSet< T >::Cell
```

[Cell](#) of a data table.

Stores the value of a cell. The value is 0 if the [Cell](#) is a null cell.

5.4.2 Constructor & Destructor Documentation

5.4.2.1 [Cell\(\)](#) [1/2]

```
template<typename T >
DataSet< T >::Cell::Cell ( ) [inline]
```

Creates a new null [Cell](#).

5.4.2.2 [Cell\(\)](#) [2/2]

```
template<typename T >
DataSet< T >::Cell::Cell (
    T value_ ) [inline]
```

Creates a new non-null [Cell](#) storing the value of T

5.4.3 Member Data Documentation

5.4.3.1 [null](#)

```
template<typename T >
const bool DataSet< T >::Cell::null
```

Null or not

5.4.3.2 [value](#)

```
template<typename T >
const T DataSet< T >::Cell::value
```

The value of the cell

The documentation for this struct was generated from the following file:

- include/DataSet.h

5.5 Color Class Reference

RGB color representation.

```
#include <Color.h>
```

Public Member Functions

- [Color](#) (double [r](#)=0, double [g](#)=0, double [b](#)=0, double [a](#)=1)
- **Color** (const [Color](#) &c, double [a](#))
- const double & [r](#) () const
- const double & [g](#) () const
- const double & [b](#) () const
- const double & [a](#) () const
- bool [operator==](#) (const [Color](#) &color) const
- bool [operator!=](#) (const [Color](#) &color) const
- void [set_red](#) (double red)
- void [set_green](#) (double green)
- void [set_blue](#) (double blue)
- void [set_alpha](#) (double alpha)

Static Public Attributes

- static const [Color](#) [BLACK](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &o, const [Color](#) &c)

5.5.1 Detailed Description

RGB color representation.

[Color](#) class represents a color by RGB and alpha value.

Authors

beyss, stratmann

Date

27.07.2017

5.5.2 Constructor & Destructor Documentation

5.5.2.1 Color()

```
Color::Color (  
    double r = 0,  
    double g = 0,  
    double b = 0,  
    double a = 1 ) [inline]
```

Creates a [Color](#) from RGB and Alpha values.

Parameters

<i>r</i>	the red value
<i>g</i>	the green value
<i>b</i>	the blue value
<i>a</i>	the alpha value

5.5.3 Member Function Documentation

5.5.3.1 a()

```
const double& Color::a ( ) const [inline]
```

Access function for the color's alpha value.

Returns

a reference to the colors alpha value

5.5.3.2 b()

```
const double& Color::b ( ) const [inline]
```

Access function for the color's blue value.

Returns

a reference to the colors blue value

5.5.3.3 g()

```
const double& Color::g ( ) const [inline]
```

Access function for the color's green value.

Returns

a reference to the colors green value

5.5.3.4 operator!=()

```
bool Color::operator!= (
    const Color & color ) const [inline]
```

Checks whether or not two colors are not equal. Two colors would be equal if their RGBA values were the same.

Parameters

<i>color</i>	the other color
--------------	-----------------

Returns

not equal or equal

5.5.3.5 operator==()

```
bool Color::operator== (
    const Color & color ) const [inline]
```

Checks whether or not two colors are equal. This is the case if RGBA values are the same.

Parameters

<i>color</i>	the other color
--------------	-----------------

Returns

equal or not

5.5.3.6 r()

```
const double& Color::r ( ) const [inline]
```

Access function for the color's red value.

Returns

a reference to the colors red value

5.5.3.7 set_alpha()

```
void Color::set_alpha (
    double alpha ) [inline]
```

Sets the alpha value of this Color. Input values from 0 to 255 will be automatically corrected to values from [0,1].

Parameters

<i>alpha</i>	the alpha value to set
--------------	------------------------

5.5.3.8 set_blue()

```
void Color::set_blue (
    double blue ) [inline]
```

Sets the blue value of this [Color](#). Input values from 0 to 255 will be automatically corrected to values from [0,1].

Parameters

<i>blue</i>	the blue value to set
-------------	-----------------------

5.5.3.9 set_green()

```
void Color::set_green (
    double green ) [inline]
```

Sets the green value of this [Color](#). Input values from 0 to 255 will be automatically corrected to values from [0,1].

Parameters

<i>green</i>	the green value to set
--------------	------------------------

5.5.3.10 set_red()

```
void Color::set_red (
    double red ) [inline]
```

Sets the red value of this [Color](#). Input values from 0 to 255 will be automatically corrected to values from [0,1].

Parameters

<i>red</i>	the red value to set
------------	----------------------

5.5.4 Friends And Related Function Documentation

5.5.4.1 operator<<

```
std::ostream& operator<< (
    std::ostream & o,
    const Color & c ) [friend]
```

Puts string representation of [Color](#) c to the output stream o.

Parameters

<i>o</i>	the ostream to put into
<i>c</i>	the color to put

5.5.5 Member Data Documentation

5.5.5.1 BLACK

```
const Color Color::BLACK [static]
```

A [Color](#) constant representing black (0,0,0,1)

The documentation for this class was generated from the following file:

- include/Color.h

5.6 Configuration Class Reference

[Configuration](#) for a MooViE run.

```
#include <Configuration.h>
```

Public Member Functions

- const std::string & [get_input_file](#) () const
- void [set_input_file](#) (const std::string &input_file)
- const std::string & [get_output_file](#) () const
- void [set_output_file](#) (const std::string &output_file)
- int [get_width](#) () const
- void [set_width](#) (int width)
- int [get_height](#) () const
- void [set_height](#) (int height)
- double [get_output_angle_span](#) () const
- void [set_output_angle_span](#) (double output_angle_span)
- double [get_output_inner_radius](#) () const
- void [set_output_inner_radius](#) (double output_inner_radius)

- double [get_output_thickness](#) () const
- void [set_output_thickness](#) (double output_thickness)
- double [get_grid_size](#) () const
- void [set_grid_size](#) (double grid_size)
- int [get_num_major_sections_grid](#) () const
- void [set_num_major_sections_grid](#) (int major_sections)
- int [get_num_minor_sections_grid](#) () const
- void [set_num_minor_sections_grid](#) (int minor_sections)
- double [get_input_inner_radius](#) () const
- void [set_input_inner_radius](#) (double input_inner_radius)
- double [get_input_separation_angle](#) () const
- void [set_input_separation_angle](#) (double input_separation_angle)
- double [get_input_thickness](#) () const
- void [set_input_thickness](#) (double input_thickness)
- int [get_num_major_sections_axis](#) () const
- void [set_num_major_sections_axis](#) (int major_sections)
- int [get_num_minor_sections_axis](#) () const
- void [set_num_minor_sections_axis](#) (int minor_sections)
- bool [is_histograms_enabled](#) () const
- void [set_histograms_enabled](#) (bool histograms_enabled)
- int [get_num_histogram_classes](#) () const
- void [set_num_histogram_classes](#) (int num_histogram_classes)
- double [get_histogram_height](#) () const
- void [set_histogram_height](#) (double histogram_height)
- const [Color](#) & [get_histogram_background](#) () const
- void [set_histogram_background](#) (const [Color](#) &histogram_background)
- const [Color](#) & [get_histogram_fill](#) () const
- void [set_histogram_fill](#) (const [Color](#) &histogram_fill)
- double [get_connector_arc_ratio](#) () const
- void [set_connector_arc_ratio](#) (double connector_arc_ratio)
- const [DrawerProperties](#) & [get_prop_thick](#) () const
- void [set_prop_thick](#) (const [DrawerProperties](#)<> &prop_thick)
- const [DrawerProperties](#) & [get_prop_thin](#) () const
- void [set_prop_thin](#) (const [DrawerProperties](#)<> &prop_thin)
- const [TextProperties](#) & [get_prop_scale_label](#) () const
- void [set_prop_scale_label](#) (const [TextProperties](#) &prop_scale_label)
- const [TextProperties](#) & [get_prop_axis_label](#) () const
- void [set_prop_axis_label](#) (const [TextProperties](#) &prop_axis_label)

Static Public Member Functions

- static [Configuration](#) & [get_instance](#) ()
- static void [initialize](#) (const std::string &fname, const std::string &cpath)
- static void [initialize](#) (const std::string &fname)

Static Public Attributes

- static const std::array< [Color](#), 10 > [GLOW_10](#)
- static const [Triangle](#)< [Color](#), 12 > [SET3](#)
- static const [Color](#) [SET2_3_1](#)
- static const [Color](#) [SET2_3_2](#)
- static const [Color](#) [SET2_3_3](#)

5.6.1 Detailed Description

[Configuration](#) for a MooViE run.

A class wrapping the settings and information that is necessary for a MooViE run. [Configuration](#) is implemented as a singleton. Before calling [Configuration::get_instance](#) to get the singleton instance [Configuration::initialize](#) need to be called once.

Author

stratmann

Date

16.01.2018

5.6.2 Member Function Documentation

5.6.2.1 `get_connector_arc_ratio()`

```
double Configuration::get_connector_arc_ratio ( ) const [inline]
```

Returns the ratio of the radial distance between two data points that will be drawn as connector.

Returns

the connector arc ratio

5.6.2.2 `get_grid_size()`

```
double Configuration::get_grid_size ( ) const [inline]
```

Returns the size of actual grid that is a part of the [OutputGrid](#).

Returns

the m_grid_size

5.6.2.3 get_height()

```
int Configuration::get_height ( ) const [inline]
```

Returns the height of the MooViE scene

Returns

the height

5.6.2.4 get_histogram_background()

```
const Color& Configuration::get_histogram_background ( ) const [inline]
```

Returns the background color that each histogram has.

Returns

the histogram background color

5.6.2.5 get_histogram_fill()

```
const Color& Configuration::get_histogram_fill ( ) const [inline]
```

Returns the fill color of each histogram's bars.

Returns

the histogram fill color

5.6.2.6 get_histogram_height()

```
double Configuration::get_histogram_height ( ) const [inline]
```

Returns the height that each histogram has.

Returns

the histogram height

5.6.2.7 `get_input_file()`

```
const std::string& Configuration::get_input_file ( ) const [inline]
```

Returns the path to the input file.

Returns

the input file path

5.6.2.8 `get_input_inner_radius()`

```
double Configuration::get_input_inner_radius ( ) const [inline]
```

Returns the inner radius of an input, the radius where the [InputAxis](#) start.

Returns

the input inner radius

5.6.2.9 `get_input_separation_angle()`

```
double Configuration::get_input_separation_angle ( ) const [inline]
```

Returns the separation angle between inputs.

Returns

the input separation angle

5.6.2.10 `get_input_thickness()`

```
double Configuration::get_input_thickness ( ) const [inline]
```

Returns the thickness of the colored ring of the [InputAxis](#).

Returns

the input thickness

5.6.2.11 `get_instance()`

```
static Configuration& Configuration::get_instance ( ) [inline], [static]
```

Returns a reference to the singleton instance of [Configuration](#). [Configuration::initialize](#) needs to be called at least once before.

Returns

the reference to the [Configuration](#) instance

Exceptions

<i>bad_function_call</i>	if instance was not initialized
--------------------------	---------------------------------

5.6.2.12 `get_num_histogram_classes()`

```
int Configuration::get_num_histogram_classes ( ) const [inline]
```

Returns the number of classes that each histogram consists of.

Returns

the number of histogram classes

5.6.2.13 `get_num_major_sections_axis()`

```
int Configuration::get_num_major_sections_axis ( ) const [inline]
```

Returns the number of bold sections of the scale of the [InputAxis](#).

Returns

the number of major sections

5.6.2.14 `get_num_major_sections_grid()`

```
int Configuration::get_num_major_sections_grid ( ) const [inline]
```

Returns the number of bold sections of the scale of the [OutputGrid](#).

Returns

the number of major sections

5.6.2.15 `get_num_minor_sections_axis()`

```
int Configuration::get_num_minor_sections_axis ( ) const [inline]
```

Returns the number of narrow sections of the scale of the [InputAxis](#).

Returns

the number of minor sections

5.6.2.16 `get_num_minor_sections_grid()`

```
int Configuration::get_num_minor_sections_grid ( ) const [inline]
```

Returns the number of narrow sections of the scale of the [OutputGrid](#).

Returns

the number of minor sections

5.6.2.17 `get_output_angle_span()`

```
double Configuration::get_output_angle_span ( ) const [inline]
```

Returns the output angle span, the angle span for the [OutputGrid](#).

Returns

the output angle span

5.6.2.18 `get_output_file()`

```
const std::string& Configuration::get_output_file ( ) const [inline]
```

Returns the path to the output file.

Returns

the output file path

5.6.2.19 `get_output_inner_radius()`

```
double Configuration::get_output_inner_radius ( ) const [inline]
```

Returns the inner radius of the output, the radius at which the [OutputGrid](#) starts.

Returns

the output inner radius

5.6.2.20 `get_output_thickness()`

```
double Configuration::get_output_thickness ( ) const [inline]
```

Returns the thickness of the outputs colored segmented ring.

Returns

the output thickness

5.6.2.21 `get_prop_axis_label()`

```
const TextProperties& Configuration::get_prop_axis_label ( ) const [inline]
```

Returns MooViEs [TextProperties](#) for [InputAxis](#) labels.

Returns

the [TextProperties](#) for [InputAxis](#) labels

5.6.2.22 `get_prop_scale_label()`

```
const TextProperties& Configuration::get_prop_scale_label ( ) const [inline]
```

Returns MooViEs [TextProperties](#) for [Scale](#) labels.

Returns

the [TextProperties](#) for [Scale](#) labels

5.6.2.23 `get_prop_thick()`

```
const DrawerProperties& Configuration::get_prop_thick ( ) const [inline]
```

Returns MooViEs [DrawerProperties](#) for thick black lines.

Returns

the [DrawerProperties](#) for thick lines

5.6.2.24 `get_prop_thin()`

```
const DrawerProperties& Configuration::get_prop_thin ( ) const [inline]
```

Returns MooViEs [DrawerProperties](#) for thin black lines.

Returns

the [DrawerProperties](#) for thin lines

5.6.2.25 `get_width()`

```
int Configuration::get_width ( ) const [inline]
```

Returns the width of the MooViE scene

Returns

the width

5.6.2.26 `initialize()` [1/2]

```
static void Configuration::initialize (
    const std::string & fname,
    const std::string & cpath ) [static]
```

Initializes the singleton instance with the given input file path and the information given by the configuration file located under the given configuration file path.

Parameters

<i>fname</i>	the path to the input file
<i>cpath</i>	the path to the configuration file

5.6.2.27 `initialize()` [2/2]

```
static void Configuration::initialize (
    const std::string & fname ) [static]
```

Initializes the singleton instance with the given input file path and the standard configuration information.

Parameters

<i>fname</i>	the path to the input file
--------------	----------------------------

5.6.2.28 is_histograms_enabled()

```
bool Configuration::is_histograms_enabled ( ) const [inline]
```

Returns whether or not histograms should be drawn.

Returns

histograms enabled or not

5.6.2.29 set_connector_arc_ratio()

```
void Configuration::set_connector_arc_ratio (
    double connector_arc_ratio ) [inline]
```

Sets the ratio of the radial distance between two data points that will be drawn as connector.

Parameters

<i>ratio_connector_arc</i>	the connector arc ratio to set
----------------------------	--------------------------------

5.6.2.30 set_grid_size()

```
void Configuration::set_grid_size (
    double grid_size ) [inline]
```

Sets the size of actual grid that is a part of the [OutputGrid](#).

Parameters

<i>grid_size</i>	the m_grid_size to set
------------------	------------------------

5.6.2.31 set_height()

```
void Configuration::set_height (
```

```
int height ) [inline]
```

Sets the height of a MooViE scene.

Parameters

<i>height</i>	the height to set
---------------	-------------------

5.6.2.32 set_histogram_background()

```
void Configuration::set_histogram_background (
    const Color & histogram_background ) [inline]
```

Sets the background color that each histogram has.

Parameters

<i>histogram_background</i>	the histogram background color to set
-----------------------------	---------------------------------------

5.6.2.33 set_histogram_fill()

```
void Configuration::set_histogram_fill (
    const Color & histogram_fill ) [inline]
```

Sets the fill color of each histogram's bars.

Parameters

<i>histogram↵ _fill</i>	the histogram fill color to set
-----------------------------	---------------------------------

5.6.2.34 set_histogram_height()

```
void Configuration::set_histogram_height (
    double histogram_height ) [inline]
```

Sets the height that each histogram has.

Parameters

<i>histogram_height</i>	the histogram height to set
-------------------------	-----------------------------

5.6.2.35 set_histograms_enabled()

```
void Configuration::set_histograms_enabled (
    bool histograms_enabled ) [inline]
```

Sets whether or not histograms should be drawn.

Parameters

<i>histograms_enabled</i>	histograms enabled or not
---------------------------	---------------------------

5.6.2.36 set_input_inner_radius()

```
void Configuration::set_input_inner_radius (
    double input_inner_radius ) [inline]
```

Sets the inner radius of an input, the radius where the [InputAxis](#) start.

Parameters

<i>input_inner_radius</i>	the input inner radius to set
---------------------------	-------------------------------

5.6.2.37 set_input_separation_angle()

```
void Configuration::set_input_separation_angle (
    double input_separation_angle ) [inline]
```

Sets the separation angle between inputs.

Parameters

<i>input_separation_angle</i>	the input separation angle to set
-------------------------------	-----------------------------------

5.6.2.38 set_input_thickness()

```
void Configuration::set_input_thickness (
    double input_thickness ) [inline]
```

Sets the thickness of the colored ring of the [InputAxis](#).

Parameters

<i>input_thickness</i>	the input thickness to set
------------------------	----------------------------

5.6.2.39 `set_num_histogram_classes()`

```
void Configuration::set_num_histogram_classes (
    int num_histogram_classes ) [inline]
```

Sets the number of classes that each histogram consists of.

Parameters

<i>num_histogram_classes</i>	the number of histogram classes to set
------------------------------	--

5.6.2.40 `set_num_major_sections_axis()`

```
void Configuration::set_num_major_sections_axis (
    int major_sections ) [inline]
```

Sets the number of bold sections of the scale of the [InputAxis](#).

Parameters

<i>major_sections</i>	the number of major sections to set
-----------------------	-------------------------------------

5.6.2.41 `set_num_major_sections_grid()`

```
void Configuration::set_num_major_sections_grid (
    int major_sections ) [inline]
```

Sets the number of bold sections of the scale of the [OutputGrid](#).

Parameters

<i>major_sections</i>	the number of major sections to set
-----------------------	-------------------------------------

5.6.2.42 `set_num_minor_sections_axis()`

```
void Configuration::set_num_minor_sections_axis (
    int minor_sections ) [inline]
```

Sets the number of narrow sections of the scale of the [InputAxis](#).

Parameters

<i>minor_sections</i>	the number minor sections to set
-----------------------	----------------------------------

5.6.2.43 `set_num_minor_sections_grid()`

```
void Configuration::set_num_minor_sections_grid (
    int minor_sections ) [inline]
```

Sets the number of narrow sections of the scale of the [OutputGrid](#).

Parameters

<i>minor_sections</i>	the number of minor sections to set
-----------------------	-------------------------------------

5.6.2.44 `set_output_angle_span()`

```
void Configuration::set_output_angle_span (
    double output_angle_span ) [inline]
```

Sets the output angle span, the angle span for the [OutputGrid](#).

Parameters

<i>output_angle_span</i>	the output angle span to set
--------------------------	------------------------------

5.6.2.45 `set_output_file()`

```
void Configuration::set_output_file (
    const std::string & output_file ) [inline]
```

Sets the path to the output file.

Parameters

<i>output_file</i>	the output file path to set
--------------------	-----------------------------

5.6.2.46 `set_output_inner_radius()`

```
void Configuration::set_output_inner_radius (
    double output_inner_radius ) [inline]
```

Sets the inner radius of the output, the radius at which the [OutputGrid](#) starts.

Parameters

<i>output_inner_radius</i>	the output inner radius to set
----------------------------	--------------------------------

5.6.2.47 `set_output_thickness()`

```
void Configuration::set_output_thickness (
    double output_thickness ) [inline]
```

Sets the thickness of the outputs colored segmented ring.

Parameters

<i>output_thickness</i>	the output_thickness to set
-------------------------	-----------------------------

5.6.2.48 `set_prop_axis_label()`

```
void Configuration::set_prop_axis_label (
    const TextProperties & prop_axis_label ) [inline]
```

Sets MooViEs [TextProperties](#) for [InputAxis](#) labels.

Parameters

<i>prop_axis_label</i>	the TextProperties to set
------------------------	---

5.6.2.49 set_prop_scale_label()

```
void Configuration::set_prop_scale_label (
    const TextProperties & prop_scale_label ) [inline]
```

Sets MooViEs [TextProperties](#) for [Scale](#) labels.

Parameters

<i>prop_scale_label</i>	the TextProperties to set
-------------------------	---

5.6.2.50 set_prop_thick()

```
void Configuration::set_prop_thick (
    const DrawerProperties<> & prop_thick ) [inline]
```

Sets MooViEs [DrawerProperties](#) for thick black lines.

Parameters

<i>prop_thick</i>	the DrawerProperties to set
-------------------	---

5.6.2.51 set_prop_thin()

```
void Configuration::set_prop_thin (
    const DrawerProperties<> & prop_thin ) [inline]
```

Sets MooViEs [DrawerProperties](#) for thin black lines.

Parameters

<i>prop_thin</i>	the DrawerProperties to set
------------------	---

5.6.2.52 set_width()

```
void Configuration::set_width (
    int width ) [inline]
```

Sets the width of a MooViE scene.

Parameters

<i>width</i>	the width to set
--------------	------------------

5.6.3 Member Data Documentation

5.6.3.1 GLOW_10

```
const std::array<Color, 10> Configuration::GLOW_10 [static]
```

An array of Colors

5.6.3.2 SET2_3_1

```
const Color Configuration::SET2_3_1 [static]
```

Further color constants

5.6.3.3 SET3

```
const Triangle<Color, 12> Configuration::SET3 [static]
```


A Triangular storage which contains i+1 matching colors at the i-th index.

The documentation for this class was generated from the following file:

- include/Configuration.h

5.7 DataSet< T >::DataRow::const_iterator Class Reference

Inheritance diagram for DataSet< T >::DataRow::const_iterator:



Public Member Functions


- **const_iterator** (const typename std::vector< [MockColumn](#) >::const_iterator &_it, const typename std::vector< [MockColumn](#) >::const_iterator &_end, std::size_t _offset)
- [const_iterator](#) & **operator++** ()
- [const_iterator](#) **operator++** (int)
- bool **operator==** (const [const_iterator](#) &other) const
- bool **operator!=** (const [const_iterator](#) &other) const
- const [Cell](#) & **operator*** () const

The documentation for this class was generated from the following file:

- include/DataSet.h

5.8 DataSet< T >::const_iterator Class Reference

Inheritance diagram for DataSet< T >::const_iterator:



Public Member Functions

- **const_iterator** (const typename std::vector< [DataRow](#) >::const_iterator &it, const typename std::vector< [DataRow](#) >::const_iterator &end)
- [const_iterator](#) & **operator++** ()
- [const_iterator](#) **operator++** (int)
- bool **operator==** (const [const_iterator](#) &other) const
- bool **operator!=** (const [const_iterator](#) &other) const
- const [DataRow](#) & **operator*** () const

The documentation for this class was generated from the following file:

- include/DataSet.h

5.9 CoordinateConverter Class Reference

Converter between polar and cartesian coordinates.

```
#include <Coordinates.h>
```

Public Member Functions

- [CoordinateConverter](#) (size_t width, size_t height)
a converter for coordinates
- void [convert](#) (const [Cartesian](#) &from, [Polar](#) &to) const
- void [convert](#) (const [Polar](#) &from, [Cartesian](#) &to) const
- double [get_center_x](#) () const
- double [get_center_y](#) () const

5.9.1 Detailed Description

Converter between polar and cartesian coordinates.

[CoordinateConverter](#) simulates a fixed width/height coordinate system. It can convert polar and cartesian coordinates.

5.9.2 Constructor & Destructor Documentation

5.9.2.1 CoordinateConverter()

```
CoordinateConverter::CoordinateConverter (  
    size_t width,  
    size_t height ) [inline]
```

a converter for coordinates

Creates a new coordinate system with given width and height. The center coordinate is at (width / 2, height / 2).

Parameters

<i>width</i>	the coordinate system width
<i>height</i>	the coordinate system system

5.9.3 Member Function Documentation

5.9.3.1 convert() [1/2]

```
void CoordinateConverter::convert (  
    const Cartesian & from,  
    Polar & to ) const [inline]
```

Converts a [Cartesian](#) coordinate to a [Polar](#) coordinate.

Parameters

<i>from</i>	the Cartesian to convert
<i>to</i>	the Polar to store

5.9.3.2 `convert()` [2/2]

```
void CoordinateConverter::convert (
    const Polar & from,
    Cartesian & to ) const [inline]
```

Converts a [Polar](#) coordinate to a [Cartesian](#) coordinate.

Parameters

<i>from</i>	the Polar to convert
<i>to</i>	the Polar to store

5.9.3.3 `get_center_x()`

```
double CoordinateConverter::get_center_x ( ) const [inline]
```

Returns the x value of the center coordinate.

Returns

the center's x value

5.9.3.4 `get_center_y()`

```
double CoordinateConverter::get_center_y ( ) const [inline]
```

Returns the y value of the center coordinate.

Returns

the center's y value

The documentation for this class was generated from the following file:

- include/Coordinates.h

5.10 DataSet< T >::DataColumn Struct Reference

Column of a data table.

```
#include <DataSet.h>
```

Public Member Functions

- [DataColumn](#) ([ColumnType](#) type_, [Variable](#) var_)

Public Attributes

- const [ColumnType](#) type
- [Variable](#) var
- std::vector< [Cell](#) > cells

5.10.1 Detailed Description

```
template<typename T>
struct DataSet< T >::DataColumn
```

Column of a data table.

[DataColumn](#) represents a column of a data set. It has a type (INPUT, OUTPUT), a [Variable](#) and a set of cells

5.10.2 Constructor & Destructor Documentation

5.10.2.1 DataColumn()

```
template<typename T >
DataSet< T >::DataColumn::DataColumn (
    ColumnType type_,
    Variable var_ ) [inline]
```

Creates a new column with given ColumnType and [Variable](#).

Parameters

<i>type</i> ↔ —	the ColumnType
<i>var</i> ↔ —	the Variable

5.10.3 Member Data Documentation

5.10.3.1 cells

```
template<typename T >
std::vector<Cell> DataSet< T >::DataColumn::cells
```

An array of the cells of this column

5.10.3.2 type

```
template<typename T >
const ColumnType DataSet< T >::DataColumn::type
```

The ColumnType

5.10.3.3 var

```
template<typename T >
Variable DataSet< T >::DataColumn::var
```

The header information about this column (name, unit, range)

The documentation for this struct was generated from the following file:

- include/DataSet.h

5.11 DataSet< T >::DataRow Class Reference

Row of a data table.

```
#include <DataSet.h>
```

Classes

- class [const_iterator](#)

Public Member Functions

- [DataRow](#) (const std::vector< [MockColumn](#) > &columns, const std::size_t &enabled_columns, std::size_t offset)
- const [Cell](#) & [operator\[\]](#) (std::size_t i) const
- void [set_enabled](#) (bool enabled)
- std::size_t [size](#) () const
- bool [is_enabled](#) () const
- [const_iterator](#) [begin](#) () const
- [const_iterator](#) [end](#) () const

5.11.1 Detailed Description

```
template<typename T>
class DataSet< T >::DataRow
```

Row of a data table.

[DataRow](#) represents a row in this [DataSet](#). A [DataRow](#) does not become invalid when column order is changed or a column is disabled. It might get invalid when restricting columns to a certain interval.

5.11.2 Constructor & Destructor Documentation

5.11.2.1 DataRow()

```
template<typename T >
DataRow< T >::DataRow (
    const std::vector< MockColumn > & columns,
    const std::size_t & enabled_columns,
    std::size_t offset ) [inline]
```

Creates a [DataRow](#) from given reference to the columns and to the number of enabled columns (needed for update) and the row number (aka column offset).

Parameters

<i>columns</i>	a reference to the column array
<i>enabled_columns</i>	a reference to the number of enabled columns
<i>offset</i>	the row offset

5.11.3 Member Function Documentation

5.11.3.1 begin()

```
template<typename T >
const_iterator DataSet< T >::DataRow::begin ( ) const [inline]
```

Returns a [const_iterator](#) pointing to the first cell in this [DataRow](#).

Returns

the iterator

5.11.3.2 end()

```
template<typename T >
const_iterator DataSet< T >::DataRow::end ( ) const [inline]
```

Returns a [const_iterator](#) pointing to the end of this [DataRow](#)

Returns

the iterator

5.11.3.3 is_enabled()

```
template<typename T >
bool DataSet< T >::DataRow::is_enabled ( ) const [inline]
```

Returns the value of the enabled flag.

Returns

enabled or not

5.11.3.4 operator[]()

```
template<typename T >
const Cell& DataSet< T >::DataRow::operator[] (
    std::size_t i ) const [inline]
```

Accesses the i-th [Cell](#) of this [DataRow](#).

Parameters

<i>i</i>	the index
----------	-----------

Returns

the [Cell](#)

5.11.3.5 set_enabled()

```
template<typename T >
void DataSet< T >::DataRow::set_enabled (
    bool enabled ) [inline]
```

Sets the enabled flag of this [MockColumn](#) to the specified value.

Parameters

<i>enabled</i>	set enabled or not
----------------	--------------------

5.11.3.6 size()

```
template<typename T >
std::size_t DataSet< T >::DataRow::size ( ) const [inline]
```

Returns the size of this [MockColumn](#).

Returns

the size

The documentation for this class was generated from the following file:

- include/DataSet.h

5.12 DataSet< T > Class Template Reference

Table of data.

```
#include <DataSet.h>
```

Classes

- struct [Cell](#)
Cell of a data table.
- class [const_iterator](#)
- struct [DataColumn](#)
Column of a data table.
- class [DataRow](#)
Row of a data table.
- class [MockColumn](#)
Technical column for internal use.
- struct [Variable](#)
Header description.

Public Types

- enum [ColumnType](#) { **INPUT**, **OUTPUT** }

Public Member Functions

- void [toggle_column](#) (std::size_t c, bool mode)
- void [swap_columns](#) (std::size_t c0, std::size_t c1)
- void [restrict_column](#) (std::size_t c, T l_restr, T u_restr)
- std::size_t [get_num_cols](#) () const
- std::size_t [get_num_rows](#) () const
- std::size_t [get_num_inputs](#) () const
- std::size_t [get_num_outputs](#) () const
- const [DataRow](#) & [operator\[\]](#) (std::size_t i) const
- std::vector< [Variable](#) > [input_variables](#) (void) const
- std::vector< [Variable](#) > [output_variables](#) (void) const
- [const_iterator](#) [begin](#) () const
- [const_iterator](#) [end](#) () const

Static Public Member Functions

- static [DataSet](#) * [parse_from_csv](#) (const std::string &cont, std::string separator=",", std::string comment="#", std::string newline="\n")

5.12.1 Detailed Description

```
template<typename T>
class DataSet< T >
```

Table of data.

A class for storing data of some type. It is accessible row-wise and not directly changeable, but columns can be swapped, toggled and restricted. Rows are divided in INPUTs and OUTPUTs, so they can be used in MooViE terms. It can also be parsed from a CSV file.

Author

stratmann

Date

28.11.2017

5.12.2 Member Enumeration Documentation

5.12.2.1 ColumnType

```
template<typename T >
enum DataSet::ColumnType
```

MooViE columns can either represent outputs or inputs. This is indicated by a member of the type ColumnType.

5.12.3 Member Function Documentation

5.12.3.1 begin()

```
template<typename T >  
const_iterator DataSet< T >::begin ( ) const [inline]
```

Returns a constant iterator pointing to the first [DataRow](#).

Returns

a [const_iterator](#)

5.12.3.2 end()

```
template<typename T >  
const_iterator DataSet< T >::end ( ) const [inline]
```

Returns a constant iterator pointing to the end element of the [DataRow](#) storage.

Returns

a [const_iterator](#)

5.12.3.3 get_num_cols()

```
template<typename T >  
std::size_t DataSet< T >::get_num_cols ( ) const [inline]
```

Returns the number of columns in this table.

Returns

the number of columns

5.12.3.4 get_num_inputs()

```
template<typename T >
std::size_t DataSet< T >::get_num_inputs ( ) const [inline]
```

Returns the number of inputs in this table.

Returns

the number of inputs

5.12.3.5 get_num_outputs()

```
template<typename T >
std::size_t DataSet< T >::get_num_outputs ( ) const [inline]
```

Returns the number of outputs in this table.

Returns

the number of outputs

5.12.3.6 get_num_rows()

```
template<typename T >
std::size_t DataSet< T >::get_num_rows ( ) const [inline]
```

Returns the number of rows in this table.

Returns

the number of rows

5.12.3.7 input_variables()

```
template<typename T >
std::vector<Variable> DataSet< T >::input_variables (
    void ) const [inline]
```

Returns a constant vector containing row (referred to as variables) information like the name and min/max values of the selected row.

Returns

the input variables

5.12.3.8 operator[]()

```
template<typename T >
const DataRow& DataSet< T >::operator[] (
    std::size_t i ) const [inline]
```

Returns the row at position *i* in the table (starting at 0). [DataRow](#) can be used like a vector from the given type.

Returns

the [DataRow](#) object

5.12.3.9 output_variables()

```
template<typename T >
std::vector<Variable> DataSet< T >::output_variables (
    void ) const [inline]
```

Returns a constant vector containing column (referred to as variables) information like the name and min/max values of the selected row.

Returns

the output variables

5.12.3.10 parse_from_csv()

```
template<typename T >
DataSet< T > * DataSet< T >::parse_from_csv (
    const std::string & cont,
    std::string separator = ",",
    std::string comment = "#",
    std::string newline = "\n" ) [static]
```

Returns a data table parsed from a csv encoded string and encapsulated in a [DataSet](#) object. The table must have the form: <input1>[<unit1>], ... , <inputN>[<unitN>], <output1>[<unit1>], ... , <outputM>[<unitM>] <datai1>, ... , <dataiN>, <datao1>, ... , <dataoM>

Parameters

<i>cont</i>	the csv encoded string
<i>num_ins</i>	the number of input variables
<i>separator</i>	the column separator used in this csv string
<i>comment</i>	the comment indicator used in this csv string
<i>newline</i>	the newline indicator used in this csv string

Returns

the [DataSet](#) object

5.12.3.11 restrict_column()

```
template<typename T >
void DataSet< T >::restrict_column (
    std::size_t c,
    T l_restr,
    T u_restr ) [inline]
```

Restricts a column to values in the given interval. The DataRows that contain a [Cell](#) not fitting in this interval will be disabled.

Parameters

<i>c</i>	the column index
<i>l_restr</i>	lower restriction value
<i>u_restr</i>	upper restriction value

Exceptions

<i>out_↔ _of</i>	range if c is incorrect
--------------------------------	-------------------------

5.12.3.12 swap_columns()

```
template<typename T >
void DataSet< T >::swap_columns (
    std::size_t c0,
    std::size_t c1 ) [inline]
```

Swaps the two columns with the given index. The DataRows are changed accordingly.

Parameters

<i>c0</i>	the index of the first column
<i>c1</i>	the index of the second column

Exceptions

<i>out_of_bounds</i>	if indices are incorrect
----------------------	--------------------------

5.12.3.13 toggle_column()

```
template<typename T >
void DataSet< T >::toggle_column (
    std::size_t c,
    bool mode ) [inline]
```

Enables/disables a column. The DataRows now do not contain the affected [Cell](#) anymore.

Parameters

<i>c</i>	the column index
<i>mode</i>	set enabled or disabled

Exceptions

<i>out_of_range</i>	id c is incorrect
---------------------	-------------------

The documentation for this class was generated from the following file:


- include/DataSet.h

5.13 Drawer Class Reference

Abstract [Drawer](#) for MooViE scenes.

```
#include <Drawer.h>
```

Inheritance diagram for Drawer:



Classes

- struct [TextAlignment](#)
Text alignment representation.

Public Member Functions

- [Drawer](#) (int width, int height, std::size_t num_inputs)
- virtual void [change_surface](#) (const std::string &fpath, int width, int height, std::size_t num_inputs)=0
- virtual void [draw_output_grid](#) (const [OutputGrid](#) &grid)=0
- virtual void [draw_input_axis](#) (const [InputAxis](#) &axis)=0
- virtual void [draw_relation_element](#) (const [IOVector](#) &elem)=0
- virtual void [finish](#) ()=0

Static Public Attributes

- static constexpr double **LINK_CONTROL_STRENGTH** = 100

Protected Member Functions

- virtual void **set_surface** (const std::string &fpath, int width, int height)=0
- virtual void **draw_histogram** (const [InputAxis::Histogram](#) &histogram, double radius, const [Angle](#) &start, const [Angle](#) &end)=0
- virtual void **draw_link** (const [Polar](#) &origin1, const [Polar](#) &origin2, const [Polar](#) &target1, const [Polar](#) &target2, const [DrawerProperties](#)<> &prop)=0
- virtual void **draw_connector** (const [Polar](#) &from, const [Polar](#) &to, const [DrawerProperties](#)<> &prop)=0
- virtual void **draw_segment_axis** (double inner_radius, double thickness, const [Angle](#) &begin, const [Angle](#) &end, const [DrawerProperties](#)< std::array< [Color](#), 10 >> &prop, Direction dir)=0
- virtual void **draw_output_label** (const [Label](#) &output_label, double radius_label, double radius_output, const [Angle](#) &begin, const [Angle](#) &end)=0
- virtual void **draw_arrow** (const [Polar](#) &start, const [DrawerProperties](#)<> &prop)=0
- virtual void **draw_ring_segment** (double radius, double thickness, const [Angle](#) &start, const [Angle](#) &end, const [DrawerProperties](#)<> &prop, Direction dir)=0
- virtual void **draw_connector_segment** (double start_radius, double start_angle, double end_radius, double end_angle, const [DrawerProperties](#)<> &prop)=0
- virtual void **draw_line** (const [Polar](#) &from, const [Polar](#) &to, const [DrawerProperties](#)<> &prop)=0
- virtual void **draw_arc** (double inner_radius, const [Angle](#) &start, const [Angle](#) &end, Direction dir)=0
- virtual void **draw_coord_point** (const [Polar](#) &coord, const [Angle](#) &width, double height, const [DrawerProperties](#)<> &prop)=0
- virtual void **draw_text_parallel** (const [Label](#) &label, const [Polar](#) &start, const [TextAlignment](#) &alignment=[TextAlignment::CENTERED](#))=0
- virtual void **draw_text_orthogonal** (const [Label](#) &label, const [Polar](#) &start, const [TextAlignment](#) &alignment=[TextAlignment::CENTERED](#))=0
- [Polar](#) **get_connector_start** (const [Polar](#) &from, const [Polar](#) &to)
- [Polar](#) **get_connector_end** (const [Polar](#) &from, const [Polar](#) &to)
- [Cartesian](#) **create_link_control_point** (const [Polar](#) &point) const

Protected Attributes

- const [CoordinateConverter](#) m_coord_converter
- std::size_t m_num_inputs

5.13.1 Detailed Description

Abstract [Drawer](#) for MooViE scenes.

An abstract [Drawer](#) class that can be used to draw MooViE elements. [Drawer](#) is supposed to cover the strategy that is used to actually draw an image with a MooViE scene. It provides the implementation with a [CoordinateConverter](#), [TextAlignment](#) wrapper and basic calculation functions for points.

Author

stratmann

Date

27.04.2018

5.13.2 Constructor & Destructor Documentation

5.13.2.1 Drawer()

```
Drawer::Drawer (
    int width,
    int height,
    std::size_t num_inputs ) [inline]
```

Creates a [Drawer](#) which draws on a surface with the given width and height.

Parameters

<i>width</i>	the surface width
<i>height</i>	the surface height
<i>num_inputs</i>	the number of inputs

5.13.3 Member Function Documentation

5.13.3.1 change_surface()

```
virtual void Drawer::change_surface (
    const std::string & fpath,
    int width,
    int height,
    std::size_t num_inputs ) [pure virtual]
```

Alters the surface of this [Drawer](#) in number of inputs, width, height and storage path. All unsafed changes will be stored and all kept resources freed correctly.

Parameters

<i>fpath</i>	a string containing an valid existing or accessible not existing path
<i>width</i>	an integer between 0 and MAX_INT
<i>height</i>	an integer between 0 and MAX_INT
<i>num_inputs</i>	the number of inputs

Implemented in [CairoDrawer](#).

5.13.3.2 create_link_control_point()

```
Cartesian Drawer::create_link_control_point (
    const Polar & point ) const [inline], [protected]
```

Creates a control point for a Bezier curve approximating a link.

Parameters

<i>point</i>	coordinate to which the control point will be created
--------------	---

Returns

the control point

5.13.3.3 draw_arc()

```
virtual void Drawer::draw_arc (
    double inner_radius,
    const Angle & start,
    const Angle & end,
    Direction dir ) [protected], [pure virtual]
```

Draws a simple edge segment around the center of its coordinate system between the two given Angles and with the given radius.

Parameters

<i>inner_radius</i>	the inner radius
<i>start</i>	the start Angle
<i>end</i>	the end Angle
<i>dir</i>	the direction

Implemented in [CairoDrawer](#).

5.13.3.4 draw_arrow()

```
virtual void Drawer::draw_arrow (
    const Polar & start,
    const DrawerProperties<> & prop ) [protected], [pure virtual]
```

Draws a arrow head from a given start pointing.

Parameters

<i>start</i>	the start of the arrow head
<i>prop</i>	DrawerProperties for the arrow head

Implemented in [CairoDrawer](#).

5.13.3.5 draw_connector()

```
virtual void Drawer::draw_connector (
    const Polar & from,
    const Polar & to,
    const DrawerProperties<> & prop ) [protected], [pure virtual]
```

Draws a connection between to given polar coordinates. The connection is a bezier curve which is controlled by automatically generated control points.

Parameters

<i>from</i>	the start Polar
<i>to</i>	the end Polar
<i>prop</i>	the DrawerProperties

Implemented in [CairoDrawer](#).

5.13.3.6 draw_connector_segment()

```
virtual void Drawer::draw_connector_segment (
    double start_radius,
    double start_angle,
    double end_radius,
    double end_angle,
    const DrawerProperties<> & prop ) [protected], [pure virtual]
```

Draws a Bezier curve from [Polar\(start_radius, start_angle\)](#) to [Polar\(end_radius, end_angle\)](#) which approximately behaves like Archimedean spiral. If the smaller difference angle between start_angle and end_angle is bigger than PI, the spiral will be approximated by two Bezier curves.

Parameters

<i>start_radius</i>	the radius of the starting point
<i>start_angle</i>	the angle of the starting point
<i>end_radius</i>	the radius of the end point
<i>end_angle</i>	the angle of the end point
<i>prop</i>	the DrawerProperties for the segment

Implemented in [CairoDrawer](#).

5.13.3.7 draw_coord_point()

```
virtual void Drawer::draw_coord_point (
    const Polar & coord,
    const Angle & width,
```

```
double height,
const DrawerProperties<> & prop ) [protected], [pure virtual]
```

Draws a coordinate point with given height and with.

Parameters

<i>coord</i>	the polar coordinate to draw
<i>width</i>	the width
<i>height</i>	the height
<i>prop</i>	the DrawerProperties

Implemented in [CairoDrawer](#).

5.13.3.8 draw_histogram()

```
virtual void Drawer::draw_histogram (
    const InputAxis::Histogram & histogram,
    double radius,
    const Angle & start,
    const Angle & end ) [protected], [pure virtual]
```

Draws a Histogram from the given radius, between begin and end [Angle](#). For the histogram height, thin or thick lines the properties given by the [Configuration](#) instance are used.

Parameters

<i>histogram</i>	the Histogram to draw
<i>radius</i>	the start radius of the Histogram
<i>start</i>	the starting angle of the Histogram
<i>end</i>	the end angle of the Histogram

Implemented in [CairoDrawer](#).

5.13.3.9 draw_input_axis()

```
virtual void Drawer::draw_input_axis (
    const InputAxis & axis ) [pure virtual]
```

Draws a [InputAxis](#) using its radius and angles. For thin or thick lines the properties given by the [Configuration](#) instance are used.

Parameters

<i>axis</i>	the InputAxis to draw
-------------	---------------------------------------

Implemented in [CairoDrawer](#).

5.13.3.10 draw_line()

```
virtual void Drawer::draw_line (
    const Polar & from,
    const Polar & to,
    const DrawerProperties<> & prop ) [protected], [pure virtual]
```

Draws a line from a given starting vertice to a given end vertice.

Parameters

<i>from</i>	the starting coordinates
<i>to</i>	the end coordinates
<i>prop</i>	the DrawerProperties to use

Implemented in [CairoDrawer](#).

5.13.3.11 draw_link()

```
virtual void Drawer::draw_link (
    const Polar & origin1,
    const Polar & origin2,
    const Polar & target1,
    const Polar & target2,
    const DrawerProperties<> & prop ) [protected], [pure virtual]
```

Draws a bold line between the lines origin1-origin2 and target1-target2. This is realized by drawing Bezier curves from origin1 to target1 and from origin2 to target2 and filling the so created surface.

Parameters

<i>origin1</i>	first origin coordinate
<i>origin2</i>	second origin coordinate
<i>target1</i>	first target coordinate
<i>target2</i>	second target coordinate
<i>prop</i>	DrawerProperties for the link

Implemented in [CairoDrawer](#).

5.13.3.12 draw_output_grid()

```
virtual void Drawer::draw_output_grid (
    const OutputGrid & grid ) [pure virtual]
```

Draws a [OutputGrid](#) using its radius and angles. For thin or thick lines the properties given by the [Configuration](#) instance are used.

Parameters

<i>grid</i>	the OutputGrid to draw
-------------	--

Implemented in [CairoDrawer](#).

5.13.3.13 draw_output_label()

```
virtual void Drawer::draw_output_label (
    const Label & output_label,
    double radius_label,
    double radius_output,
    const Angle & begin,
    const Angle & end ) [protected], [pure virtual]
```

Draws the given [Label](#) output_label with the radius radius_label and a descriptive path that connects the output label with the associated output. The path consists of an arc segment and a line.

Parameters

<i>output_label</i>	the output label to draw
<i>radius_label</i>	the radius of the output label
<i>radius_output</i>	the radius of the associated output
<i>begin</i>	the angle at which the output ends
<i>end</i>	the angle at which the arc ends

Implemented in [CairoDrawer](#).

5.13.3.14 draw_relation_element()

```
virtual void Drawer::draw_relation_element (
    const IOVector & elem ) [pure virtual]
```

Draws a [IOVector](#) using its coordinates.

Parameters

<i>elem</i>	the IOVector to draw
-------------	--------------------------------------

Implemented in [CairoDrawer](#).

5.13.3.15 `draw_ring_segment()`

```
virtual void Drawer::draw_ring_segment (
    double radius,
    double thickness,
    const Angle & start,
    const Angle & end,
    const DrawerProperties<> & prop,
    Direction dir ) [protected], [pure virtual]
```

Draws a filled ring segment around the center of its coordinate system between the two given Angles and with the given radius.

Parameters

<i>radius</i>	the radius
<i>thickness</i>	the thickness of the edge segment
<i>begin</i>	the begin Angle
<i>end</i>	the end Angle
<i>prop</i>	the CairoDrawer properties
<i>dir</i>	the direction

Implemented in [CairoDrawer](#).

5.13.3.16 `draw_segment_axis()`

```
virtual void Drawer::draw_segment_axis (
    double inner_radius,
    double thickness,
    const Angle & begin,
    const Angle & end,
    const DrawerProperties< std::array< Color, 10 >> & prop,
    Direction dir ) [protected], [pure virtual]
```

Draws a circle segment which is itself divided in colored segments.

Parameters

<i>inner_radius</i>	inner radius of the split axis
<i>thickness</i>	width of the split axis
<i>begin</i>	angle of the segments begin
<i>end</i>	angle of the segments end
<i>prop</i>	color
<i>dir</i>	direction of the split axis' colors

Implemented in [CairoDrawer](#).

5.13.3.17 draw_text_orthogonal()

```
virtual void Drawer::draw_text_orthogonal (
    const Label & label,
    const Polar & start,
    const TextAlignment & alignment = TextAlignment::CENTERED ) [protected], [pure
virtual]
```

Draws the given label orthogonal to the angle of the given coordinate's angle.

Parameters

<i>label</i>	the label to draw
<i>start</i>	the coordinate to adjust to

Implemented in [CairoDrawer](#).

5.13.3.18 draw_text_parallel()

```
virtual void Drawer::draw_text_parallel (
    const Label & label,
    const Polar & start,
    const TextAlignment & alignment = TextAlignment::CENTERED ) [protected], [pure
virtual]
```

Draws the given label with the same angle like the given coordinate.

Parameters

<i>label</i>	the label to draw
<i>start</i>	the coordinate to adjust to

Implemented in [CairoDrawer](#).

5.13.3.19 finish()

```
virtual void Drawer::finish ( ) [pure virtual]
```

Save the [Drawer](#)'s result to the given file.

Implemented in [CairoDrawer](#).

5.13.3.20 get_connector_end()

```
Polar Drawer::get_connector_end (
    const Polar & from,
    const Polar & to ) [inline], [protected]
```

Calculates a [Polar](#) coordinate for the end of a connector between 'from' and 'to'. If the resulting coordinate is passed to a connector drawing function, the connector does not immediately end at to.

Parameters

<i>from</i>	the Polar coordinate to start the connector from
<i>to</i>	the Polar coordinate to draw the connector to

Returns

the modified connector end coordinate

5.13.3.21 get_connector_start()

```
Polar Drawer::get_connector_start (
    const Polar & from,
    const Polar & to ) [inline], [protected]
```

Calculates a [Polar](#) coordinate for the beginning of a connector between 'from' and 'to'. If the resulting coordinate is passed to a connector drawing function, the connector does not immediately start at from.

Parameters

<i>from</i>	the Polar coordinate to start the connector from
<i>to</i>	the Polar coordinate to draw the connector to

Returns

the modified connector start coordinate

5.13.3.22 set_surface()

```
virtual void Drawer::set_surface (
    const std::string & fpath,
    int width,
    int height ) [protected], [pure virtual]
```

Alters the surface of this [Drawer](#) in with, height and storage path.

Parameters

<i>fpath</i>	a string containing an valid or accessible path
<i>width</i>	an integer between 0 and MAX_INT
<i>height</i>	an integer between 0 and MAX_INT

Implemented in [CairoDrawer](#).

5.13.4 Member Data Documentation**5.13.4.1 m_coord_converter**

```
const CoordinateConverter Drawer::m_coord_converter [protected]
```

Polar-Cartesian converting

5.13.4.2 m_num_inputs

```
std::size_t Drawer::m_num_inputs [protected]
```

Number of input variables of the multi-objective data to draw

The documentation for this class was generated from the following file:

- include/Drawer.h

5.14 DrawerProperties< FillT > Struct Template Reference

Properties to modify a MooViE drawers behavior.

```
#include <DrawerProperties.h>
```

Public Member Functions

- [DrawerProperties](#) (double line_width_, const [Color](#) &line_color_, const FillT &fill_color_)

Public Attributes

- double [line_width](#)
- [Color](#) [line_color](#)
- FillT [fill_color](#)

5.14.1 Detailed Description

```
template<typename FillT = Color>
struct DrawerProperties< FillT >
```

Properties to modify a MooViE drawers behavior.

[DrawerProperties](#) can be used to control the line thinkness, stroke and fill color of a [Drawer](#).

Author

beyss

Date

05.07.2017

5.14.2 Constructor & Destructor Documentation

5.14.2.1 DrawerProperties()

```
template<typename FillT = Color>
DrawerProperties< FillT >::DrawerProperties (
    double line_width_,
    const Color & line_color_,
    const FillT & fill_color_ ) [inline]
```

Creates a [DrawerProperties](#) instance storing the given line thinkness, stroke and fill color of a [Drawer](#).

Parameters

<i>_line_width</i>	the line width
<i>_line_color</i>	the line color
<i>_fill_color</i>	the fill color

5.14.3 Member Data Documentation

5.14.3.1 fill_color

```
template<typename FillT = Color>
FillT DrawerProperties< FillT >::fill_color
```

Fill color(s)

5.14.3.2 line_color

```
template<typename FillT = Color>
Color DrawerProperties< FillT >::line_color
```

Line color

5.14.3.3 line_width

```
template<typename FillT = Color>
double DrawerProperties< FillT >::line_width
```

The line width

The documentation for this struct was generated from the following file:

- include/DrawerProperties.h

5.15 InputAxis::Histogram Class Reference

Public Member Functions

- [Histogram](#) ([DefVariable](#) var)
- void [calculate](#) (const std::vector< double > &data)
- double [get_section_frequency](#) (std::size_t i) const
- std::size_t [get_num_intervals](#) (void) const
- void [set_num_intervals](#) (std::size_t num_intervals)

5.15.1 Constructor & Destructor Documentation

5.15.1.1 Histogram()

```
InputAxis::Histogram::Histogram (
    DefVariable var )
```

Creates an empty [Histogram](#) for this variable with the specified number of intervals.

Parameters

<i>var</i>	the variable to present
------------	-------------------------

5.15.2 Member Function Documentation

5.15.2.1 calculate()

```
void InputAxis::Histogram::calculate (
    const std::vector< double > & data )
```

Calculates equidistant data sections and stores them.

Parameters

<i>data</i>	the input values of this variable
-------------	-----------------------------------

5.15.2.2 get_num_intervals()

```
std::size_t InputAxis::Histogram::get_num_intervals (
    void ) const [inline]
```

Returns the number of equidistant intervals the domain of this [Histogram](#)'s Variable is divided in.

Returns

the interval count

5.15.2.3 get_section_frequency()

```
double InputAxis::Histogram::get_section_frequency (
    std::size_t i ) const
```

Returns the value of the histogram graph in this section. They are associated with the relative frequency of the equidistant intervals.

Parameters

<i>i</i>	index of the section
----------	----------------------

Returns

the height

5.15.2.4 set_num_intervals()

```
void InputAxis::Histogram::set_num_intervals (
    std::size_t num_intervals ) [inline]
```

Sets the histogram to have a given number of equidistant intervals. If values for an old number of intervals have been stored, all data from is deleted and the frequencies set to 0.

Parameters

<i>num_interval</i>	the new interval count
---------------------	------------------------

The documentation for this class was generated from the following file:

- include/InputAxis.h

5.16 InputAxis Class Reference

[InputAxis](#) MooViE component representation.

```
#include <InputAxis.h>
```

Classes

- class [Histogram](#)

Public Member Functions

- [InputAxis](#) ([DefVariable](#) variable, const [Angle](#) &start, const [Angle](#) &end, double radius, double height, const [DrawerProperties](#)<> &prop)
constructor
- const [DefVariable](#) & [get_var](#) () const
- const [Histogram](#) & [get_histogram](#) () const
- const [Angle](#) & [get_start](#) () const
- void [set_start](#) (const [Angle](#) &start)
- const [Angle](#) & [get_end](#) () const
- void [set_end](#) (const [Angle](#) &end)
- double [get_radius](#) () const
- void [set_radius](#) (double radius)
- double [get_height](#) () const
- void [set_height](#) (double height)
- const [DrawerProperties](#) & [get_prop](#) () const
- void [set_prop](#) (const [DrawerProperties](#)<> &prop)
- const [SimpleScale](#) & [get_scale](#) () const
- [Label](#) [make_label](#) (const [TextProperties](#) &prop) const
- void [calculate_histogram](#) (const std::vector< double > &data)

5.16.1 Detailed Description

[InputAxis](#) MooViE component representation.

A [InputAxis](#) is an axis which displays the possible values of a input variable. It is visualized as a ring segment with a distinct color and has ticks for better readability.

Author

stratmann

Date

12.12.2017

5.16.2 Constructor & Destructor Documentation

5.16.2.1 InputAxis()

```
InputAxis::InputAxis (
    DefVariable variable,
    const Angle & start,
    const Angle & end,
    double radius,
    double height,
    const DrawerProperties<> & prop )
```

constructor

Creates a [InputAxis](#) presenting a given variable and is drawn between given angles with given radius, height and properties.

Parameters

<i>variable</i>	the variable to present
<i>start</i>	the start angle
<i>end</i>	the end angle
<i>radius</i>	the radius from the center
<i>height</i>	the height beginning at the radius
<i>prop</i>	the DrawerProperties

5.16.3 Member Function Documentation

5.16.3.1 calculate_histogram()

```
void InputAxis::calculate_histogram (
    const std::vector< double > & data )
```

Calculates the frequencies of the [Histogram](#).

Parameters

<i>data</i>	the data used
-------------	---------------

5.16.3.2 get_end()

```
const Angle& InputAxis::get_end ( ) const [inline]
```

Returns the end [Angle](#) of this [InputAxis](#)' drawing span.

Returns

the end [Angle](#)

5.16.3.3 get_height()

```
double InputAxis::get_height ( ) const [inline]
```

Returns the height measured from the radius.

Returns

the height

5.16.3.4 get_histogram()

```
const Histogram& InputAxis::get_histogram ( ) const [inline]
```

Returns a reference to its histogram. The [InputAxis::calculate_histogram](#) function has to be called before drawing the histogram because it is empty by default.

Returns

the [Histogram](#)

5.16.3.5 get_prop()

```
const DrawerProperties& InputAxis::get_prop ( ) const [inline]
```

Returns the [DrawerProperties](#) that will be used to draw this [InputAxis](#).

Returns

the [DrawerProperties](#)

5.16.3.6 get_radius()

```
double InputAxis::get_radius ( ) const [inline]
```

Returns the radius measured from the center of the coordinate system.

Returns

the radius

5.16.3.7 get_scale()

```
const SimpleScale& InputAxis::get_scale ( ) const [inline]
```

Returns the [SimpleScale](#) of this [InputAxis](#). This scale instance defines how the graphical scale will be drawn.

Returns

the [SimpleScale](#)

5.16.3.8 get_start()

```
const Angle& InputAxis::get_start ( ) const [inline]
```

Returns the start [Angle](#) of this [InputAxis](#)' drawing span.

Returns

the start [Angle](#)

5.16.3.9 `get_var()`

```
const DefVariable& InputAxis::get_var ( ) const [inline]
```

Returns a const reference to the variable this [InputAxis](#) presents.

Returns

the Var

5.16.3.10 `make_label()`

```
Label InputAxis::make_label (
    const TextProperties & prop ) const [inline]
```

Constructs a label using the given [TextProperties](#)' style and this [InputAxis](#)' variable name.

Parameters

<i>prop</i>	
-------------	--

5.16.3.11 `set_end()`

```
void InputAxis::set_end (
    const Angle & end ) [inline]
```

Sets the end [Angle](#) of this [InputAxis](#)' drawing span.

Parameters

<i>end</i>	the end Angle to set
------------	--------------------------------------

5.16.3.12 `set_height()`

```
void InputAxis::set_height (
    double height ) [inline]
```

Sets the height measured from the radius.

Parameters

<i>height</i>	the height to set
---------------	-------------------

5.16.3.13 set_prop()

```
void InputAxis::set_prop (
    const DrawerProperties<> & prop ) [inline]
```

Sets the [DrawerProperties](#) that will be used to draw this [InputAxis](#).

Parameters

<i>prop</i>	the DrawerProperties to set
-------------	---

5.16.3.14 set_radius()

```
void InputAxis::set_radius (
    double radius ) [inline]
```

Sets the radius measured from the center of the coordinate system.

Parameters

<i>radius</i>	the radius to set
---------------	-------------------

5.16.3.15 set_start()

```
void InputAxis::set_start (
    const Angle & start ) [inline]
```

Starts the start [Angle](#) of this [InputAxis](#)' drawing span.

Parameters

<i>start</i>	the start Angle to set
--------------	--

The documentation for this class was generated from the following file:

- include/InputAxis.h

5.17 IOVector Class Reference

[IOVector](#) MooViE component representation.

```
#include <IOVector.h>
```

Public Member Functions

- const [Point](#) & [operator\[\]](#) (std::size_t i) const
- std::size_t [size](#) (void) const
- template<typename ... Arg>
void [emplace_back](#) (Arg &&... args)

5.17.1 Detailed Description

[IOVector](#) MooViE component representation.

An element of the relation $R^n \times R^m$ or a row of data consisting of n inputs and m outputs. It can be drawn using n links and m connectors using the style specified for each [Point](#). It is necessary to know the index $i=n-1$ to draw a [IOVector](#).

Author

stratmann

Date

07.03.2018

5.17.2 Member Function Documentation

5.17.2.1 [emplace_back\(\)](#)

```
template<typename ... Arg>
void IOVector::emplace_back (
    Arg &&... args ) [inline]
```

Constructs and adds [Point](#) in-place using the given arguments.

Parameters

<i>args</i>	the arguments (Polar , DrawerProperties)
-------------	--

5.17.2.2 [operator\[\]\(\)](#)

```
const Point& IOVector::operator[] (
    std::size_t i ) const [inline]
```

Returns a const-reference to the [Point](#) of the i -th position of this [IOVector](#). There is no boundry check so that the result for $i > \text{IOVector::size}$ is undefined.

Parameters

<i>the</i>	index of the Point
------------	------------------------------------

Returns

the [Point](#)

5.17.2.3 size()

```
std::size_t IOVector::size (
    void ) const [inline]
```

Returns the total number of Points n+m of this [IOVector](#).

Returns

the size

The documentation for this class was generated from the following file:

- include/IOVector.h

5.18 IOVectorFactory Class Reference

```
#include <IOVector.h>
```

Public Member Functions

- [IOVectorFactory](#) (std::size_t num_data_rows, const [OutputGrid](#) &grid, const std::vector< [InputAxis](#) > &axis)
- [IOVector create](#) (const [DefDataRow](#) &row) const

5.18.1 Detailed Description

A class for constructing IOVectors. It follows the factory pattern.

Author

stratmann

Date

07.03.2018

5.18.2 Constructor & Destructor Documentation

5.18.2.1 IOVectorFactory()

```
IOVectorFactory::IOVectorFactory (
    std::size_t num_data_rows,
    const OutputGrid & grid,
    const std::vector< InputAxis > & axis )
```

Creates a new [IOVector](#) factory which needs the number of rows in the data set and the [OutputGrid](#) and the [InputAxis](#) with which the [IOVector](#) will be drawn.

Parameters

<i>num_data_rows</i>	the number of rows of the data set
<i>grid</i>	the OutputGrid
<i>axis</i>	the InputAxis '

5.18.3 Member Function Documentation

5.18.3.1 create()

```
IOVector IOVectorFactory::create (
    const DefDataRow & row ) const
```

Creates a new [IOVector](#) from a given DefDataRow.

Parameters

<i>row</i>	the DefDataRow
------------	----------------

Returns

the so created [IOVector](#)

The documentation for this class was generated from the following file:

- include/IOVector.h

5.19 Label Class Reference

Text label MooViE component representation.

```
#include <Label.h>
```

Public Member Functions

- [Label](#) (const std::string &text, const [TextProperties](#) &prop)
- const std::string & [get_text](#) () const
- const [TextProperties](#) & [get_properties](#) () const

5.19.1 Detailed Description

Text label MooViE component representation.

A [Label](#) is a formatted text that is stored as a text string and a [TextProperties](#) object.

Author

stratmann

Date

27.04.2018

5.19.2 Constructor & Destructor Documentation

5.19.2.1 Label()

```
Label::Label (
    const std::string & text,
    const TextProperties & prop ) [inline]
```

Creates a [Label](#) from given text and [TextProperties](#).

Parameters

<i>text</i>	the text to be displayed
<i>prop</i>	the TextProperties to be used

5.19.3 Member Function Documentation

5.19.3.1 get_properties()

```
const TextProperties& Label::get_properties ( ) const [inline]
```

Returns a const reference to this Labels [TextProperties](#).

Returns

a reference to the [TextProperties](#)

5.19.3.2 get_text()

```
const std::string& Label::get_text ( ) const [inline]
```

Returns a const reference to this Labels text.

Returns

a reference to the text

The documentation for this class was generated from the following file:

- include/Label.h

5.20 Mapper Class Reference

[Mapper](#) is a bijective function $f: [a,b] \rightarrow [c,d]$.

```
#include <Mapper.h>
```

Public Member Functions

- [Mapper](#) (const std::pair< double, double > &in, const std::pair< double, double > &out)
- double [map](#) (const double &out_val) const
- double [inverse](#) (const double &in_val) const

5.20.1 Detailed Description

[Mapper](#) is a bijective function $f: [a,b] \rightarrow [c,d]$.

[Mapper](#) represent a mapping of from one interval to another: $[a,b] \rightarrow [c,d]$. It solves the linear equations

1. $f(a) = r \cdot a + s = c$
2. $f(b) = r \cdot b + s = d$ for r and s so that it can determine f .

Author

beys

Date

26.07.2017

5.20.2 Constructor & Destructor Documentation

5.20.2.1 Mapper()

```
Mapper::Mapper (
    const std::pair< double, double > & in,
    const std::pair< double, double > & out ) [inline]
```

Creates a [Mapper](#) from two given intervals.

Parameters

<i>in</i>	the first interval
<i>out</i>	the second interval

5.20.3 Member Function Documentation**5.20.3.1 inverse()**

```
double Mapper::inverse (
    const double & in_val ) const [inline]
```

Returns the value associated to the given input using the inverse of its linear mapping function.

Parameters

<i>in_val</i>	the value to map
---------------	------------------

Returns

the mapped value

5.20.3.2 map()

```
double Mapper::map (
    const double & out_val ) const [inline]
```

Returns the value associated to the given input using its linear mapping function.

Parameters

<i>out_val</i>	the value to map
----------------	------------------

Returns

the mapped value

The documentation for this class was generated from the following file:

- include/Mapper.h

5.21 DataSet< T >::MockColumn Class Reference

Technical column for internal use.

```
#include <DataSet.h>
```

Public Member Functions

- [MockColumn](#) ([DataColumn](#) *column)
- const [Cell](#) & [operator\[\]](#) (std::size_t i) const
- void [set_enabled](#) (bool enabled)
- [ColumnType](#) [get_type](#) () const
- [Variable](#) [get_var](#) () const
- std::size_t [size](#) () const
- bool [is_enabled](#) () const

Static Public Member Functions

- static void [swap](#) ([MockColumn](#) &m0, [MockColumn](#) &m1)

5.21.1 Detailed Description

```
template<typename T>
class DataSet< T >::MockColumn
```

Technical column for internal use.

A mock column that is supposed to hold a pointer to the column storage. The DataColumns can be swapped between the [MockColumn](#). MockColumns can be enabled and disabled which alters the number of cells in the DataRows accordingly.

5.21.2 Constructor & Destructor Documentation

5.21.2.1 MockColumn()

```
template<typename T >
DataSet< T >::MockColumn::MockColumn (
    DataColumn * column ) [inline]
```

Creates a [MockColumn](#) from a [DataColumn](#). This [MockColumn](#) wraps and it and provides read-only access to all its components.

Parameters

<code>_column</code>	the DataColumn
----------------------	--------------------------------

5.21.3 Member Function Documentation

5.21.3.1 get_type()

```
template<typename T >
ColumnType DataSet< T >::MockColumn::get_type ( ) const [inline]
```

Returns the ColumnType of this [MockColumn](#). It is either INPUT or OUTPUT.

Returns

the ColumnType

5.21.3.2 get_var()

```
template<typename T >
Variable DataSet< T >::MockColumn::get_var ( ) const [inline]
```

Returns the [Variable](#) of this [MockColumn](#).

Returns

the [Variable](#)

5.21.3.3 is_enabled()

```
template<typename T >
bool DataSet< T >::MockColumn::is_enabled ( ) const [inline]
```

Returns the value of the enabled flag.

Returns

enabled or not

5.21.3.4 operator[]()

```
template<typename T >
const Cell& DataSet< T >::MockColumn::operator[] (
    std::size_t i ) const [inline]
```

Accesses the i-th [Cell](#) in the stored column.

Parameters

<i>i</i>	the row index
----------	---------------

Returns

the [Cell](#)

5.21.3.5 set_enabled()

```
template<typename T >
void DataSet< T >::MockColumn::set_enabled (
    bool enabled ) [inline]
```

Sets the enabled flag of this [MockColumn](#) to the specified value.

Parameters

<i>enabled</i>	set enabled or not
----------------	--------------------

5.21.3.6 size()

```
template<typename T >
std::size_t DataSet< T >::MockColumn::size ( ) const [inline]
```

Returns the size of this [MockColumn](#).

Returns

the size

5.21.3.7 swap()

```
template<typename T >
static void DataSet< T >::MockColumn::swap (
    MockColumn & m0,
    MockColumn & m1 ) [inline], [static]
```

Class function to swap the columns of two [MockColumns](#).

Parameters

<i>m0</i>	the first MockColumn
<i>m1</i>	the second MockColumn


The documentation for this class was generated from the following file:

- include/DataSet.h

5.22 MultiScale Class Reference

```
#include <Scale.h>
```

Inheritance diagram for MultiScale:



Public Member Functions

- [MultiScale](#) (size_t ticks_major, size_t ticks_minor, const [TextProperties](#) &label_prop, const std::string &label←_suffix="")
- void [add_scale](#) (const std::pair< double, double > &extremes)
- size_t [get_scale_number](#) (void) const
- const std::pair< double, double > [get_extremes](#) (size_t i) const
- std::vector< [Label](#) > [make_labels](#) (size_t i) const

Additional Inherited Members

5.22.1 Detailed Description

A [Scale](#) that represents a graphical axis that can display data from the R^n with two given extremes for each entry.

Author

stratmann

Date

15.05.2018

5.22.2 Constructor & Destructor Documentation

5.22.2.1 MultiScale()

```
MultiScale::MultiScale (
    size_t ticks_major,
    size_t ticks_minor,
    const TextProperties & label_prop,
    const std::string & label_suffix = "" ) [inline]
```

Creates a new [MultiScale](#) from major (big) and minor intersections, label properties, label suffix (unit) and extreme values. To use [MultiScale](#), extreme values of each entry need to be added.

Parameters

<i>major_intersections</i>	number of big intersection lines
<i>minor_intersections</i>	number of small intersection lines
<i>label_prop</i>	the style of the label text
<i>label_suffix</i>	the unit of the presented data

5.22.3 Member Function Documentation**5.22.3.1 add_scale()**

```
void MultiScale::add_scale (
    const std::pair< double, double > & extremes ) [inline]
```

Adds extreme value of another scalable entry to this [MultiScale](#).

Parameters

<i>extremes</i>	the extreme values
-----------------	--------------------

5.22.3.2 get_extremes()

```
const std::pair<double, double> MultiScale::get_extremes (
    size_t i ) const [inline]
```

Returns the extreme values of the i-th entry.

Returns

the extremes

5.22.3.3 get_scale_number()

```
size_t MultiScale::get_scale_number (
    void ) const [inline]
```

Returns the number of scales of this [MultiScale](#).

Returns

number of scales

5.22.3.4 make_labels()

```
std::vector<Label> MultiScale::make_labels (
    size_t i ) const
```

Constructs description labels using the scale with the given index.

Returns

the labels

The documentation for this class was generated from the following file:

- include/Scale.h

5.23 OutputGrid Class Reference

[OutputGrid](#) MooViE component representation.

```
#include <OutputGrid.h>
```

Public Member Functions

- [OutputGrid](#) (const std::vector< [DefVariable](#) > &output_vars, const [Angle](#) &start, const [Angle](#) &end, double radius, double height, Direction dir)
- const [DefVariable](#) & [get_var](#) (std::size_t num_output) const
- std::size_t [get_num_outputs](#) () const
- const [Angle](#) & [get_start](#) () const
- void [set_start](#) (const [Angle](#) &start)
- const [Angle](#) & [get_end](#) () const
- void [set_end](#) (const [Angle](#) &end)
- double [get_radius](#) () const
- void [set_radius](#) (double radius)
sets the radius
- double [get_height](#) () const
- void [set_height](#) (double height)
- Direction [get_direction](#) () const
- void [set_direction](#) (Direction direction)
- const [MultiScale](#) & [get_scale](#) () const

5.23.1 Detailed Description

[OutputGrid](#) MooViE component representation.

Representing a coordinate grid by its dimensional constraints.

Author

beyss

Date

26.07.2017

5.23.2 Constructor & Destructor Documentation

5.23.2.1 OutputGrid()

```
OutputGrid::OutputGrid (
    const std::vector< DefVariable > & output_vars,
    const Angle & start,
    const Angle & end,
    double radius,
    double height,
    Direction dir )
```

Creates a [OutputGrid](#) presenting given variables and is drawn between given angles with given radius and height.

Parameters

<i>output_vars</i>	a vector containing the output variables
<i>start</i>	the start angle
<i>end</i>	the end angle
<i>radius</i>	the radius from the center
<i>height</i>	the height beginning at the radius
<i>dir</i>	the Direction the outputs values increase

5.23.3 Member Function Documentation

5.23.3.1 get_direction()

```
Direction OutputGrid::get_direction ( ) const [inline]
```

Returns the direction this [OutputGrid](#)'s output values increase. The Direction is either COUNTER_CLOCKWISE (with increasing [Angle](#)) or CLOCKWISE (with decreasing [Angle](#)).

Returns

the Direction

5.23.3.2 get_end()

```
const Angle& OutputGrid::get_end ( ) const [inline]
```

Returns the end [Angle](#) of this [OutputGrid](#)'s drawing span.

Returns

the end [Angle](#)

5.23.3.3 get_height()

```
double OutputGrid::get_height ( ) const [inline]
```

Returns the height measured from the radius.

Returns

the height

5.23.3.4 get_num_outputs()

```
std::size_t OutputGrid::get_num_outputs ( ) const [inline]
```

Returns the total number of stored output variables.

Returns

the number of outputs

5.23.3.5 get_radius()

```
double OutputGrid::get_radius ( ) const [inline]
```

Returns the radius measured from the center of the coordinate system.

Returns

the radius

5.23.3.6 get_scale()

```
const MultiScale& OutputGrid::get_scale ( ) const [inline]
```

Returns the [MultiScale](#) of this [OutputGrid](#). This scale instance defines how the graphical scale will be drawn for each output.

Returns

the [MultiScale](#)

5.23.3.7 `get_start()`

```
const Angle& OutputGrid::get_start ( ) const [inline]
```

Returns the start [Angle](#) of this [OutputGrid](#)'s drawing span.

Returns

the start [Angle](#)

5.23.3.8 `get_var()`

```
const DefVariable& OutputGrid::get_var (
    std::size_t num_output ) const
```

Returns the i-th output variable. If `num_output >= num_outputs` an exception is thrown.

Parameters

<i>num_output</i>	the number of the output to return
-------------------	------------------------------------

5.23.3.9 `set_direction()`

```
void OutputGrid::set_direction (
    Direction direction ) [inline]
```

Sets the direction this [OutputGrid](#)'s output values increase. The Direction is either COUNTER_CLOCKWISE (with increasing [Angle](#)) or CLOCKWISE (with decreasing [Angle](#)).

Parameters

<i>direction</i>	the Direction to set
------------------	----------------------

5.23.3.10 `set_end()`

```
void OutputGrid::set_end (
    const Angle & end ) [inline]
```

Sets the end [Angle](#) of this [OutputGrid](#)'s drawing span.

Parameters

<i>end</i>	the end Angle to set
------------	--------------------------------------

5.23.3.11 `set_height()`

```
void OutputGrid::set_height (
    double height ) [inline]
```

Sets the height measured from the radius.

Parameters

<i>height</i>	the height to set
---------------	-------------------

5.23.3.12 `set_radius()`

```
void OutputGrid::set_radius (
    double radius ) [inline]
```

sets the radius

Sets the radius measured from the center of the coordinate system.

Parameters

<i>radius</i>	the radius to set
---------------	-------------------

5.23.3.13 `set_start()`

```
void OutputGrid::set_start (
    const Angle & start ) [inline]
```

Starts the start [Angle](#) of this [OutputGrid](#)'s drawing span.

Parameters

<i>start</i>	the start Angle to set
--------------	--

The documentation for this class was generated from the following file:

- include/OutputGrid.h

5.24 Point Struct Reference

Styled polar coordinate.

```
#include <IOVector.h>
```

Public Member Functions

- [Point](#) ([Polar](#) &&coord_, const [DrawerProperties](#)<> &prop_)
constructor

Public Attributes

- const [Polar](#) coord
- const [DrawerProperties](#) prop

5.24.1 Detailed Description

Styled polar coordinate.

A point in a polar coordinate system. The point has additional properties specifying how a curve starting from its coordinate should be styled.

Author

stratmann

Date

07.03.2018

5.24.2 Constructor & Destructor Documentation

5.24.2.1 Point()

```
Point::Point (  
    Polar && coord_,  
    const DrawerProperties<> & prop_ ) [inline]
```

constructor

Creates a [Point](#) using a given [Polar](#) and [DrawerProperties](#).

Parameters

<i>coord</i> ↔ —	the coordinate
<i>prop</i> ↔ —	the DrawerProperties

5.24.3 Member Data Documentation

5.24.3.1 coord

```
const Polar Point::coord
```

The coordinate

5.24.3.2 prop

```
const DrawerProperties Point::prop
```

The property with which to draw

The documentation for this struct was generated from the following file:

- include/IOVector.h

5.25 Polar Class Reference

[Polar](#) coordinate representation.

```
#include <Coordinates.h>
```

Public Member Functions

- [Polar](#) (double [radius](#)=0, [Angle](#) [angle](#)=0)
- bool [operator==](#) (const [Polar](#) &rhs) const
- const double & [radius](#) () const
- double & [radius](#) ()
- const [Angle](#) & [angle](#) () const
- [Angle](#) & [angle](#) ()

Static Public Member Functions

- static [Polar interpolate](#) (const [Polar](#) &p1, const [Polar](#) &p2, double p)
interpolate
- static [Polar center](#) (const [Polar](#) &p1, const [Polar](#) &p2)
center

5.25.1 Detailed Description

[Polar](#) coordinate representation.

[Polar](#) represents a tuple from \mathbb{C} in polar coordinate form.

Authors

beys, stratmann

Date

03.07.2018

5.25.2 Constructor & Destructor Documentation

5.25.2.1 [Polar\(\)](#)

```
Polar::Polar (
    double radius = 0,
    Angle angle = 0 ) [inline]
```

Creates a [Polar](#) coordinate from a given radius and angle.

Parameters

<i>r</i>	the radius
<i>phi</i>	the angle

5.25.3 Member Function Documentation

5.25.3.1 [angle\(\)](#) [1/2]

```
const Angle& Polar::angle ( ) const [inline]
```

Access function for this [Polar](#)'s m_angle readonly.

Returns

a constant reference to the [Angle](#)

5.25.3.2 angle() [2/2]

```
Angle& Polar::angle ( ) [inline]
```

Access function for this [Polar](#)'s m_angle.

Returns

a reference to the [Angle](#)

5.25.3.3 center()

```
static Polar Polar::center (
    const Polar & p1,
    const Polar & p2 ) [inline], [static]
```

center

Returns a [Polar](#) centered between two given Polars.

Parameters

<i>p1</i>	the first Polar
<i>p2</i>	the second Polar

Returns

the centered [Polar](#)

5.25.3.4 interpolate()

```
static Polar Polar::interpolate (
    const Polar & p1,
    const Polar & p2,
    double p ) [inline], [static]
```

interpolate

Returns an [Polar](#) whose radius and [Angle](#) are (1-p) percent of p1's and p percent of p2's radius and [Angle](#). To be consistent, p should be in [0,1].

Parameters

<i>p1</i>	the first Polar
<i>p2</i>	the second Polar
<i>p</i>	the percentage

Returns

the interpolated [Polar](#)

5.25.3.5 `operator==()`

```
bool Polar::operator== (
    const Polar & rhs ) const [inline]
```

Equal to operator checking for equality of radius and angle.

Parameters

<i>rhs</i>	the other Polar
------------	---------------------------------

Returns

if equal or not

5.25.3.6 `radius()` [1/2]

```
const double& Polar::radius ( ) const [inline]
```

Access function for this [Polar](#)'s radius as readonly.

Returns

a constant reference to this [Polar](#)'s radius

5.25.3.7 `radius()` [2/2]

```
double& Polar::radius ( ) [inline]
```

Access function for this [Polar](#)'s radius.

Returns

a reference to this [Polar](#)'s radius

The documentation for this class was generated from the following file:


- include/Coordinates.h

5.26 Scale Class Reference

Ticked scale.

```
#include <Scale.h>
```

Inheritance diagram for Scale:



Public Member Functions

- [Scale](#) (size_t major_intersections, size_t minor_intersections, const [TextProperties](#) &label_prop, const std::string &label_suffix="")
- size_t [get_major_intersections](#) (void) const
- size_t [get_minor_intersections](#) (void) const

Protected Attributes

- size_t **m_major_intersections**
- size_t **m_minor_intersections**
- [TextProperties](#) **m_label_prop**
- std::string **m_label_suffix**

5.26.1 Detailed Description

Ticked scale.

The [Scale](#) class represents a graphical scale of an axis by its extreme values and intersections counts.

Author

beyss

Date

22.08.2017

5.26.2 Constructor & Destructor Documentation

5.26.2.1 Scale()

```
Scale::Scale (
    size_t major_intersections,
    size_t minor_intersections,
    const TextProperties & label_prop,
    const std::string & label_suffix = "" ) [inline]
```

Creates a [Scale](#) from major (big) and minor intersections, label properties and a label suffix (unit).

Parameters

<i>major_intersections</i>	number of big intersection lines
<i>minor_intersections</i>	number of small intersection lines
<i>label_prop</i>	the style of the label text
<i>label_suffix</i>	the unit of the presented data

5.26.3 Member Function Documentation**5.26.3.1 get_major_intersections()**

```
size_t Scale::get_major_intersections (
    void ) const [inline]
```

Returns the number of major intersection lines of this scale.

Returns

number of major intersections

5.26.3.2 get_minor_intersections()

```
size_t Scale::get_minor_intersections (
    void ) const [inline]
```

Returns the number of major intersection lines of this scale.

Returns

number of minor intersections

The documentation for this class was generated from the following file:

- include/Scale.h

5.27 Scene Class Reference

MooViE scene.

```
#include <Scene.h>
```

Public Member Functions

- [Scene](#) ()
- void [update](#) (void)
- std::vector< [DefVariable](#) > [get_input_variables](#) () const
- std::vector< [DefVariable](#) > [get_output_variables](#) () const
- void [toggle_input](#) (std::size_t index, bool mode)
- void [toggle_output](#) (std::size_t index, bool mode)
- void [swap_inputs](#) (std::size_t from_index, std::size_t to_index)
- void [swap_outputs](#) (std::size_t from_index, std::size_t to_index)
- void [restrict_input](#) (std::size_t index, double lower_restr, double upper_restr)
- void [restrict_output](#) (std::size_t index, double lower_restr, double upper_restr)

5.27.1 Detailed Description

MooViE scene.

[Scene](#) class represents a MooViE scene. It is initially drawn and every alteration will require an update to be persistent.

Author

beyss

Date

28.08.2017

5.27.2 Constructor & Destructor Documentation

5.27.2.1 Scene()

```
Scene::Scene ( )
```

Creates a new MooViE [Scene](#) and draws it immediately. It is required to first initialize a [Configuration](#).

5.27.3 Member Function Documentation

5.27.3.1 get_input_variables()

```
std::vector<DefVariable> Scene::get_input_variables ( ) const
```

Returns the current input variables of this MooViE scene. Needs to be called again if [Scene](#) was altered.

Returns

the input variables

5.27.3.2 `get_output_variables()`

```
std::vector<DefVariable> Scene::get_output_variables ( ) const
```

Returns the current output variables of this MooViE scene. Needs to be called again if [Scene](#) was altered.

Returns

the output variables

5.27.3.3 `restrict_input()`

```
void Scene::restrict_input (
    std::size_t index,
    double lower_restr,
    double upper_restr )
```

Restricts the input with given index to a given interval. Every row whose associated input value is not in the interval will be disabled. The scene needs to be updated afterwards.

Parameters

<i>index</i>	the input index
<i>lower_restr</i>	the lower bound
<i>upper_restr</i>	the upper bound

5.27.3.4 `restrict_output()`

```
void Scene::restrict_output (
    std::size_t index,
    double lower_restr,
    double upper_restr )
```

Restricts the output with given index to a given interval. Every row whose associated output value is not in the interval will be disabled. The scene needs to be updated afterwards.

Parameters

<i>index</i>	the output index
<i>lower_restr</i>	the lower bound
<i>upper_restr</i>	the upper bound

5.27.3.5 swap_inputs()

```
void Scene::swap_inputs (
    std::size_t from_index,
    std::size_t to_index )
```

Rearranges the order of inputs in this MooViE scene by swapping the inputs with the given indices. The scene needs to be updated afterwards.

Parameters

<i>from_index</i>	the first inputs index
<i>to_index</i>	the second inputs index

Exceptions

<i>out_of_bounds</i>	if indices are incorrect
----------------------	--------------------------

5.27.3.6 swap_outputs()

```
void Scene::swap_outputs (
    std::size_t from_index,
    std::size_t to_index )
```

Rearranges the order of outputs in this MooViE scene by swapping the outputs with the given indices. The scene needs to be updated afterwards.

Parameters

<i>from_index</i>	the first outputs index
<i>to_index</i>	the second outputs index

Exceptions

<i>out_of_bounds</i>	if indices are incorrect
----------------------	--------------------------

5.27.3.7 toggle_input()

```
void Scene::toggle_input (
    std::size_t index,
    bool mode )
```

Enables/disables the input with the given index. The scene needs to be updated afterwards.

Parameters

<i>index</i>	the input index
<i>mode</i>	set enabled or disabled

Exceptions

<i>out_of_bounds</i>	if index is incorrect
----------------------	-----------------------

5.27.3.8 toggle_output()

```
void Scene::toggle_output (
    std::size_t index,
    bool mode )
```

Enables/disables the output with the given index. The scene needs to be updated afterwards.

Parameters

<i>index</i>	the output index
<i>mode</i>	set enabled or disabled

Exceptions

<i>out_of_bounds</i>	if index is incorrect
----------------------	-----------------------

5.27.3.9 update()

```
void Scene::update (
    void )
```

Reinitializes all components and redraws the MooViE scene.


The documentation for this class was generated from the following file:

- include/Scene.h

5.28 SimpleScale Class Reference

```
#include <Scale.h>
```

Inheritance diagram for SimpleScale:



Public Member Functions

- [SimpleScale](#) (size_t major_intersections, size_t minor_intersections, const std::pair< double, double > &extremes, const [TextProperties](#) &label_prop, const std::string &label_suffix="")
- const std::pair< double, double > & [get_extremes](#) () const
- std::vector< [Label](#) > [make_labels](#) (void) const

Additional Inherited Members

5.28.1 Detailed Description

A [Scale](#) that represents a graphical axis that can display data from the real numbers with two given extremes.

Author

stratmann

Date

15.05.2018

5.28.2 Constructor & Destructor Documentation

5.28.2.1 SimpleScale()

```

SimpleScale::SimpleScale (
    size_t major_intersections,
    size_t minor_intersections,
    const std::pair< double, double > & extremes,
    const TextProperties & label_prop,
    const std::string & label_suffix = "" ) [inline]
  
```

Creates a new [SimpleScale](#) from major (big) and minor intersections, label properties, label suffix (unit) and extreme values.

Parameters

<i>major_intersections</i>	number of big intersection lines
<i>minor_intersections</i>	number of small intersection lines
<i>extremes</i>	the extreme values of the scale
<i>label_prop</i>	the style of the label text
<i>label_suffix</i>	the unit of the presented data

5.28.3 Member Function Documentation

5.28.3.1 `get_extremes()`

```
const std::pair<double, double>& SimpleScale::get_extremes ( ) const [inline]
```

Access function for the Ticks extreme values.

Returns

a reference to the extreme values

5.28.3.2 `make_labels()`

```
std::vector<Label> SimpleScale::make_labels (
    void ) const
```

Constructs description labels from the

Returns

the labels

The documentation for this class was generated from the following file:

- `include/Scale.h`

5.29 `Drawer::TextAlignment` Struct Reference

Text alignment representation.

```
#include <Drawer.h>
```

Public Member Functions

- **`TextAlignment`** (double ratio)

Public Attributes

- double **ratio**

Static Public Attributes

- static const [TextAlignment](#) **LEFT**
- static const [TextAlignment](#) **HALF_LEFT**
- static const [TextAlignment](#) **CENTERED**
- static const [TextAlignment](#) **HALF_RIGHT**
- static const [TextAlignment](#) **RIGHT**

5.29.1 Detailed Description

Text alignment representation.

[TextAlignment](#) represents the alignment of MooViE Labels. It can be used for both horizontal and vertical alignment.

The documentation for this struct was generated from the following file:

- include/Drawer.h

5.30 TextProperties Struct Reference

Properties to modify a MooViE Drawers text style.

```
#include <TextProperties.h>
```

Public Member Functions

- [TextProperties](#) (const std::string &font_name_, double font_size_, const [Color](#) &color_=[Color::BLACK](#), bool bold_=false, bool italic_=false)

Public Attributes

- std::string [font_name](#)
- double [font_size](#)
- [Color](#) [color](#)
- bool [bold](#)
- bool [italic](#)

5.30.1 Detailed Description

Properties to modify a MooViE Drawers text style.

[TextProperties](#) can be used to control font, size, color and style of a drawn text.

Authors

beyss, stratmann

Date

05.07.2017

5.30.2 Constructor & Destructor Documentation

5.30.2.1 TextProperties()

```
TextProperties::TextProperties (
    const std::string & font_name_,
    double font_size_,
    const Color & color_ = Color::BLACK,
    bool bold_ = false,
    bool italic_ = false ) [inline]
```

Creates a [TextProperties](#) instance with the given style information.

Parameters

<i>font_↔ name_</i>	
<i>font_size↔ _</i>	
<i>color_</i>	
<i>bold_</i>	
<i>italic_</i>	

5.30.3 Member Data Documentation

5.30.3.1 bold

```
bool TextProperties::bold
```

The boldness of the text

5.30.3.2 color

```
Color TextProperties::color
```

The text color

5.30.3.3 font_name

```
std::string TextProperties::font_name
```

The font name

5.30.3.4 font_size

```
double TextProperties::font_size
```

The font size

5.30.3.5 italic

```
bool TextProperties::italic
```

The skewness of the text

The documentation for this struct was generated from the following file:

- include/TextProperties.h

5.31 Triangle< T, dim > Class Template Reference

Triangular set storage.

```
#include <Triangle.h>
```

Public Member Functions

- [Triangle](#) ()
- [Triangle](#) (const std::vector< T > data)
- const T & [at](#) (size_t i, size_t j) const
- T & [at](#) (size_t i, size_t j)

5.31.1 Detailed Description

```
template<typename T, size_t dim>  
class Triangle< T, dim >
```

Triangular set storage.

[Triangle](#) stores sets who have a size equal to their their index + 1. The total storage of a [Triangle](#) instance is equal to the dim-th triangular number (starting with $T_1 = 1$). 0: Elem00 1: Elem10 Elem11 2: Elem20 Elem21 Elem22 ...

Author

beyss

Date

23.08.2017

5.31.2 Constructor & Destructor Documentation

5.31.2.1 Triangle() [1/2]

```
template<typename T, size_t dim>
Triangle< T, dim >::Triangle ( ) [inline]
```

Creates a [Triangle](#) with an empty storage.

5.31.2.2 Triangle() [2/2]

```
template<typename T, size_t dim>
Triangle< T, dim >::Triangle (
    const std::vector< T > data ) [inline]
```

Creates a [Triangle](#) from a given data vector whose size must be the dim-th triangular number.

Parameters

<i>data</i>	the data vector
-------------	-----------------

5.31.3 Member Function Documentation

5.31.3.1 at() [1/2]

```
template<typename T, size_t dim>
const T& Triangle< T, dim >::at (
    size_t i,
    size_t j ) const [inline]
```

Readonly access function for the j-th element of the i-th set.

Parameters

<i>i</i>	the "row"
<i>j</i>	the "column"

Returns

a constant reference to the storage element

5.31.3.2 `at()` [2/2]

```
template<typename T, size_t dim>
T& Triangle< T, dim >::at (
    size_t i,
    size_t j ) [inline]
```

Access function for the j-th element of the i-th set.

Parameters

<i>i</i>	the "row"
<i>j</i>	the "column"

Returns

a reference to the storage element

The documentation for this class was generated from the following file:

- include/Triangle.h

5.32 DataSet< T >::Variable Struct Reference

Header description.

```
#include <DataSet.h>
```

Public Member Functions

- [Variable](#) (T min_, T max_, const std::string &name_, const std::string &unit_="")

Public Attributes

- T [min](#)
- T [max](#)
- std::string [name](#)
- std::string [unit](#)

5.32.1 Detailed Description

```
template<typename T>
struct DataSet< T >::Variable
```

Header description.

[Variable](#) represents an entity attribute and stores its name, maximal and minimal value.

5.32.2 Constructor & Destructor Documentation

5.32.2.1 Variable()

```
template<typename T >
DataSet< T >::Variable::Variable (
    T min_,
    T max_,
    const std::string & name_,
    const std::string & unit_ = "" ) [inline]
```

Creates a [Variable](#) with the given name, min and max value.

Parameters

<i>min</i>	the min value
<i>max</i>	the max value
<i>name</i>	the name

5.32.3 Member Data Documentation

5.32.3.1 max

```
template<typename T >
T DataSet< T >::Variable::max
```

Maximal value

5.32.3.2 min

```
template<typename T >
T DataSet< T >::Variable::min
```

Minimal value

5.32.3.3 name

```
template<typename T >
std::string DataSet< T >::Variable::name
```

[Variable](#) name

5.32.3.4 unit

```
template<typename T >  
std::string DataSet< T >::Variable::unit
```

Unit of the Variables values

The documentation for this struct was generated from the following file:

- include/DataSet.h

