

Opgave 1

```
IDENTIFICATION DIVISION.  
PROGRAM-ID. HELLO.  
  
DATA DIVISION.  
WORKING-STORAGE SECTION.  
01 VAR-TEXT          PIC X(30) VALUE "HELLO med Variabel".  
  
PROCEDURE DIVISION.  
* Nedenfor kommer en DISPLAY - COBOLs måde at skrive i konsollen  
DISPLAY "HELLO, WORLD!"  
DISPLAY VAR-TEXT  
STOP RUN.
```

Opgave 2

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave2.

DATA DIVISION.
WORKING-STORAGE SECTION.
*-----*
* Variabler *
*-----*
01 KUNDE-ID      PIC X(10)  VALUE SPACES.
01 FORNAVN      PIC X(20)  VALUE SPACES.
01 EFTERNAVN    PIC X(20)  VALUE SPACES.
01 KONTONUMMER  PIC X(20)  VALUE SPACES.
01 BALANCE      PIC 9(7)V99 VALUE ZEROS.
01 VALUTAKODE   PIC X(3)   VALUE SPACES.

PROCEDURE DIVISION.
*-----*
* Tildel værdier til variabler *
*-----*
      MOVE "K123456789" TO KUNDE-ID
      MOVE "Morten"    TO FORNAVN
      MOVE "Jensen"    TO EFTERNAVN
      MOVE "DK1234567890" TO KONTONUMMER
      MOVE 12345.67     TO BALANCE
      MOVE "DKK"       TO VALUTAKODE

*-----*
* Udskriv værdierne *
*-----*
      DISPLAY "-----"
      DISPLAY "Kunde ID      : " KUNDE-ID
      DISPLAY "Navn        : " FORNAVN " " EFTERNAVN
      DISPLAY "Kontonummer  : " KONTONUMMER
      DISPLAY "Balance     : " BALANCE " " VALUTAKODE
      DISPLAY "-----"

      STOP RUN.
```

Opgave 3

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave3.

DATA DIVISION.
WORKING-STORAGE SECTION.
* -----
* Oprindelige variabler
* -----
    01 KUNDE-ID          PIC X(10)  VALUE SPACES.
    01 FORNAVN          PIC X(20)  VALUE SPACES.
    01 EFTERNAVN        PIC X(20)  VALUE SPACES.
    01 KONTONUMMER       PIC X(20)  VALUE SPACES.
    01 BALANCE           PIC 9(7)V99 VALUE ZEROS.
    01 VALUTAKODE        PIC X(3)   VALUE SPACES.

* -----
* Variabler til fuldt navn og renset output
* -----
    01 FULDT-NAVN        PIC X(40)  VALUE SPACES.
    01 RENS-FULDT-NAVN   PIC X(40)  VALUE SPACES.

    01 IX                PIC 9(2)    VALUE 1.
    01 IX2                PIC 9(2)    VALUE 0.
    01 CURRENT-CHAR       PIC X(1)    VALUE SPACE.
    01 PREVIOUS-CHAR      PIC X(1)    VALUE SPACE.

PROCEDURE DIVISION.
* -----
* Flyt data til kundeinfo
* -----
    MOVE "K123456789"      TO KUNDE-ID
    MOVE "Michael B"       TO FORNAVN
    MOVE "Nielsen"         TO EFTERNAVN
    MOVE "DK0987654321"    TO KONTONUMMER
    MOVE 98765.43           TO BALANCE
    MOVE "DKK"             TO VALUTAKODE

* -----
* Sammensæt fornavn og efternavn til fuldt navn
* -----
    STRING FORNAVN DELIMITED BY SIZE
           " "      DELIMITED BY SIZE
           EFTERNAVN DELIMITED BY SIZE
    INTO FULDT-NAVN
    END-STRING

* -----
```

```

* Vis fuldt navn før løkke
* -----
    DISPLAY "FOER LOOP (FULDT-NAVN) : [" FULDT-NAVN "]"

* -----
* Loop for at fjerne ekstra mellemrum
* -----
    MOVE SPACE TO RENS-FULDT-NAVN
    MOVE 1     TO IX
    MOVE 0     TO IX2
    MOVE SPACE TO PREVIOUS-CHAR

    PERFORM VARYING IX FROM 1 BY 1
        UNTIL IX > LENGTH OF FULDT-NAVN
        MOVE FULDT-NAVN(IX:1) TO CURRENT-CHAR

        IF CURRENT-CHAR NOT = SPACE
            OR PREVIOUS-CHAR NOT = SPACE
            ADD 1 TO IX2
            MOVE CURRENT-CHAR TO RENS-FULDT-NAVN(IX2:1)
        END-IF

        MOVE CURRENT-CHAR TO PREVIOUS-CHAR
    END-PERFORM.

* -----
* Vis fuldt navn efter loop
* -----
    DISPLAY "EFTER LOOP (RENS-FULDT-NAVN) : ["
        RENS-FULDT-NAVN "]"

* -----
* Udskriv resultat sammen med øvrige kundeinfo
* -----
    DISPLAY "-----"
    DISPLAY "Kunde ID       : " KUNDE-ID
    DISPLAY "Navn (renset)  : " RENS-FULDT-NAVN
    DISPLAY "Kontonummer   : " KONTONUMMER
    DISPLAY "Balance       : " BALANCE " " VALUTAKODE
    DISPLAY "-----"

    STOP RUN.

```

Opgave 4

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave4.

DATA DIVISION.
WORKING-STORAGE SECTION.
* -----
* Struktureret kundeoplysninger
* -----
    01 KUNDEOPL.
        02 KUNDE-ID          PIC X(10) VALUE SPACES.
        02 NAVN.
            03 FORNAVN       PIC X(20) VALUE SPACES.
            03 EFTERNAVN     PIC X(20) VALUE SPACES.
        02 KONTOINFO.
            03 KONTONUMMER   PIC X(20) VALUE SPACES.
            03 BALANCE       PIC 9(7)V99 VALUE ZEROS.
            03 VALUTAKODE    PIC X(3) VALUE SPACES.

* -----
* Beregnede variabler udenfor strukturen
* -----
    01 FULDT-NAVN           PIC X(40) VALUE SPACES.
    01 RENS-FULDT-NAVN     PIC X(40) VALUE SPACES.
    01 IX                   PIC 9(2) VALUE 1.
    01 IX2                  PIC 9(2) VALUE 0.
    01 CURRENT-CHAR        PIC X(1) VALUE SPACE.
    01 PREVIOUS-CHAR       PIC X(1) VALUE SPACE.

PROCEDURE DIVISION.
* -----
* Flyt data ind i strukturen
* -----
    MOVE "K123456789"      TO KUNDE-ID OF KUNDEOPL
    MOVE "Michael B"       TO FORNAVN OF NAVN OF KUNDEOPL
    MOVE "Nielsen"         TO EFTERNAVN OF NAVN OF KUNDEOPL
    MOVE "DK0987654321"    TO KONTONUMMER OF KONTOINFO OF KUNDEOPL
    MOVE 98765.43          TO BALANCE OF KONTOINFO OF KUNDEOPL
    MOVE "DKK"             TO VALUTAKODE OF KONTOINFO OF KUNDEOPL

* -----
* Sammensæt fuldt navn
* -----
    STRING FORNAVN OF NAVN OF KUNDEOPL DELIMITED BY SIZE
           " " DELIMITED BY SIZE
           EFTERNAVN OF NAVN OF KUNDEOPL DELIMITED BY SIZE
           INTO FULDT-NAVN
    END-STRING
```

```

* -----
* Loop for at fjerne ekstra mellemrum
* -----

    MOVE SPACE TO RENS-FULDT-NAVN
    MOVE 1     TO IX
    MOVE 0     TO IX2
    MOVE SPACE TO PREVIOUS-CHAR

    PERFORM VARYING IX FROM 1 BY 1
        UNTIL IX > LENGTH OF FULDT-NAVN
        MOVE FULDT-NAVN(IX:1) TO CURRENT-CHAR

        IF CURRENT-CHAR NOT = SPACE
            OR PREVIOUS-CHAR NOT = SPACE
            ADD 1 TO IX2
            MOVE CURRENT-CHAR TO RENS-FULDT-NAVN(IX2:1)
        END-IF

        MOVE CURRENT-CHAR TO PREVIOUS-CHAR
    END-PERFORM.

* -----
* Vis individuelle felter
* -----

    DISPLAY "-----"
    DISPLAY "Kunde ID       : " KUNDE-ID OF KUNDEOPL
    DISPLAY "Navn (renset)  : " RENS-FULDT-NAVN
    DISPLAY "Kontonummer    : " KONTONUMMER OF KONTOINFO OF
                                KUNDEOPL
    DISPLAY "Balance       : " BALANCE OF KONTOINFO OF KUNDEOPL
                                " "
                                VALUTAKODE OF KONTOINFO OF KUNDEOPL
    DISPLAY "-----"

* -----
* Vis hele strukturen på 01-niveau
* -----

    DISPLAY "HELE STRUKTUREN:"
    DISPLAY KUNDEOPL

    STOP RUN.

```

Opgave 5

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave4.

DATA DIVISION.
WORKING-STORAGE SECTION.
* -----
* Struktureret kundeoplysninger
* -----
    01 KUNDEOPL.
        02 KUNDE-ID          PIC X(10) VALUE SPACES.
        02 NAVN.
            03 FORNAVN       PIC X(20) VALUE SPACES.
            03 EFTERNAVN     PIC X(20) VALUE SPACES.
        02 KONTOINFO.
            03 KONTONUMMER   PIC X(20) VALUE SPACES.
            03 BALANCE       PIC 9(7)V99 VALUE ZEROS.
            03 VALUTAKODE    PIC X(3) VALUE SPACES.

* -----
* Beregnede variabler udenfor strukturen
* -----
    01 FULDT-NAVN           PIC X(40) VALUE SPACES.
    01 RENS-FULDT-NAVN     PIC X(40) VALUE SPACES.
    01 IX                   PIC 9(2) VALUE 1.
    01 IX2                  PIC 9(2) VALUE 0.
    01 CURRENT-CHAR        PIC X(1) VALUE SPACE.
    01 PREVIOUS-CHAR       PIC X(1) VALUE SPACE.

PROCEDURE DIVISION.
* -----
* Flyt data ind i strukturen
* -----
    MOVE "K123456789"      TO KUNDE-ID OF KUNDEOPL
    MOVE "Michael B"       TO FORNAVN OF NAVN OF KUNDEOPL
    MOVE "Nielsen"         TO EFTERNAVN OF NAVN OF KUNDEOPL
    MOVE "DK0987654321"    TO KONTONUMMER OF KONTOINFO OF KUNDEOPL
    MOVE 98765.43           TO BALANCE OF KONTOINFO OF KUNDEOPL
    MOVE "DKK"             TO VALUTAKODE OF KONTOINFO OF KUNDEOPL

* -----
* Sammensæt fuldt navn
* -----
    STRING FORNAVN OF NAVN OF KUNDEOPL DELIMITED BY SIZE
           " " DELIMITED BY SIZE
           EFTERNAVN OF NAVN OF KUNDEOPL DELIMITED BY SIZE
           INTO FULDT-NAVN
    END-STRING
```

```

* -----
* Loop for at fjerne ekstra mellemrum
* -----

    MOVE SPACE TO RENS-FULDT-NAVN
    MOVE 1     TO IX
    MOVE 0     TO IX2
    MOVE SPACE TO PREVIOUS-CHAR

    PERFORM VARYING IX FROM 1 BY 1
        UNTIL IX > LENGTH OF FULDT-NAVN
        MOVE FULDT-NAVN(IX:1) TO CURRENT-CHAR

        IF CURRENT-CHAR NOT = SPACE
            OR PREVIOUS-CHAR NOT = SPACE
            ADD 1 TO IX2
            MOVE CURRENT-CHAR TO RENS-FULDT-NAVN(IX2:1)
        END-IF

        MOVE CURRENT-CHAR TO PREVIOUS-CHAR
    END-PERFORM.

* -----
* Vis individuelle felter
* -----

    DISPLAY "-----"
    DISPLAY "Kunde ID       : " KUNDE-ID OF KUNDEOPL
    DISPLAY "Navn (renset)  : " RENS-FULDT-NAVN
    DISPLAY "Kontonummer    : " KONTONUMMER OF KONTOINFO OF
                                KUNDEOPL
    DISPLAY "Balance       : " BALANCE OF KONTOINFO OF KUNDEOPL
                                " "
                                VALUTAKODE OF KONTOINFO OF KUNDEOPL
    DISPLAY "-----"

* -----
* Vis hele strukturen på 01-niveau
* -----

    DISPLAY "HELE STRUKTUREN:"
    DISPLAY KUNDEOPL

    STOP RUN.

```


Opgave 6

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave6.

ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
    SELECT KUNDEFIL ASSIGN TO "Kundeoplysninger.txt"
        ORGANIZATION IS LINE SEQUENTIAL.

DATA DIVISION.
FILE SECTION.
FD KUNDEFIL.
01 KUNDE-REKORD.
    COPY "KUNDEOPL.cpy".

WORKING-STORAGE SECTION.
01 EOF-FLAG          PIC X VALUE "N".
    88 END-OF-FILE    VALUE "Y".
    88 MORE-TO-READ   VALUE "N".

01 FULDT-NAVN        PIC X(40) VALUE SPACES.
01 RENS-FULDT-NAVN   PIC X(40) VALUE SPACES.

PROCEDURE DIVISION.
MAIN-PROGRAM.
    OPEN INPUT KUNDEFIL

    PERFORM UNTIL END-OF-FILE
        READ KUNDEFIL
        AT END
            SET END-OF-FILE TO TRUE
        NOT AT END
            *> Sammensæt fuldt navn
            STRING FORNAVN DELIMITED BY SIZE
                " " DELIMITED BY SIZE
                EFTERNAVN DELIMITED BY SIZE
            INTO FULDT-NAVN
            END-STRING
            MOVE FUNCTION TRIM(FULDT-NAVN) TO RENS-FULDT-NAVN

            DISPLAY "----- Kunde -----"
            DISPLAY "Kunde ID          : " KUNDE-ID
            DISPLAY "Navn (renset)      : " RENS-FULDT-NAVN
            DISPLAY "Kontonummer       : " KONTONUMMER OF
            KONTAINFO
            DISPLAY "Balance           : " BALANCE OF KONTAINFO
            " " VALUTAKODE OF KONTAINFO
```

```
        DISPLAY "Adresse          : " VEJNAVN OF ADRESSE  
        " " HUSNR OF ADRESSE ", "  
                                ETAGE OF ADRESSE  
                                SIDE OF ADRESSE  
        DISPLAY "By/Postnr       : " BY-X OF ADRESSE " "  
        POSTNR OF ADRESSE  
        DISPLAY "Telefon/Email   : " TELEFON OF  
        KONTAKTINFO " " EMAIL OF KONTAKTINFO  
  
    END-READ  
END-PERFORM  
  
CLOSE KUNDEFIL  
STOP RUN.
```

Opgave 7

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave7.

ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
    SELECT KUNDEFIL-IN ASSIGN TO "Kundeoplysninger.txt"
        ORGANIZATION IS LINE SEQUENTIAL.
    SELECT KUNDEFIL-OUT ASSIGN TO "KundeoplysningerOut.txt"
        ORGANIZATION IS LINE SEQUENTIAL.

DATA DIVISION.
FILE SECTION.

FD KUNDEFIL-IN.
01 KUNDE-REKORD-IN.
    COPY "KUNDEOPL.cpy".

FD KUNDEFIL-OUT.
01 KUNDE-ADR.
    02 NAVN-ADR          PIC X(100).

WORKING-STORAGE SECTION.
01 EOF-FLAG             PIC X VALUE "N".
    88 END-OF-FILE      VALUE "Y".
    88 MORE-TO-READ     VALUE "N".

01 FULDT-NAVN           PIC X(40) VALUE SPACES.
01 ADR-LINJE            PIC X(100) VALUE SPACES.
01 BY-LINJE            PIC X(60) VALUE SPACES.
01 KONTO-LINJE         PIC X(60) VALUE SPACES.
01 KONTAKT-LINJE       PIC X(80) VALUE SPACES.

PROCEDURE DIVISION.
MAIN-PROGRAM.
    OPEN INPUT KUNDEFIL-IN
        OUTPUT KUNDEFIL-OUT

    PERFORM UNTIL END-OF-FILE
        READ KUNDEFIL-IN
            AT END
                SET END-OF-FILE TO TRUE
            NOT AT END
                PERFORM BEHANDL-KUNDE
        END-READ
    END-PERFORM
```

```
CLOSE KUNDEFIL-IN
      KUNDEFIL-OUT
```

```
DISPLAY "Kundedata er nu skrevet til KundeoplysningerOut.txt"
STOP RUN.
```

```
*-----
*  HOVEDROUTINE: Behandling og skrivning af én kunde
*-----
```

```
BEHANDL-KUNDE.
```

```
    PERFORM FORMAT-NAVN
    PERFORM FORMAT-KONTO
    PERFORM FORMAT-ADR
    PERFORM FORMAT-BY
    PERFORM FORMAT-KONTAKT
```

```
*  SKRIV OUTPUT I RÆKKEFØLGE
```

```
    MOVE SPACES TO NAVN-ADR
    STRING "KUNDE-ID: " KUNDE-ID DELIMITED BY SIZE
           INTO NAVN-ADR
    END-STRING
    WRITE KUNDE-ADR.
```

```
    MOVE SPACES TO NAVN-ADR
    STRING "NAVN: " FULDT-NAVN DELIMITED BY SIZE
           INTO NAVN-ADR
    END-STRING
    WRITE KUNDE-ADR.
```

```
    MOVE SPACES TO NAVN-ADR
    STRING "KONTO: " KONTO-LINJE DELIMITED BY SIZE
           INTO NAVN-ADR
    END-STRING
    WRITE KUNDE-ADR.
```

```
    MOVE SPACES TO NAVN-ADR
    STRING "ADRESSE: " ADR-LINJE DELIMITED BY SIZE
           INTO NAVN-ADR
    END-STRING
    WRITE KUNDE-ADR.
```

```
    MOVE SPACES TO NAVN-ADR
    STRING "BY: " BY-LINJE DELIMITED BY SIZE
           INTO NAVN-ADR
    END-STRING
    WRITE KUNDE-ADR.
```

```
    MOVE SPACES TO NAVN-ADR
```

```

        STRING "KONTAKT: " KONTAKT-LINJE DELIMITED BY SIZE
            INTO NAVN-ADR
        END-STRING
        WRITE KUNDE-ADR.

*   BLANK LINJE MELLEM KUNDER
        MOVE SPACES TO NAVN-ADR
        WRITE KUNDE-ADR.
        EXIT.

*-----
*   PARAGRAFFER TIL FORMATERING
*-----

FORMAT-NAVN.
        MOVE SPACES TO FULDT-NAVN
        STRING FORNAVN DELIMITED BY SPACE
            " " DELIMITED BY SIZE
            EFTERNAVN DELIMITED BY SPACE
            INTO FULDT-NAVN
        END-STRING
        MOVE FUNCTION TRIM(FULDT-NAVN) TO FULDT-NAVN
        EXIT.

FORMAT-KONTO.
        MOVE SPACES TO KONTO-LINJE
        STRING KONTONUMMER OF KONTOINFO DELIMITED BY SIZE
            " - " DELIMITED BY SIZE
            BALANCE OF KONTOINFO DELIMITED BY SIZE
            " " DELIMITED BY SIZE
            VALUTAKODE OF KONTOINFO DELIMITED BY SIZE
            INTO KONTO-LINJE
        END-STRING
        EXIT.

FORMAT-ADR.
        MOVE SPACES TO ADR-LINJE
        STRING VEJNAVN OF ADRESSE DELIMITED BY SPACE
            " " DELIMITED BY SIZE
            HUSNR OF ADRESSE DELIMITED BY SPACE
            " " DELIMITED BY SIZE
            ETAGE OF ADRESSE DELIMITED BY SPACE
            " " DELIMITED BY SIZE
            SIDE OF ADRESSE DELIMITED BY SPACE
            INTO ADR-LINJE
        END-STRING
        EXIT.

FORMAT-BY.

```

```
MOVE SPACES TO BY-LINJE
STRING POSTNR OF ADRESSE DELIMITED BY SPACE
      " " DELIMITED BY SIZE
      BY-X OF ADRESSE DELIMITED BY SPACE
      INTO BY-LINJE
END-STRING
EXIT.
```

FORMAT-KONTAKT.

```
MOVE SPACES TO KONTAKT-LINJE
STRING TELEFON OF KONTAKTINFO DELIMITED BY SPACE
      " " DELIMITED BY SIZE
      EMAIL OF KONTAKTINFO DELIMITED BY SPACE
      INTO KONTAKT-LINJE
END-STRING
EXIT.
```

Opgave 8

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave8.

ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
    SELECT KUNDEFIL ASSIGN TO "Kundeoplysninger.txt"
        ORGANIZATION IS LINE SEQUENTIAL.
    SELECT KONTOFIL ASSIGN TO "KontoOpl.txt"
        ORGANIZATION IS LINE SEQUENTIAL.
    SELECT OUT-FIL ASSIGN TO "KUNDEKONTO.txt"
        ORGANIZATION IS LINE SEQUENTIAL.

DATA DIVISION.
FILE SECTION.

FD KUNDEFIL.
01 KUNDE-REKORD.
    COPY "KUNDEOPL.cpy".

FD KONTOFIL.
01 KONTO-REKORD.
    COPY "KONTOOPL.cpy".

FD OUT-FIL.
01 OUT-REKORD.
    02 OUTPUT-TEXT          PIC X(150).

WORKING-STORAGE SECTION.
01 EOF-KUNDE                PIC X VALUE "N".
    88 END-KUNDE            VALUE "Y".
    88 MORE-KUNDE           VALUE "N".

01 EOF-KONTI                PIC X VALUE "N".
    88 END-KONTI            VALUE "Y".
    88 MORE-KONTI           VALUE "N".

01 FULDT-NAVN               PIC X(40) VALUE SPACES.
01 ADR-LINJE1               PIC X(60) VALUE SPACES.
01 ADR-LINJE2               PIC X(40) VALUE SPACES.

PROCEDURE DIVISION.
MAIN-PROGRAM.
    OPEN INPUT KUNDEFIL
    OPEN OUTPUT OUT-FIL

    PERFORM UNTIL END-KUNDE
```

```

        READ KUNDEFIL
        AT END
            SET END-KUNDE TO TRUE
        NOT AT END
            *> Formater kundedata
            PERFORM FORMAT-NAVN
            PERFORM FORMAT-VEJ
            PERFORM FORMAT-BY

            *> Skriv kundeheader og adresse
            PERFORM SKRIV-KUNDE

            *> Læs og skriv konti for denne kunde
            PERFORM LÆS-KONTI

            *> Skriv en blank linje mellem kunder
            MOVE SPACES TO OUTPUT-TEXT
            WRITE OUT-REKORD
    END-READ
END-PERFORM

CLOSE KUNDEFIL
CLOSE OUT-FIL
STOP RUN.

*> -----
*> Paragraf til behandling af navn
FORMAT-NAVN.
    STRING FORNAVN OF KUNDE-REKORD DELIMITED BY SPACE
        " " DELIMITED BY SIZE
        EFTERNAVN OF KUNDE-REKORD DELIMITED BY SPACE
        INTO FULDT-NAVN
    END-STRING
    EXIT.
*> Paragraf slut

*> -----
*> Paragraf til behandling af vejadresse
FORMAT-VEJ.
    STRING VEJNAVN OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        " " HUSNR OF ADRESSE OF KUNDE-REKORD
        DELIMITED BY SIZE
        " " ETAGE OF ADRESSE OF KUNDE-REKORD
        DELIMITED BY SIZE
        " " SIDE OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        INTO ADR-LINJE1
    END-STRING
    EXIT.

```



```

*> Paragraf slut

*> -----
*> Paragraf til behandling af by/postnummer
FORMAT-BY.
    STRING POSTNR OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        " " BY-X OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        INTO ADR-LINJE2
    END-STRING
    EXIT.
*> Paragraf slut

*> -----
*> Paragraf til at skrive kundeinfo
SKRIV-KUNDE.
    MOVE SPACES TO OUTPUT-TEXT
    STRING "Kunde-ID: " KUNDE-ID OF KUNDE-REKORD
        DELIMITED BY SIZE
        " | Navn: " FULDT-NAVN DELIMITED BY SIZE
        INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD

    MOVE SPACES TO OUTPUT-TEXT
    STRING "Adresse: " ADR-LINJE1 DELIMITED BY SIZE
        ", " ADR-LINJE2 DELIMITED BY SIZE
        INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD

    MOVE SPACES TO OUTPUT-TEXT
    STRING "Tlf: " TELEFON OF KONTAKTINFO OF KUNDE-REKORD
        DELIMITED BY SIZE
        " | Email: " EMAIL OF KONTAKTINFO OF KUNDE-REKORD
        DELIMITED BY SIZE
        INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD
    EXIT.
*> Paragraf slut

*> -----
*> Paragraf til læsning og skrivning af konti
LÆS-KONTI.
    OPEN INPUT KONTOFIL
    MOVE "N" TO EOF-KONTI

    PERFORM UNTIL END-KONTI

```

```

        READ KONTOFIL
        AT END
            SET END-KONTI TO TRUE
        NOT AT END
            IF KUNDE-ID OF KONTO-REKORD = KUNDE-ID OF
                KUNDE-REKORD
                PERFORM SKRIV-KONTI
            END-IF
        END-READ
    END-PERFORM

    CLOSE KONTOFIL
    EXIT.
*> Paragraf slut

*> -----
*> Paragraf til skrivning af en enkelt konto
SKRIV-KONTI.
    MOVE SPACES TO OUTPUT-TEXT
    STRING "    Konto-ID: " KONTO-ID OF KONTO-REKORD
        DELIMITED BY SIZE
        " | Type: "      KONTO-TYPE OF KONTO-REKORD
        DELIMITED BY SIZE
        " | Saldo: " BALANCE OF KONTO-REKORD
        DELIMITED BY SIZE
        " " VALUTA-KD OF KONTO-REKORD DELIMITED BY SIZE
    INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD
    EXIT.
*> Paragraf slut

```

Opgave 9

```
IDENTIFICATION DIVISION.
PROGRAM-ID. Opgave9.

ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
    SELECT KUNDEFIL ASSIGN TO "Kundeoplysninger.txt"
        ORGANIZATION IS LINE SEQUENTIAL.
    SELECT KONTOFIL ASSIGN TO "KontoOpl.txt"
        ORGANIZATION IS LINE SEQUENTIAL.
    SELECT OUT-FIL ASSIGN TO "KUNDEKONTO.txt"
        ORGANIZATION IS LINE SEQUENTIAL.

DATA DIVISION.
FILE SECTION.

FD KUNDEFIL.
01 KUNDE-REKORD.
    COPY "KUNDEOPL.cpy".

FD KONTOFIL.
01 KONTO-REKORD.
    COPY "KONTOOPL.cpy".

FD OUT-FIL.
01 OUT-REKORD.
    02 OUTPUT-TEXT          PIC X(150).

WORKING-STORAGE SECTION.
01 EOF-KUNDE                PIC X VALUE "N".
    88 END-KUNDE            VALUE "Y".
    88 MORE-KUNDE          VALUE "N".

01 EOF-KONTI                PIC X VALUE "N".
    88 END-KONTI            VALUE "Y".
    88 MORE-KONTI          VALUE "N".

01 FULDT-NAVN              PIC X(40) VALUE SPACES.
01 ADR-LINJE1              PIC X(60) VALUE SPACES.
01 ADR-LINJE2              PIC X(40) VALUE SPACES.

*> Array til konti på 01 niveau
01 KONTO-ARRAY OCCURS 50 TIMES.
    COPY "KONTOOPL.cpy".

01 KONTO-COUNT              PIC 9(3) VALUE 0.
01 IX-KONTI                 PIC 9(3) VALUE 1.
```

```

PROCEDURE DIVISION.
MAIN-PROGRAM.
    *> Læs kontofilen ind i array
    OPEN INPUT KONTOFIL
    MOVE 1 TO KONTO-COUNT
    MOVE "N" TO EOF-KONTI
    PERFORM UNTIL END-KONTI
        READ KONTOFIL
        AT END
            SET END-KONTI TO TRUE
        NOT AT END
            MOVE KONTO-REKORD TO KONTO-ARRAY(KONTO-COUNT)
            ADD 1 TO KONTO-COUNT
    END-READ
    END-PERFORM
    CLOSE KONTOFIL

    OPEN INPUT KUNDEFIL
    OPEN OUTPUT OUT-FIL

    *> Læs kunder og match med konti i array
    PERFORM UNTIL END-KUNDE
        READ KUNDEFIL
        AT END
            SET END-KUNDE TO TRUE
        NOT AT END
            PERFORM FORMAT-NAVN
            PERFORM FORMAT-VEJ
            PERFORM FORMAT-BY
            PERFORM SKRIV-KUNDE
            PERFORM MATCH-KONTI
            *> blank linje
            MOVE SPACES TO OUTPUT-TEXT
            WRITE OUT-REKORD
    END-READ
    END-PERFORM

    CLOSE KUNDEFIL
    CLOSE OUT-FIL
    STOP RUN.

*> -----
*> Formateringsparagraffer
FORMAT-NAVN.
    STRING FORNAVN OF KUNDE-REKORD DELIMITED BY SPACE
        " " DELIMITED BY SIZE
        EFTERNAVN OF KUNDE-REKORD DELIMITED BY SPACE

```

```
        INTO FULDT-NAVN
    END-STRING
    EXIT.
```

FORMAT-VEJ.

```
    STRING VEJNAVN OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        " " HUSNR OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        " " ETAGE OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        " " SIDE OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
    INTO ADR-LINJE1
    END-STRING
    EXIT.
```

FORMAT-BY.

```
    STRING POSTNR OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
        " " BY-X OF ADRESSE OF KUNDE-REKORD DELIMITED BY SIZE
    INTO ADR-LINJE2
    END-STRING
    EXIT.
```

SKRIV-KUNDE.

```
    MOVE SPACES TO OUTPUT-TEXT
    STRING "Kunde-ID: " KUNDE-ID OF KUNDE-REKORD
        DELIMITED BY SIZE
        " | Navn: " FULDT-NAVN DELIMITED BY SIZE
    INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD
```

```
    MOVE SPACES TO OUTPUT-TEXT
    STRING "Adresse: " ADR-LINJE1 DELIMITED BY SIZE
        ", " ADR-LINJE2 DELIMITED BY SIZE
    INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD
```

```
    MOVE SPACES TO OUTPUT-TEXT
    STRING "Tlf: " TELEFON OF KONTAKTINFO OF KUNDE-REKORD
        DELIMITED BY SIZE
        " | Email: " EMAIL OF KONTAKTINFO OF KUNDE-REKORD
        DELIMITED BY SIZE
    INTO OUTPUT-TEXT
    END-STRING
    WRITE OUT-REKORD
    EXIT.
```

MATCH-KONTI.

```
    PERFORM VARYING IX-KONTI FROM 1 BY 1 UNTIL IX-KONTI >=
```

```
KONTO-COUNT
  IF KUNDE-ID OF KONTO-ARRAY(IX-KONTI) = KUNDE-ID OF
    KUNDE-REKORD
    MOVE SPACES TO OUTPUT-TEXT
    STRING "    Konto-ID: " KONTO-ID OF
      KONTO-ARRAY(IX-KONTI) DELIMITED BY SIZE
      " | Type: " KONTO-TYPE OF
      KONTO-ARRAY(IX-KONTI) DELIMITED BY SIZE
      " | Saldo: " BALANCE OF
      KONTO-ARRAY(IX-KONTI) DELIMITED BY SIZE
      " " VALUTA-KD OF
      KONTO-ARRAY(IX-KONTI) DELIMITED BY SIZE
    INTO OUTPUT-TEXT
  END-STRING
  WRITE OUT-REKORD
END-IF
END-PERFORM
EXIT.
```