

The background features abstract, low-poly geometric shapes in shades of blue and green, resembling stylized trees or crystalline structures. A solid red horizontal banner spans the middle of the image, containing the chapter title in white text. To the right of the red banner, there is a small blue rectangular area.

Chap 5. Trees (3)

Contents

5.1 Introduction

5.2 Binary Trees

5.3 Binary Trees Traversals

5.4 Additional Binary Tree Operations

5.5 Threaded Binary Trees

5.6 Heaps

5.7 Binary Search Trees

5.8 Selection Trees

5.4 Additional Binary Tree Operations

5.4.1 Copying Binary trees

❖ A slightly modified version of *postorder* traversal

```
treePointer copy(treePointer original)
{/* this function returns a treePointer to an exact copy
   of the original tree */
treePointer temp;
if (original) {
    MALLOC(temp, sizeof(*temp));
    temp→leftChild = copy(original→leftChild);
    temp→rightChild = copy(original→rightChild);
    temp→data = original→data;
    return temp;
}
return NULL;
}
```

Program 5.6: Copying a binary tree

The diagram illustrates the execution of a program on a 3-processor system. The program consists of five instructions: ori_1 , ori_2 , ori_3 , ori_4 , and $temp_1$. The execution flow is shown as a tree structure. ori_1 points to a node with 'A'. This node points to ori_2 (node with 'B') and a node with '0 C 0'. ori_2 points to ori_3 (node with '0 D 0') and ori_4 (node with '0 E 0'). $temp_1$ points to a node with three empty slots. $temp_2$ points to a node with three empty slots. $temp_3$ points to a node with '0' in the first slot and two empty slots.


[illegible]

	temp ₃	xxx
copy() ₃	ori ₃	xxx
	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

	temp ₄	
copy() ₄	ori ₄	0
	temp ₃	xxx
copy() ₃	ori ₃	xxx
	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

	temp ₃	xxx
copy() ₃	ori ₃	xxx
	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

```
treePointer copy(treePointer original)
{
    treePointer temp;
    if (original) {
        MALLOC(temp, sizeof(*temp));
        temp->leftChild = copy(original->leftChild);
        temp->rightChild = copy(original->rightChild);
        temp->data = original->data;
        return temp;
    }
    return NULL;
}
```



temp ₅		
copy() ₅	ori ₅	0
temp ₃	xxx	
copy() ₃	ori ₃	xxx
temp ₂	xxx	
copy() ₂	ori ₂	xxx
temp ₁	xxx	
copy() ₁	ori ₁	xxx

temp ₃	xxx	
copy() ₃	ori ₃	xxx
temp ₂	xxx	
copy() ₂	ori ₂	xxx
temp ₁	xxx	
copy() ₁	ori ₁	xxx


temp ₂	xxx	
copy() ₂	ori ₂	xxx
temp ₁	xxx	
copy() ₁	ori ₁	xxx

temp ₆	xxx	
copy() ₆	ori ₆	xxx
temp ₂	xxx	
copy() ₂	ori ₂	xxx
temp ₁	xxx	
copy() ₁	ori ₁	xxx

temp ₇		
copy() ₇	ori ₇	0
temp ₆	xxx	
copy() ₆	ori ₆	xxx
temp ₂	xxx	
copy() ₂	ori ₂	xxx
temp ₁	xxx	
copy() ₁	ori ₁	xxx

```
treePointer copy(treePointer original)
```

```
{
  treePointer temp;
  if (original) {
    MALLOC(temp, sizeof(*temp));
    temp->leftChild = copy(original->leftChild);
    temp->rightChild = copy(original->rightChild);
    temp->data = original->data;
    return temp;
  }
  return NULL;
}
```



	temp ₆	xxx
copy() ₆	ori ₆	xxx
	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx


		temp ₈
copy() ₈	ori ₈	0
	temp ₆	xxx
copy() ₆	ori ₆	xxx
	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

	temp ₆	xxx
copy() ₆	ori ₆	xxx
	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

	temp ₂	xxx
copy() ₂	ori ₂	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

		temp ₁
copy() ₁	ori ₁	xxx

```
treePointer copy(treePointer original)
{
    treePointer temp;
    if (original) {
        MALLOC(temp, sizeof(*temp));
        temp->leftChild = copy(original->leftChild);
        temp->rightChild = copy(original->rightChild);
        temp->data = original->data;
        return temp;
    }
    return NULL;
}
```


[illegible]

	temp ₉	xxx
copy() ₉	ori ₉	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

	temp ₁₁	xxx
copy() ₁₁	ori ₁₁	0
	temp ₉	xxx
copy() ₉	ori ₉	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

	temp ₉	xxx
copy() ₉	ori ₉	xxx
	temp ₁	xxx
copy() ₁	ori ₁	xxx

```
{
    treePointer temp;
    if (original) {
        MALLOC(temp, sizeof(*temp));
        temp->leftChild = copy(original->leftChild);
        temp->rightChild = copy(original->rightChild);
        temp->data = original->data;
        return temp;
    }
    return NULL;
}
```

[illegible]

5.4 Additional Binary Tree Operations

5.4.2 Testing Equality

- ❖ Determining the equivalence of two binary trees
- ❖ Equivalent binary trees have the *same structure* and the *same information* in the corresponding nodes.
- ❖ A modification of *preorder* traversal

```
int equal(treePointer first, treePointer second)
{
    /* function returns FALSE if the binary trees first and
       second are not equal, Otherwise it returns TRUE */
    return ((!first && !second) || (first && second &&
        (first->data == second->data) &&
        equal(first->leftChild, second->leftChild) &&
        equal(first->rightChild, second->rightChild)))
}
```

Program 5.7: Testing for equality of binary trees

5.4.3 The Satisfiability Problem

- ❖ Consider the set of formulas from $\{x_1, \dots, x_n\}$ and $\{\wedge \text{ (and)}, \vee \text{ (or)}, \neg \text{ (not)}\}$
- ❖ The *variables* are **Boolean variables**
 - Have only two possible values, *true* or *false*
- ❖ Set of expressions are defined by the following rules
 - A variable is an expression
 - If x and y are expression, then $\neg x$, $x \wedge y$, $x \vee y$ are expressions
 - Parentheses can be used to alter the normal order of evaluation
- ❖ formula of propositional calculus : $x_1 \vee (x_2 \wedge \neg x_3)$
 - If x_1 and x_3 are *false* and x_2 is *true*, it is *true*

5.4.3 The Satisfiability Problem

❖ *The satisfiability problem*

- Is there an assignment of values to the variables that causes the value of the expression to be true?

❖ **The most obvious algorithm**

- let (x_1, \dots, x_n) take on **all possible combinations of *true* and *false* values** and to check the formula for each combination
 - $O(g 2^n)$, or exponential time, where g is the time to substitute values for x_1, x_2, \dots, x_n and evaluate the expression.
- ***Postorder*** evaluation

5.4.3 The Satisfiability Problem

$$\clubsuit (x_1 \wedge \neg x_2) \vee (\neg x_1 \wedge x_3) \vee \neg x_3$$




Figure 5.18: Propositional formula in a binary tree

For $n = 3$,
All possible combinations
of *true* = t , *false* = f
 $(t, t, t), (t, t, f), (t, f, t), (t, f, f)$
 $(f, t, t), (f, t, f), (f, f, t), (f, f, f)$

5.4.3 The Satisfiability Problem

<i>leftChild</i>	<i>data</i>	<i>value</i>	<i>rightChild</i>
------------------	-------------	--------------	-------------------

```
typedef enum {not,and,or,true,false}  
logical;  
typedef struct node *treePointer;  
typedef struct node {  
    treePointer leftChild;  
    logical data;  
    short int value;  
    treePointer rightChild;  
};
```




Figure 5.18: Propositional formula in a binary tree

```
for (all  $2^n$  possible combinations) {  
    generate the next combination;  
    replace the variables by their values;  
    evaluate root by traversing it in  
    postorder;  
    if (root->value) {  
        printf(<combination>);  
        return;  
    }  
}  
printf("No satisfiable combination\n");
```


Program 5.8: First version of satisfiability algorithm

```

void postOrderEval(treePointer node)
{
    /* modified post order traversal to evaluate a
       propositional calculus tree */
    if (node) {
        postOrderEval(node->leftChild);
        postOrderEval(node->rightChild);
        switch(node->data) {
            case not:    node->value =
                        !node->rightChild->value;
                        break;
            case and:    node->value =
                        node->rightChild->value &&
                        node->leftChild->value;
                        break;
            case or:     node->value =
                        node->rightChild->value ||
                        node->leftChild->value;
                        break;
            case true:   node->value = TRUE;
                        break;
            case false:  node->value = FALSE;
                        break;
        }
    }
}

```

Program 5.9: Postorder evaluation function




ex) for a combination
 $(x_1, x_2, x_3) = (t, f, t)$

not/and/or in the data
 field of non-leaf nodes

true/false in the data
 field of leaf nodes, x_1 ,
 x_2 , and x_3


5.5 Threaded Binary Trees

- ❖ In a linked representation of a binary tree, the number of null links (null pointers) are actually more than non-null pointers.
- ❖ Consider the following binary tree:



A Binary tree with the null pointers

5.5 Threaded Binary Trees



A Binary tree with the null pointers

- ❖ In above binary tree, there are 7 null pointers & actual 5 pointers.
- ❖ In all there are 12 pointers.
- ❖ We can generalize it that for any binary tree with n nodes there will be $(n+1)$ null pointers and $2n$ total pointers.
- ❖ The objective here to make effective use of these null pointers.
- ❖ to replace all the null pointers by the appropriate pointer values called threads.

5.5 Threaded Binary Trees

Construct the threads

(1) If *leftChild* is null, replace *leftChild* with a pointer to the node that would be visited before *ptr* in an inorder traversal.

That is we replace the null link with a pointer to the *inorder predecessor* of *ptr*.

(2) If *rightChild* is null, replace *rightChild* with a pointer to the node that would be visited after *ptr* in an inorder traversal.

That is we replace the null link with a pointer to the *inorder successor* of *ptr*.

5.51. Threads




Figure 5.21: Threaded tree corresponding to Figure 5.10(b)

```
typedef struct threadedTree *threadedPointer;
typedef struct threadedTree {
    short int leftThread;
    threadedPointer leftChild;
    char data;
    threadedPointer rightChild;
    short int rightThread;
} ;
```

5.5.1. Threads

- ❖ An empty binary tree is represented by its header node as in Figure 5.22




Figure 5.22: An empty threaded binary tree

5.5.1. Threads




Figure 5.23: Memory representation of threaded tree

5.5.2. Inorder Traversal of a Threaded Binary Tree

- ❖ By using the threads, we can perform an inorder traversal without making use of a stack.
- ❖ The succfunction *insucc* finds the inorder essor of any node in a threaded tree without using a stack.

```

threadedPointer insucc(threadedPointer tree)
/* find the inorder successor of tree in a threaded binary
   tree */
threadedPointer temp;
temp = tree->rightChild;
if (!tree->rightThread)
    while (!temp->leftThread)
        temp = temp->leftChild;
return temp;
}

```

Program 5.10: Finding the inorder successor of a node




Figure 5.23: Memory representation of threaded tree

5.5.2. Inorder Traversal of a Threaded Binary Tree

```
void tinorder(threadedPointer tree)  
{/* traverse the threaded binary tree  
inorder */
```

```

    threadedPointer temp = tree;
    for (;;) {
        temp= insucc(temp);
        if (temp == tree) break;
        printf("%3c", temp->data);
    }

```

}

Program 5.11: Inorder traversal of a threaded binary tree




Figure 5.23: Memory representation of threaded tree

5.5.3 Inserting a Node into a Threaded Binary Tree




Figure 5.24: Insertion of r as a right child of s in a threaded binary tree

5.5.3 Inserting a Node into a Threaded Binary Tree

```
void insertRight(threadedPointer s,  
threadedPointer r)  
{ /* insert r as the right child of s */  
    threadedPointer temp;  
    r->rightChild = parent->rightChild;  
    r->rightThread = parent->rightThread;  
    r->leftChild = parent;  
    r->leftThread = TRUE;  
    s->rightChild = child;  
    s->rightThread = FALSE;  
    if (! r->rightThread) {  
        temp= insucc(r);  
        temp->leftChild = r;  
    }  
}
```

Program 5.12: Right insertion in a threaded binary tree

