

# PVsyst - Simulation report

## Grid-Connected System

Project: Saha Farm

Variant: 03

No 3D scene defined, no shadings

System power: 1001 kWp

Ban Noen Sawang - Thailand

Author

**PVsyst V7.4.6**

VC2, Simulation date:  
05/01/24 20:44  
with V7.4.6

**Project summary****Geographical Site****Ban Noen Sawang**

Thailand

**Situation**

Latitude 16.15 °N

Longitude 101.12 °E

Altitude 90 m

Time zone UTC+7

**Project settings**

Albedo 0.20

**Weather data**

Ban Noen Sawang

Meteonorm 8.1 (1996-2015), Sat=100% - Synthetic

**System summary****Grid-Connected System****No 3D scene defined, no shadings****PV Field Orientation**

Fixed planes 2 orientations

Tilts/azimuths 20 / -25 °

20 / 155 °

**Near Shadings**

No Shadings

**User's needs**

Unlimited load (grid)

**System information****PV Array**

Nb. of modules

1440 units

Pnom total

1001 kWp

**Inverters**

Nb. of units

9 units

Pnom total

900 kWac

Pnom ratio

1.112

**Results summary**

Produced Energy	1219674 kWh/year	Specific production	1219 kWh/kWp/year	Perf. Ratio PR	75.01 %
-----------------	------------------	---------------------	-------------------	----------------	---------

**Table of contents**

Project and results summary	2
General parameters, PV Array Characteristics, System losses	3
Main results	4
Loss diagram	5
Predef. graphs	6
Single-line diagram	7



## PVsyst V7.4.6

VC2, Simulation date:  
05/01/24 20:44  
with V7.4.6

## General parameters

## Grid-Connected System

No 3D scene defined, no shadings

## PV Field Orientation

## Orientation

Fixed planes 2 orientations  
Tilts/azimuths 20 / -25 °  
20 / 155 °

## Sheds configuration

No 3D scene defined

## Models used

Transposition Perez  
Diffuse Perez, Meteonorm  
Circumsolar separate

## Horizon

Free Horizon

## Near Shadings

No Shadings

## User's needs

Unlimited load (grid)

## PV Array Characteristics

## PV module

Manufacturer

Generic

Model

CS7N-695TB-AG 1500V

(Original PVsyst database)

Unit Nom. Power

695 Wp

Number of PV modules

1440 units

Nominal (STC)

1001 kWp

Modules

90 string x 16 In series

## At operating cond. (50°C)

Pmpp

928 kWp

U mpp

585 V

I mpp

1586 A

## Total PV power

Nominal (STC)

1001 kWp

Total

1440 modules

Module area

4473 m<sup>2</sup>

## Inverter

Manufacturer

Generic

Model

SUN2000-100KTL-M1-400Vac

(Original PVsyst database)

Unit Nom. Power

100 kWac

Number of inverters

9 units

Total power

900 kWac

Operating voltage

200-1000 V

Max. power (=&gt;33°C)

110 kWac

Pnom ratio (DC:AC)

1.11

Power sharing within this inverter

## Total inverter power

Total power

900 kWac

Max. power

990 kWac

Number of inverters

9 units

Pnom ratio

1.11

## Array losses

## Array Soiling Losses

Loss Fraction 7.3 %

## Thermal Loss factor

Module temperature according to irradiance

Uc (const)

20.0 W/m<sup>2</sup>K

Uv (wind)

0.0 W/m<sup>2</sup>K/m/s

## DC wiring losses

Global array res.

6.0 mΩ

Loss Fraction

1.5 % at STC

## LID - Light Induced Degradation

Loss Fraction 3.0 %

## Module Quality Loss

Loss Fraction 2.0 %

## Module mismatch losses

Loss Fraction 2.0 % at MPP

## IAM loss factor

Incidence effect (IAM): Fresnel, AR coating, n(glass)=1.526, n(AR)=1.290

0°	30°	50°	60°	70°	75°	80°	85°	90°
1.000	0.999	0.987	0.962	0.892	0.816	0.681	0.440	0.000



## PVsyst V7.4.6

VC2, Simulation date:  
05/01/24 20:44  
with V7.4.6

## Main results

## System Production

Produced Energy 1219674 kWh/year


Specific production

1219 kWh/kWp/year


Perf. Ratio PR

75.01 %

Normalized productions (per installed kWp)



Performance Ratio PR



## Balances and main results

	GlobHor	DiffHor	T_Amb	GlobInc	GlobEff	EArray	E_Grid	PR
	kWh/m <sup>2</sup>	kWh/m <sup>2</sup>	°C	kWh/m <sup>2</sup>	kWh/m <sup>2</sup>	kWh	kWh	ratio
January	129.6	57.53	24.75	125.3	112.2	95851	94047	0.750
February	125.4	70.59	26.97	121.0	109.0	92626	90876	0.750
March	158.9	88.64	29.15	153.2	138.6	116498	114237	0.745
April	165.7	92.19	29.92	159.7	144.7	121548	119174	0.746
May	155.3	84.75	29.33	149.2	134.9	113704	111484	0.746
June	160.8	78.68	28.43	154.7	139.9	118264	115946	0.749
July	140.4	88.22	28.19	135.1	121.8	103788	101820	0.753
August	137.5	78.98	27.68	132.2	119.5	101669	99693	0.753
September	142.7	82.60	27.18	137.3	124.0	105585	103570	0.754
October	131.9	74.78	27.63	127.0	114.5	97343	95474	0.751
November	113.1	69.12	26.24	108.9	97.7	83767	82219	0.754
December	125.2	63.02	24.96	121.0	108.2	92841	91135	0.753
Year	1686.6	929.10	27.54	1624.6	1464.9	1243484	1219674	0.750

## Legends

GlobHor Global horizontal irradiation

DiffHor Horizontal diffuse irradiation

T\_Amb Ambient Temperature

GlobInc Global incident in coll. plane

GlobEff Effective Global, corr. for IAM and shadings

EArray Effective energy at the output of the array

E\_Grid Energy injected into grid



PR Performance Ratio



**PVsyst V7.4.6**

VC2, Simulation date:  
05/01/24 20:44  
with V7.4.6

**Loss diagram**



**Global horizontal irradiation**

**Global incident in coll. plane**

IAM factor on global

Soiling loss factor

**Effective irradiation on collectors**

PV conversion

**Array nominal energy (at STC eff.)**

PV loss due to irradiance level

PV loss due to temperature

Module quality loss

LID - Light induced degradation

Module array mismatch loss

Ohmic wiring loss

Mixed orientation mismatch loss

**Array virtual energy at MPP**

Inverter Loss during operation (efficiency)

Inverter Loss over nominal inv. power

Inverter Loss due to max. input current

Inverter Loss over nominal inv. voltage

Inverter Loss due to power threshold

Inverter Loss due to voltage threshold

Night consumption

**Available Energy at Inverter Output**

Energy injected into grid




**PVsyst V7.4.6**


VC2, Simulation date:  
05/01/24 20:44  
with V7.4.6

**Predef. graphs**

**Daily Input/Output diagram**



**System Output Power Distribution**





**PVsyst V7.4.6**

VC2, Simulation date:  
05/01/24 20:44  
with V7.4.6

e-line diagram not available