■ HackerRank | Prepare Certify Compete Apply Q Search □ □ □ □ □

All Contests > utp-open-2018 > The Book Thie

# The Book Thief

ons	
-----	--

On February 18, 2014, Red Matemática proposed the following mathematical challenge on their twitter account (@redmatematicant): "While Anita read: *The book thief* by Markus Zusak, She added all the page numbers starting from 1. When she finished the book, she got a sum equal to 9.000 but she realized that one page number was forgotten in the process. What is such number? and, how many pages does the book have?"

Using this interesting puzzle as our starting point, the problem you are asked to solve now is: Given a positive integer s ( $1 \le s \le 10^8$ ) representing the result obtained by Anita, find out the number of the forgotten page and the total number of pages in the book.

### **Input Format**

The input begins with a positive integer t ( $1 \le t \le 10^6$ ), denoting the number of test cases.

Each test case is presented on a single line, and contains one positive integer s.

#### **Constraints**

 $1 \le t \le 10^6$ 

 $1 \le s \le 10^8$ 

## **Output Format**

For each test case, your program must print two positive integers, separated by a space, denoting the number of the forgotten page and the total number pages in the book. Each valid test case must generate just one output line.

## Sample Input 0

9 1

2

3

5 6

9000

499977

49999775

## Sample Output 0

5225 10000

f in

Submissions: 162

Max Score: 100

Difficulty: Medium

Rate This Challenge:

ななななな

C

```
1 #include <stdio.h>
  #include <string.h>
  #include <math.h>
  #include <stdlib.h>
  int main() {
      /* Enter your code here. Read input from STDIN. Print output to STDOUT */
      int totalCases, idCase, s, totalPages, forgottenPage, page, triangular;
      scanf("%d", &totalCases);
      for(idCase = 1; idCase <= totalCases; idCase++)</pre>
           scanf("%d", &s);
           page = (-1 + sqrt(1 + 8 * s)) / 2;
           triangular = (page * (page + 1)) / 2;
           if(s == triangular)
           {
               totalPages = page + 1;
               forgottenPage = page + 1;
           }
           else
           {
               page++;
               triangular = (page * (page + 1)) / 2;
               forgottenPage = triangular - s;
               totalPages = page;
           }
           printf("%d %d\n", forgottenPage, totalPages);
      return 0;
  }
                                                                                             Line: 1 Col: 1
```

<u>La Upload Code as File</u> Test against custom input

Run Code

Submit Code

Interview Prep | Blog | Scoring | Environment | FAQ | About Us | Support | Careers | Terms Of Service | Privacy Policy |