

There's a newer version of Bootstrap!

[Ctrl + /](#)

v5.1 ▾

[View on GitHub](#)

Checks and radios

Create consistent cross-browser and cross-device checkboxes and radios with our completely rewritten checks component.



Design and Development
tips in your inbox. Every
weekday.

ads via Carbon

On this page

[Approach](#)[Checks](#)[Indeterminate](#)[Disabled](#)[Radios](#)[Disabled](#)[Switches](#)[Default \(stacked\)](#)[Inline](#)[Without labels](#)[Toggle buttons](#)[Checkbox toggle buttons](#)[Radio toggle buttons](#)[Outlined styles](#)[Sass](#)[Variables](#)

Approach

Browser default checkboxes and radios are replaced with the help of `.form-check`, a series of classes for both input types that improves the layout and behavior of their HTML elements, that provide greater customization and cross browser consistency. Checkboxes are for selecting one or several options in a list, while radios are for selecting one option from many.

Structurally, our `<input>`s and `<label>`s are sibling elements as opposed to an `<input>` within a `<label>`. This is slightly more verbose as you must specify `id` and `for` attributes to relate the `<input>` and `<label>`. We use the sibling selector (`~`) for all our `<input>` states, like `:checked` or `:disabled`. When combined with the `.form-check-label` class, we can easily style the text for each item based on the `<input>`'s state.

Our checks use custom Bootstrap icons to indicate checked or indeterminate states.

Checks

- ☐ Default checkbox
- ☒ Checked checkbox

```
<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="flexCheckDefault">
  <label class="form-check-label" for="flexCheckDefault">
    Default checkbox
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="flexCheckChecked" checked="">
  <label class="form-check-label" for="flexCheckChecked">
    Checked checkbox
  </label>
</div>
```

Indeterminate

Checkboxes can utilize the `:indeterminate` pseudo class when manually set via JavaScript (there is no available HTML attribute for specifying it).

- ☐ Indeterminate checkbox

```
<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="flexCheckIndeterminat
  <label class="form-check-label" for="flexCheckIndeterminate">
    Indeterminate checkbox
  </label>
</div>
```

Disabled

Add the `disabled` attribute and the associated `<label>`s are automatically styled to match with a lighter color to help indicate the input's state.

☐ Disabled checkbox

☒ Disabled checked checkbox

```
<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="flexCheckDisabled" di
  <label class="form-check-label" for="flexCheckDisabled">
    Disabled checkbox
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="flexCheckCheckedDisab
  <label class="form-check-label" for="flexCheckCheckedDisabled">
    Disabled checked checkbox
  </label>
</div>
```

Radios

☐ Default radio

☒ Default checked radio

```
<div class="form-check">
  <input class="form-check-input" type="radio" name="flexRadioDefault" id="flexRadio
  <label class="form-check-label" for="flexRadioDefault1">
```

```

    Default radio
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="radio" name="flexRadioDefault" id="flexRadio
  <label class="form-check-label" for="flexRadioDefault2">
    Default checked radio
  </label>

```

Disabled

Add the `disabled` attribute and the associated `<label>`s are automatically styled to match with a lighter color to help indicate the input's state.

☐ Disabled radio

☒ Disabled checked radio

```

<div class="form-check">
  <input class="form-check-input" type="radio" name="flexRadioDisabled" id="flexRadi
  <label class="form-check-label" for="flexRadioDisabled">
    Disabled radio
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="radio" name="flexRadioDisabled" id="flexRadi
  <label class="form-check-label" for="flexRadioCheckedDisabled">
    Disabled checked radio
  </label>
</div>

```

Switches

A switch has the markup of a custom checkbox but uses the `.form-switch` class to render a toggle switch. Consider using `role="switch"` to more accurately convey the nature of the control to assistive technologies that support this role. In older assistive technologies, it will simply be announced as a regular checkbox as a fallback. Switches also support the `disabled` attribute.

☐ Default switch checkbox input

☒ Checked switch checkbox input

☐ Disabled switch checkbox input

☒ Disabled checked switch checkbox input

```

<div class="form-check form-switch">
  <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckD
  <label class="form-check-label" for="flexSwitchCheckDefault">Default switch checkb
</div>
<div class="form-check form-switch">
  <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckC
  <label class="form-check-label" for="flexSwitchCheckChecked">Checked switch checkb
</div>
<div class="form-check form-switch">
  <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckD
  <label class="form-check-label" for="flexSwitchCheckDisabled">Disabled switch chec
</div>
<div class="form-check form-switch">
  <input class="form-check-input" type="checkbox" role="switch" id="flexSwitchCheckC
  <label class="form-check-label" for="flexSwitchCheckCheckedDisabled">Disabled chec
</div>

```

Default (stacked)

By default, any number of checkboxes and radios that are immediate sibling will be vertically stacked and appropriately spaced with `.form-check`.

☐ Default checkbox

☐ Disabled checkbox

```

<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="defaultCheck1">
  <label class="form-check-label" for="defaultCheck1">
    Default checkbox
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="checkbox" value="" id="defaultCheck2" disabl
  <label class="form-check-label" for="defaultCheck2">
    Disabled checkbox

```

```
</label>
</div>
```

- ☒ Default radio
- ☐ Second default radio
- ☐ Disabled radio

```
<div class="form-check">
  <input class="form-check-input" type="radio" name="exampleRadios" id="exampleRadio
  <label class="form-check-label" for="exampleRadios1">
    Default radio
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="radio" name="exampleRadios" id="exampleRadio
  <label class="form-check-label" for="exampleRadios2">
    Second default radio
  </label>
</div>
<div class="form-check">
  <input class="form-check-input" type="radio" name="exampleRadios" id="exampleRadio
  <label class="form-check-label" for="exampleRadios3">
    Disabled radio
  </label>
</div>
```

Inline

Group checkboxes or radios on the same horizontal row by adding `.form-check-inline` to any `.form-check`.

☐ 1 ☐ 2 ☐ 3 (disabled)

```
<div class="form-check form-check-inline">
  <input class="form-check-input" type="checkbox" id="inlineCheckbox1" value="option
  <label class="form-check-label" for="inlineCheckbox1">1</label>
</div>
<div class="form-check form-check-inline">
```

```

<input class="form-check-input" type="checkbox" id="inlineCheckbox2" value="option
<label class="form-check-label" for="inlineCheckbox2">2</label>
</div>
<div class="form-check form-check-inline">
  <input class="form-check-input" type="checkbox" id="inlineCheckbox3" value="option
  <label class="form-check-label" for="inlineCheckbox3">3 (disabled)</label>

```

```

<div class="form-check form-check-inline">
  <input class="form-check-input" type="radio" name="inlineRadioOptions" id="inlineR
  <label class="form-check-label" for="inlineRadio1">1</label>
</div>
<div class="form-check form-check-inline">
  <input class="form-check-input" type="radio" name="inlineRadioOptions" id="inlineR
  <label class="form-check-label" for="inlineRadio2">2</label>
</div>
<div class="form-check form-check-inline">
  <input class="form-check-input" type="radio" name="inlineRadioOptions" id="inlineR
  <label class="form-check-label" for="inlineRadio3">3 (disabled)</label>
</div>

```

Without labels

Omit the wrapping `.form-check` for checkboxes and radios that have no label text. Remember to still provide some form of accessible name for assistive technologies (for instance, using `aria-label`). See the [forms overview accessibility](#) section for details.

```

<div>
  <input class="form-check-input" type="checkbox" id="checkboxNoLabel" value="" aria
</div>

<div>

```

```
<input class="form-check-input" type="radio" name="radioNoLabel" id="radioNoLabel1">  
</div>
```

Toggle buttons

Create button-like checkboxes and radio buttons by using `.btn` styles rather than `.form-check-label` on the `<label>` elements. These toggle buttons can further be grouped in a [button group](#) if needed.

Checkbox toggle buttons



```
<input type="checkbox" class="btn-check" id="btn-check" autocomplete="off">  
<label class="btn btn-primary" for="btn-check">Single toggle</label>
```



```
<input type="checkbox" class="btn-check" id="btn-check-2" checked="" autocomplete="off">  
<label class="btn btn-primary" for="btn-check-2">Checked</label>
```



```
<input type="checkbox" class="btn-check" id="btn-check-3" autocomplete="off" disabled="">  
<label class="btn btn-primary" for="btn-check-3">Disabled</label>
```


Visually, these checkbox toggle buttons are identical to the [button plugin toggle buttons](#). However, they are conveyed differently by assistive technologies: the checkbox toggles will be announced by screen readers as “checked”/“not checked” (since, despite their appearance, they are fundamentally still checkboxes), whereas the button plugin toggle buttons will be announced as “button”/“button pressed”. The choice between these two approaches will depend on the type of toggle you are creating, and whether or not the toggle will make sense to users when announced as a checkbox or as an actual button.

Radio toggle buttons



```
<input type="radio" class="btn-check" name="options" id="option1" autocomplete="off"
<label class="btn btn-secondary" for="option1">Checked</label>
```


```
<input type="radio" class="btn-check" name="options" id="option2" autocomplete="off"
<label class="btn btn-secondary" for="option2">Radio</label>
```

```
<input type="radio" class="btn-check" name="options" id="option3" autocomplete="off"
<label class="btn btn-secondary" for="option3">Disabled</label>
```

```
<input type="radio" class="btn-check" name="options" id="option4" autocomplete="off"
<label class="btn btn-secondary" for="option4">Radio</label>
```

Outlined styles

Different variants of `.btn`, such as the various outlined styles, are supported.



```

<input type="checkbox" class="btn-check" id="btn-check-outlined" autocomplete="off">
<label class="btn btn-outline-primary" for="btn-check-outlined">Single toggle</label>

<input type="checkbox" class="btn-check" id="btn-check-2-outlined" checked="" autocomplete="off">
<label class="btn btn-outline-secondary" for="btn-check-2-outlined">Checked</label><

<input type="radio" class="btn-check" name="options-outlined" id="success-outlined" checked="">
<label class="btn btn-outline-success" for="success-outlined">Checked success radio</label>

<input type="radio" class="btn-check" name="options-outlined" id="danger-outlined" checked="">
<label class="btn btn-outline-danger" for="danger-outlined">Danger radio</label>

```

Sass

Variables

\$form-check-input-width:	1em;
\$form-check-min-height:	\$font-size-base * \$line-height-base;
\$form-check-padding-start:	\$form-check-input-width + .5em;
\$form-check-margin-bottom:	.125rem;
\$form-check-label-color:	null;
\$form-check-label-cursor:	null;
\$form-check-transition:	null;
 \$form-check-input-active-filter:	 brightness(90%);
 \$form-check-input-bg:	 \$input-bg;
\$form-check-input-border:	1px solid rgba(\$black, .25);
\$form-check-input-border-radius:	.25em;
\$form-check-radio-border-radius:	50%;
\$form-check-input-focus-border:	\$input-focus-border-color;
\$form-check-input-focus-box-shadow:	\$input-btn-focus-box-shadow;
 \$form-check-input-checked-color:	 \$component-active-color;
\$form-check-input-checked-bg-color:	\$component-active-bg;
\$form-check-input-checked-border-color:	\$form-check-input-checked-bg-color;
\$form-check-input-checked-bg-image:	url("data:image/svg+xml,<svg xmlns='http:// url("data:image/svg+xml,<svg xmlns='http://
 \$form-check-input-indeterminate-color:	 \$component-active-color;
\$form-check-input-indeterminate-bg-color:	\$component-active-bg;
\$form-check-input-indeterminate-border-color:	\$form-check-input-indeterminate-bg-c
\$form-check-input-indeterminate-bg-image:	url("data:image/svg+xml,<svg xmlns='

```
$form-check-input-disabled-opacity: .5;  
$form-check-label-disabled-opacity: $form-check-input-disabled-opacity;  
$form-check-btn-check-disabled-opacity: $btn-disabled-opacity;
```



Designed and built with all the love in the world by the Bootstrap team with the help of our contributors.

Code licensed MIT, docs CC BY 3.0.

Currently v5.1.3.

Analytics by Fathom.

Links

[Home](#)

[Docs](#)

[Examples](#)

[Themes](#)

[Blog](#)

[Swag Store](#)

Guides

[Getting started](#)

[Starter template](#)

[Webpack](#)

[Parcel](#)

Projects

[Bootstrap 5](#)

[Bootstrap 4](#)

[Icons](#)

[RFS](#)

[npm starter](#)

Community

[Issues](#)

[Discussions](#)

[Corporate sponsors](#)

[Open Collective](#)

[Stack Overflow](#)