



CODIGO DE IURIS

Código base – capa aplicación – proyecto
IURIS.MOVIL.Android

DESCRIPCIÓN BREVE

Se muestra el código del proyecto IURIS.MOVIL.Android que representa la capa aplicación para la plataforma Android, donde podemos interactuar con una interfaz gráfica quien obtendrá los elementos necesarios para poder trabajar del proyecto IURIS.MOVIL ya que el proyecto es de tipo híbrido de tal forma que existe un código base del cual se toman los datos para compilar esta plataforma.

Juan Carlos Ortega Santiago

Desarrollador

Contenido

CustomEditorAndroid.cs	2
CustomEntryAndroid.cs.....	2
CustomLabelAndriod.cs.....	3
customLabelJust.cs	4
MainActivity.cs.....	5
NavigationRendered.cs	7
SplashScreen.cs.....	8
AndroidManifest.xml	8

CustomEditorAndroid.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;

using Android.App;
using Android.Content;
using Android.Graphics.Drawables;
using Android.OS;
using Android.Runtime;
using Android.Text;
using Android.Views;
using Android.Widget;
using IURIS.MOVIL.Droid;
using IURIS.MOVIL.Modelos_y_clases;
using Xamarin.Forms;
using Xamarin.Forms.Platform.Android;

[assembly: ExportRenderer(typeof(CustomEditor), typeof(CustomEditorAndroid))]

namespace IURIS.MOVIL.Droid
{
    public class CustomEditorAndroid : EditorRenderer
    {
        public CustomEditorAndroid(Context context) : base(context)
        {
        }

        protected override void
        OnElementChanged(ElementChangedEventArgs<Editor> e)
        {
            base.OnElementChanged(e);
            if (Control != null)
            {
                GradientDrawable gd = new GradientDrawable();
                gd.SetColor(global::Android.Graphics.Color.Transparent);
                Control.SetBackgroundDrawable(gd);

                //Control.JustificationMode = JustificationMode.InterWord;
            }
        }
    }
}
```

CustomEntryAndroid.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;
```

```

using Android.App;
using Android.Content;
using Android.Content.Res;
using Android.Graphics.Drawables;
using Android.OS;
using Android.Runtime;
using Android.Views;
using Android.Widget;
using IURIS.MOVIL.Droid;
using IURIS.MOVIL.Modelos_y_clases;
using Xamarin.Forms;
using Xamarin.Forms.Platform.Android;

[assembly: ExportRenderer(typeof(CustomEntry), typeof(CustomEntryAndroid))]

namespace IURIS.MOVIL.Droid
{
    public class CustomEntryAndroid:EntryRenderer
    {
        public CustomEntryAndroid(Context context) : base(context)
        {
        }

        protected override void OnElementChanged(ElementChangedEventArgs<Entry>
e)
        {
            base.OnElementChanged(e);
            if (Control != null)
            {
                GradientDrawable gd = new GradientDrawable();
                gd.SetColor(global::Android.Graphics.Color.Transparent);
                Control.SetBackgroundDrawable(gd);

                //Control.SetCursorVisible(true);
                //GradientDrawable g = new GradientDrawable();
                //g.SetColor(global::Android.Graphics.Color.Green);
                //Control.TextCursorDrawable = g;
                //Control.SetTextCursorDrawable(0);

                EditText nativeEditText =
(global::Android.Widget.EditText)Control;

                nativeEditText.SetTextCursorDrawable(Resource.Drawable.xml_file_name);

            }
        }
    }
}

```

CustomLabelAndriod.cs

```

using System;

```

```

using System.Collections.Generic;
using System.Linq;
using System.Text;

using Android.App;
using Android.Content;
using Android.OS;
using Android.Runtime;
using Android.Text;
using Android.Views;
using Android.Widget;
using IURIS.MOVIL.Droid;
using IURIS.MOVIL.Modelos_y_clases;
using Xamarin.Forms;
using Xamarin.Forms.Platform.Android;

[assembly:ExportRenderer(typeof(CustomLabel), typeof(CustomLabelAndriod))]
namespace IURIS.MOVIL.Droid
{
    public class CustomLabelAndriod:LabelRenderer
    {
        public CustomLabelAndriod(Context context):base(context)
        {
            //Control.JustificationMode = JustificationMode.InterWord;
        }
        protected override void OnElementChanged(ElementChangedEventArgs<Label>
e)
        {
            base.OnElementChanged(e);
            if (Control != null)
            {
                Control.SetTextIsSelectable(true);
                Control.Selected = true;
                //Control.SetSelectAllOnFocus(true);
            }
        }
    }
}

```

customLabelJust.cs

```

using Android.App;
using Android.Content;
using Android.OS;
using Android.Runtime;
using Android.Views;
using Android.Widget;
using IURIS.MOVIL.Droid;
using IURIS.MOVIL.Modelos_y_clases;
using System;
using System.Collections.Generic;
using System.ComponentModel;

```

```

using System.Linq;
using System.Text;
using Xamarin.Forms;
using Xamarin.Forms.Platform.Android;

[assembly: ExportRenderer(typeof(CustomLabelJustify),
typeof(CustomLabelJust))]
namespace IURIS.MOVIL.Droid
{
    public class CustomLabelJust:LabelRenderer
    {
        public CustomLabelJust(Context context):base(context)
        {
        }

        protected override void OnElementPropertyChanged(object sender,
PropertyChangeEventArgs e)
        {
            base.OnElementPropertyChanged(sender, e);
        }
        protected override void OnElementChanged(ElementChangedEventArgs<Label>
e)
        {
            base.OnElementChanged(e);
            if (Control != null)
            {
                Control.SetTextIsSelectable(true);
                Control.Selected = true;
            }
        }
    }
}

```

MainActivity.cs

```

using System;

using Android.App;
using Android.Content.PM;
using Android.Runtime;
using Android.Views;
using Android.Widget;
using Android.OS;
using Xamarin.Forms;
using Acr.UserDialogs;
using PayPal.Forms.Abstractions;
using PayPal.Forms;
using Android.Content;
using Matcha.BackgroundService.Droid;

namespace IURIS.MOVIL.Droid
{
    [Activity(Label = "IURIS", Icon = "@mipmap/icon", Theme =
"@style/MainTheme", MainLauncher = true, ConfigurationChanges =
ConfigChanges.ScreenSize | ConfigChanges.Orientation)]

```

```

    public class MainActivity :
global::Xamarin.Forms.Platform.Android.FormsAppCompatActivity
    {
        protected override void OnCreate(Bundle savedInstanceState)
        {
            TabLayoutResource = Resource.Layout.Tabbar;
            ToolbarResource = Resource.Layout.Toolbar;

            BackgroundAggregator.Init(this);

            base.OnCreate(savedInstanceState);

            UserDialogs.Init(this);

            Rg.Plugins.Popup.Popup.Init(this);

            Xamarin.Essentials.Platform.Init(this, savedInstanceState);

            //Forms.SetFlags(new[] { "Expander_Experimental" });
            Forms.SetFlags(new[] { "RadioButton_Experimental",
"Expander_Experimental", "SwipeView_Experimental",
"IndicatorView_Experimental", "Shapes_Experimental" });

            global::Xamarin.Forms.Forms.Init(this, savedInstanceState);
            LoadApplication(new App());

            var config = new PayPalConfiguration(PayPalEnvironment.NoNetwork,
"AauEBKZSRHuv0o2gyEjSwxgxCKR06xI5vbt3ARQaFmyAjrPUaxyPrUXl29RX9QNRXcN0_sUTE-
kF4xFT")
            {
                //If you want to accept credit cards
                AcceptCreditCards = true,
                //Your business name
                MerchantName = "Test Store",
                MerchantPrivacyPolicyUri = "https://www.example.com/privacy",
                MerchantUserAgreementUri = "https://www.example.com/legal",
                // OPTIONAL - ShippingAddressOption (Both, None, PayPal,
Provided)
                //ShippingAddressOption = ShippingAddressOption.Both,
                // OPTIONAL - Language: Default language for PayPal Plug-In
                Language = "es",
                // OPTIONAL - PhoneCountryCode: Default phone country code for
PayPal Plug-In
                PhoneCountryCode = "52",
            };
            CrossPayPalManager.Init(config, this);
        }
        public override void OnRequestPermissionsResult(int requestCode,
string[] permissions, [GeneratedEnum] Android.Content.PM.Permission[]
grantResults)
        {
            Xamarin.Essentials.Platform.OnRequestPermissionsResult(requestCode,
permissions, grantResults);

            base.OnRequestPermissionsResult(requestCode, permissions,
grantResults);
        }
    }

```

```

        protected override void OnActivityResult(int requestCode, Result
resultCode, Intent data)
        {
            base.OnActivityResult(requestCode, resultCode, data);
            PayPalManagerImplementation.Manager.OnActivityResult(requestCode,
resultCode, data);
        }
        protected override void OnDestroy()
        {
            base.OnDestroy();
            PayPalManagerImplementation.Manager.Destroy();
        }
    }
}

```

NavigationRendered.cs

```

using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;
using System.Threading.Tasks;
using Android.App;
using Android.Content;
using Android.OS;
using Android.Runtime;
using Android.Views;
using Android.Widget;
using IURIS.MOVIL.Droid;
using Xamarin.Forms;
using Xamarin.Forms.Platform.Android.AppCompat;

[assembly: ExportRenderer(typeof(NavigationPage), typeof(NavigationRendered))]
namespace IURIS.MOVIL.Droid
{
    public class NavigationRendered : NavigationPageRenderer
    {
        public NavigationRendered(Context context) : base(context)
        {
        }
        protected override Task<bool> OnPushAsync(Page view, bool animated)
        {
            return base.OnPushAsync(view, false);
        }
        protected override Task<bool> OnPopViewAsync(Page page, bool animated)
        {
            return base.OnPopViewAsync(page, false);
        }
        protected override Task<bool> OnPopToRootAsync(Page page, bool
animated)
        {
            return base.OnPopToRootAsync(page, false);
        }
    }
}

```



```
}
```

SplashScreen.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;
using System.Threading;
using Android.App;
using Android.Content;
using Android.Content.PM;
using Android.OS;
using Android.Runtime;
using Android.Views;
using Android.Widget;

namespace IURIS.MOVIL.Droid
{
    [Activity(Label = "IURIS", Icon = "@mipmap/icon", Theme =
"@style/SplashTheme", MainLauncher = false, ConfigurationChanges =
ConfigChanges.ScreenSize | ConfigChanges.Orientation)]
    public class SplashScreen: Activity
    {
        protected override void OnCreate(Bundle savedInstanceState)
        {
            base.OnCreate(savedInstanceState);
            StartActivity(typeof(MainActivity));
            Thread.Sleep(500);
            Finish();
            OverridePendingTransition(0, 0);
        }
    }
}
```

AndroidManifest.xml

```
<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
    android:versionName="1.0.1" package="com.SemperPapyrus.IURIS"
    android:installLocation="internalOnly" android:versionCode="3">
    <uses-sdk android:minSdkVersion="21" android:targetSdkVersion="32"
    android:textAllCaps="false" />
    <!-- Sample AdMob App ID: ca-app-pub-9229118148963816~2600565533 -->
    <application android:label="IURIS" android:icon="@mipmap/IURIS">
        <meta-data
            android:name="com.google.android.gms.ads.APPLICATION_ID" android:value="ca-app-
pub-2336879831564913~4192836110"></meta-data>
    </application>
    <uses-permission android:name="android.permission.ACCESS_NETWORK_STATE"
/>
```

```
        <uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"
/>
        <uses-permission android:name="android.permission.FOREGROUND_SERVICE" />
        <uses-permission android:name="android.permission.INTERNET" />
        <uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"
/>
</manifest>
```