Inkjet Waterproof Film Material Safety Data Sheet

1. The product name and manufacturer
Product name: inkjet waterproof film
Product use: used in inkjet pinting and plate making
Color: semi-transparent,milky white
Smell: no smell
Manufacturer: SHIJIAZHUANG PANDA INTERNATIONAL TRADING CO.,LTD
Address: No. 8 FEIYI ROAD,SHIJIAZHUANG,HEBEI CHINA
Telephone/fax: 311-89802851

2. The compositions information
Chemical composition: polyethylene terephthalate glycol ester
Harmful ingredients: does not contain harmful ingredients classification

3. Hazard identification information
Harmfulness is very low, no stimulation to the human body,but this model can cause damage of machine.Combustion would produce the harmful gases such as carbon monoxide
The material is likely to accumulate static charge, and lead to an electrostatic discharge.

4. The first aid measures
Eye contact: no first aid Skin contact: no first aid

5. Fire extinguishing measures
Applicable fire extinguishing agent: dry powder fire extinguishers, foam fire extinguisher
General treatment measures: as the products of combustion will produce a large number of irritant gas, need to wear protection when firefighters extinguishing fire clothing and wear protective gloves and control the respirator.

6. Accidental release measures Do not apply

7. Disposal and storage operations
7.1 Processing
Avoid long sunlight Under the condition of normal use,this product will not release harmful chemicals

After cutting, the film has a sharp edge, polyester film is smooth,can not directly on the floor, to prevent slip and fall.Please use safety equipment when transport and use

7.2 Packaging machinery
Roll of film is heavier,the same to the matters needing attention of heavy material in general.In use process may produce electrostatic, recommend the use of f static eliminator, pay attention to the electrostatic spark may cause the explosion of the inflammable steam or solvent.In the process of the machine running, the product should be ground in order to reduce electrostatic hazards.

7.3 Storage
Avoid direct sunlight, storage temperature of 25 to 35 ℃ (Celsius) and relative humidity below 50%, store environment clean, no dust, dust, grease and other pollutants.Equipped with corresponding varieties and number of fire equipment