Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

AUTO WASH 142 WM
Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: AUTO WASH 142 WM
Product code	: CW-50047

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: ROLLER AND BLANKET WASH
Use of the substance/mixture	: Industrial use

1.3. Details of the supplier of the safety data sheet

C&W Pressroom Products
837 West Hawthorne Lane
West Chicago, IL 60185 - USA
T 630-231-6500 - F 630-520-0390

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (Chemtrec)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4	H227
Carc. 2	H351
STOT SE 3	H335
STOT SE 3	H336
Aquatic Acute 1	H400

Full text of H-phrases: see section 16


Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07 GHS08 GHS09 GHS02

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H227 - Combustible liquid
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H400 - Very toxic to aquatic life

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P261 - Avoid breathing fume, gas, mist, spray, vapors
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear eye protection, protective gloves
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a doctor if you feel unwell
P370+P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to an approved waste disposal plant
P262 - Do not get in eyes, on skin, or on clothing
P264 - Wash hands thoroughly after handling

P270 - Do not eat, drink or smoke when using this product
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P352 - Wash with plenty of water
P374 - Fight fire with normal precautions from a reasonable distance
P381 - Eliminate all ignition sources if safe to do so P390
- Absorb spillage to prevent material damage

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
solvent naphtha (petroleum), light aromatic	(CAS No) 64742-95-6	70 - 80	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304
naphtha,heavy aromatic	(CAS No) 64742-94-5	20 - 30	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	: Coughing. Respiratory difficulties.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Diarrhoea. Gastrointestinal complaints. Nausea. Vomiting.
Chronic symptoms	: No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Explosion hazard	: Not applicable.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire. Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Store in a well-ventilated place. Keep cool.

Incompatible products : Oxidizing agent.

Incompatible materials : Heat sources. Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

AUTO WASH 142 WM	
ACGIH	Not applicable
OSHA	Not applicable

solvent naphtha (petroleum), light aromatic (64742-95-6)	
ACGIH	Not applicable
OSHA	Inhalation LC50 Rat >5.2 mg/L 4 h; Inhalation LC50 Rat 3400 ppm 4 h; Oral LD50 Rat 8400 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

naphtha,heavy aromatic (64742-94-5)	
ACGIH	Not applicable
OSHA	Not applicable

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses.



Materials for protective clothing : nitrile rubber.

Hand protection : Protective gloves.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.

Color : Colorless

Odor : Solvent-like odour

Odor threshold :

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

pH	:	4.2
Melting point	:	-56°F
Freezing point	:	NA
Boiling point	:	No data available
Flash point	:	350 °F
Relative evaporation rate (butyl acetate=1)	:	145 °F
Flammability (solid, gas)	:	5.4
Explosion limits	:	No data available
		Upper (UEL) - 5.9% Lower (LEL) - 0.8%
Explosive properties	:	
Oxidizing properties	:	No data available
Vapor pressure	:	No data available 0.79 mm Hg @ RT
Relative density	:	0.815 gr/cc @ RT
Relative vapor density at 20 °C	:	0.80 mm Hg @ RT
Specific gravity / density	:	0.815
Solubility	:	0.82 Moderately soluble in water. Water: 50 %
Log Pow	:	
Log Kow	:	NA
		NA
Auto-ignition temperature	:	> 233 C/ or > 453 F
Decomposition temperature	:	

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

Viscosity	:	Not available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	1.8 cSt @ 20 °C 1.46 cP @ 20°C

9.2. Other information

VOC content : 98.5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability
Stable under normal conditions.

10.3. Possibility of hazardous reactions
No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid
None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials
Oxidizing agent.

10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

naphtha,heavy aromatic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: No data available.
Symptoms/injuries after inhalation	: Coughing. Respiratory difficulties.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Diarrhoea. Gastrointestinal complaints. Nausea. Vomiting.

Chronic symptoms	: No effects known.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

naphtha,heavy aromatic (64742-94-5)	
EC50 Daphnia 1	0.95 mg/l (EC50; 48 h)
LC50 fish 2	2.34 mg/l (LC50; 96 h; Oncorhynchus mykiss)
Threshold limit algae 2	2.5 mg/l (EC50; 72 h)

12.2. Persistence and degradability

naphtha,heavy aromatic (64742-94-5)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6

naphtha,heavy aromatic (64742-94-5)	
Log Pow	2.9 - 6.1
Bioaccumulative potential	Bioaccumable: It must be listed as a possible chemical that can accumulate in an organism. It accumulates faster than it is lost thru catabolism and excretion.

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT) In accordance with DOT

Transport document description : UN1268 Petroleum distillates, n.o.s., 3, III
: UN1268

UN-No.(DOT)
Proper Shipping Name (DOT) : Petroleum distillates, n.o.s.
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger
Dangerous for the environment : Yes
Marine pollutant : Yes



Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	242
DOT Special Provisions (49 CFR 172.102)	:	144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	220 L
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Distribuidor autorizado de:
HEIDELBERG Saphira EPSON Jowat Adhesives preflex Vacuumatic

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : 1268
Proper Shipping Name (IMDG) : PETROLEUM DISTILLATES, N.O.S.
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

AUTO WASH 142 WM

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

naphtha,heavy aromatic (64742-94-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

15.3. US State regulations

Destek Comercial S.A.S.
Cra. 60 No. 4 G-53
Bogotá D.C. - Colombia
Tels.: (+ 57 1) 260 22 81 / 702 05 71
Telefax: (+ 57 1) 702 07 21
ventas@destekcomercial.com
www.destekcomercial.com

SECTION 16: Other information

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : B

B - Safety glasses, Gloves

Distribuidor autorizado de: