Saphira

SAFETY DATA SHEET

SAPHIRA LUBRICANT HP 1

Compilation date: 23.04.2015

Sent to: en

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SAPHIRA LUBRICANT HP 1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3. Details of the supplier of the safety data sheet

Company name: Heidelberger Druckmaschinen AG
Kurfuersten-Anlage 60
D-69115 Heidelberg
Deutschland

Tel: +49-6221-92-00

Email: consumables-msds@heidelberg.com

1.4. Emergency telephone number

Emergency tel: +49 (0) 7454 965231

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R52/53

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319

Most important adverse effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: H319: Causes serious eye irritation.
H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P264: Wash hands thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear eye protection.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

[cont...]

P337+313: If eye irritation persists: Get medical advice/attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Symbol not required.

Risk phrases: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S60: This material and its container must be disposed of as hazardous waste.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

POLYSULFIDE, DI-TERT-DODECYL- - REACH registered number(s): 01-2119540516-14-0000

EINECS	CAS	CHIP Classification	CLP Classification	Percent
270-335-7	68425-15-0	-: R53	Aquatic Chronic 4: H413	1-10%

ZINKALKYLDITHIOPHOSPHAT

272-028-3	68649-42-3	Xi: R38; Xi: R41; N: R51/53	Eye Dam. 1: H318; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%

(ISOALKYLPHENYL)PHOSPHOROTHIOAT

406-940-1	126019-82-7	N: R51/53	Aquatic Chronic 2: H411	1-10%

AMIN-PHOSPHAT

279-632-6	080939-62-4	Xi: R36/38; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: No data available.

[cont...]

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Eliminate all sources of ignition. Remove all incompatible materials as outlined in section 10 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Mix with sand or vermiculite. Wash the ground with an appropriate self-emulsifying solvent. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Smoking is forbidden. Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: 15 - 25° C Keep away from sources of ignition. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

Workplace exposure limits:

			Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m³ (Oil mist)	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Respiratory protection not required.

Hand protection: Nitrile gloves. 0,7 mm Breakthrough time of the glove material > 1 hour.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community environmental legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Beige

Odour: Characteristic odour

Solubility in water: Insoluble

Kinematic viscosity: ca. 4000

Viscosity test method: mPas, 25°C

Boiling point/range°C: n.b.

upper: n.b.

Autoflammability°C: n.b.

Relative density: ca. 0,92

VOC g/l: 0

Flammability limits %: lower: n.b.

Flash point°C: > 150

Vapour pressure: < 0,1 hPa/20°C

pH: neutral

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]