

Contents

- [CS375 HW11](#)
- [Problem 1.C](#)
- [Problem 1.E](#)
- [Problem 1.F](#)
- [Problem 2.A and 2.B](#)

CS375 HW11

Juan Alejandro Ormaza November 16 2021

```
clc ;clear all; close all;  
format long g
```

Problem 1.C

```
e= sqrt(eps)/4;  
A=[1 e; e 1];  
  
charPolynomial=charpoly(A) %characteristic polynomial  
  
eigenvalues=roots(charPolynomial) %lambda 1 and lambda 2
```

```
charPolynomial =  
  
    1    -2     1  
  
eigenvalues =  
  
    1  
    1
```

Problem 1.E

See attachments

Problem 1.F

```
e= sqrt(eps)/4;  
A=[1 e; e 1];  
x=[3;4];  
tol1=1e-8;  
tol2=1e-9;  
tol3=1e-10;  
  
[eval1,vec1]=power_method(A,x,tol1);  
[eval2,vec2]=power_method(A,x,tol2);  
  
% to run code just eliminate percentage sign:
```

```
%[eval3,eval3]=power_method(A,x,tol3);
```

```
eval1  
eval1
```

```
eval2  
eval2
```

```
eval1 =
```

```
1.00000000279397
```

```
eval1 =
```

```
0.750000001629815  
1
```

```
eval2 =
```

```
1.0000000031863
```

```
eval2 =
```

```
0.855315474301313  
1
```

Problem 2.A and 2.B

see attachments

CS375: HW11

Juan Alejandro Ormazá

Nov 16 2021

1.

$$A = \begin{bmatrix} 1 & \epsilon \\ \epsilon & 1 \end{bmatrix}$$

a) Characteristic polynomial of A:

$$\det(A - \lambda I) = \begin{vmatrix} 1-\lambda & \epsilon \\ \epsilon & 1-\lambda \end{vmatrix} = (1-\lambda)^2 - \epsilon^2$$
$$= \lambda^2 - 2\lambda + 1 - \epsilon^2$$

b) What are the eigenvalues and eigenvectors of A.

$$\lambda_{1,2} = \frac{2 \pm \sqrt{4 - 4(1 - \epsilon^2)}}{2}$$

$$\lambda_{1,2} = 1 \pm \sqrt{1 - 1 + \epsilon^2}$$

$$\lambda_{1,2} = 1 \pm \epsilon$$

$$\lambda_1 = 1 + \epsilon \quad \lambda_2 = 1 - \epsilon$$

$$(A - \lambda_1 I) v = 0$$

$$v_{\lambda_1=1+\epsilon} = \begin{bmatrix} 1 \\ 1 \end{bmatrix}$$

$$v_{\lambda_2=1-\epsilon} = \begin{bmatrix} 1 \\ -1 \end{bmatrix}$$

$$A - \lambda_1 I = \begin{bmatrix} 1 - 1 - \epsilon & \epsilon \\ \epsilon & -\epsilon \end{bmatrix} = \begin{bmatrix} -\epsilon & \epsilon \\ \epsilon & -\epsilon \end{bmatrix}$$

↑
Singular matrix
∞ Solutions

$$A - \lambda_2 I = \begin{bmatrix} \epsilon & \epsilon \\ \epsilon & \epsilon \end{bmatrix}$$

c. See Matlab code...

d. Since ϵ is $\sqrt{\epsilon_m}/4$

let's plug this in our equation for the characteristic polynomial

$$\lambda^2 - 2\lambda + 1 - \epsilon^2$$

$$\lambda^2 - 2\lambda + 1 - \frac{\epsilon_m}{16}$$

$$\text{Since } \frac{\epsilon_m}{16} < \epsilon_m$$

it essentially can
be thought of
as 0 in the
computer, yielding:

$$\rightarrow \lambda^2 - 2\lambda + 1$$

$$(\lambda - 1)(\lambda - 1)$$

$$\lambda_1 = 1 = \lambda_2$$

$$(A - \lambda_1 I) v = \begin{pmatrix} 0 & \epsilon \\ \epsilon & 0 \end{pmatrix} v$$

real
eigenvalues and eigenvectors
are not being calculated
because of.

e. } See Matlab code...

f. }

2. ?

a)

$$B = A - \frac{\lambda_i}{v^{(i)t} v^{(i)}} v^{(i)} (v^{(i)})^t \quad (1)$$

$$B v^{(i)} = 0$$

$$(v^{(i)})^t v^{(j)} = 0 \quad \text{for } i \neq j \quad (2)$$

let's multiply both sides of eq (1) by $V^{(1)}$

$$BV^{(1)} = \left(A - \frac{\lambda_1}{V^{(1)T} V^{(1)}} V^{(1)} (V^{(1)})^T \right) V^{(1)}$$

$$BV^{(1)} = \left(AV^{(1)} - \frac{\lambda_1}{\cancel{V^{(1)T} V^{(1)}}} V^{(1)} \cancel{(V^{(1)T} V^{(1)})} \right)$$

$$BV^{(1)} = AV^{(1)} - \lambda_1 V^{(1)}$$

by definition: \downarrow

$$BV^{(1)} = \cancel{AV^{(1)}} - \cancel{AV^{(1)}} = 0$$

$$BV^{(1)} = 0$$

let us try another number now $\neq 1$ and let's call it j
let us plug $V^{(j)}$ on both sides

$$BV^{(j)} = AV^{(j)} - \frac{\lambda_1}{V^{(1)T} V^{(1)}} \underbrace{V^{(1)} V^{(1)T} V^{(j)}}_{\text{using orthogonality.}} \quad 1 \neq j$$

$$BV^{(j)} = AV^{(j)} \quad \left. \begin{array}{l} \text{This means} \\ A \text{ will have} \\ \text{the same eigenvalues} \\ \text{as } B \text{ for all} \\ \lambda_j \neq 1 \end{array} \right\}$$

b. See MatLab code...

```
%Juan Alejandro Ormaza
% Algorithm based on Burden's Numerical Analysis 9th edition

function [eval, evec] = power_method(A,x,tol)

    k=1;
    N=1e100;

    x=x/norm(x,inf); %normalized

    while k<N
        y=A*x;

        lambda=norm(y,inf);

        error=norm((x-(y/norm(y,inf))),2);
        x=y/norm(y,inf);

        if error<tol
            break;
        end

        k=k+1;
    end

    eval=lambda;
    evec=x;

end
```

Not enough input arguments.

Error in power_method (line 9)
x=x/norm(x,inf); %normalized


```

% Juan Alejandro Ormaza
% Algorithm based on Burden's Numerical Analysis 9th edition

function [eval2] = power_method_mod(A,x,tol)

    k=1;
    N=1e100;

    x=x/norm(x,inf); %normalized

    while k<N
        y=A*x;

        lambda=norm(y,inf);

        error=norm((x-(y/norm(y,inf))),2);
        x=y/norm(y,inf);

        if error<tol
            break;
        end

        k=k+1;
    end

    evec=x;
    eval=lambda;

    B= A-(eval/(evec'*evec))*(evec*evec');
    eval2=eig(B);
    eval2=eval2(2);

end

```

Not enough input arguments.

Error in power_method_mod (line 9)
 x=x/norm(x,inf); %normalized

