

Contents

- [Homework 6](#)
- [Problem 2.b](#)
- [Problem 2.c](#)
- [Problem 2.d](#)
- [Problem 3.c](#)
- [Problem 4.a](#)
- [Problem 4.b](#)

Homework 6

Juan Alejandro Ormaza October 6 2021

```
clear all;clc; close all;
format LONG E
```

Problem 2.b

```
P=20;
A=gallery('poisson',P);
b = ones(P^2,1);

% Since both algorithms should be the same, I am going to use norm 2 to
% figure the difference between my_jacobi and my_vector_jacobi.

error = norm(my_jacobi(A,b,100)-my_vector_jacobi(A,b,100),2);
fprintf("the size of the differnce between my_jacobi and my_vector_jacobi is %2.8f\n",error);
```

```
the size of the differnce between my_jacobi and my_vector_jacobi is 0.00000000
```

Problem 2.c

```
% Since my_jacobi takes too long with p=20 I am going to use p=12 to
% calculate the time my algorithms take to run.

P=12;
A=gallery('poisson',P);
b = ones(P^2,1);

tic
    x1=my_vector_jacobi(A,b,100);
t1=toc;
fprintf("my vector jacobi takes %2.8f seconds\n",t1);

tic
    x2=my_jacobi(A,b,100);
t2=toc;
fprintf("my component-wise jacobi takes %10.8f seconds\n",t2);

fprintf("my_vector_jacobi is %10.8f times faster than my_jacobi\n", t2/t1);
```

```
my_vector_jacobi takes 0.00596608 seconds
my_component-wise_jacobi takes 9.96381930 seconds
my_vector_jacobi is 1670.07721884 times faster than my_jacobi
```

Problem 2.d

```
P=[ 10, 20, 40, 80, 160];
error=zeros(size(P,2),1);

for i=1:size(P,2)
    A=gallery('poisson',P(i));
    b = ones(P(i)^2,1);
    xtrue=A\b;
    x=my_vector_jacobi(A,b,100);
    error(i)=norm(xtrue-x,2)/norm(xtrue,2);
end
```

Problem 3.c

```
tot_it = [50, 100, 200, 400, 800, 1600];
error=zeros(size(tot_it,2),3);

for i=1:size(tot_it,2)
    A=gallery('poisson',160);
    b = ones(160^2,1);
    xtrue=A\b;
    x_jacobi=my_vector_jacobi(A,b,tot_it(i));
    x_CG=my_CG(A,b,tot_it(i));
    x_gauss=my_gauss_siedel(A,b,tot_it(i));
    error(i,1)=norm(xtrue-x_jacobi,2)/norm(xtrue,2);
    error(i,2)=norm(xtrue-x_gauss,2)/norm(xtrue,2);
    error(i,3)=norm(xtrue-x_CG,2)/norm(xtrue,2);
end

fprintf("Num Iterations\tError Jacobi\tError GS\tError CG\n");
for i=1:size(tot_it,2)
    fprintf("%4.0f\t\t %2.5f\t%2.5f\t\t%2.5f\t\n",tot_it(i),error(i,1),error(i,2),error(i,3));
end
```

Num Iterations	Error Jacobi	Error GS	Error CG
50	0.99012	0.98039	0.22322
100	0.98039	0.96131	0.00849
200	0.96130	0.92453	0.00000
400	0.92452	0.85577	0.00000
800	0.85574	0.73419	0.00000
1600	0.73415	0.54123	0.00000

Problem 4.a

```
P=10;
A=gallery('poisson',P);
b = ones(P^2,1);
```

```
nonZeros = nnz(A)/size(A,1);  
  
fprintf("The number of nonzeros in A is %3.6f\n", nonZeros);  
fprintf("As P increases the number of nonzeros approaches 5.")
```

The number of nonzeros in A is 4.600000
As P increases the number of nonzeros approaches 5.

Problem 4.b

```
fprintf("see in attached written solutions.\n")
```

see in attached written solutions.