



PRICE LIST 2026 - KCI

REV.01

***América do Sul
(Claudio Costa)***

Valid from July, 01st, 2026.

MAGNETIC-INDUCTIVE FLOWMETERS

INDEX

Price List 2026 Rev. 01

Mounting material WAFER		01
Flange material	3/8" - 72"	 02
Earthing rings	1/2" - 72"	 03
Liner / St.steel Housing 304/316	1/2" - 10"	 04
OPTIFLUX 1000	1/10" - 10"	 05-06
OPTIFLUX 4000	1/10" - 1"	 07-08
OPTIFLUX 4000	1 1/4" - 6"	 09-10
OPTIFLUX 4000 - FEP	8" - 20"	 11-12
OPTIFLUX 4000 - PTFE	18" - 32"	 13-14
OPTIFLUX 4000 - PFA	8" - 20"	 15-16
OPTIFLUX 2000 HR	1" - 6"	 17-18
OPTIFLUX 2000 HR	8" - 18"	 19-20
OPTIFLUX 2000 HR	20" - 40"	 21-22
OPTIFLUX 2000 HR	42" - 80"	 23-24
OPTIFLUX 2000 PU	2" - 6"	 25-26
OPTIFLUX 2000 PU	8" - 18"	 27-28
OPTIFLUX 2000 PU	20" - 40"	 29-30
WATERFLUX 3000 HR	2" - 6"	 31-32
WATERFLUX 3000 HR	8" - 24"	 33-34
Signal cable		35

OPTIFLUX 1000 WAFER

DN 2,5 - DN 250 / 1/10" - 10"

Base Price US\$

Mounting Material

Sizes ASME		Steel		Stainless steel	
		150 lb	300 lb	150 lb	300 lb
DN	2,5 - 25 / 1/10" - 1"	49	49	65	103
DN	40 / 1 1/2"	49	49	109	143
DN	50 / 2"	49	67	151	416
DN	65 / 2.1/2"	51	94	151	476
DN	80 / 3"	70	94	256	543
DN	100 / 4"	109	109	324	623
DN	150 / 6"	152	171	538	905
DN	200 / 8"	179	208	804	1042
DN	250 / 10"	207	306	961	1198

Sizes EN 1092-1 / NBR		Steel		Stainless steel	
		EN 1092-1 / NBR (PN10)	EN 1092-1 / NBR (PN16)	EN 1092-1 / NBR (PN10)	EN 1092-1 / NBR (PN16)
DN	2,5 - 25 / 1/10" - 1"	49	49	73	73
DN	40 / 1 1/2"	49	49	112	112
DN	50 / 2"	49	49	151	151
DN	65 / 2.1/2"	70	61	228	217
DN	80 / 3"	72	70	256	256
DN	100 / 4"	109	109	324	324
DN	150 / 6"	152	152	538	538
DN	200 / 8"	177	257	803	1040
DN	250 / 10"	207	289	961	1198

MAGNETIC-INDUCTIVE PRIMARY HEAD OPTIFLUX 4000 AND OPTIFLUX 2000

Base Price US\$

FLANGE MATERIAL : CARBON STEEL (Unit Price to flowmeter - US\$)

DN	PN 10	PN 16	PN 25	PN 40
10	—	—	—	Standard
15	—	—	—	Standard
25	—	—	—	Standard
40	—	—	—	Standard
50	—	—	—	Standard
65	—	Standard	—	on request
80	—	—	—	Standard
100	—	Standard	—	on request
125	—	Standard	—	on request
150	—	Standard	—	on request
200	Standard	132	on request	on request
250	Standard	192	on request	on request
300	Standard	200	on request	on request
350	Standard	836	on request	on request
400	Standard	836	on request	on request
450	Standard	1468	on request	on request
500	Standard	1907	on request	on request
600	Standard	2200	on request	on request
700	Standard	on request	on request	on request
800	Standard	on request	on request	on request
900	Standard	on request	on request	on request
1000	Standard	on request	on request	on request
1200	on request	on request	on request	on request
1400	on request	on request	on request	on request
1600	on request	on request	on request	on request
1800	on request	on request	on request	on request

DN	150 lb	300 lb
3/8"	Standard	67
1/2"	Standard	67
1"	Standard	67
1 1/2"	Standard	103
2"	Standard	121
2 1/2"	Standard	146
3"	Standard	170
4"	Standard	275
5"	Standard	430
6"	Standard	507
8"	161	857
10"	243	1335
12"	372	1654
14"	699	2304
16"	925	2433
18"	1251	2557
20"	1626	3581
24"	2008	on request
28"	on request	on request
32"	on request	on request
36"	on request	on request
40"	on request	on request

**FLANGE MATERIAL : DIN 1.4404 / 316 L
(Unit Price to flowmeter - US\$) -**

DN	150 lb	300 lb
3/8"	138	182
1/2"	138	182
1"	220	297
1 1/2"	321	510
2"	452	644
2 1/2"	620	933
3"	646	1004
4"	827	1429
6"	1399	3093
8"	1756	4220
10"	3792	7934
12"	4044	11116
14"	9178	on request
16"	11155	on request
18"	12417	on request
20"	13969	on request
24"	on request	on request
28"	on request	on request
32"	on request	on request
36"	on request	on request
40"	on request	on request

**FLANGE MATERIAL : DIN 1.4306 / 304 L
(Unit Price to flowmeter - US\$) -**

DN	150 lb	300 lb
3/8"	105	153
1/2"	105	153
1"	167	287
1 1/2"	241	476
2"	342	582
2 1/2"	450	862
3"	485	924
4"	623	1076
6"	1052	2324
8"	1317	3170
10"	2844	5235
12"	3035	8395
14"	6892	on request
16"	8367	on request
18"	9318	on request
20"	10480	on request
24"	on request	on request
28"	on request	on request
32"	on request	on request
36"	on request	on request
40"	on request	on request

FLANGE MATERIAL: CARBON STEEL

DN	INCH	AWWA Class B		AWWA Class D	
450	18"	0		1423	
500	20"	0		1626	
600	24"	0		1878	
700	28"	0		2101	
750	30"	0		3750	
800	32"	0		3911	
900	36"	0		4145	
1000	40"	0		4783	
1050	42"	0		7937	
1200	48"	0		9524	
1350	54"	0		on request	
1500	60"	0		on request	
1800	72"	on request		on request	

MAGNETIC-INDUCTIVE PRIMARY HEAD OPTIFLUX 1000 / 2000 / 4000
EARTHING RINGS

Base Price US\$

EARTHING RINGS MATERIAL : STAINLESS STEEL 1.4404 (316 L), 3 mm (PER PIECE)

DN	INCH	# 1	# 2	# 3
15 (down)	1/2 (down)	54	—	—
25	1	54	93	107
40	1 1/2	58	109	151
50	2	58	125	151
65	2 1/2	58	138	151
80	3	70	160	182
100	4	70	164	182
125	5	85	190	211
150	6	103	211	225
200	8	130	256	312
250	10	160	296	326
300	12	183	324	354
350	14	209	403	483
400	16	246	422	507
450	18	316	429	567
500	20	363	446	589
600	24	479	656	805
700	28	605	861	1124
750	30	757	971	1247
800	32	769	1046	1293
900	36	899	1230	1711
1000	40	1106	1455	2104
1050	42	1177	1606	on request
1200	48	1311	1818	on request
1400	56	on request	on request	on request
1500	60	on request	on request	on request
1600	64	on request	on request	on request
1800	72	on request	on request	on request

EARTHING RINGS MATERIAL : HASTELLOY C22, 3 mm (PER PIECE)

DN	INCH	# 1	
15 (down)	1/2 (down)	217	
25	1	300	
40	1 1/2	454	
50	2	713	
65	2 1/2	893	
80	3	998	
100	4	1328	
125	5	1738	
150	6	2259	

MAGNETIC-INDUCTIVE OPTIFLUX
LINER

Base Price US\$

PFA LINER (UNIT PRICE US\$)
HARDHUBBER / POLYURETHANE LINER (UNIT PRICE US\$)

DN	INCH	OPTIFLUX 1000 PFA	OPTIFLUX 4000 PFA	OPTIFLUX 1000 HARDRUBBER	OPTIFLUX 1000 POLYURETHANE
15 (down)	1/2 (down)	31	36	—	—
25	1	42	44	—	—
40	1 1/2	48	51	—	—
50	2	51	71	212	275
65	2 1/2	61	81	227	260
80	3	100	129	238	242
100	4	208	262	235	279
125	5	—	272	—	—
150	6	225	281	191	139
200	8	607	—	201	107
250	10	624	—	-224	-327

STAINLESS STEEL HOUSING 1.4301 - AISI 304 (UNIT PRICE US\$)
STAINLESS STEEL HOUSING 1.4401 - AISI 316 (UNIT PRICE US\$)

DN	INCH	OPTIFLUX 1000	OPTIFLUX 2000/4000	OPTIFLUX 1000	OPTIFLUX 2000/4000
15 (down)	1/2 (down)	—	204	—	253
25	1	—	174	—	203
40	1 1/2	—	192	—	227
50	2	162	237	206	261
65	2 1/2	204	237	260	261
80	3	246	242	301	274
100	4	321	288	426	322
125	5	—	306	—	365
150	6	512	324	722	413
200	8	on request	425	on request	578
250	10	on request	477	on request	691
300	12	—	481	—	709
350	14	—	688	—	1005
400	16	—	936	—	1310
450	18	—	1030	—	1445
500	20	—	1096	—	1539

Electro magnetic flow sensor OPTIFLUX 1000 F

For connection to signal converter : IFC 050 C/W, IFC100 C/W & IFC300 C/W/F/R.

DC-field operation for liquids with conductivity $\geq 20 \mu\text{S/cm}$
OPTIFLUX 1000
DN 2,5 - DN 250 / 1/10" - 10"
Code
Base Price US\$
Primary Head

VB17 4	Nominal Diameter		
F	1000 F	DN 2,5 / 1/10" **	1.481
G	1000 F	DN 4,0 / 5/32" **	1.481
H	1000 F	DN 6,0 / 1/4" **	1.481
1	1000 F	DN 10 / 3/8" **	1.492
2	1000 F	DN 15 / 1/2" **	1.292
3	1000 F	DN 20 / 3/4" **	1.317
4	1000 F	DN 25 / 1" **	1.311
6	1000 F	DN 40 / 1 1/2"	1.251
7	1000 F	DN 50 / 2"	1.063
8	1000 F	DN 65 / 2 1/2"	1.156
A	1000 F	DN 80 / 3"	1.226
B	1000 F	DN 100 / 4"	1.486
D	1000 F	DN 150 / 6"	1.899
E	1000 F	DN 200 / 8"	2.748
J	1000 F	DN 250 / 10"	3.650

* NOTE : Grounding ring DN40 / 1 1/2" up see page 3

** NOTE : Including Stainless Steel 316L earthing rings and viton gaskets

Nominal pressure			Price Adder
3	PN 16	EN 1092-1 (DN 100 - DN 250) (max.working operating pressure 16 bar)	0
5	PN 40	EN 1092-1 (DN 2,5 - DN 80) (max.working operating pressure 16 bar)	0
A	150 lb	ANSI RF (3/8" - 10") (max.working operating pressure 232 psi)	0
B	300 lb	ANSI RF (3/8" - 4") (max.working operating pressure 232 psi)	0

Approval		Price Adder
0	non Ex	0
A	CSA Ordinary Location	107

System design		
1	Compact with aluminum converter housir / at converter	0
2	Compact with stainless steel converter h ₁ / at converter	0
3	Modular / without	-105
4	Separate with aluminum connection box / 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box / PF 1/2	17
6	Separate with aluminum connection box / M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection / 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection / PF 1/2	306
C	Separate with stainless steel connection / M20 x 1,5 - CABLE GLANDS	306

Converter model		
0	Without / modular	0
I	IFC 100 W (wall mount version)	0
H	IFC 100 C (compact design)	0
J	IFC 100 C 45° (compact design)	0
C	IFC 300 C (compact design)	0
D	IFC 300 F (field mount version)	0
E	IFC 300 W (wall mount version)	0
F	IFC 300 R (rack mount version)	0
K	IFC 050 C (compact design)	0
L	IFC 050 W (wall mount version)	0

Mounting Material		
1	Steel, galv.	see page 1
2	Stainless Steel A2	see page 1
3	Rubber sleeves	0

Grounding ring material		
1	St. Steel 1.4404 - 316 L (DN 2,5 / 1/10" - DN 25 / 1"), without (DN 40 / 1 1/2" - DN250 / 10")	0
K	St. Steel 1.4404 - 316 L TYPE 1(DN 40 / 1 1/2" - DN 250 / 10")	see page 3
Y	3-rd grounding electrode (for DN50... DN250 [2"...10" only)	see page 35

Lining		
0	FEP (standard)	0
3	PFA	See page 4
2	Hardrubber DN 2" - DN 10"	See page 4
5	Polyurethane DN 2" - DN 10"	See page 4

Electrodes		
2	316 L (standard)	0
3	Hastelloy C22	50
4	Hastelloy B2	240
5	Tantalum	475
6	Titanium	240
7	Platinum	1351
N	Low noise (aluminumoxide) - Base HC22	322
P	316 L - (pointed electrode)	12
H	Hastelloy C22 - (pointed electrode)	60

Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Construction requirements		
0	Standard	0
1	Group 1	pending
2	Group 2	pending
3	Group 3	pending
QA / QC requirements		
0	Standard	0
1	Group 1	pending
2	Group 2	pending
3	Group 3	pending

VB17	Complete ordering code	Total Price
-------------	-------------------------------	--------------------

Electro magnetic flow sensor OPTIFLUX 4000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

OPTIFLUX 4000

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DN 2,5 - DN 25 / 1/10" - 1"

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

Code

Base Price US\$

Primary Head

VB03 4	Nominal Diameter			
U	4000 F	DN 2,5 / 1/10"	(for flanges DN 15 / 1/2")	1.953
V	4000 F	DN 4,0 / 5/32"	(for flanges DN 15 / 1/2")	1.953
W	4000 F	DN 6,0 / 1/4"	(for flanges DN 15 / 1/2")	1.953
1	4000 F	DN 10 / 3/8"	(for flanges DN 15 / 1/2")	1.866
2	4000 F	DN 15 / 1/2"		1.866
3	4000 F	DN 20 / 3/4"		1.866
4	4000 F	DN 25 / 1"		1.866

Nominal pressure Price Adder

5	PN 40	EN 1092-1	0
A	ASME 150 lb		0
B	ASME 300 lb		see page 2

Others on request

* NOTE : Grounding ring DN2,5 / 1/10" up see page 3

Approval (in combination with IFC 100 or 300 for Ex only) Price Adder

0	non Ex		0
L	Ex db eb [ia Ga] mb IIC T6...T3 Gb	(DN2,5 / 1/10" - DN15 / 1/2")	322
M	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN25 / 1")	413
N	Ex db eb [ia Ga] q IIC T5...T3 Gb	(DN25 / 1")	413
A	CSA Ordinary Location		107

System design

1	Compact with aluminum converter housing	/ at converter	0
2	Compact with stainless steel converter housing	/ at converter	0
3	Modular	/ without	-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box	/ PF 1/2	17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection box	/ PF 1/2	306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS	306

Converter model

0	Without / modular	0
I	IFC 100 W (wall mount version)	0
H	IFC 100 C (compact design)	0
J	IFC 100 C 45° (compact design)	0
C	IFC 300 C (compact design)	0
D	IFC 300 F (field mount version)	0
E	IFC 300 W (wall mount version)	0
F	IFC 300 R (rack mount version)	0
K	IFC 050 C (compact design)	0
L	IFC 050 W (wall mount version)	0

Lining

0	FEP (standard)	0
3	PFA	See page 4

Electrodes

2	316 L (standard)	0
3	Hastelloy C22	50
4	Hastelloy B2	240
5	Tantalum	475
6	Titanium	240
7	Platinum	1351
N	Low noise (aluminumoxide) - Base HC22	322
P	316 L - (pointed electrode)	12
H	Hastelloy C22 - (pointed electrode)	60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (DN25 1" only)	see page 35
Z	3rd and 4th grounding electrode (DN2,5 ... DN15 1/10" ... 1/2")**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
Construction requirements		
0	Standard	0
1	Group 1	*** In preparation / pending pending
2	Group 2	*** In preparation / pending pending
3	Group 3	*** In preparation / pending pending
QA / QC requirements		
0	Standard	0
1	Group 1	*** In preparation / pending pending
2	Group 2	*** In preparation / pending pending
3	Group 3	*** In preparation / pending pending
VB03	Complete ordering code	Total Price

Electro magnetic flow sensor OPTIFLUX 4000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

OPTIFLUX 4000
DN 32 - DN 150 / 1 1/4" - 6"

Code

Base Price US\$

Primary Head

VB03 4	Nominal Diameter		
5	4000 F	DN 32 / 1 1/4"	1.866
6	4000 F	DN 40 / 1 1/2"	1.866
7	4000 F	DN 50 / 2"	1.924
8	4000 F	DN 65 / 2 1/2"	1.944
A	4000 F	DN 80 / 3"	1.971
B	4000 F	DN 100 / 4"	2.157
C	4000 F	DN 125 / 5"	2.488
D	4000 F	DN 150 / 6"	2.604

Nominal pressure

Price Adder

3	PN 16	EN 1092-1 (DN 65,100...150)	0
5	PN 40	EN 1092-1 (DN 10... 80)	0
A	ASME 150 lb RF		0
B	ASME 300 lb RF		see page 2
	Others on request		

* NOTE : Grounding ring DN32 up see page 3

Approval (in combination with IFC 100 or 300 for Ex only)

Price Adder

0	non Ex		0
M	Ex db eb [ja Ga] IIC T6...T3 Gb	(DN25 / 1" - DN150 / 6")	413
N	Ex db eb [ja Ga] q IIC T5...T3 Gb	(DN25 / 1" - DN150 / 6")	413
A	CSA Ordinary Location		107

System design

1	Compact with aluminum converter housing	/ at converter	0
2	Compact with stainless steel converter housing	/ at converter	0
3	Modular	/ without	-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box	/ PF 1/2	17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection box	/ PF 1/2	306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS	306

Converter model

0	Without / modular		0
I	IFC 100 W	(wall mount version)	0
H	IFC 100 C	(compact design)	0
J	IFC 100 C 45°	(compact design)	0
C	IFC 300 C	(compact design)	0
D	IFC 300 F	(field mount version)	0
E	IFC 300 W	(wall mount version)	0
F	IFC 300 R	(rack mount version)	0
K	IFC 050 C	(compact design)	0
L	IFC 050 W	(wall mount version)	0

Lining

0	FEP (standard)		0
3	PFA		See page 4

Electrodes

2	316 L (standard)		0
3	Hastelloy C22		50
4	Hastelloy B2		240
5	Tantalum		475
6	Titanium		240
7	Platinum		1351
N	Low noise (aluminumoxide) - Base HC22		322
P	316 L - (pointed electrode)		12
H	Hastelloy C22 - (pointed electrode)		60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (DN32... DN150 1 ¼"...6")	see page 35
Construction requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB03	Complete ordering code	Total Price

Electro magnetic flow sensor OPTIFLUX 4000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

OPTIFLUX 4000

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DN 200 - DN 500 / 8" - 20"

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

Code		Base Price US\$
-------------	--	------------------------

Primary Head

VB04 4	Nominal Diameter			
E	4000 F	DN 200 / 8"	FEP	4.494
F	4000 F	DN 250 / 10"	FEP	6.265
G	4000 F	DN 300 / 12"	FEP	8.778
H	4000 F	DN 350 / 14"	FEP	9.654
K	4000 F	DN 400 / 16"	FEP	11.979
L	4000 F	DN 450 / 18"	FEP	19.494
M	4000 F	DN 500 / 20"	FEP	23.083

Nominal pressure			Price Adder
2	PN 10	EN 1092-1	0
3	PN 16	EN 1092-1	see page 2
4	PN 25	EN 1092-1	On request
5	PN 40	EN 1092-1	On request
A	ASME 150 lb RF		see page 2
B	ASME 300 lb RF		see page 2
	Others on request		

* NOTE : Grounding ring DN200 / 8" up see page 3

Approval (in combination with IFC 100 or 300 for Ex only)			Price Adder
0	non Ex		0
N	Ex db eb [ia Ga] q IIC T5...T3 Gb	(DN200 / 8" - DN300 / 12")	643
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN200 / 8" - DN400 / 16")	1.103
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN450 / 18" - DN500 / 20")	1.330
A	CSA Ordinary Location		107

System design

1	Compact with aluminum converter housing	/ at converter	0
2	Compact with stainless steel converter housing	/ at converter	0
3	Modular	/ without	-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box	/ PF 1/2	17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection box	/ PF 1/2	306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS	306

Converter model

0	Without / modular	0
I	IFC 100 W (wall mount version)	0
H	IFC 100 C (compact design)	0
J	IFC 100 C 45° (compact design)	0
C	IFC 300 C (compact design)	0
D	IFC 300 F (field mount version)	0
E	IFC 300 W (wall mount version)	0
F	IFC 300 R (rack mount version)	0
K	IFC 050 C (compact design)	0
L	IFC 050 W (wall mount version)	0

Lining

0	FEP (standard)	0
----------	----------------	---

Electrodes

2	316 L (standard)	0
3	Hastelloy C22	50
4	Hastelloy B2	240
5	Tantalum	475
6	Titanium	240
7	Platinum	1351
N	Low noise (aluminumoxide) - Base HC22	322
P	316 L - (pointed electrode)	12
H	Hastelloy C22 - (pointed electrode)	60

Construction of electrodes			
2	Exchangeable (except Ex approval)		114
Material of Flange / Housing			
1	Carbon Steel / Steel		0
2	Stainless Steel 1.4306 (304 L) / Steel		see page 2
3	Stainless Steel 1.4404 (316 L) / Steel		see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304		see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316		see page 2 + page 4
Protection category			
1	IP 67		0
2	IP 68 / Field (stainless steel connection box)		596
3	IP 68 Factory (stainless steel connection box)		650
A	IP 68 / Field (aluminum connection box)		373
B	IP 68 Factory (aluminum connection box)		407
9	IP 67 + Internally Resined		see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)		"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)		"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)		"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)		"B" + see page 35
Cable			Price Adder
0	Compact - without / separate DS		see page 31
1	Separate BTS		see page 31
Cable lenght			
0	Compact - none / separate - 5 m - 15 ft		0
1	10 m - 30 ft		see page 31
2	15 m - 45 ft		see page 31
3	20 m - 60 ft		see page 31
4	25 m - 75 ft		see page 31
5	30 m - 90 ft		see page 31
6	40 m - 120 ft		see page 31
7	50 m - 150 ft		see page 31
8	100 m - 300 ft		see page 31
Calibration			
0	Standard		0
1	Stainless Steel 1.4301 (304) tagplate		46
Ring / Material			
0	Whithout		0
2	Ring #1 / Hastelloy C		see page 3
6	Ring #1 / 1.4404 - 316 L		see page 3
E	Ring #3 / 1.4404 - 316 L		see page 3
P	Protection ring #2 / 1.4404 - 316 L		see page 3
Y	3-rd grounding electrode (for DN200...DN250" 8"...10" only)		see page 35
Z	3rd and 4th grounding electrode (DN300 ... DN500 12"...20")**		see page 35
** NOTE : Not applicable when cathodic protection is used.			
Construction requirements			
0	Standard		0
1	Group 1	*** In preparation / pending	pending
2	Group 2	*** In preparation / pending	pending
3	Group 3	*** In preparation / pending	pending
QA / QC requirements			
0	Standard		0
1	Group 1	*** In preparation / pending	pending
2	Group 2	*** In preparation / pending	pending
3	Group 3	*** In preparation / pending	pending
VB04	Complete ordering code		Total Price



Electro magnetic flow sensor OPTIFLUX 4000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

OPTIFLUX 4000
DN 450 - DN 800 / 18" - 32"

Code

Base Price US\$

Primary Head

VB05 4	Nominal Diameter				
	L	4000 F	DN 450 / 18"	PTFE	On request
	M	4000 F	DN 500 / 20"	PTFE	On request
	N	4000 F	DN 600 / 24"	PTFE	On request
	P	4000 F	DN 700 / 28"	PTFE	On request
	R	4000 F	DN 800 / 32"	PTFE	On request
	Nominal pressure				Price Adder
	2	PN 10	EN 1092-1		0
	3	PN 16	EN 1092-1		see page 2
	4	PN 25	EN 1092-1		on request
	5	PN 40	EN 1092-1		on request
	A	ASME 150 lb RF			see page 2
	B	ASME 300 lb RF			On request
	X	AWWA C207 Class B			see page 2
	W	AWWA C207 Class D			see page 2
	Others on request				
	* NOTE : Grounding ring DN450 / 18" up see page 3				
	Approval (in combination with IFC 100 or 300 for Ex only)				Price Adder
	0	non Ex			0
	P	Ex db eb [ia Ga] IIC T6...T3 Gb (DN450 / 18" - DN600 / 24")			1.330
	P	Ex db eb [ia Ga] IIC T6...T3 Gb (DN700 / 28" - DN1000 / 40")			On request
	A	CSA Ordinary Location			107
	System design				
	1	Compact with aluminum converter housing / at converter			0
	2	Compact with stainless steel converter housing / at converter			0
	3	Modular / without			-105
	4	Separate with aluminum connection box / 1/2" NPT - ADAPTER (to be used only with conduits)			17
	5	Separate with aluminum connection box / PF 1/2			17
	6	Separate with aluminum connection box / M20 x 1,5 - CABLE GLANDS			0
	A	Separate with stainless steel connection box / 1/2" NPT - ADAPTER (to be used only with conduits)			306
	B	Separate with stainless steel connection box / PF 1/2			306
	C	Separate with stainless steel connection box / M20 x 1,5 - CABLE GLANDS			306
	Converter model				
	0	Without / modular			0
	I	IFC 100 W (wall mount version)			0
	H	IFC 100 C (compact design)			0
	J	IFC 100 C 45° (compact design)			0
	C	IFC 300 C (compact design)			0
	D	IFC 300 F (field mount version)			0
	E	IFC 300 W (wall mount version)			0
	F	IFC 300 R (rack mount version)			0
	K	IFC 050 C (compact design)			0
	L	IFC 050 W (wall mount version)			0
	Lining				
	4	PTFE (standard)			0
	9	Provided for protection rings (PTFE)			see page 3
	Electrodes				
	2	316 L (standard)			0
	3	Hastelloy C22			50
	4	Hastelloy B2			240
	5	Tantalum			475
	6	Titanium			240
	7	Platinum			1351
	N	Low noise (aluminumoxide) - Base HC22			322
	P	316 L - (pointed electrode)			12
	H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes			
2	Exchangeable (except Ex approval)		114
Material of Flange			
1	Carbon Steel		0
2	Stainless Steel 1.4306 (304 L)		see page 2
3	Stainless Steel 1.4404 (316 L)		see page 2
Protection category			
1	IP 67		0
2	IP 68 / Field	(stainless steel connection box)	596
3	IP 68 Factory	(stainless steel connection box)	650
A	IP 68 / Field	(aluminum connection box)	373
B	IP 68 Factory	(aluminum connection box)	407
9	IP 67 + Internally Resined		see page 35
C	IP 68 / Field + Internally Resined	(stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined	(stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined	(aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined	(aluminum connection box)	"B" + see page 35
Cable			Price Adder
0	Compact - without / separate DS		see page 31
1	Separate BTS		see page 31
Cable lenght			
0	Compact - none / separate - 5 m - 15 ft		0
1	10 m - 30 ft		see page 31
2	15 m - 45 ft		see page 31
3	20 m - 60 ft		see page 31
4	25 m - 75 ft		see page 31
5	30 m - 90 ft		see page 31
6	40 m - 120 ft		see page 31
7	50 m - 150 ft		see page 31
8	100 m - 300 ft		see page 31
Calibration			
0	Standard		0
1	Stainless Steel 1.4301 (304) tagplate		46
Ring / Material			
0	Whithout		0
2	Ring #1 / Hastelloy C		see page 3
6	Ring #1 / 1.4404 - 316 L		see page 3
E	Ring #3 / 1.4404 - 316 L		see page 3
P	Protection ring #2 / 1.4404 - 316 L		see page 3
Construction requirements			
0	Standard		0
1	Group 1	*** In preparation / pending	pending
2	Group 2	*** In preparation / pending	pending
3	Group 3	*** In preparation / pending	pending
QA / QC requirements			
0	Standard		0
1	Group 1	*** In preparation / pending	pending
2	Group 2	*** In preparation / pending	pending
3	Group 3	*** In preparation / pending	pending
VB05	Complete ordering code		Total Price


Electro magnetic flow sensor OPTIFLUX 4000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

OPTIFLUX 4000
DN 200 - DN 500 / 8" - 20"
Code
Base Price US\$
Primary Head

VB04 4	Nominal Diameter			
4	4000 F	DN 200 / 8"	PFA	5.828
5	4000 F	DN 250 / 10"	PFA	8.111
6	4000 F	DN 300 / 12"	PFA	10.664
7	4000 F	DN 350 / 14"	PFA	12.775
8	4000 F	DN 400 / 16"	PFA	15.419
L	4000 F	DN 450 / 18"	PFA	29.777
M	4000 F	DN 500 / 20"	PFA	34.634
Nominal pressure				Price Adder
2	PN 10	EN 1092-1		0
3	PN 16	EN 1092-1		see page 2
4	PN 25	EN 1092-1		on request
5	PN 40	EN 1092-1		on request
A	ASME 150 lb RF			see page 2
B	ASME 300 lb RF			see page 2
	Others on request			
* NOTE : Grounding ring DN200 / 8" up see page 3				
Approval (in combination with IFC 100 or 300 for Ex only)				Price Adder
0	non Ex			0
N	Ex db eb [ia Ga] q IIC T5...T3 Gb	(DN200 / 8" - DN300 / 12")		643
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN200 / 8" - DN400 / 16")		1.103
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN450 / 18" - DN500 / 20")		1.330
A	CSA Ordinary Location			107
System design				
1	Compact with aluminum converter housing	/ at converter		0
2	Compact with stainless steel converter housing	/ at converter		0
3	Modular	/ without		-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		17
5	Separate with aluminum connection box	/ PF 1/2		17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS		0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		306
B	Separate with stainless steel connection box	/ PF 1/2		306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS		306
Converter model				
0	Without / modular			0
I	IFC 100 W	(wall mount version)		0
H	IFC 100 C	(compact design)		0
J	IFC 100 C 45°	(compact design)		0
C	IFC 300 C	(compact design)		0
D	IFC 300 F	(field mount version)		0
E	IFC 300 W	(wall mount version)		0
F	IFC 300 R	(rack mount version)		0
K	IFC 050 C	(compact design)		0
L	IFC 050 W	(wall mount version)		0
Lining				
3	PFA (standard)			0
Electrodes				
2	316 L (standard)			0
3	Hastelloy C22			50
4	Hastelloy B2			240
5	Tantalum			475
6	Titanium			240
7	Platinum			1351
N	Low noise (aluminumoxide) - Base HC22			322
P	316 L - (pointed electrode)			12
H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (for DN200...DN250" 8"...10" only)	see page 35
Z	3rd and 4th grounding electrode (DN300...DN500 12"...20")**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
Construction requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB04	Complete ordering code	Total Price

Electro magnetic flow sensor OPTIFLUX 2000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

OPTIFUX 2000
DN 25 - DN 150 / 1" - 6"

Code Base Price US\$

Primary Head

VB14 4	Nominal Diameter			
4	2000 F	DN 25 / 1"	Hardrubber	1.488
5	2000 F	DN 32 / 1¼"	Hardrubber	1.488
6	2000 F	DN 40 / 1½"	Hardrubber	1.488
7	2000 F	DN 50 / 2"	Hardrubber	1.430
8	2000 F	DN 65 / 2½"	Hardrubber	1.441
A	2000 F	DN 80 / 3"	Hardrubber	1.460
B	2000 F	DN 100 / 4"	Hardrubber	1.807
C	2000 F	DN 125 / 5"	Hardrubber	2.045
D	2000 F	DN 150 / 6"	Hardrubber	2.196

Nominal pressure			Price Adder
3	PN 16	EN 1092-1 (DN 65, 100, 125, 150)	0
4	PN 25	EN 1092-1 (DN 100, 125, 150)	on request
5	PN 40	EN 1092-1 (DN 10... 80)	0
A	ASME 150 lb RF		0
B	ASME 300 lb RF (DN 10...DN 300)		see page 2
Others on request			
* NOTE : Grounding ring DN10 / 3/8" up see page 3			

Approval (in combination with IFC 100 or 300 for Ex only)			Price Adder
0	non Ex		0
M	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN25 / 1" - DN150 / 6")	413
N	Ex db eb [ia Ga] q IIC T5...T3 Gb	(DN25 / 1" - DN150 / 6")	413
A	CSA Ordinary Location		107

System design			
1	Compact with aluminum converter housing	/ at converter	0
2	Compact with stainless steel converter housing	/ at converter	0
3	Modular	/ without	-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box	/ PF 1/2	17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection box	/ PF 1/2	306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS	306

Converter model			
0	Without / modular		0
I	IFC 100 W	(wall mount version)	0
H	IFC 100 C	(compact design)	0
J	IFC 100 C 45°	(compact design)	0
C	IFC 300 C	(compact design)	0
D	IFC 300 F	(field mount version)	0
E	IFC 300 W	(wall mount version)	0
F	IFC 300 R	(rack mount version)	0
K	IFC 050 C	(compact design)	0
L	IFC 050 W	(wall mount version)	0

Lining			
2	Hardrubber	(standard)	0

Electrodes			
2	316 L (standard)		0
3	Hastelloy C22		50
4	Hastelloy B2		240
5	Tantalum		475
6	Titanium		240
7	Platinum		1351
N	Low noise (aluminumoxide) - Base HC22		322
P	316 L - (pointed electrode)		12
H	Hastelloy C22 - (pointed electrode)		60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (for DN50...DN150" 2"...6" only)**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
Construction requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB14	Complete ordering code	Total Price

Electro magnetic flow sensor OPTIFLUX 2000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

OPTIFLUX 2000
DN 200 - DN 450 / 8" - 18"

Code

Base Price US\$

Primary Head

VB15 4	Nominal Diameter			
E	2000 F	DN 200 / 8"	Hardrubber	3.064
F	2000 F	DN 250 / 10"	Hardrubber	3.948
G	2000 F	DN 300 / 12"	Hardrubber	4.282
H	2000 F	DN 350 / 14"	Hardrubber	4.969
K	2000 F	DN 400 / 16"	Hardrubber	6.171
L	2000 F	DN 450 / 18"	Hardrubber	7.572

Nominal pressure				Price Adder
2	PN 10	EN 1092-1		0
3	PN 16	EN 1092-1		see page 2
4	PN 25	EN 1092-1		On request
5	PN 40	EN 1092-1		On request
A	ASME 150 lb RF			see page 2
B	ASME 300 lb RF			see page 2
W	AWWA C207 Class D			On request
	Others on request			

* **NOTE** : Grounding ring DN200 / 8" up see page 3

Approval (in combination with IFC 100 or 300 for Ex only)				Price Adder
0	non Ex			0
N	Ex db eb [ia Ga] q IIC T5...T3 Gb	(DN200 / 8" - DN300 / 12")		643
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN200 / 8" - DN400 / 16")		1.103
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN450 / 18")		1.330
A	CSA Ordinary Location			107

System design				
1	Compact with aluminum converter housing	/ at converter		0
2	Compact with stainless steel converter housing	/ at converter		0
3	Modular	/ without		-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		17
5	Separate with aluminum connection box	/ PF 1/2		17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS		0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		306
B	Separate with stainless steel connection box	/ PF 1/2		306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS		306

Converter model				
0	Without / modular			0
I	IFC 100 W	(wall mount version)		0
H	IFC 100 C	(compact design)		0
J	IFC 100 C 45°	(compact design)		0
C	IFC 300 C	(compact design)		0
D	IFC 300 F	(field mount version)		0
E	IFC 300 W	(wall mount version)		0
F	IFC 300 R	(rack mount version)		0
K	IFC 050 C	(compact design)		0
L	IFC 050 W	(wall mount version)		0

Lining				
2	Hardrubber	(standard)		0

Electrodes				
2	316 L (standard)			0
3	Hastelloy C22			50
4	Hastelloy B2			240
5	Tantalum			475
6	Titanium			240
7	Platinum			1351
N	Low noise (aluminumoxide) - Base HC22			322
P	316 L - (pointed electrode)			12
H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (for DN200...DN250" 8"...10" only)**	see page 35
Z	3rd and 4th grounding electrode (DN300 ... DN450 12"...18")**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
Construction requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB15	Complete ordering code	Total Price

**Electro magnetic flow sensor OPTIFLUX 2000 F**

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)**OPTIFLUX 2000****DN 500 - DN 1000 / 20" - 40"****Code** **Base Price US\$****Primary Head**

VB16 4	Nominal Diameter			
M	2000 F	DN 500 / 20"	Hardrubber	8.379
N	2000 F	DN 600 / 24"	Hardrubber	9.509
P	2000 F	DN 700 / 28"	Hardrubber	11.184
Y	2000 F	DN 750 / 30"	Hardrubber	13.592
R	2000 F	DN 800 / 32"	Hardrubber	15.099
S	2000 F	DN 900 / 36"	Hardrubber	18.575
T	2000 F	DN 1000 / 40"	Hardrubber	22.879

Nominal pressure				Price Adder
2	PN 10	EN 1092-1	(except DN750 / 30")	0
3	PN 16	EN 1092-1	(except DN750 / 30")	see page 2
4	PN 25	EN 1092-1	(except DN750 / 30")	on request
5	PN 40	EN 1092-1	(except DN750 / 30")	on request
A	ASME 150 lb RF			see page 2
B	ASME 300 lb RF			On request
X	AWWA C207 Class B			see page 2
W	AWWA C207 Class D			see page 2
	Others on request			

* **NOTE** : Grounding ring DN500 / 20" up see page 3

Approval (in combination with IFC 100 or 300 for Ex only)				Price Adder
0	non Ex			0
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN500 / 20" - DN600 / 24")		1.330
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN700 / 28" - DN1000 / 40")		On request
A	CSA Ordinary Location			107

System design			
1	Compact with aluminum converter housing	/ at converter	0
2	Compact with stainless steel converter housing	/ at converter	0
3	Modular	/ without	-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box	/ PF 1/2	17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection box	/ PF 1/2	306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS	306

Converter model			
0	Without / modular		0
I	IFC 100 W	(wall mount version)	0
H	IFC 100 C	(compact design)	0
J	IFC 100 C 45°	(compact design)	0
C	IFC 300 C	(compact design)	0
D	IFC 300 F	(field mount version)	0
E	IFC 300 W	(wall mount version)	0
F	IFC 300 R	(rack mount version)	0
K	IFC 050 C	(compact design)	0
L	IFC 050 W	(wall mount version)	0

Lining			
2	Hardrubber	(standard)	0

Electrodes			
2	316 L (standard)		0
3	Hastelloy C22		50
4	Hastelloy B2		240
5	Tantalum		475
6	Titanium		240
7	Platinum		1351
N	Low noise (aluminumoxide) - Base HC22		322
P	316 L - (pointed electrode)		12
H	Hastelloy C22 - (pointed electrode)		60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304 (DN 500 / 20")	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316 (DN 500 / 20")	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Z	3rd and 4th grounding electrode (DN500 ... DN1000 20"...40")**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
Construction requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB16	Complete ordering code	Total Price

Electro magnetic flow sensor OPTIFLUX 2000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W ($\leq$ DN1200 | 48"), & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) μ S/cm. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) μ S/cm. (IFC 050 and IFC 100)

OPTIFLUX 2000
DN 1050 - DN 2000 / 42" - 80"

Code		Base Price US\$
-------------	--	------------------------

Primary Head

VB16 4	Nominal Diameter			
W	2000 F	DN 1050 / 42"	Hardrubber	28.083
U	2000 F	DN 1200 / 48"	Hardrubber	32.685
X	2000 F	DN 1350 / 54"	Hardrubber	53.612
V	2000 F	DN 1400 / 56"	Hardrubber	55.378
Z	2000 F	DN 1500 / 60"	Hardrubber	57.921
Q	2000 F	DN 1600 / 64"	Hardrubber	On request
1	2000 F	DN 1800 / 72"	Hardrubber	On request
2	2000 F	DN 2000 / 80"	Hardrubber	On request

Nominal pressure				Price Adder
1	PN 6	EN 1092-1	(DN1200, DN1400, DN1600, DN1800 and DN2000)	On request
2	PN 10	EN 1092-1	(DN1200, DN1400, DN1600, DN1800)	see page 2
3	PN 16	EN 1092-1		On request
A	ASME 150 lb RF			On request
B	ASME 300 lb RF			On request
X	AWWA C207 Class B	(42", 48", 54", 60" and 72")		see page 2
W	AWWA C207 Class D	(42", 48", 54", 60" and 72")		see page 2
	Others on request			

* **NOTE** : Grounding ring DN1050 / 42" up see page 3

Approval (in combination with IFC 100 or 300 for Ex only)				Price Adder
0	non Ex			0
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN1050 / 42" - DN2000 / 80")		On request
A	CSA Ordinary Location			107

System design				
1	Compact with aluminum converter housing	/ at converter		0
2	Compact with stainless steel converter housing	/ at converter		0
3	Modular	/ without		-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		17
5	Separate with aluminum connection box	/ PF 1/2		17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS		0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		306
B	Separate with stainless steel connection box	/ PF 1/2		306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS		306

Converter model				
0	Without / modular			0
I	IFC 100 W	(wall mount version)		0
H	IFC 100 C	(compact design)		0
J	IFC 100 C 45°	(compact design)		0
C	IFC 300 C	(compact design)		0
D	IFC 300 F	(field mount version)		0
E	IFC 300 W	(wall mount version)		0
F	IFC 300 R	(rack mount version)		0
K	IFC 050 C	(compact design)		0
L	IFC 050 W	(wall mount version)		0

Lining				
2	Hardrubber	(standard)		0

Electrodes				
2	316 L (standard)			0
3	Hastelloy C22			50
4	Hastelloy B2			240
5	Tantalum			475
6	Titanium			240
7	Platinum			1351
N	Low noise (aluminumoxide) - Base HC22			322
P	316 L - (pointed electrode)			12
H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange		
1	Carbon Steel	0
2	Stainless Steel 1.4306 (304 L)	see page 2
3	Stainless Steel 1.4404 (316 L)	see page 2
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
* Z	3rd and 4th grounding electrode (DN1050 ... DN1500 42" ... 60")**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
Construction requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB16	Complete ordering code	Total Price

Electro magnetic flow sensor OPTIFLUX 2000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

OPTIFLUX 2000
DN 50 - DN 150 / 2" - 6"

Code

Base Price US\$

Primary Head

VB14 4	Nominal Diameter			
7	2000 F	DN 50 / 2"	Polyurethane	1.905
8	2000 F	DN 65 / 2 1/2"	Polyurethane	1.923
A	2000 F	DN 80 / 3"	Polyurethane	1.949
B	2000 F	DN 100 / 4"	Polyurethane	2.218
C	2000 F	DN 125 / 5"	Polyurethane	2.301
D	2000 F	DN 150 / 6"	Polyurethane	2.490

Nominal pressure				Price Adder
3	PN 16	EN 1092-1	(DN 65, 100... 150)	0
4	PN 25	EN 1092-1	(DN 100, 125, 150)	on request
5	PN 40	EN 1092-1	(DN50 - DN80)	0
A	ASME 150 lb RF			0
B	ASME 300 lb RF			see page 2
Others on request				

* NOTE : Grounding ring DN50 / 2" up see page 3

Approval (in combination with IFC 100 or 300 for Ex only)			Price Adder
0	non Ex		0
M	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN25 / 1" - DN150 / 6")	413
N	Ex db eb [ia Ga] q IIC T5...T3 Gb	(DN25 / 1" - DN150 / 6")	413
A	CSA Ordinary Location		107

System design				
1	Compact with aluminum converter housing / at converter			0
2	Compact with stainless steel converter housing / at converter			0
3	Modular / without			-105
4	Separate with aluminum connection box / 1/2" NPT - ADAPTER (to be used only with conduits)			17
5	Separate with aluminum connection box / PF 1/2			17
6	Separate with aluminum connection box / M20 x 1,5 - CABLE GLANDS			0
A	Separate with stainless steel connection box / 1/2" NPT - ADAPTER (to be used only with conduits)			306
B	Separate with stainless steel connection box / PF 1/2			306
C	Separate with stainless steel connection box / M20 x 1,5 - CABLE GLANDS			306

Converter model				
0	Without / modular			0
I	IFC 100 W (wall mount version)			0
H	IFC 100 C (compact design)			0
J	IFC 100 C 45° (compact design)			0
C	IFC 300 C (compact design)			0
D	IFC 300 F (field mount version)			0
E	IFC 300 W (wall mount version)			0
F	IFC 300 R (rack mount version)			0
K	IFC 050 C (compact design)			0
L	IFC 050 W (wall mount version)			0

Lining				
5	Polyurethane (standard)			0

Electrodes				
2	316 L (standard)			0
3	Hastelloy C22			50
4	Hastelloy B2			240
5	Tantalum			475
6	Titanium			240
7	Platinum			1351
N	Low noise (aluminumoxide) - Base HC22			322
P	316 L - (pointed electrode)			12
H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes

2	Exchangeable (except Ex approval)	114
----------	-----------------------------------	------------

Material of Flange / Housing

1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4

Protection category

1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35

Cable

0	Compact - without / separate DS	Price Adder
1	Separate BTS	see page 31

Cable lenght

0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31

Calibration

0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46

Ring / Material

0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (DN50...DN150" 2"...6")**	see page 35

**** NOTE : Not applicable when cathodic protection is used.**

Construction requirements

0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending

QA / QC requirements

0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending

VB14

Complete ordering code

Total Price

Electro magnetic flow sensor OPTIFLUX 2000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DN 200 - DN 450 / 8" - 18"

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

Code	Base Price US\$
-------------	------------------------

Primary Head

VB15 4	Nominal Diameter			
	E 2000 F	DN 200 / 8"	Polyurethane	3.600
	F 2000 F	DN 250 / 10"	Polyurethane	4.646
	G 2000 F	DN 300 / 12"	Polyurethane	5.428
	H 2000 F	DN 350 / 14"	Polyurethane	6.363
	K 2000 F	DN 400 / 16"	Polyurethane	7.134
	L 2000 F	DN 450 / 18"	Polyurethane	8.756

	Nominal pressure	Price Adder
2	PN 10 EN 1092-1	0
3	PN 16 EN 1092-1	see page 2
4	PN 25 EN 1092-1	on request
5	PN 40 EN 1092-1	on request
A	ASME 150 lb RF	see page 2
B	ASME 300 lb RF	see page 2
W	AWWA C207 Class D	0
	Others on request	

* NOTE : Grounding ring DN200 / 8" up see page 3

	Approval (in combination with IFC 100 or 300 for Ex only)	Price Adder
0	non Ex	0
N	Ex db eb [ia Ga] q IIC T5...T3 Gb (DN200 / 8" - DN300 / 12")	643
P	Ex db eb [ia Ga] IIC T6...T3 Gb (DN200 / 8" - DN400 / 16")	1.103
P	Ex db eb [ia Ga] IIC T6...T3 Gb (DN450 / 18")	1.330
A	CSA Ordinary Location	107

	System design	
1	Compact with aluminum converter housing / at converter	0
2	Compact with stainless steel converter housing / at converter	0
3	Modular / without	-105
4	Separate with aluminum connection box / 1/2" NPT - ADAPTER (to be used only with conduits)	17
5	Separate with aluminum connection box / PF 1/2	17
6	Separate with aluminum connection box / M20 x 1,5 - CABLE GLANDS	0
A	Separate with stainless steel connection box / 1/2" NPT - ADAPTER (to be used only with conduits)	306
B	Separate with stainless steel connection box / PF 1/2	306
C	Separate with stainless steel connection box / M20 x 1,5 - CABLE GLANDS	306

	Converter model	
0	Without / modular	0
I	IFC 100 W (wall mount version)	0
H	IFC 100 C (compact design)	0
J	IFC 100 C 45° (compact design)	0
C	IFC 300 C (compact design)	0
D	IFC 300 F (field mount version)	0
E	IFC 300 W (wall mount version)	0
F	IFC 300 R (rack mount version)	0
K	IFC 050 C (compact design)	0
L	IFC 050 W (wall mount version)	0

	Lining	
5	Polyurethane (standard)	0

	Electrodes	
2	316 L (standard)	0
3	Hastelloy C22	50
4	Hastelloy B2	240
5	Tantalum	475
6	Titanium	240
7	Platinum	1351
N	Low noise (aluminumoxide) - Base HC22	322
P	316 L - (pointed electrode)	12
H	Hastelloy C22 - (pointed electrode)	60

Construction of electrodes

2	Exchangeable (except Ex approval)	114
---	-----------------------------------	-----

Material of Flange / Housing

1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316	see page 2 + page 4

Protection category

1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35

Cable

0	Compact - without / separate DS	Price Adder
1	Separate BTS	see page 31

Cable lenght

0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31

Calibration

0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46

Ring / Material

0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Y	3-rd grounding electrode (for DN200...DN250" 8"...10" only)**	see page 35
Z	3rd and 4th grounding electrode (DN300 ... DN450 12"...18")**	see page 35

**** NOTE : Not applicable when cathodic protection is used.**

Construction requirements

0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending

QA / QC requirements

0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending

VB15	Complete ordering code	Total Price
------	------------------------	-------------

Electro magnetic flow sensor OPTIFLUX 2000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DN 500 - DN 1000 / 20" - 40"

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

Code

Base Price US\$

Primary Head

VB16 4	Nominal Diameter			
M	2000 F	DN 500 / 20"	Polyurethane	10.235
N	2000 F	DN 600 / 24"	Polyurethane	13.868
P	2000 F	DN 700 / 28"	Polyurethane	21.101
Y	2000 F	DN 750 / 30"	Polyurethane	26.071
R	2000 F	DN 800 / 32"	Polyurethane	28.893
S	2000 F	DN 900 / 36"	Polyurethane	38.132
T	2000 F	DN 1000 / 40"	Polyurethane	43.690
Nominal pressure				Price Adder
2	PN 10	EN 1092-1	(except DN750 / 30")	0
3	PN 16	EN 1092-1	(except DN750 / 30")	see page 2
4	PN 25	EN 1092-1	(except DN750 / 30")	on request
5	PN 40	EN 1092-1	(except DN750 / 30")	on request
A	ASME 150 lb RF			see page 2
B	ASME 300 lb RF			On request
X	AWWA C207 Class B			see page 2
W	AWWA C207 Class D			see page 2
	Others on request			
* NOTE : Grounding ring DN500 / 20" up see page 3				
Approval (in combination with IFC 100 or 300 for Ex only)				Price Adder
0	non Ex			0
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN500 / 20" - DN600 / 24")		1.330
P	Ex db eb [ia Ga] IIC T6...T3 Gb	(DN700 / 28" - DN1000 / 40")		On request
A	CSA Ordinary Location			107
System design				
1	Compact with aluminum converter housing	/ at converter		0
2	Compact with stainless steel converter housing	/ at converter		0
3	Modular	/ without		-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		17
5	Separate with aluminum connection box	/ PF 1/2		17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS		0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		306
B	Separate with stainless steel connection box	/ PF 1/2		306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS		306
Converter model				
0	Without / modular			0
I	IFC 100 W	(wall mount version)		0
H	IFC 100 C	(compact design)		0
J	IFC 100 C 45°	(compact design)		0
C	IFC 300 C	(compact design)		0
D	IFC 300 F	(field mount version)		0
E	IFC 300 W	(wall mount version)		0
F	IFC 300 R	(rack mount version)		0
K	IFC 050 C	(compact design)		0
L	IFC 050 W	(wall mount version)		0
Lining				
5	Polyurethane	(standard)		0
Electrodes				
2	316 L (standard)			0
3	Hastelloy C22			50
4	Hastelloy B2			240
5	Tantalum			475
6	Titanium			240
7	Platinum			1351
N	Low noise (aluminumoxide) - Base HC22			322
P	316 L - (pointed electrode)			12
H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes		
2	Exchangeable (except Ex approval)	114
Material of Flange / Housing		
1	Carbon Steel / Steel	0
2	Stainless Steel 1.4306 (304 L) / Steel	see page 2
3	Stainless Steel 1.4404 (316 L) / Steel	see page 2
4	Stainless Steel 1.4306 (304 L) / Stainless Steel 304 (DN 500 / 20")	see page 2 + page 4
5	Stainless Steel 1.4306 (316 L) / Stainless Steel 316 (DN 500 / 20")	see page 2 + page 4
Protection category		
1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35
Cable		Price Adder
0	Compact - without / separate DS	see page 31
1	Separate BTS	see page 31
Cable lenght		
0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 31
2	15 m - 45 ft	see page 31
3	20 m - 60 ft	see page 31
4	25 m - 75 ft	see page 31
5	30 m - 90 ft	see page 31
6	40 m - 120 ft	see page 31
7	50 m - 150 ft	see page 31
8	100 m - 300 ft	see page 31
Calibration		
0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46
Ring / Material		
0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3
Z	3rd and 4th grounding electrode (DN500 ... DN1000 20"...40")**	see page 35
** NOTE : Not applicable when cathodic protection is used.		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
QA / QC requirements		
0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending
VB16	Complete ordering code	Total Price

Electro magnetic flow sensor WATERFLUX 3000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

WATERFLUX 3000
DN 50 - DN 150 / 2" - 6"

Code Base Price US\$
Primary Head

VB46 4		Nominal Diameter	
7	3000 F DN 50 / 2"	Hardrubber	1.710
A	3000 F DN 80 / 3"	Hardrubber	1.743
B	3000 F DN 100 / 4"	Hardrubber	2.005
D	3000 F DN 150 / 6"	Hardrubber	2.438
Nominal pressure			Price Adder
3	PN 16 EN 1092-1		0
A	ASME 150 lb RF		0
Others on request			
Approval			Price Adder
0	non Ex		0
System design			
1	Compact with aluminum converter housing / at converter		0
2	Compact with stainless steel converter housing / at converter		0
3	Modular / without		-105
4	Separate with aluminum connection box / 1/2" NPT - ADAPTER (to be used only with conduits)		17
5	Separate with aluminum connection box / PF 1/2		17
6	Separate with aluminum connection box / M20 x 1,5 - CABLE GLANDS		0
A	Separate with stainless steel connection box / 1/2" NPT - ADAPTER (to be used only with conduits)		306
B	Separate with stainless steel connection box / PF 1/2		306
C	Separate with stainless steel connection box / M20 x 1,5 - CABLE GLANDS		306
Converter model			
0	Without / modular		0
I	IFC 100 W (wall mount version)		0
H	IFC 100 C (compact design)		0
J	IFC 100 C 45° (compact design)		0
C	IFC 300 C (compact design)		0
D	IFC 300 F (field mount version)		0
E	IFC 300 W (wall mount version)		0
F	IFC 300 R (rack mount version)		0
K	IFC 050 C (compact design)		0
L	IFC 050 W (wall mount version)		0
Lining			
2	Hardrubber (standard)		0
Electrodes			
2	316 L (standard)		0
3	Hastelloy C22		50
P	316 L - (pointed electrode)		12
H	Hastelloy C22 - (pointed electrode)		60

Construction of electrodes

1	Fixed	0
----------	-------	----------

Material of Flange

1	Carbon Steel	0
2	Stainless Steel 1.4306 (304 L)	see page 2
3	Stainless Steel 1.4404 (316 L)	see page 2

Protection category

1	IP 67	0
2	IP 68 / Field (stainless steel connection box)	596
3	IP 68 Factory (stainless steel connection box)	650
A	IP 68 / Field (aluminum connection box)	373
B	IP 68 Factory (aluminum connection box)	407
9	IP 67 + Internally Resined	see page 35
C	IP 68 / Field + Internally Resined (stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined (stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined (aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined (aluminum connection box)	"B" + see page 35

**** NOTE : Waterflux 3000 hardrubber model with internally resinlined standard construction.**

Cable**Price Adder**

0	Compact - without / separate DS	see page 35
1	Separate BTS	see page 35

Cable lenght

0	Compact - none / separate - 5 m - 15 ft	0
1	10 m - 30 ft	see page 35
2	15 m - 45 ft	see page 35
3	20 m - 60 ft	see page 35
4	25 m - 75 ft	see page 35
5	30 m - 90 ft	see page 35
6	40 m - 120 ft	see page 35
7	50 m - 150 ft	see page 35
8	100 m - 300 ft	see page 35

Calibration

0	Standard	0
1	Stainless Steel 1.4301 (304) tagplate	46

Ring / Material

0	Whithout	0
2	Ring #1 / Hastelloy C	see page 3
6	Ring #1 / 1.4404 - 316 L	see page 3
E	Ring #3 / 1.4404 - 316 L	see page 3
P	Protection ring #2 / 1.4404 - 316 L	see page 3

Construction requirements

0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending

QA / QC requirements

0	Standard	0
1	Group 1 *** In preparation / pending	pending
2	Group 2 *** In preparation / pending	pending
3	Group 3 *** In preparation / pending	pending

VB14	Complete ordering code	Total Price
-------------	-------------------------------	--------------------

Electro magnetic flow sensor WATERFLUX 3000 F

For connection to signal converter : IFC 050 C/W, IFC 100 C/W & IFC 300 C/W/F/R.

DC-field operation for liquids with conductivity ≥ 1 (water ≥ 20) $\mu\text{S/cm}$. (IFC 300)

DC-field operation for liquids with conductivity ≥ 5 (water ≥ 20) $\mu\text{S/cm}$. (IFC 050 and IFC 100)

WATERFLUX 3000
DN 200 - DN 600 / 8" - 24"

Code

Base Price US\$

Primary Head

VB47 4	Nominal Diameter			
E	3000 F	DN 200 / 8"	Hardrubber	3.401
F	3000 F	DN 250 / 10"	Hardrubber	4.382
G	3000 F	DN 300 / 12"	Hardrubber	4.753
H	3000 F	DN 350 / 14"	Hardrubber	5.873
K	3000 F	DN 400 / 16"	Hardrubber	7.275
L	3000 F	DN 450 / 18"	Hardrubber	8.521
M	3000 F	DN 500 / 20"	Hardrubber	9.766
N	3000 F	DN 600 / 24"	Hardrubber	11.122

Nominal pressure

Price Adder

2	PN 10	EN 1092-1		0
A	ASME 150 lb RF			see page 2
	Others on request			

Approval

Price Adder

0	non Ex			0
----------	--------	--	--	---

System design

1	Compact with aluminum converter housing	/ at converter		0
2	Compact with stainless steel converter housing	/ at converter		0
3	Modular	/ without		-105
4	Separate with aluminum connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		17
5	Separate with aluminum connection box	/ PF 1/2		17
6	Separate with aluminum connection box	/ M20 x 1,5 - CABLE GLANDS		0
A	Separate with stainless steel connection box	/ 1/2" NPT - ADAPTER (to be used only with conduits)		306
B	Separate with stainless steel connection box	/ PF 1/2		306
C	Separate with stainless steel connection box	/ M20 x 1,5 - CABLE GLANDS		306

Converter model

0	Without / modular			0
I	IFC 100 W	(wall mount version)		0
H	IFC 100 C	(compact design)		0
J	IFC 100 C 45°	(compact design)		0
C	IFC 300 C	(compact design)		0
D	IFC 300 F	(field mount version)		0
E	IFC 300 W	(wall mount version)		0
F	IFC 300 R	(rack mount version)		0
K	IFC 050 C	(compact design)		0
L	IFC 050 W	(wall mount version)		0

Lining

2	Hardrubber	(standard)		0
----------	------------	------------	--	---

Electrodes

2	316 L (standard)			0
3	Hastelloy C22			50
P	316 L - (pointed electrode)			12
H	Hastelloy C22 - (pointed electrode)			60

Construction of electrodes			
1	Fixed		0
Material of Flange			
1	Carbon Steel		0
2	Stainless Steel 1.4306 (304 L)		see page 2
3	Stainless Steel 1.4404 (316 L)		see page 2
Protection category			
1	IP 67		0
2	IP 68 / Field	(stainless steel connection box)	596
3	IP 68 Factory	(stainless steel connection box)	650
A	IP 68 / Field	(aluminum connection box)	373
B	IP 68 Factory	(aluminum connection box)	407
9	IP 67 + Internally Resined		see page 35
C	IP 68 / Field + Internally Resined	(stainless steel connection box)	"2" + see page 35
D	IP 68 Factory + Internally Resined	(stainless steel connection box)	"3" + see page 35
E	IP 68 / Field + Internally Resined	(aluminum connection box)	"A" + see page 35
F	IP 68 Factory + Internally Resined	(aluminum connection box)	"B" + see page 35
** NOTE : Waterflux 3000 hardrubber model with internally resinlined standard construction.			
Cab			Price Adder
0	Compact - without / separate DS		see page 35
1	Separate BTS		see page 35
Cable lenght			
0	Compact - none / separate - 5 m - 15 ft		0
1	10 m - 30 ft		see page 35
2	15 m - 45 ft		see page 35
3	20 m - 60 ft		see page 35
4	25 m - 75 ft		see page 35
5	30 m - 90 ft		see page 35
6	40 m - 120 ft		see page 35
7	50 m - 150 ft		see page 35
8	100 m - 300 ft		see page 35
Calibration			
0	Standard		0
1	Stainless Steel 1.4301 (304) tagplate		46
Ring / Material			
0	Whithout		0
2	Ring #1 / Hastelloy C		see page 3
6	Ring #1 / 1.4404 - 316 L		see page 3
E	Ring #3 / 1.4404 - 316 L		see page 3
P	Protection ring #2 / 1.4404 - 316 L		see page 3
Construction requirements			
0	Standard		0
1	Group 1	*** In preparation / pending	pending
2	Group 2	*** In preparation / pending	pending
3	Group 3	*** In preparation / pending	pending
QA / QC requirements			
0	Standard		0
1	Group 1	*** In preparation / pending	pending
2	Group 2	*** In preparation / pending	pending
3	Group 3	*** In preparation / pending	pending
VB15	Complete ordering code		Total Price

Electro magnetic flow sensor OPTIFLUX

Signal cable OPTIFLUX

Base Price US\$

Cable type	Recommended for converter type	Stock Code	Price per m	Base List US\$
DS grey	IFC 050/100 W & IFC 300 F / W / R	A060051		23,00
DS blue	IFC 300 F / W / R	A060067		on request
BTS grey	IFC 050/100 W & IFC 300 F / W / R	A060068		on request
BTS blue	IFC 300 F / W / R	A060069		34,00
LIYCY	coil cable, black, 3 x 0,75 mm ²	A060070		20,00
LIYCY	4 x 2,5 mm ² (DIV 2 cable)	A060071		on request

MAGNETIC METER INTERNALLY RESINED

Base Price US\$

DN	IN	OPT1000	OPT2000/4000/3000	OPT6000
2,5	1/10"	18	18	NA
4	4/32"	18	18	NA
6	1/4"	18	18	NA
10	3/8"	18	18	NA
15	1/2"	18	18	NA
20	3/4"	18	18	NA
25	1"	18	18	19
40	1 1/2"	19	19	19
50	2"	18	24	19
65	2 1/2"	20	25	20
80	3"	23	26	20
100	4"	26	70	26
125	5"	NA	71	49
150	6"	49	71	50
200	8"	86	87	NA
250	10"	100	208	NA
300	12"	NA	232	NA
350	14"	NA	274	NA
400	16"	NA	346	NA
450	18"	NA	374	NA
500	20"	NA	401	NA
600	24"	NA	505	NA
700	28"	NA	883	NA
800	32"	NA	991	NA
900	36"	NA	1.063	NA
1000	40"	NA	1.137	NA
1200	48"	NA	1.356	NA

Grounding electrode

ELECTRODE MATERIAL	3RD GROUNDING ELECTRODE	3RD AND 4TH GROUNDING ELECTRODE	GROUNDING ELECTRODE APPLICATION	
			3RD ELECTRODE	OPT1000 DN50 A DN250
Stainless steel -316L	82	173		OPT2000/4000 DN25 A DN250
Hastelloy C22	104	220	3RD AND 4TH ELECTRODE	OPT4000 DN2,5 A DN20
Titanium	139	278		OPT2000/4000 DN300 A DN1800
Tantalum	266	528		
Platinum	971	1938		