




Material: UL94 V-2 Nylon 6/6			
Color: Natural			
Part No.	A		
	mm	in	
CBLSP305A	2.5	.098	
CBLSP310A	3	.118	
CBLSP315A	3.5	.138	
CBLSP320A	4	.157	
CBLSP325A	4.5	.177	
CBLSP330A	5	.197	
CBLSP335A	5.5	.217	
CBLSP340A	6	.236	
CBLSP345A	6.4	.252	
CBLSP350A	7	.276	
CBLSP355A	8	.315	
CBLSP360A	9	.354	
CBLSP365A	10	.394	
CBLSP370A	11	.433	
CBLSP375A	12	.472	
CBLSP380A	15	.591	

TO SNAP LOCK IN A 3.5 (.137) Ø HOLE, IN  
A 1.2 - 1.7 (.047 - .067) PANEL THICKNESS



TO SNAP LOCK IN A 3.5 (.137) Ø HOLE, IN  
A 1.2 - 1.7 (.047 - .067) PANEL THICKNESS

TOLERANCES  
UNLESS NOTED  
≤ 5 mm ±0.2  
5 - 20 mm ±0.3  
20 - 40 mm ±0.4  
40 - 60 mm ±0.5  
60 - 100 mm ±0.8  
≥ 100 mm ±1.0

TITLE: DUAL LOCKING CIRCUIT BOARD SUPPORT			
FILE: CBLSP3XX	DWN: CLC	DWG IN MM (IN)	
	SHEET: 1 OF 1		
	SHEET SIZE: A		
RE:		PART #	PRINT TYPE
 ESSENTRA COMPONENTS		SEE TABLE	
		CA	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Essentra:

[CBLSP345A](#) [CBLSP320A](#) [CBLSP375A](#) [CBLSP315A](#) [CBLSP330A](#) [CBLSP360A](#) [CBLSP340A](#) [CBLSP310A](#)  
[CBLSP380A](#) [CBLSP370A](#) [CBLSP350A](#) [CBLSP335A](#) [CBLSP305A](#) [CBLSP325A](#) [CBLSP365A](#) [CBLSP355A](#)