UDP bus transport layer

This chapter defines the UDP bus based transport layer of DroneCAN.

Ports and IP addresses

DroneCAN is carried over UDP using multicast packets. The default multicast IP is 239.65.82.B where B is the DroneCAN bus number, where 0 is used for the first system bus.

The default multicast port is 57732.

Packet format

The packet format is:

```
- MAGIC 0x2934 16 bit
- 16 bit CRC CRC-16-CCITT (over all bytes after CRC)
- 16 bit flags
- 32 bit message ID
- data[]
```

All data is little endian.

URIs

In tools where the transport is enumerated the URI is “mcast:B” where B is the bus number. This means “mcast:0” is 239.65.82.0 on UDP port 57732.

Specification

1. Introduction
2. Basic concepts
3. Data structure description language
4.1 CAN bus transport layer
4.2 UDP bus transport layer
4.3 MAVLink bus transport layer
4.4 CANFD bus transport layer
5. Application level conventions
6. Application level functions
7. List of standard data types
8. Hardware design recommendations
dsdl
  ardupilot
  uavcan

Contents

UDP bus transport layer
  Ports and IP addresses
  Packet format
  URIs

License

This work is licensed under a Creative Commons Attribution 4.0 International License.
Much of the content of this site is based upon prior work by Pavel Kirienko and the UAVCAN Development Team.