




Using Single-Row Functions to Customize Output


2/15/11 Agenda

- Homework 1 & 2 review
- Lesson 3
- In-class Lab
- Lesson 4
- In-class Lab

SQL Functions



Two Types of SQL Functions




Single-Row Functions

Single-row functions:


- Manipulate data items
- Accept arguments and return one value
- Act on each row that is returned
- Return one result per row
- May modify the data type
- Can be nested
- Accept arguments that can be a column or an expression

```
function_name [(arg1, arg2,...)]
```

Single-Row Functions



Character Functions



Case-Conversion Functions

These functions convert the case for character strings:

Function	Result
<code>LOWER('SQL Course')</code>	sql course
<code>UPPER('SQL Course')</code>	SQL COURSE
<code>INITCAP('SQL Course')</code>	Sql Course

Using Case-Conversion Functions

Display the employee number, name, and department number for employee Higgins:

```
SELECT employee_id, last_name, department_id
FROM   employees
WHERE  last_name = 'higgins';
```

0 rows selected

```
SELECT employee_id, last_name, department_id
FROM   employees
WHERE  LOWER(last_name) = 'higgins';
```

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
1	205	Higgins	110


Character-Manipulation Functions

These functions manipulate character strings:


Function	Result
CONCAT('Hello', 'World')	HelloWorld
SUBSTR('HelloWorld',1,5)	Hello
LENGTH('HelloWorld')	10
INSTR('HelloWorld', 'W')	6
LPAD(salary,10,'*')	*****24000
RPAD(salary, 10, '*')	24000*****
REPLACE ('JACK and JUE','J','BL')	BLACK and BLUE
TRIM('H' FROM 'HelloWorld')	elloWorld

Using the Character-Manipulation Functions

```
SELECT employee_id, CONCAT(first_name, last_name) NAME,  
       job_id, LENGTH (last_name),  
       INSTR(last_name, 'a') "Contains 'a'?"  
FROM   employees  
WHERE  SUBSTR(job_id, 4) = 'REP';
```



	EMPLOYEE_ID	NAME	JOB_ID	LENGTH(LAST_NAME)	Contains 'a'?
1	174	EllenAbel	SA_REP	4	0
2	176	JonathonTaylor	SA_REP	6	2
3	178	KimberelyGrant	SA_REP	5	3
4	202	PatFay	MK_REP	3	2



Number Functions

- **ROUND:** Rounds value to a specified decimal
- **TRUNC:** Truncates value to a specified decimal
- **MOD:** Returns remainder of division

Function	Result
ROUND (45.926, 2)	45.93
TRUNC (45.926, 2)	45.92
MOD (1600, 300)	100

Using the ROUND Function

The diagram illustrates the use of the ROUND function in SQL. It shows a query and its output with three numbered annotations:

- Annotation 1:** Points to the first argument of the ROUND function, the number 45.923.
- Annotation 2:** Points to the second argument of the ROUND function, the number of decimal places (2, 0, or -1).
- Annotation 3:** Points to the entire ROUND function call.

SQL Query:

```
SELECT ROUND (45.923, 2), ROUND (45.923, 0),  
       ROUND (45.923, -1)  
FROM   DUAL;
```

Query Results:

	ROUND(45.923,2)	ROUND(45.923,0)	ROUND(45.923,-1)
1	45.92	46	50

DUAL is a dummy table that you can use to view results from functions and calculations.

Using the TRUNC Function

1 2 3

```
SELECT TRUNC(45.923, 2), TRUNC(45.923),  
FROM DUAL;
```

	TRUNC(45.923,2)	TRUNC(45.923)	TRUNC(45.923,-1)
1	45.92	45	40

1

2

3

Using the MOD Function

For all employees with the job title of Sales Representative, calculate the remainder of the salary after it is divided by 5,000.

```
SELECT last_name, salary, MOD(salary, 5000)
FROM employees
WHERE job_id = 'SA_REP';
```

	R2	LAST_NAME	R2	SALARY	R2	MOD(SALARY,5000)
1		Abel		11000		1000
2		Taylor		8600		3600
3		Grant		7000		2000

Working with Dates

- The Oracle database stores dates in an internal numeric format: century, year, month, day, hours, minutes, and seconds.
- The default date display format is DD-MON-RR.
 - Enables you to store 21st-century dates in the 20th century by specifying only the last two digits of the year
 - Enables you to store 20th-century dates in the 21st century in the same way

```
SELECT last_name, hire_date
FROM   employees
WHERE  hire_date < '01-FEB-88';
```

	LAST_NAME	HIRE_DATE
1	King	17-JUN-87
2	Whalen	17-SEP-87

RR Date Format

Current Year	Specified Date	RR Format	YY Format
1995	27-OCT-95	1995	1995
1995	27-OCT-17	2017	1917
2001	27-OCT-17	2017	2017
2001	27-OCT-95	1995	2095

		If the specified two-digit year is:	
		0–49	50–99
If two digits of the current year are:	0–49	The return date is in the current century	The return date is in the century before the current one
	50–99	The return date is in the century after the current one	The return date is in the current century

Using the SYSDATE Function

SYSDATE is a function that returns:

- Date
- Time

```
SELECT sysdate  
FROM dual;
```

	SYSDATE
1	31-MAY-07

Arithmetic with Dates

- Add or subtract a number to or from a date for a resultant date value.
- Subtract two dates to find the number of days between those dates.
- Add hours to a date by dividing the number of hours by 24.

Using Arithmetic Operators with Dates

```
SELECT last_name, (SYSDATE-hire_date)/7 AS WEEKS  
FROM employees  
WHERE department_id = 90;
```

	LAST_NAME	WEEKS
1	King	1041.168239087301587301587301587302
2	Kochhar	923.025381944444444444444444444444
3	De Haan	750.168239087301587301587301587302

Date-Manipulation Functions

Function	Result
MONTHS_BETWEEN	Number of months between two dates
ADD_MONTHS	Add calendar months to date
NEXT_DAY	Next day of the date specified
LAST_DAY	Last day of the month
ROUND	Round date
TRUNC	Truncate date

Using Date Functions

Function	Result
MONTHS_BETWEEN ('01-SEP-95','11-JAN-94')	19.6774194
ADD_MONTHS ('31-JAN-96',1)	'29-FEB-96'
NEXT_DAY ('01-SEP-95','FRIDAY')	'08-SEP-95'
LAST_DAY ('01-FEB-95')	'28-FEB-95'

Using ROUND and TRUNC Functions with Dates

Assume SYSDATE = '25-JUL-03':

Function	Result
ROUND (SYSDATE, 'MONTH')	01-AUG-03
ROUND (SYSDATE , 'YEAR')	01-JAN-04
TRUNC (SYSDATE , 'MONTH')	01-JUL-03
TRUNC (SYSDATE , 'YEAR')	01-JAN-03

Quiz

Which of the following statements are true about single-row functions?

1. Manipulate data items
2. Accept arguments and return one value per argument
3. Act on each row that is returned
4. Return one result per set of rows
5. May not modify the data type
6. Can be nested
7. Accept arguments that can be a column or an expression