IT-24027 (1)

```
import java.util.concurrent.atomic.AtomicLong;

public class SubayerThread {
    static final AtomicLong safeStatic = new AtomicLong();
    static long unsafeStatic = 0;

    static class CounterTask implements Runnable {
        long nonStaticCount = 0;
        Counter
        final long increments;
        final boolean threadSafe;

    CounterTask(long increments, boolean threadSafe) {
        this.increments = increments;
        this.threadSafe = threadSafe;
    }

public void run() {
    for (long i = 0; i < increments; i++) {
        nonStaticCount++;
    if (threadSafe) safeStatic.increment();
    }
}
```

IT-24027(2)

```
public static void main(String[] args) throws
InterruptException {
        if (args.length != 3) {
        System.out.println("  ");
        return;
        }
    int threads = Integer.parseInt(args[0]);
    long ines = Long.parseLong(args[1]);

CounterTask[] tasks = new CounterTask[threads]
Threads[] ts = new Thread();
 }
for (Thread t : ts) t.start();
for (Thread t : ts) t.join();
```

IT-24027(A)

```
long staticCount=0;
for (CounterTask t : tasks) nonStatic+= static;

long expected = threads * incs;

System.out.println("Mode :");
System.out.println("Thread :"+ Threads);
System.out.println("Absoulute diff:" +abs);

    }
}
}
```