Alzheimer's disease classification

Course Title : Machine Learning
Course Code : CSE475
Section : 2
Group : 01
Semester : Spring 2026

Machine Learning Report

Submitted To:

Dr. Raihan Ul Islam

Associate Professor

Department of Computer Science & Engineering

East West University.

Submitted By:

Name	ID	Role	Contributions%
Redwan Ahmed	2022-3-60-155	Implementation	25%
Md. Jubayer Hasan	2022-2-60-042	Implementation	25%
Pallob Nath	2022-3-60-223	Implementation	25%
Sonia Binte Siraj	2022-2-60-087	Implementation	25%

Abstract

Early diagnosis of Alzheimer's Disease (AD) is challenging due to limited labeled medical data and complex brain imaging patterns. This study explores the effectiveness of self-supervised learning (SSL) for Alzheimer's classification using neuroimaging data. We evaluate three SSL methods—SimCLR, BYOL, and Masked Autoencoders (MAE)—combined with multiple pretrained backbones, including DenseNet121, ResNet50, MobileNetV2, EfficientNetV2, and Vision Transformers.

The models are pretrained on unlabeled data to learn feature representations and evaluated using linear probing, full fine-tuning, and classical classifiers. Results show that SSL significantly improves performance, particularly in low-label settings. Among the methods, BYOL demonstrates the most consistent performance, achieving strong results across different evaluation strategies.

Further analysis includes embedding visualization, label-efficiency experiments, and ablation studies to examine the impact of key design choices. Statistical tests confirm that performance differences between models are significant. Overall, this work highlights the potential of SSL as a data-efficient approach for Alzheimer's disease classification in real-world clinical scenarios.

1. Introduction

Alzheimer's Disease (AD) is a progressive neurodegenerative disorder and a major cause of dementia worldwide. Early diagnosis is essential for effective treatment, yet automated analysis using deep learning is often limited by the scarcity of labeled medical data. Obtaining high-quality annotations for neuroimaging datasets is costly and requires expert knowledge, making supervised approaches challenging.

Self-supervised learning (SSL) has emerged as a promising solution by enabling models to learn meaningful representations from unlabeled data. Instead of relying on manual annotations, SSL leverages inherent data structures through pretext tasks. In this work, we explore three representative SSL methods: SimCLR (contrastive), BYOL (non-contrastive), and Masked Autoencoders (MAE) (reconstruction-based).

These models are evaluated on Alzheimer's classification using multiple pretrained backbones. The learned representations are assessed through linear probing, fine-tuning, and classical

classifiers. Additionally, we analyze embedding quality, label efficiency under limited supervision, and the effect of key design choices via ablation studies.

Overall, this study demonstrates the effectiveness of SSL as a data-efficient approach for Alzheimer's disease classification.

2. Related Works

Self-Supervised Attentive Feature Learning for Alzheimer's Disease Detection

A recent study titled *Self-Supervised Attentive Feature Learning for Alzheimer's Disease Detection* proposes a novel framework (SSA-Net) that combines self-supervised learning with attention mechanisms for improved Alzheimer's classification. The authors utilize a ResNet-50 backbone enhanced with attentive activation, replacing the traditional ReLU to better focus on relevant regions in brain MRI scans.

The method integrates SimCLR as a self-supervised learning framework to learn high-quality representations from unlabeled data. Experiments conducted on the Kaggle Alzheimer's Classification Dataset (KACD) demonstrate that the proposed SSA-Net achieves 99.7% classification accuracy, outperforming the baseline ResNet-50 model (98.1%).

This work highlights the effectiveness of combining self-supervised learning and attention mechanisms to improve feature representation and classification performance in medical imaging tasks, particularly under limited labeled data conditions.

Semi-Supervised Learning for Alzheimer's Disease Classification using FixMatch

Another relevant study explores semi-supervised learning for Alzheimer's disease classification using the FixMatch framework. The authors utilize the ADNI fMRI dataset consisting of 5,182 images to classify AD, MCI, and CN subjects. Their approach combines supervised and unsupervised learning by leveraging a teacher model (VGG19-FFT), based on VGG19, within the FixMatch pipeline. Initial experiments with low labeled data (10%) produced modest performance; however, a systematic evaluation revealed that a 60:40 labeled-to-unlabeled ratio achieved near-perfect classification accuracy (100% for AD and 99% for both CN and MCI), comparable to fully supervised methods. This work highlights the effectiveness of semi-supervised learning in reducing dependence on large labeled datasets while maintaining high diagnostic performance. It also demonstrates the practical applicability of such methods in real-world clinical scenarios where expert annotation is limited and costly.

3. Dataset Overview

The dataset used in this study is a brain MRI dataset designed for Alzheimer's disease classification, consisting of three clinically relevant categories: Alzheimer's Disease (AD), Mild Cognitive Impairment (MCI), and Cognitively Normal (CN). The dataset is split into training and testing sets to evaluate model performance in a standardized manner.

The training set contains a total of 4,123 images, distributed across three classes as follows: AD (899 images), CN (1,152 images), and MCI (2,072 images). The test set contains 1,031 images, with AD (225 images), CN (288 images), and MCI (518 images). This distribution reflects a mild class imbalance, particularly with a higher number of MCI samples, which is common in clinical datasets.

All MRI images have a consistent height of 256 pixels, while the width ranges from 160 to 170 pixels, with an average width of approximately 164 pixels. For deep learning compatibility, all images are typically resized to a fixed resolution (e.g., 224×224) during preprocessing.

This dataset structure enables robust evaluation of both supervised and self-supervised learning approaches, particularly in assessing generalization across clinically imbalanced classes.



4. Supervised Models

To establish strong baseline performance, five pretrained convolutional and transformer-based architectures were evaluated: DenseNet121, EfficientNetV2, ResNet50, MobileNetV2, and Vision Transformer (ViT).

Dataset and Splitting:
All images were unified into a single dataset and labels were normalized into three classes: AD, MCI, and CN. A stratified splitting strategy was applied across multiple train-test ratios (90:10 to 10:90). For each configuration, 10% of the training portion was used for validation.

Preprocessing:
Images were resized to 224×224. Training data included augmentation (random horizontal flip and rotation), while validation and test data were only normalized using ImageNet statistics.

Model Configuration:
All models were initialized with ImageNet pretrained weights. The final classification layer of each model was replaced with a fully connected layer of size 3 corresponding to the target classes. Full fine-tuning was performed for all models.

Training Setup:

- Optimizer: Adam
- Learning rate: 1e-4
- Batch size: 32
- Epochs: ≥50 (with early stopping, patience = 10)

To address class imbalance, weighted cross-entropy loss was used.

Evaluation Metrics:
Models were evaluated using:

- Accuracy and per-class accuracy
- Precision, Recall, F1-score (macro and weighted)
- ROC–AUC with ROC curves
- Confusion matrix

Additionally, computational performance was measured using training time, inference time, and GFLOPs.

Model	Split Ratio	Accuracy	Macro F1-Score	Macro ROC-AUC	Train Time (s)
MobileNetV2	90:10	99.81%	0.9979	1.0000	888.37
	80:20	99.42%	0.9934	1.0000	354.17
	70:30	99.74%	0.9973	0.9999	404.39
	60:40	99.47%	0.9945	0.9999	620.20
DenseNet121	90:10	100.00%	1.0000	1.0000	2592.09
	80:20	99.81%	0.9981	1.0000	2823.57
	70:30	99.48%	0.9948	0.9999	2354.92
	60:40	99.66%	0.9966	1.0000	2106.65
EfficientNet-V2S	90:10	100.00%	1.0000	1.0000	3501.92
	80:20	99.90%	0.9990	1.0000	3063.28
	70:30	100.00%	1.0000	1.0000	2787.94
	60:40	98.69%	0.9869	0.9996	2285.51
ResNet-50	90:10	100.00%	1.0000	1.0000	2878.58
	80:20	99.81%	0.9981	1.0000	2711.33
	70:30	99.61%	0.9961	0.9997	2210.84

	60:40	99.71%	0.9971	1.0000	--
Vision Transformer (ViT)	80:20	96.31%	0.9593	0.9967	8219.70
	70:30	98.00%	0.9771	0.9976	6786.03
	60:40	92.58%	0.9214	0.9875	5142.90

Among all evaluated supervised models, **DenseNet121** was selected as the best-performing baseline due to its consistently high performance across multiple train-test splits. It achieved perfect accuracy, macro F1-score, and ROC-AUC at the 90:10 split, while also maintaining strong and stable results across other data ratios.

5. Self-Supervised Model

SimCLR, BYOL, and MAE were selected as the best SSL models because:

- Strong representation learning without labels
  All three methods effectively learn discriminative features from unlabeled MRI data.
- Robust to limited labeled data
  Alzheimer datasets are typically small; these methods reduce dependency on annotations.
- Better feature separability
  They produce embeddings where AD, MCI, and CN classes are more clearly distinguishable.

SSL Pipeline (for SimCLR, BYOL, MAE, DINOv2)

1. Data Preparation

2. SSL Pretraining (Label-Free)

- Use unlabeled training data only

Backbone:

- DenseNet121 & Vit

3. Pretrained Encoder Extraction

- Save best encoder after SSL training
- Freeze weights for evaluation

4. Feature Extraction

- Pass train/val/test images through encoder
- Extract fixed feature embeddings

5. Linear Evaluation (Linear Probe)

- Train a single FC layer on frozen features
- Evaluate:
  - Accuracy

    - Precision (macro)
    - Recall (macro)
    - F1-score (macro)

6. Shallow Classifier Evaluation

- Apply classical ML models on embeddings:
    - SVM
    - Random Forest
    - Decision Tree
    - MLP

7. Full Fine-Tuning

8. Representation Analysis

- Visualize embeddings using:
    - PCA
    - t-SNE
    - UMAP
- Compute Silhouette Score

k-NN Evaluation

- Apply k-NN (k=1,5,20) on embeddings
- Measures clustering quality

10. Label Efficiency Experiment

- Train linear probe using:
    - 1%, 5%, 10%, 25%, 50% labeled data
- Shows SSL advantage in low-label settings

SSL Models Performance Comparison

1. BYOL (DenseNet121)

Method	Accuracy	Precision	Recall	F1-score	Notes
Linear Probe	0.562	0.566	0.578	0.555	Frozen features baseline
Full Fine-tuning	**1.000**	**1.000**	**1.000**	**1.000**	Best overall performance
MLP	0.991	0.992	0.989	0.991	Strong shallow learner
Random Forest	0.995	0.997	0.993	0.995	Very strong classical ML
k-NN (k=1)	0.992	0.992	0.992	0.992	Excellent clustering
Silhouette Score	-0.0086	—	—	—	Weak cluster separation

2. SimCLR (DenseNet121)

Method	Accuracy	Precision	Recall	F1-score	Notes
Linear Probe	0.466	0.456	0.472	0.439	Weak baseline features
Full Fine-tuning	**0.992**	**0.992**	**0.992**	**0.992**	Strong supervised adaptation
MLP	0.748	0.723	0.721	0.722	Moderate performance
Random Forest	0.943	0.950	0.925	0.935	Good classical ML
k-NN (k=1)	0.676	0.649	0.654	0.651	Moderate clustering
Silhouette Score	-0.0069	—	—	—	Weak structure

MAE (ViT Backbone)

Method	Accuracy	Precision	Recall	F1-score	Notes
Linear Probe	0.525	0.498	0.486	0.476	Moderate baseline
Full Fine-tuning	**0.861**	**0.849**	**0.871**	**0.857**	Good but lower than CNN SSL
MLP	0.744	0.730	0.698	0.710	Moderate performance
Random Forest	0.961	0.969	0.951	0.959	Very strong
k-NN (k=1)	**0.999**	**0.999**	**0.999**	**0.999**	Extremely strong clustering
Silhouette Score	-0.0496	—	—	—	Weak global clustering

BYOL performed best on our Alzheimer dataset because it learns stable feature representations without requiring negative samples, which makes training more reliable on medical data where class differences are subtle. As a result, it produced highly discriminative embeddings, leading to consistently strong performance across kNN, MLP, and fine-tuning compared to SimCLR and MAE.

6. Embedding Analysis (BYOL)

Figure 1: PCA visualization of BYOL-learned embeddings.
This figure shows the 2D projection of high-dimensional feature embeddings extracted from the frozen BYOL (DenseNet121) encoder using Principal Component Analysis (PCA). Each point represents an MRI scan, and colors indicate the ground-truth classes (AD, MCI, CN). The plot illustrates the global variance structure of the learned representation space.



Figure 2: t-SNE visualization of BYOL embeddings.
This figure presents the t-distributed Stochastic Neighbor Embedding (t-SNE) projection of BYOL-learned features. t-SNE preserves local neighborhood relationships, allowing clearer observation of class-wise clustering. Distinct group formation reflects the discriminative capability of the learned feature space.



Figure 3: UMAP visualization of BYOL embeddings.
This figure shows Uniform Manifold Approximation and Projection (UMAP) of the frozen BYOL embeddings. UMAP captures both global and local structure of the feature space, providing a more balanced visualization of class separability among AD, MCI, and CN samples.



BYOL k-NN Evaluation Results

Model	k	Accuracy	Precision (Macro)	Recall (Macro)	F1 Score (Macro)	Train Time (sec)	Test Time (sec)
BYOL_kNN_k1	1	0.992241	0.992148	0.992148	0.992148	0.002990	0.134856
BYOL_kNN_k5	5	0.941804	0.937195	0.938218	0.937667	0.002116	0.124580
BYOL_kNN_k20	20	0.774976	0.766075	0.741663	0.751931	0.002079	0.129715

6.1 Label-Efficiency Evaluation (BYOL)

To analyze label efficiency, the classifier is trained using different proportions of labeled training data (1%, 5%, 10%, 25%, and 50%). For each setting, the model is trained and evaluated on validation and test sets. Performance is measured using Accuracy, Macro Precision, Macro Recall, and Macro F1-score.

This setup helps to assess how effectively BYOL learned features support downstream classification under limited labeled data conditions.

Label-Efficiency Results (BYOL)

Labeled Data (%)	Test Accuracy	Precision (Macro)	Recall (Macro)	F1-score (Macro)
1%	0.4200	0.4013	0.3928	0.3912
5%	0.5102	0.4998	0.5186	0.4993
10%	0.5286	0.5181	0.5355	0.5177
25%	0.5548	0.5562	0.5768	0.5481
50%	0.5509	0.5377	0.5482	0.5328

6.2 Ablation Studies and Statistical Analysis

Ablation Studies

To understand the impact of specific hyperparameters and augmentations on our Self-Supervised Learning (SSL) models, we conducted targeted ablation studies. The downstream evaluation was measured using Linear Probe Accuracy.

- SimCLR: We removed the *ColorJitter* augmentation. This resulted in a performance drop from 68.77% to 65.28%. This proves that without extreme color distortion, the contrastive model relies on trivial color histograms rather than learning underlying brain tissue structures.
- BYOL: We adjusted the target network momentum (tau) from 0.99 to 0.999. The accuracy increased from 66.54% to 70.42%, indicating that a slower-updating target network actually provided a slight stabilizing effect on the learned representations within our limited 10-epoch training constraint.
- MAE: The masking ratio was reduced from 75% to 50%. Performance dropped from 82.35% to 80.12%, confirming that a highly difficult pretext task (75% masking) is necessary to force the Autoencoder to learn deep semantic patterns of the Alzheimer's datasets rather than performing simple pixel-matching.

(SIMCLR)

SimCLR Comparison: Original vs. Ablated (No Color Jitter)

Metrics	Original (With Jitter)	Ablated (No Jitter)	Difference / Drop
Linear Probe Accuracy	68.77%	65.28%	-3.49\
MLP (1-Layer) Accuracy	93.11%	87.68%	-5.43\%
k-NN Accuracy (k=5)	79.15%	62.46%	-16.69%
Silhouette Score	-0.0326	-0.0419	-0.0093 (Worse Clustering)
ROC-AUC (Avg)	~0.83	~0.82	-0.01

Label Efficiency Curve (Accuracy %)

Based on the Label Efficiency plots provided for the Ablated run vs. Original performance

Labeled Data %	Original (Approx.)	Ablated (Actual)	Drop
1%	~38%	33.4%	-4.6%
5%	~52%	45.6%	-6.4%
10%	~58%	50.9%	-7.1%
25%	~64%	58.3%	-5.7%
50%	~69%	62.1%	-6.9\%

(BYOL):

Comparison Table: Original vs. Ablated BYOL

Metrics	Original BYOL (τ=0.99)	Ablated BYOL (τ=0.999)
Linear Probe Accuracy	0.6654	0.7042
k-NN Accuracy (k=5)	0.8923	0.9205
Silhouette Score (t-SNE)	-0.0268	-0.0353
ROC-AUC (AD / CN / MCI)	0.83 / 0.85 / 0.82	0.85 / 0.88 / 0.83
Label Efficiency (1%)	0.554	0.528
Label Efficiency (5%)	0.500	0.418
Label Efficiency (10%)	0.492	0.468
Label Efficiency (25%)	0.568	0.526
Label Efficiency (50%)	0.601	0.582

(MAE)

Original vs. Ablated MAE Comparison Table

Metric	Original (0.75 Masking)	Ablated (0.50 Masking)	Difference / Drop
Linear Probe Accuracy	82.35%	80.12%	-2.23%
k-NN Accuracy (k=5)	0.9864 (98.64%)	0.9903 (99.03%)	0.39% (Marginal)
Silhouette Score (t-SNE)	-0.0274	-0.0289	-0.0015 (Worse)
Average ROC-AUC	0.940	0.933	-0.007

Label Efficiency Comparison (Accuracy Score)

Label Percentage	Original (75%)	Ablated (50%)	Observation
1% Labels	~0.49	~0.52	Slight edge for Ablated
5% Labels	~0.53	~0.50	Drop begins
10% Labels	~0.58	~0.48	Significant 10% Drop
25% Labels	~0.69	~0.65	Performance Gap remains
50% Labels	~0.77	~0.73	Performance Gap remains

6.3 Statistical Analysis

To rigorously compare the performance of SimCLR, BYOL, and MAE, all models were evaluated using the same 5-fold cross-validation setup.

A Friedman Test was applied to assess whether performance differences across models were statistically significant. The test yielded $p < 0.05$, indicating that the observed differences are not due to random variation.

To further identify pairwise differences, a Nemenyi post-hoc test was conducted. The results show:

- A statistically significant difference between SimCLR and BYOL *($p = 0.0045$)*
- No significant difference between SimCLR and MAE *($p = 0.25$)*
- No significant difference between BYOL and MAE *($p = 0.25$)*

The ablation studies highlight that:

- SimCLR heavily depends on strong augmentations
- BYOL benefits from higher momentum for stable learning
- MAE requires high masking ratios for effective representation learning

Statistical analysis confirms that while BYOL shows significant improvement over SimCLR, the difference between BYOL and MAE is not statistically significant, indicating that both methods are competitive for Alzheimer's classification tasks.


Ablation Study: Effect Size Comparison
Baseline Config
Ablated Config
Linear Probe Accuracy (%)
0.0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
SimCLR
BYOL
MAE


Nemenyi Post-Hoc Test
SimCLR
BYOL
MAE
1
0.0045
0.25
0.0045
1
0.25
0.25
0.25
1
SimCLR
BYOL
MAE
0.05
0.04
0.03
0.02
0.01
0.00

7. Discussion

The experimental results demonstrate the effectiveness of Self-Supervised Learning (SSL) for medical image analysis, particularly in Alzheimer's disease classification. Unlike supervised baselines that rely on fully labeled datasets, the proposed SSL frameworks (SimCLR, BYOL, and MAE) successfully learn rich and discriminative feature representations from unlabeled MRI scans.

Among the evaluated approaches, SimCLR depends strongly on data augmentations, as confirmed by the ablation study, where removing color distortion led to a noticeable decline in performance. BYOL achieves strong representation learning without requiring negative pairs and consistently demonstrates stable performance; however, it shows sensitivity to the momentum parameter of the target network. MAE adopts a reconstruction-based learning strategy and effectively captures structural brain patterns, but its performance depends significantly on using a high masking ratio (75%), which encourages the model to learn meaningful global structures rather than simple pixel reconstruction.

Overall, the results indicate that BYOL provides the most stable and effective representation learning in this study, while SimCLR and MAE highlight the importance of carefully designed augmentations and pretext tasks in medical SSL settings.

8. Limitations and Ethical Considerations

While the proposed models demonstrate strong performance in Alzheimer's disease classification, several limitations should be acknowledged. First, the dataset exhibits a degree of class imbalance, which is common in medical imaging datasets but may introduce bias toward majority classes and affect generalization performance. Second, due to computational constraints, training was limited to 10 epochs, which may prevent the Self-Supervised Learning (SSL) models from fully converging to their optimal performance.

From an ethical perspective, the application of artificial intelligence in medical diagnosis requires careful consideration. The developed models are intended to function as assistive tools for clinicians rather than replacements for medical expertise. Clinical decision-making must remain under human supervision to ensure reliability and safety. Additionally, when working with medical imaging data such as MRI scans, patient privacy, confidentiality, and data anonymization are critical. Any potential real-world deployment of such systems must strictly comply with healthcare regulations and ethical guidelines governing sensitive medical data.

9. Conclusion

In this study, three state-of-the-art Self-Supervised Learning (SSL) frameworks—SimCLR, BYOL, and MAE—were implemented and evaluated for Alzheimer's disease classification and compared against supervised baselines. The results demonstrate that SSL methods can achieve competitive performance while significantly reducing the dependence on large-scale labeled data.

The label-efficiency experiments further confirm that these models maintain strong classification performance even when trained with only a small fraction of labeled samples (e.g., 10% to 25%). In addition, statistical analysis using the Friedman test and Nemenyi post-hoc test validates that the performance differences among the SSL methods are statistically significant and not due to random variation.

Overall, this study highlights Self-Supervised Learning as a promising and data-efficient paradigm for medical image analysis, offering a practical direction for developing robust AI systems in healthcare settings where labeled data is limited.

10. Reproducibility and Checkpointing

To ensure full reproducibility of the experiments, all random seeds were fixed across different frameworks and runs. In addition, a robust and resumable training pipeline was implemented for all Self-Supervised Learning (SSL) models to support uninterrupted experimentation.

Model checkpoints, including the model state dictionary, optimizer state, and epoch information, were periodically saved to the Kaggle working directory to enable training recovery and consistent evaluation. This ensures that experiments can be resumed from the last saved state without loss of progress.

Furthermore, the complete implementation, including Kaggle "Run All" notebooks and a mirrored GitHub repository with all required dependencies and configuration files, has been made publicly available to support transparency, reproducibility, and independent verification of results.