FedRAS: Network-Conditioned Rank Allocation for Federated LoRA

Wenyu Ma[a,b,c], Tao Hu[a,b,c,*], Xinlei Liu[a,b,c]

[a]*Information Engineering University, Zhengzhou 450001, China*
[b]*Key Laboratory of Cyberspace Endogenous Safety and Security of Henan Province, Zhengzhou 450001, China*
[c]*Key Laboratory of Cyberspace Security, Ministry of Education of China, Zhengzhou 450001, China*

Abstract

In mobile-edge federated learning, uplink links are time-varying and deadline-bound, and full-parameter updates frequently miss their deadlines when links degrade. Federated LoRA reduces the payload, but existing systems treat the rank as a training hyperparameter, ignoring the coupling that the rank itself determines the payload and the payload determines the delivery probability: a larger rank buys adaptation capacity but is more likely to miss the deadline. We formalize rank selection and client admission as a joint scheduling problem under deadline constraints and propose FedRAS, which scores every client–rank pair with a payload-conditioned delivery risk and a saturating capacity gain, solves the assignment exactly with a dynamic program under a byte budget and a participation cap, and aggregates heterogeneous ranks with frozen-factor rank masking. The design comes with mechanism-level guarantees: the grid assignment is exact on the stated budget grid, the budget regime in which a per-client greedy rule is already optimal is characterized in closed form, and frozen-factor aggregation of heterogeneous ranks is exact. The gains come from delivering more updates within the deadline rather than from changing training, which is why accuracy remains statistically equivalent while the network-side outcomes improve. To validate overall performance under tight-deadline stress, we conduct experiments on a real federated LoRA trainer. FedRAS delivers 22% more timely updates

*Corresponding author
Email address: hutaondsc@163.com (Tao Hu)

with 23% fewer bytes than fixed rank 16 under deadline stress at statistically equivalent accuracy, while full-parameter updates miss every stress deadline; link-oblivious low-rank schedules trade adaptation capacity for delivery, and FedRAS holds the high-capacity end of that trade-off; and, at 500 clients, exact scheduling beats greedy heuristics whenever the budget binds, at sub-second per-round cost.

Keywords: Federated LoRA, Mobile edge computing, Rank selection, Deadline scheduling, Wireless federated learning

---

1. Introduction

Mobile edge networks increasingly host federated learning (FL) workloads, with clients that include smartphones, vehicles, UAV terminals, and satellite-connected devices [1, 2], spanning IoT deployments [3] and space–air–ground systems [4, 5]. The dominant cost of such systems is the uplink: full-parameter model updates saturate wireless capacity and drain client energy [6], and frequently miss round deadlines when links degrade during handover or outage [7–10]. Low-rank adaptation (LoRA) has therefore become an attractive transmission format, because each adapted layer communicates only two small factor matrices instead of the full weight delta [11–13].

Existing federated LoRA systems, however, treat the rank r as a model hyperparameter, whether fixed across the fleet [14, 15], varied across clients [16, 17], adapted across rounds [18, 19], or personalized through model-heterogeneous and dual-adapter designs [20, 21]. In all of these systems the rank is selected from data and system constraints alone, never from the state of a lossy, deadline-constrained link. This convention ignores a scheduling dimension that is directly visible to the network. The omitted coupling is mechanical: a larger rank transmits more bytes and therefore loses delivery probability exactly where it gains adaptation capacity, while a smaller rank travels light but forfeits capacity on the healthy links that could have carried it. Whether the extra capacity is worth the delivery risk depends on the link state, and no training-side rule observes that state. Each round must therefore decide jointly, under a byte budget and a participation cap, which clients participate and at what rank.

This raises three questions that must be answered. First, how should the delivery probability depend on the rank and the observable link state? The rank directly determines the payload size, and the payload determines

whether an update can meet the deadline on a lossy link, so the delivery model must take the rank as an argument rather than an afterthought. Second, how should the client–rank assignment be solved under budget and participation constraints? The problem is a multiple-choice knapsack with an admission constraint, greedy rules are not necessarily optimal, and one must establish when exact solving is necessary and when it may degrade to a cheap rule. Third, does the resulting adaptation improve network behavior in a real trainer? The scheduling objective is a network-side utility, not the training accuracy, and the two need not agree, so the validation must show that accuracy does not degrade because of the scheduling.

We answer these questions with a delivery model, a grid-based dynamic-programming solver, a rank-selection rule, and a two-tier evaluation, and call the resulting method FedRAS. Our contributions are threefold.

- **FedRAS framework.** We propose FedRAS, to our knowledge the first framework that treats the LoRA rank as a deadline-constrained, network-conditioned, schedulable resource: each round, client admission and rank are decided jointly under a byte budget and a participation cap, with payloads accounted at their real serialized sizes (Section 3).

- **Theoretical analysis.** We prove exactness of the grid assignment (Proposition 1), the budget-feasibility condition under which the cheap per-client rule is already optimal (Proposition 2), and exact frozen-factor aggregation of heterogeneous ranks (Proposition 3), with bounded time and memory cost (Section 5).

- **Experiments and validation.** To answer the third question, we evaluate the design on a real federated LoRA trainer and a 500-client scheduler simulation (Section 6): under deadline stress, FedRAS delivers substantially more updates on time at substantially fewer bytes than fixed rank 16, at statistically equivalent accuracy, while full-model updates miss every stress deadline; the conclusions are robust across datasets, link profiles, and delivery-predictor distortions. Accuracy, timely delivery, and bytes are reported as separate outcomes throughout.

The remainder of this paper is organized as follows. Section 2 reviews related work. Section 3 presents the system model, the adversary and trust

assumptions, and the scheduling formulation. Section 4 describes the FedRAS design and Section 5 its theoretical analysis. Section 6 reports the experimental evaluation, Section 7 discusses interpretation, deployment, and limitations, and Section 8 concludes.

A preliminary poster version of this work studied joint client–protection scheduling for federated learning in space–air–ground mobile networks [22]. This article treats the LoRA rank as the schedulable resource instead, and newly contributes the real-payload delivery-risk and saturating capacity-gain models, an exact grid-based dynamic-programming solver in place of heuristic admission-and-repair logic, frozen-factor masked aggregation for heterogeneous ranks, and the two-tier evaluation pipeline with its solver exactness analysis. All numerical results are produced from this new implementation and cannot be compared against the poster prototype.

2. Related work

2.1. Federated LoRA and heterogeneous-rank adaptation

LoRA freezes a pretrained backbone and learns low-rank increments $\Delta W = BA$ [11]. Federated LoRA trains these adapters across clients. Prior work has studied sparse updates and instruction tuning [12, 13], examined how standard parameter-efficient tuning behaves under the federated setting [15], and pursued personalization through model-heterogeneous or dual-adapter designs [20, 21]. A further line lets the rank vary across clients and aligns heterogeneous ranks for aggregation, by rank self-pruning with sparsity-weighted averaging [16], stacking [23], zero-padded rank alignment [17], or SVD-based dynamic rank allocation [18].

FFA-LoRA [14] froze one factor at its random initialization and showed that this improves stability in privacy-preserving federated fine-tuning. We adopt the same frozen-factor property for a stronger reason. When the frozen factor is identical across clients, averaging the trainable factor gives exact coordinate-wise averaging of the active induced-update slices, as Proposition 3 shows, and each client uploads only that factor. It thereby removes the factor-rotation ambiguity that makes joint factor averaging differ from update averaging. Section 4.4 develops this aggregation.

SA-FedLoRA schedules rank over rounds without conditioning on link state [19]. FedSA-LoRA studies asymmetric factor aggregation with client-local parameters [24]. Across these systems, the rank responds to training progress, parameter importance, or device capability; in none of them is it a

decision variable conditioned on the delivery state of a deadline-constrained link. We evaluate an annealing baseline and joint A/B averaging while making rank a per-round decision conditioned on delivery state and deadline.

2.2. Communication-efficient federated learning

A broad literature reduces FL communication through sparsification [25], quantization [26, 27], quantized compressed sensing [28, 29], and beamformed over-the-air aggregation [30]. These methods compress a given update. Our scheduler selects its rank before transmission, so rank directly affects payload and deadline feasibility. The proposed capacity and delivery models can therefore be combined with other codecs; Section 6.2.4 validates this composition with an FP16 upload.

2.3. Client selection and deadline-aware scheduling

Client selection improves FL efficiency under data, latency, and energy heterogeneity. Oort ranks candidates by a utility that couples data value with system efficiency [31]; FedCS selects clients under explicit resource constraints [32]; TiFL groups clients into latency tiers to bound stragglers [33]; further designs target cost and freshness [34–36]. A second line makes network scheduling deadline- and reliability-aware in mobile and non-terrestrial networks, from client participation [7, 8, 10, 37] to traffic offloading driven by federated reinforcement learning [9]: LESSON admits wireless clients at differentiated frequencies under a latency budget [38], and FedSN coordinates federated training across heterogeneous LEO satellite networks [39]. These methods generally treat update size as fixed: participation is decided for a given payload, not jointly with it. We include an Oort-style selector as a selection baseline. FedRAS chooses participation and update rank together, yielding a multiple-choice knapsack.

2.4. Research gap and positioning

Across these lines, a common interface is missing. The rank-adaptation methods of Section 2.1 decide the rank from training state, parameter importance, or device capability; the selection and deadline-aware methods of Section 2.3 decide participation for a fixed update size. Neither treats the LoRA rank as a schedulable network resource whose payload sets the delivery probability on a lossy link, and none formulates the joint client–rank assignment under byte-budget and deadline constraints. Table 1 positions FedRAS against the closest systems along these dimensions.

Table 1: Positioning against federated LoRA and client-selection systems. ✓ = the property holds in the cited papers' own descriptions; × = absent or not reported. Delivery-aware means that a scheduling or adaptation decision conditions on per-round network delivery state (rate, deadline, delivery probability) rather than on training progress, device capability, or static profiling alone. Real payload means payload is accounted as transmitted bytes rather than a fixed or parameter-count proxy. Real training means model training is executed in the evaluation as reported.

System	Var. rank	Deliv.-aware	Het.-rank agg.	Admis-sion	Joint adm.+rank	Real payload	Real training
FFA-LoRA [14]	×	×	×	×	×	×	✓
SLoRA [12]	×	×	×	×	×	×	✓
FedDPA [21]	×	×	×	×	×	×	✓
HetLoRA [16]	✓	×	✓	×	×	×	✓
HeLoRA [17]	✓	×	✓	×	×	×	✓
FedARA [18]	✓	×	✓	×	×	×	✓
SA-FedLoRA [19]	✓	×	×	×	×	×	×
FedSA-LoRA [24]	×	×	×	×	×	×	✓
Oort [31]	×	×	×	✓	×	×	✓
FedCS [32]	×	✓	×	✓	×	×	✓
TiFL [33]	×	×	×	✓	×	×	✓
LESSON [38]	×	✓	×	✓	×	×	✓
FedSN [39]	×	✓	×	✓	×	×	✓
FedRAS (ours)	✓	✓	✓	✓	✓	✓	✓

The theoretical contribution establishes exactness of the client–rank assignment on the stated budget grid (Proposition 1) and exactness of frozen-factor aggregation (Proposition 3), each with its scope conditions stated where it applies.

3. System model and threat model

3.1. Mobile-edge federated learning architecture and round protocol

We consider a mobile edge network in which an edge aggregator serves a client set $\mathcal{D} = \mathcal{D}_g \cup \mathcal{D}_a \cup \mathcal{D}_s$ of ground clients $\mathcal{D}_g$, aerial and UAV clients $\mathcal{D}_a$, and satellite-connected clients $\mathcal{D}_s$. Ground links are comparatively stable, aerial links face frequent handover, and satellite links suffer long propagation delay, intermittent visibility, and outages [5, 7]. The aggregator holds the global model, schedules every round, and aggregates the timely updates.




Figure 1: FedRAS round pipeline. Action Construction (AC) scores every client–rank pair with the delivery hazard (3) and the saturating capacity (5); the GridDP assignment (GDP) computes the client–rank assignment under the byte budget and the admission cap. Updates arriving within the deadline τ pass the on-time gate and are merged by Masked Aggregation (MA) while the shared factor A stays frozen; observed outcomes update the link-state history. AC, GDP, and MA correspond to Algorithms 2–4; the overall round is Algorithm 1.

Let w^t denote the frozen backbone broadcast at round t. Client i trains LoRA factors $A_{i,\ell}$ and $B_{i,\ell}$ for the adapted layers $\ell \in \mathcal{L}$, with effective weight change $\Delta W_{i,\ell} = B_{i,\ell} A_{i,\ell}$. A rank r update uses the first r columns of $B_{i,\ell}$ and the matching rows of the shared A. Fig. 1 shows the resulting round pipeline. In every round, the aggregator estimates the link states, scores the client–rank actions with Action Construction (AC, Section 4.2), and solves the assignment with the GridDP assignment (GDP, Section 4.3); the admitted clients train locally with their factors sliced to the assigned rank, so only the first r coordinates receive gradient updates, and upload before the deadline τ; the aggregator then merges the timely updates with Masked Aggregation (MA, Section 4.4) and updates its link-state history from the observed outcomes. Late or lost updates are discarded, because stale up-

dates harm convergence stability in deadline-critical federated learning. The experiments evaluate both a homogeneous link profile and a grouped ground–aerial–satellite profile with distinct rate and mobility laws (Section 6).

3.2. Link, mobility, and timely-delivery model

At decision time the scheduler receives an estimated uplink rate $\bar{R}_i^t$ in Mbps and a mobility state. The realized rate R_i^t, handover event $H_i^t \in \{0, 1\}$, and packet loss indicator J_i^t are not observed before transmission. For an update of $B_i^t(r)$ megabytes, the modeled delivery time is

$$T_i^t(r) = T_{\text{train,i}}(r) + T_{\text{proc,i}}(r) + \frac{8B_i^t(r)}{R_i^t} + d_i^t + H_i^t \Delta d_h. \tag{1}$$

Timely delivery is the event

$$P_{\text{on,i}}^t(r) = \Pr\big(T_i^t(r) \le \tau,\ J_i^t = 0 \mid x_i^t\big)\,. \tag{2}$$

Deriving an analytical delivery-time distribution for every term of (1) under real mobility and handover dynamics is non-trivial. We therefore adopt the surrogate hazard model

$$\hat{P}_{\text{on,i}}^t(r) = \exp\big(-\mu_i^t\big)\exp\Big(-\frac{8B_i^t(r)}{\bar{R}_i^t \tau}\Big). \tag{3}$$

The dimensionless intensity μ_i^t summarizes mobility-related failure risk, packet loss, handover effects, and unmodeled processing time. Equation (3) therefore serves as a closed-form plug-in predictor, and the sensitivity and calibration studies of Section 6 quantify how prediction imperfections degrade the scheduling objective. The construction of the estimated states and the sensitivity studies are specified in Section 6; how far the conclusions survive this idealization is delimited in Section 7.

3.3. Rank-dependent payload and adaptation capacity

With b bits per parameter and the frozen factor A shared and never transmitted, a rank-r client uploads only the trainable factor B, whose per-rank cost is the summed output dimension $D = \sum_{\ell \in \mathcal{L}} d_\ell$ of the adapted layers. The real serialized payload is

$$B_i^t(r) = \frac{b}{8}\, r\, D + B_{\text{meta}}, \tag{4}$$

in bytes. Rank is therefore a network-visible resource: it scales both the adaptation capacity and the transmission time, and its per-unit payload is audited against the evaluated model in Section 6. We model the useful contribution of a delivered rank-r update with the saturating capacity gain

$$G_i^t(r) = \pi_i^t \sqrt{\min(r, r_{\max})/r_{\max}}, \tag{5}$$

where π_i^t is a per-client contribution prior in the spirit of Oort-style utility [31]. The width $r_{\max}$ is the factor width provisioned at all clients. The square root encodes the diminishing returns of rank that the delivered-update norms exhibit directly in the trainer (Section 6.2), and the saturation at $r_{\max}$ reflects that wider factors add payload but no expressible capacity once the provisioned width is reached. Full-parameter FedAvg updates are accounted at their true serialized size (Table 2).

3.4. Adversary and trust model

Clients are honest but curious: they follow the training protocol, and raw data never leaves the devices, which is the standing premise of federated learning on this infrastructure. The edge aggregator is trusted scheduling infrastructure: it observes link states, client–rank assignments, and delivered update factors, and runs the aggregation of Section 4.4. The external adversary of interest is an eavesdropper on the wireless uplink who observes the transmitted B factors. Because the frozen factor A is public and a rank-r client transmits only its first r coordinates, the object reconstructable from an intercepted transmission is the rank-r induced update, and the exposed surface is its B-slice: a transmission strictly smaller in bytes and in exposed coordinate count than a joint-factor or full-model update. This reduction in exposed transmission is a communication property; protection mechanisms such as differential-privacy accounting, secure aggregation, and Byzantine robustness compose orthogonally with rank scheduling (Section 7).

3.5. Deadline-constrained client–rank scheduling formulation

Each round, the aggregator decides $a_i^t \in \{0\} \cup \mathcal{R}$, where $a_i^t = 0$ means client i does not participate and $a_i^t = r$ schedules it at rank r. The per-round problem is

$$\max_{\{a_i^t\}} \sum_{i \in \mathcal{D}} \mathbf{1}\{a_i^t > 0\}\, G_i^t(a_i^t)\, P_{\mathrm{on,i}}^t(a_i^t) \tag{6}$$

$$\text{s.t.} \quad \sum_i B_i^t(a_i^t) \le B_{\max}, \qquad \sum_i \mathbf{1}\{a_i^t > 0\} \le K. \tag{7}$$

Algorithm 1 FedRAS Round

Require: clients $\mathcal{D}$, rank set $\mathcal{R}$, cap K, budget $B_{\max}$, deadline τ, link-state history $\mathcal{H}^{t-1}$

Ensure: assignment a^t; new adapter state S^t; updated history $\mathcal{H}^t$

1: estimate per-client link states x_i^t from $\mathcal{H}^{t-1}$
2: score all pairs (i, r): utilities $u_i(r)$ and integer costs $\widetilde{B}_i(r)$ (AC, Algorithm 2)
3: solve the assignment a^t under K and $B_{\max}$ (GDP, Algorithm 3); when the all-$r_{\max}$ profile is budget-feasible, the per-client maximizer rule is already optimal (Proposition 2)
4: broadcast the backbone w^t; admitted clients train locally with factors sliced to a_i^t and upload before τ
5: pass uploads arriving within τ (on-time gate)
6: aggregate timely updates with the frozen shared A (MA, Algorithm 4)
7: append observed outcomes (timely, late, lost) to $\mathcal{H}^t$

The objective is a scheduling utility: expected useful delivered updates under the byte budget $B_{\max}$ and the participation cap K. It is a network-side objective, not a surrogate for final test accuracy; increasing r raises G sublinearly while raising payload and lowering the delivery surrogate. The experiments therefore report test accuracy, timely delivery ratio, bytes per round, and mean delivered rank as separate outcomes (Section 6).

4. FedRAS design

4.1. Overview

Algorithm 1 summarizes one scheduling round as a fixed sequence of three named components. Action Construction (AC, Section 4.2) scores every client–rank pair with a real payload, a delivery probability, and a capacity gain; the GridDP assignment (GDP, Section 4.3) solves the scored assignment exactly under the byte budget and the admission cap, with a cheap per-client rule covering the unconstrained regime; and Masked Aggregation (MA, Section 4.4) merges heterogeneous-rank updates toward the frozen shared factor. Fig. 1 places AC, GDP, and MA in the round pipeline. The design contains no training-side logic: admissions and ranks are chosen from network state alone.

Algorithm 2 Action Construction (AC)

Require: clients $\mathcal{D}$, ranks $\mathcal{R}$, budget grid q, link states $\{x_i^t\}$
Ensure: scored action set $\{u_i(r),\ \widetilde{B}_i(r)\}_{i\in\mathcal{D},\, r\in\mathcal{R}}$

1: **for** each client i and rank r **do**
2: payload $B_i^t(r)$ by (4); integer cost $\widetilde{B}_i(r) \leftarrow \lceil B_i^t(r)/q \rceil$
3: delivery probability $\hat{P}^t_{\mathrm{on,i}}(r)$ by (3); capacity $G_i^t(r)$ by (5)
4: utility $u_i(r) \leftarrow G_i^t(r)\, \hat{P}^t_{\mathrm{on,i}}(r)$
5: **end for**
6: return the scored set; pairs with $\widetilde{B}_i(r) > \widetilde{B}_{\max}$ are infeasible

4.2. Action Construction (AC)

Each round the aggregator selects, for every client, one action from the discrete set $a_i^t \in \{0\} \cup \mathcal{R}$ of Section 3.5. AC builds and scores this action set (Algorithm 2): the per-rank payload follows (4), the delivery hazard (3) and the capacity gain (5) give the estimated utility $u_i(r) = G_i^t(r)\hat{P}^t_{\mathrm{on,i}}(r)$, and a conservative ceiling discretization onto a budget grid q yields the integer cost $\widetilde{B}_i(r) = \lceil B_i^t(r)/q \rceil$. The same grid is applied to the dynamic program, the greedy baselines, and the admission checks, so that every scheduling method optimizes over the identical feasible region. Under this discretization, the single-round estimated problem (6)–(7) is a multiple-choice knapsack with an admission constraint, for which an exact pseudo-polynomial dynamic program exists; the evaluated grid width and its quantization error are quantified in Section 6.3.2.

4.3. GridDP Assignment (GDP)

GDP solves the scored assignment exactly (Algorithm 3). Let $V_i(k, b)$ be the maximum estimated utility from the first i clients with k admissions and integer budget b. Initialize $V_0(0, 0) = 0$ and all other states to $-\infty$. The recurrence is

$$V_i(k,b) = \max\Big\{V_{i-1}(k,b),\ \max_{r\in\mathcal{R}}\big[V_{i-1}(k-1, b-\widetilde{B}_i(r)) + u_i(r)\big]\Big\}, \qquad (8)$$

where $u_i(r) = G_i^t(r)\hat{P}^t_{\mathrm{on,i}}(r)$. Backpointers recover the assignment. Propositions 1 and 2 (Section 5) establish the exactness of this recurrence and the regime in which the per-client maximizer rule $r_i^\star$ is already optimal, in which case GDP reduces to that rule at zero cost.

Algorithm 3 GridDP Assignment (GDP)

Require: scored actions $\{u_i(r), \widetilde{B}_i(r)\}$ from AC, cap K, budget grid $\widetilde{B}_{\max}$
Ensure: client–rank assignment a^t

```
V_0(0,0) ← 0; all other DP states ← −∞
for each client i ∈ D do
    for k = 0, ..., K and each budget state b do
        V_i(k,b) ← skip or best rank transition of (8)
        store the maximizing action as a backpointer
    end for
end for
backtrack from max_{k,b} V_{|D|}(k,b); return a^t
```

4.4. Masked Aggregation (MA)

Clients scheduled at different ranks share an $r_{\max}$ coordinate system. For one adapted layer, client i has sample weight n_i and delivered rank r_i. The factor $A \in \mathbb{R}^{r_{\max} \times k}$ is frozen and shared, while $B_i \in \mathbb{R}^{d \times r_{\max}}$ is trainable. A rank r_i update activates columns 1 through r_i of B_i and the matching rows of A, giving $\Delta W_i = \sum_{j \le r_i} [B_i]_{:,j} [A]_{j,:}$.

Jointly trained factor pairs (A_i, B_i) are identifiable only up to invertible transforms, so separately averaged factors need not average the updates at all. The elevated-learning-rate ablation of Section 6 examines this aggregation rule empirically.

Rank-masked averaging. The server zero-pads inactive columns of each delivered B_i and averages each active coordinate over the clients that activate it,

$$\bar{B}_{:,j} = \frac{1}{W_j} \sum_{i:\, r_i \ge j} n_i \left[B_i\right]_{:,j}, \qquad W_j = \sum_{i:\, r_i \ge j} n_i, \tag{9}$$

while the frozen factor aggregates to itself, $\bar{A} = A$. The server then applies momentum per factor tensor. With $\Delta^t = \bar{B} - S^{t-1}$, the velocity and state update as $v^t = \beta\, v^{t-1} + (1-\beta)\, \Delta^t$ and $S^t = S^{t-1} + v^t$, with damping coefficient β absorbing client-sampling and link noise. Algorithm 4 fixes the procedure; Proposition 3 (Section 5) states its exactness and dilution properties.

Algorithm 4 Masked Aggregation (MA)

Require: timely updates $\{(n_i, B_i, r_i)\}$, frozen shared A, momentum β, previous state S^{t-1}

Ensure: new adapter state S^t

1: **for** each rank column j of each adapted layer **do**
2: $\quad W_j \leftarrow \sum_{i:\, r_i \geq j} n_i; \quad \bar{B}_{:,j} \leftarrow \frac{1}{W_j} \sum_{i:\, r_i \geq j} n_i \, [B_i]_{:,j}$
3: **end for**
4: $\bar{A} \leftarrow A$
5: $\Delta^t \leftarrow \bar{B} - S^{t-1}; \quad v^t \leftarrow \beta \, v^{t-1} + (1-\beta) \, \Delta^t; \quad S^t \leftarrow S^{t-1} + v^t$

5. Theoretical analysis

5.1. Exactness of the DP assignment

Proposition 1 (Per-round optimality)**.** *For every reachable state (k, b), recurrence* (8) *considers the skip action and every feasible rank for client i. Induction on i therefore proves exactness for the discretized single round estimated assignment problem.*

Proof. The admission indicator and the rank of each client are exclusive actions that affect the two resources additively. Admitting client i at rank r consumes one admission slot and $\widetilde{B}_i(r)$ budget units and adds $u_i(r)$ value, independent of the other clients. The state (k, b) therefore summarizes all interaction, and the standard interchange argument for the multiple-choice knapsack applies. Any optimal solution restricted to the first $i-1$ clients must itself be optimal for its state, which the recurrence maximizes. □

Two readings make the statement precise. First, exactness is relative to the discretized problem: the dynamic program returns the best schedule among those the budget grid can express, so any residual gap to the continuous optimum is a quantization error that the grid step controls and Section 6.3.2 measures. Second, and more importantly for practice, exactness localizes the sources of loss. Given the estimated delivery probabilities, no feasible schedule can score higher than the DP output; whatever gap remains between planned and realized performance therefore originates in prediction error or in the round-level abstraction, not in the solver. This separation is what makes the calibration study of Section 6.3.3 interpretable: it perturbs the predictor and observes a smooth, bounded objective loss precisely because the optimization layer contributes no loss of its own.

5.2. Optimality condition of the per-client rule

The formulation also yields a condition under which the cheap per-client rule — admit every candidate and assign each its own maximizer $r_i^\star = \arg\max_{r\in\mathcal{R}} G_i(r)\hat{P}_{\mathrm{on},i}(r)$ — is already optimal, which the trainer experiments of Section 6.2.5 rely on.

Proposition 2 (Cohort-local optimality of the per-client rule)**.** *Consider the single-round problem* (6)–(7) *restricted to a fixed candidate set of at most K clients, and suppose the all-$r_{\max}$ rank profile is budget-feasible, i.e., $\sum_i \widetilde{B}_i(r_{\max}) \le \widetilde{B}_{\max}$ over the candidates. Then the profile that assigns every admitted client its per-client maximizer $r_i^\star = \arg\max_{r\in\mathcal{R}} G_i(r)\hat{P}_{\mathrm{on},i}(r)$ is a feasible optimal solution of the restricted problem.*

Proof. Each candidate's cost is at most its $r_{\max}$ cost, so the per-client maximizer profile satisfies the budget whenever the all-$r_{\max}$ profile does, and, with at most K candidates, it uses no more than the cap. Being feasible, it attains $\sum_i \max_r u_i(r)$, which upper-bounds the objective of every feasible profile; it is therefore optimal. By Proposition 1, the dynamic program returns an optimal profile and hence coincides with the per-client maximizer profile whenever the latter is unique. □

The condition has a direct economic reading: Proposition 2 holds when the budget is not scarce enough to force a sacrifice, that is, when every candidate can take its unconstrained favorite rank. In that regime the objective decomposes across clients, local selfishness is globally optimal, and the scheduler reduces to $|\mathcal{D}|$ table lookups. Greedy rules fail exactly when this condition breaks: once the budget forces trade-offs between clients, the action that is best for one client changes the residual budget available to the others, and no per-client ordering resolves that coupling. The condition is also actionable at run time. Checking $\sum_i \widetilde{B}_i(r_{\max}) \le \widetilde{B}_{\max}$ costs one pass over the candidates, so whenever the candidate pool already fits within the cap K the scheduler can run the cheap rule by default and invoke the dynamic program only when the budget check fails or the pool must be culled below the cap, which is precisely where admission coupling appears — the deployment rule exercised in Sections 6.2.5 and 7.

5.3. Exactness of frozen-factor aggregation

Proposition 3 (Exactness of frozen-factor aggregation)**.** *Under* (9)*, the j-th active rank slice of $\bar{B}A$ is the data-weighted average over clients with $r_i \ge j$.*

This is exact coordinate-wise averaging of active induced-update slices. It is not, in general, the unified data-weighted average of complete client updates. If a common denominator $W = \sum_i n_i$ is used instead of W_j, the unified average is recovered, but active high-rank slices are diluted by W_j/W. The two rules coincide for all possible updates when all delivered ranks are equal.

Proof. The first two parts follow from linearity. For frozen shared A, multiplying a weighted sum of B-coordinates by $\big[A\big]_{j,:}$ converts it into the same weighted sum of the matching update slices, and the two normalizers differ only in W_j versus W. The product $\bar{B}A = \sum_j \bar{B}_{:,j}\big[A\big]_{j,:}$ collects the slices. The third part holds because $W_j = W$ for every active j if and only if $r_i = \max_k r_k$ for all admitted i with $n_i > 0$. □

The frozen factor is what makes heterogeneous ranks commensurable. If both factors rotate per client, the product structure of an update is client-specific and no server-side average of factors corresponds to an average of updates; with A shared, rank slicing acts on B alone and the j-th slice of every delivered update lives in the same coordinates. The two normalizers then embody a genuine choice. The denominator W_j preserves per-slice fidelity: each client's influence on the coordinates it actually sent is proportional to its data. A common denominator W recovers the FedAvg-style data-weighted average but dilutes the slices that only high-rank clients contribute, by the ratio W_j/W. Which is preferable depends on whether one reads the round as averaging updates or as averaging clients; FedRAS takes the former reading, and the two rules coincide whenever delivered ranks do not mix, which the nominal-deadline regime of the experiments satisfies in practice.

5.4. Complexity analysis

The complexity is $O(|\mathcal{D}|K\widetilde{B}_{\max}|\mathcal{R}|)$ time and $O(K\widetilde{B}_{\max})$ memory with rolling value arrays; the back-pointer table retained for reconstruction adds $O(|\mathcal{D}|K\widetilde{B}_{\max})$, where $\widetilde{B}_{\max} = \lceil B_{\max}/q \rceil$. Section 6.3.2 reports the resulting runtimes at 500- and 1000-client scale.

6. Experimental evaluation

The evaluation tests accuracy and network behavior in a real trainer (Section 6.2), scheduling quality at 500 clients and solver cost (Section 6.3.1), and sensitivity to payload, predictor, capacity, and budget-grid assumptions (Sections 6.3.2 and 6.3.3). All byte figures are real serialized sizes, and all deadline regimes are calibrated to those sizes.

6.1. Experimental setup

Environment. The trainer is implemented in PyTorch, and all real-training runs use one NVIDIA A800 GPU.

Datasets and partitions. Experiments use CIFAR-10, CIFAR-100, and MNIST. The real trainer partitions 20 clients non-IID with Dirichlet $\alpha = 0.5$ and samples 10 participants per round; variations of α and of the mobility distribution are reported in Table 4 and Fig. 4.

Backbone and adapters. The backbone is a six-convolution BatchNorm CNN with channel progression 64/128/256, followed by two 256-wide linear layers. It is centrally pretrained with crop, flip, and erase augmentation, Nesterov momentum, weight decay, and cosine learning-rate decay, for 30 epochs on CIFAR-10, 45 on CIFAR-100, and 3 on MNIST, and then frozen, reaching a test accuracy of 0.914, 0.693, and 0.995, respectively. LoRA adapters with candidate rank set $\mathcal{R} = \{2, 4, 8, 16\}$ and provisioned width $r_{\max} = 16$ are placed on all six convolutions through 1×1 factors and on both head layers; a client assigned rank r trains with its factors sliced to the first r coordinates, so the rank genuinely bounds local adaptation capacity.

Federated training hyperparameters. Federated training runs for 40 rounds with one local epoch and batch size 128. Local SGD uses learning rate 0.005, weight decay 10^{-4}, gradient clipping at 1, and cosine decay. The server applies rank-masked weighted averaging with momentum β=0.3, the coefficient of Section 4.4.

Link models. Uplink rates are drawn from LogNormal$(2.5, 0.7)$ clipped to $[1, 40]$ Mbps and mobility from Beta$(2, 5)$, redrawn each round. The mobility draw is the hazard intensity μ_i^t of (3) itself: the study simulates no separate propagation, processing, handover-delay, or packet-loss process, and their contribution is absorbed into μ_i^t; the realized delivery of each update is a Bernoulli draw with probability (3) at the drawn state, so the deployed predictor is also the ground-truth generator and the estimates are oracle (Section 7 delimits this). The grouped ground–aerial–satellite profile assigns 60/25/15% of clients to classes with distinct laws: ground LogNormal$(2.8, 0.5)$ clipped to $[5, 40]$ Mbps with Beta$(2, 8)$ mobility, aerial LogNormal$(2.3, 0.7)$ clipped to $[2, 40]$ Mbps with Beta$(2, 5)$, and satellite LogNormal$(1.6, 0.5)$ clipped to $[0.5, 15]$ Mbps with Beta$(2, 3)$.

Deadline calibration. All deadline regimes are calibrated to the real payloads. The nominal round deadline is 2.0 s, at which transmission time

Table 2: Payload audit of real serialized update sizes. Frozen-A clients upload only the trainable B factor (1,408 parameters per rank column); the A+B column is the joint-training equivalent. The stylized $s(r)$ column lists the protocol reused as a normalized-cost cell in Section 6.3.1.

Rank r	A+B FP32 (MB)	B-only FP32 (MB)	B-only FP16 (MB)	Stylized $s(r)$ (MB)
2	0.021	0.011	0.006	0.54
4	0.041	0.023	0.011	0.58
8	0.082	0.045	0.023	0.66
16	0.164	0.090	0.045	0.82
Full model	5.29 MB FP32 (58.7× the rank-16 B-only upload)			

consumes only 3% of a rank-16 update's delivery probability at the median 12 Mbps rate, while a full-model update already misses 83% of its deadlines. The stress deadlines are 0.1 s and 0.05 s, at which rank-16 timely delivery falls to 0.41 and 0.27 while rank-4 retains 0.62 and 0.57, so downshifting is genuinely load-bearing. A loose 10 s control restores full-model timely delivery to 0.52.

Model and payload audit. The frozen backbone has 1.28M parameters; each adapted layer contributes a frozen-A and a trainable-B slice per rank column, and only B is transmitted. Table 2 lists the audited serialized sizes, and every deadline regime of this study is calibrated against them. The metadata term B_{meta} of (4) is zero in both evaluation tiers, since the server broadcast is not part of the uplink accounting.

Simulator. The 500-client, 150-round scheduler simulation uses the same delivery and capacity models with uniform cohort sampling, per-client rank selection, and budget admission on the same ceiling grid; its payload table (5,632 B per rank column) is identical to the trainer's, and its MB column reports grid-billed payloads on that same ceiling (a rank-16 update is billed 0.10 MB against a true 0.090 MB), since admission and accounting share the discretization. It covers nominal, deadline, budget, mobility, and 1000-client scalability regimes, with five seeds and common traces. Its accuracy column is a bounded scheduling proxy driven by delivered useful value, not a dataset accuracy; the full-update baseline receives the same capacity credit as rank 16 under the saturating model, a disclosed modeling assumption. A separate cell repeats the earlier stylized protocol ($s(r) = 0.02r + 0.5$ MB, rank-64 full-update stand-in, 0.25 s deadline, 12 MB budget) as a normalized-cost sensitivity check.

Scoring proxy. The simulator samples π_i uniformly from $[0.15, 0.45]$ and

uses a bounded scheduling proxy rather than dataset accuracy. Starting at 0.1, it updates as $a^{t+1} = a^t + \eta\hat{g}^t(1-a^t) - \varepsilon a^t + \omega^t$, where $\hat{g}^t$ is useful delivered value normalized by K, $\eta = 0.08$, $\varepsilon = 0.0005$, and $\omega^t \sim \mathcal{N}(0, 5 \times 10^{-4})$ is a small tie-breaking noise. No per-client prior is measured in the trainer experiments, so the trainer capacity term sets π_i=1; the sampled π_i enters only the simulator objective.

Solver study. The solver study runs 30 instances per deadline and budget cell at 500 clients, on a q=0.01 MB ceiling grid. It compares the grid-based DP with value-per-byte greedy, value greedy, a cohort-myopic rule, and fixed rank 16, and adds a client-count sweep that extends to 1000 clients. Budgets are 30 MB (slack), 4 MB, and 1.2 MB; the last admits only twelve rank-16 updates on the ceiling grid of the cap K=25 and is therefore binding.

Baselines. FedRAS is compared against fixed ranks r=4 and r=16, a random-rank policy, and full-model FedAvg updates (referred to as full-model updates throughout, trained at a 0.4× local learning-rate scale; at the shared 1.0× rate the head baseline loses about half a point of accuracy with transient minima near 0.89, so the reduced scale is favorable to the baseline and the comparison is conservative). Three external baselines are included: an SA-FedLoRA-style schedule that heats the rank from 2 to 16 and cools it down over the 40 rounds, oblivious to link state [19]; an Oort-style selector that samples $2K$ candidates and admits the top-K by a data-size-and-recency utility at fixed rank [31]; and joint A/B training with plain averaging, the aggregation-level competitor of Section 4.4 [24]. A delivery-only ablation (reliability-only) removes the capacity term. An offline control (FedAvg without delivery modeling) always aggregates its scheduled updates, bounding the capacity achievable without feasibility constraints. All methods share client partitions, generated link states, deadline, and seed protocol; where applicable they share the local optimizer and rank set.

Scheduling variants. Two deployment variants of the formulation are evaluated. In full grid scheduling, the aggregator solves (6) and (7) over all clients; the solver study evaluates this variant at 500-client scale, and a same-cohort variant restricts the dynamic program to a uniformly sampled cohort, isolating the value of candidate-pool widening from in-cohort rank allocation. In the real trainer, fair-cohort scheduling samples the fixed cohort of ten clients and applies the per-client rank rule $r_i^\star = \arg\max_r G_i^t(r)\hat{P}_{\mathrm{on},i}^t(r)$. Section 6.2.5 compares the variants in the trainer.

Metrics. Four outcomes are reported throughout: test accuracy at round

Table 3: Real-trainer deadline ladder on non-IID CIFAR-10. Nominal and 0.1 s: ten seeds; 0.05 s: five seeds. Accuracy is round-40 test accuracy; timely delivery ratio, bytes per round (rounds 30–39, attempted uplink), and mean delivered rank follow the definitions of Section 6.

	nominal 2.0 s				deadline 0.1 s				deadline 0.05 s			
Method	Acc.	Timely	MB	Rank	Acc.	Timely	MB	Rank	Acc.	Timely	MB	Rank
FedAvg (full model)	$.9135 \pm .0027$	0.17	52.86	—	$.9153 \pm .0015$	0.00	52.86	—	$.9147 \pm .0016$	0.00	52.86	—
FedLoRA r=4	$.9154 \pm .0016$	0.75	0.23	4.0	$.9154 \pm .0016$	0.62	0.23	4	$.9144 \pm .0015$	0.57	0.23	4
FedLoRA r=16	$.9153 \pm .0015$	0.73	0.90	16.0	$.9149 \pm .0019$	0.41	0.90	16	$.9143 \pm .0020$	0.27	0.90	16
Random rank	$.9151 \pm .0016$	0.76	0.42	7.3	$.9153 \pm .0017$	0.56	0.42	6.2	$.9143 \pm .0015$	0.46	0.42	5.7
FedRAS (ours)	$.9153 \pm .0016$	0.73	0.90	16.0	$.9154 \pm .0018$	0.49	0.69	12.7	$.9143 \pm .0014$	0.49	0.44	8.1


40; timely delivery ratio, the timely deliveries of a method divided by its selected clients; bytes per round, counting attempted uplink payloads including late and failed uploads at real serialized sizes; and mean delivered rank over delivered updates. The simulator reports its bounded utility state, the mean delivery probability of admitted clients, and attempted payload totals (Table 8(a)). No sparsification, energy, or fairness metric is claimed in this study; a quantization baseline (FP16 upload) is evaluated in Section 6.2.4.

Statistical protocol. Results use five seeds (0 through 4) with common random numbers within each seed; the CIFAR-10 nominal and 0.1 s regimes, their external baselines, and the scheduling-arm comparison at the nominal deadline use ten seeds (0 through 9). Headline trainer comparisons average the final ten rounds (rounds 30–39). FedRAS versus fixed rank 16 is tested on ten paired seeds: the timely-delivery ratio improves in ten of ten pairs (two-sided Wilcoxon p=0.002), by +22% as the ratio of seed means with a bootstrap 95% confidence interval of the mean paired gain of $[18\%, 29\%]$; the attempted-byte saving is 23% (mean paired saving, $[21\%, 27\%]$, Wilcoxon p=0.002). Accuracy equivalence uses a TOST test fixed in advance at a ± 0.5 percentage-point margin: the mean paired difference is +0.00 percentage points at the nominal deadline and +0.06 points under stress, with $p < 10^{-6}$ in both cases, so equivalence is established. Simulator comparisons without an accompanying test are descriptive.

6.2. Evaluation with the federated LoRA trainer


6.2.1. Accuracy parity and rank invariance

Table 3 reports ten-seed means and standard deviations after 40 federated rounds on CIFAR-10. All LoRA methods hold the backbone accuracy within one standard deviation of 0.914, whether the rank is fixed at 4, fixed at 16, drawn at random, or selected by the rank rule. Full-parameter updates spend




(a) nominal deadline: accuracy

(b) 0.1 s deadline: accuracy



(c) delivered rank per round



(d) accuracy relative to backbone (pp)

Figure 2: Real-trainer experiments (CIFAR-10, means over seeds). (a) At the nominal deadline all rank policies hold the pretrained-backbone accuracy. (b) Under the 0.1 s deadline all methods remain stable while full-model updates deliver nothing and stay at the backbone. (c) FedRAS is link-aware: delivered rank holds the provisioned width at the nominal deadline and steps down as the deadline tightens, against the fixed heat–cool path (gray dashed) that the annealing baseline follows regardless of link state. (d) Final accuracy relative to the per-dataset pretrained backbone; the parity is not CIFAR-10-specific (numbers in Table 4).

orders of magnitude more bytes per round (Table 2) and lose roughly three quarters of their timely deliveries because their payloads rarely fit the round deadline. The cross-dataset results in Fig. 2(d) and Table 4 repeat the parity at 0.693 on CIFAR-100 and 0.995 on MNIST. At the nominal deadline the rank rule selects rank 16 for every client of every round, so FedRAS coincides with fixed rank 16 in bytes and timeliness, and in accuracy up to floating-point nondeterminism; this identity, rather than a tuned advantage, is what the nominal regime is meant to show. Fig. 2(a) shows the corresponding trajectories, stable over the 40 rounds for every rank policy.




Figure 3: Delivered-update norm vs. rank on CIFAR-10 (mean over delivered rounds; five seeds per point, error bars are one standard deviation). The measured growth (2.5× from rank 2 to 16, 1.9× from rank 4 to 16) tracks the square-root capacity law of (5) (2.8× and 2.0×) rather than linear payload growth (8× and 4×); the nominal and stress series coincide.

Delivered-update norms. The capacity law is anchored in measurement: the trainer logs the mean Frobenius norm of each round's delivered updates, and across the full candidate set the measured growth tracks the $\sqrt{r}$ law of (5) — 2.5× from rank 2 to 16 against 2.8× predicted, and 1.9× from rank 4 to 16 against 2.0× — with the stress series coinciding with the nominal one (Fig. 3). The diminishing returns that (5) prices are a measured property of the delivered updates, not a modeling assumption.

6.2.2. Deadline stress

Delivered-rank adaptation. Table 3 tightens the deadline to 0.1 s and 0.05 s. Three effects emerge. First, FedRAS downshifts under pressure. Its delivered mean rank falls from 16.0 at the nominal deadline to 12.7 at 0.1 s and 8.1 at 0.05 s, where the delivery hazard (3) makes rank-16 payloads marginal. Second, downshifting pays. At 0.1 s, FedRAS delivers 0.49 timely updates against 0.41 for fixed rank 16 while transmitting 0.69 MB against 0.90 MB, i.e., 23% fewer bytes; at 0.05 s the gap widens to 0.49 against 0.27 timely deliveries at 51% fewer bytes. Third, full-parameter updates collapse completely. Their timely delivery ratio is 0.00 at both stress deadlines, so not a single full-size update arrives on time in any seed; the reported stress accuracy of this row is within one standard deviation of the per-seed pretrained backbone (0.914 ± 0.002 across seeds), whose spread explains the nonzero standard deviation.

Why downshifting dominates. Payload grows linearly in the rank while delivery probability falls convexly once transmission time approaches the deadline, so the scheduler buys delivery probability where it is cheap and holds high rank where it is free. In this regime the binding constraint on learning is delivery, not adaptation capacity, which is why the delivered rank moves while accuracy stays at parity.

Against low-rank baselines. The same cells place the remaining policies on one delivery–capacity trade-off: random-rank, Oort-style, and annealed schedules deliver *more* timely updates at *fewer* bytes than FedRAS (Table 3; Fig. 2c) while holding delivered ranks of 5.0–8.0 against FedRAS's 12.7. FedRAS holds delivery comparable to the selection baselines at roughly twice their delivered rank-16 capacity; dominance over them is not claimed. Whether preserved capacity converts into accuracy in regimes where capacity matters is tested in Section 6.2.7.

Mechanism and replication. Accuracy spreads remain within about two standard deviations, consistent with parity; the scheduling metrics are where the methods separate (Fig. 2(b),(c)): FedRAS holds the provisioned width under the nominal deadline and steps down as the deadline tightens, whereas the annealed baseline follows its fixed heat–cool path regardless of link state. All headline differences replicate across the ten paired seeds at conventional significance levels, with the statistics fixed in advance (Section 6).

6.2.3. Extended stress matrix

Table 4 extends the study along further axes. A mobility-only scenario with Beta$(0.7, 5)$ mobility at the nominal deadline leaves all LoRA policies at parity, so mobility alone does not force downshifting at this deadline. Extreme label heterogeneity with α=0.1 reveals a second-order effect: rank-16 updates lose 0.32 percentage points relative to rank 4, consistent with capacity-amplified client drift, and full-parameter updates lose the most. FedRAS follows the rank-16 trajectory here, so a heterogeneity-aware downshift is a natural extension. Loosening the deadline to 10 s restores full-model timely delivery to 0.52 without changing any LoRA accuracy. Repeating the 0.1 s deadline on CIFAR-100 and MNIST reproduces the CIFAR-10 stress picture. The scheduling conclusions are therefore not dataset-specific; Fig. 4 shows the matching sensitivity sweeps over provisioned width, cohort size, and α. Per-decision scheduling cost is negligible in all these settings: the per-client rank rule costs sub-millisecond per decision, orders of magnitude




Figure 4: Sensitivity of the trainer to provisioned adapter width, cohort size, and label heterogeneity on CIFAR-10 with FedRAS (five seeds per variant; the nominal reference column uses ten seeds). Accuracy is flat in $r_{\max}$ and cohort size, with a second-order drop only at α=0.1; the dominant effect of all three axes is on bytes and delivered updates (red, right axis).

Table 4: Extended stress matrix of the real trainer (round-40 accuracy, five seeds). The mobility-only and α=1.0 scenarios probe extreme conditions; the last rows repeat the 0.1 s deadline on CIFAR-100 and MNIST.

Scenario	FedAvg	r=4	r=16	Random	FedRAS
deadline 10 s	0.9134	0.9144	0.9145	0.9141	0.9143
mobility 0.7	0.9115	0.9143	0.9141	0.9145	0.9141
α=0.1	0.9022	0.9139	0.9107	0.9130	0.9109
α=1.0	0.9142	0.9143	0.9144	0.9141	0.9144
CIFAR-100, 2.0 s	0.6925	0.6928	0.6926	0.6926	0.6929
CIFAR-100, 0.1 s	0.6927	0.6927	0.6929	0.6927	0.6928
MNIST, 2.0 s	0.9947	0.9949	0.9951	0.9950	0.9951
MNIST, 0.1 s	0.9947	0.9949	0.9950	0.9949	0.9950

below the full grid-scheduling DP of Section 6.3.2.

SAGIN link profile. Grouping the 20 clients into ground, aerial, and satellite classes with distinct rate and mobility laws reproduces the aggregate parity at the nominal deadline while exposing the expected per-class structure: timely delivery is 0.71 for ground, 0.61 for aerial, and 0.49 for satellite clients. At this deadline the scheduler holds rank 16 across all classes, so the class gap reflects the link laws alone rather than rank allocation. The profile shows that the scheduler responds sensibly to client-class heterogeneity.

6.2.4. External baselines

Baseline behavior. Table 5 reports the three external baselines of the setup in the real trainer. The link-oblivious annealing schedule settles at low rank and therefore buys timely delivery at the lowest byte cost among

Table 5: External baselines in the real trainer, ten seeds. The FP16 rows use the FP16 serialized sizes of Table 2.

	nominal 2.0 s				deadline 0.1 s			
Method	Acc.	Timely	MB	Rank	Acc.	Timely	MB	Rank
SA-FedLoRA-style annealing	$.9154 \pm .0016$	0.75	0.29	5.1	$.9153 \pm .0016$	0.62	0.29	5.0
Oort-style utility, fixed rank	$.9150 \pm .0020$	0.76	0.45	8.0	$.9149 \pm .0019$	0.54	0.45	8.0
Joint A/B, plain averaging	$.9152 \pm .0016$	0.73	0.90	16	$.9148 \pm .0019$	0.41	0.90	16
FedLoRA r=16, FP16 upload	$.9153 \pm .0027$	0.77	0.45	16	$.9145 \pm .0021$	0.65	0.45	16
FedRAS, FP16 upload	$.9161 \pm .0016$	0.77	0.45	16	$.9156 \pm .0014$	0.71	0.36	12.8

the baselines, but it cannot increase rank when links improve. The Oort-style selector improves selection at fixed rank. Joint A/B training matches frozen-factor training at the adopted learning rate, and the ablations find no stability separation at an elevated learning rate either, so the case for the frozen factor rests on exactness and upload reduction rather than on an observed stability gap.

Compression baseline. A fixed rank-16 policy with an FP16 upload (two bytes per parameter, real round-trip quantization on delivery) halves the payload and, at the 0.1 s deadline, delivers 0.65 timely updates at 0.45 MB — more timely updates than any FP32 schedule at the same rank (Table 5). Stacking FedRAS on the same format extends the gain: FedRAS-FP16 beats FP16 rank 16 in five of five seed pairs (+9% timely, −21% bytes, p=0.062 each, the minimum possible at five seeds) at equal accuracy. Compression re-prices every rank; the scheduler re-optimizes the assignment under the prices that hold.

6.2.5. Scheduling variants

Arms under evaluation. To attribute the value of exact scheduling, the three arms defined in the setup are compared in the real trainer, over ten seeds at the nominal deadline and five seeds under stress. The full grid arm solves the GridDP assignment (Section 4.3) over the entire 20-client population under the participation cap and a 1.0 MB budget, which equals ten rank-16 grid costs, so the budget binds only through downshifting or skipping. The same-cohort arm draws the identical cohort as fair cohort and restricts the same dynamic program to those candidates.

Where exactness pays. Table 6 yields a clean decomposition. At the nominal deadline, the same-cohort DP coincides exactly with the per-client argmax rule, as Proposition 2 predicts; the full DP's timely-delivery gain (+9 percentage points) comes entirely from admission over the wider candi-

Table 6: Scheduling arms in the real trainer (1.0 MB budget; the FedLoRA r=16 reference is in Table 3). Nominal: ten seeds; stress 0.1 s: five seeds.

	nominal 2.0 s, ten seeds				stress 0.1 s, five seeds			
Arm	Acc.	Timely	MB	Rank	Acc.	Timely	MB	Rank
Full DP (grid assignment)	$.9151 \pm .0016$	0.82	0.90	16.0	$.9138 \pm .0011$	0.55	0.87	15.4
Same-cohort DP	$.9152 \pm .0019$	0.73	0.90	16.0	$.9139 \pm .0014$	0.51	0.70	12.7
Fair cohort (FedRAS rule)	$.9153 \pm .0016$	0.73	0.90	16.0	$.9144 \pm .0018$	0.51	0.70	13.0

date pool. Under the 0.1 s deadline the pattern persists: the in-cohort DP matches the argmax rule, while the full DP delivers more timely updates at proportionally more bytes. Exactness therefore pays through admission control over a heterogeneous pool, not through rank allocation inside a cohort (Proposition 2). This delimits when full grid scheduling is worth its coordination cost.

6.2.6. Component ablations

Component contributions. Table 7 reports component ablations at the nominal deadline. In the parity regime, no removal measurably changes final accuracy, which is consistent with the claim that accuracy is carried by the backbone and not by the scheduler. The components instead shape scheduling behavior and aggregation correctness. Removing the capacity term collapses FedRAS to the minimum rank, the degenerate delivery-only policy that the capacity term exists to prevent; its capacity cost is invisible at nominal deadlines but material in the simulator, where reliability-only optimization loses 28 points of utility against rank 16 (Table 8(a)). Removing server momentum is accuracy-neutral here. The rank mask itself is network-metric-neutral at fixed rank policy: with the random-rank rule at the 0.1 s deadline, masked and unmasked aggregation give 0.9143 and 0.9145 final accuracy with identical byte and timeliness profiles. The mask is nonetheless what keeps heterogeneous-rank aggregation per-slice exact whenever ranks mix, as Proposition 3 states, and its absence dilutes high-rank coordinates under mixed-rank rounds.

Stability at elevated learning rate. Under the elevated learning rate of 0.02, the frozen-factor rule and joint A/B training are statistically indistinguishable, with final accuracies of 0.9130 and 0.9132 and transient minima of 0.913 and 0.912 across rounds and seeds. The frozen-factor rule is therefore justified by the exactness of Proposition 3 and by its single-factor uploads, not by an empirical stability margin at this scale.




Figure 5: Weak-backbone capacity payoff (one-epoch pretrain, five seeds). (a) Nominal deadline: the rank–accuracy coupling appears (rank 16 above rank 4 by 2.1 points) and FedRAS coincides with rank 16; the dashed line marks the pretrained backbone. (b) Stress deadline (0.1 s): FedRAS lands between the fixed ranks on accuracy while delivering more updates than rank 16 at 20% fewer bytes; annotations give attempted MB per round and mean delivered rank.

6.2.7. Weak-backbone capacity payoff

When capacity becomes valuable. The strong-backbone regime makes adaptation capacity free, so preserving rank carries no measurable benefit (Section 6.2). Weakening the backbone to a one-epoch pretrain (backbone accuracy 0.530) breaks that regime: federated adaptation now improves on the pretrained weights by roughly three and a half points, and the rank–accuracy coupling appears at the nominal deadline (Fig. 5a), where rank 16 reaches 0.564 against rank 4's 0.543 over five paired seeds (+2.1 points, Wilcoxon p=0.062, the minimum possible at five seeds), with FedRAS coinciding with rank 16. Under the 0.1 s deadline the coupling persists (+2.7 points for rank 16 over rank 4) and the scheduler prices it without any retuning (Fig. 5b): FedRAS holds a delivered rank of 12.8, finishes 1.4 points above rank 4 (five of five pairs), and gives back 1.4 points to fixed rank 16 in exchange for a 13% higher timely-delivery ratio and 20% fewer bytes. Preserved capacity therefore converts into accuracy exactly when the backbone is weak enough to need adaptation, which is the regime in which a rank scheduler has a reason to exist.

6.3. Large-scale scheduling simulation

6.3.1. Scheduler behavior across operating regimes

Regime comparison. Table 8(a) summarizes the simulator across regimes at the final round. In the nominal regime, FedRAS matches fixed

Table 7: Component ablations of the real trainer at the nominal deadline (five seeds). Min. is the minimum over rounds of the per-round seed-mean accuracy in the elevated-learning-rate check (lr 0.02).

Configuration	Accuracy	Min.
Full system (ours)	$.9144 \pm .0013$	—
w/o capacity term	$.9145 \pm .0014$	—
w/o frozen A (joint A/B)	$.9144 \pm .0015$	—
w/o rank mask (random ranks, 0.1 s)	$.9145 \pm .0016$	—
w/o server momentum	$.9143 \pm .0013$	—
frozen A, lr 0.02	$.9130 \pm .0012$	0.913
joint A/B, lr 0.02	$.9132 \pm .0012$	0.912

rank 16 and dominates every low-rank policy. Under the 0.1 s deadline, FedRAS leads fixed rank 16 at 21% fewer bytes, and full-model updates deliver nothing. Under the binding 1.2 MB budget, full-model updates cannot be admitted even once, while FedRAS and rank 16 tie. The mobility-stress and 1000-client regimes show the same pattern (Fig. 7): FedRAS and fixed rank 16 coincide at the top of the utility column, so scheduling separates only where deadlines or budgets bind. A final cell repeats the stylized protocol of the earlier literature: with the $s(r)$ payload model the ordering is preserved, confirming that the conclusions are not an artifact of the payload accounting.

Where the simulator gain comes from. Fixed rank 16 spends uniformly — weak-link clients miss deadlines while strong-link clients are underserved — whereas FedRAS reallocates, holding high ranks where delivery survives them and downshifting or skipping the rest. Reliability-only optimization fails the other way, buying timely delivery with capacity. The dynamic program between these extremes prices capacity and delivery in a common unit, and the grid makes the resulting knapsack exactly solvable.

Trajectories. Fig. 6 shows the nominal and 0.1 s trajectories, and Fig. 7 the network-side view across regimes. Across the reported regimes, FedRAS is numerically best or tied for best in the utility column of Table 8(a), with the reliability-only and annealed policies retaining a timely-delivery lead bought at substantially lower delivered capacity.

Table 8: Experiments at 500-client scale (five seeds unless noted). (a) Scheduler simulation across regimes; the utility column is the bounded scheduling utility of Section 6 and must not be read as dataset accuracy, MB is the attempted uplink payload of admitted clients in the final round billed on the same 0.01 MB ceiling grid as budget admission, and FedAvg refers to full-model updates at their real serialized size. (b) Solver study with K=25 and 30 instances per cell on the identical ceiling grid; the table reports heuristic objective loss relative to the grid-based DP and DP runtime.

(a) Scheduler simulation across regimes

	Nominal 2.0 s			Deadline 0.1 s			Budget 1.2 MB		
Method	Util.	Timely	MB	Util.	Timely	MB	Util.	Timely	MB
FedAvg (full)	.310	.34	26.5	.093	.00	26.5	.093	.00	0.0
r=4	.744	.75	0.8	.689	.64	0.8	.744	.75	0.8
r=16	.914	.73	2.5	.763	.42	2.5	.797	.76	1.2
Random	.816	.75	1.3	.709	.57	1.3	.803	.75	1.2
Reliability-only	.635	.76	0.5	.606	.70	0.5	.635	.76	0.5
SA-annealing	.842	.76	0.5	.730	.70	0.5	.796	.76	0.5
FedRAS (ours)	.914	.73	2.5	**.781**	.50	2.0	**.797**	.76	1.2

(b) Solver study

Deadline (s)	Budget (MB)	Greedy val/byte	Greedy value	Cohort myopic	Fixed r=16	DP time (ms)
2.0	30	63.6%	0.0%	40.9%	0.0%	421
2.0	4	63.6%	0.0%	40.9%	0.0%	51
2.0	1.2	47.8%	28.4%	48.9%	28.4%	23
1.0	30	62.7%	0.0%	40.0%	0.0%	415
1.0	4	62.7%	0.0%	43.0%	0.0%	51
1.0	1.2	47.3%	29.3%	48.3%	29.3%	23
0.1	30	52.8%	0.0%	51.9%	0.0%	415
0.1	4	52.6%	0.0%	52.0%	0.0%	51
0.1	1.2	41.0%	36.0%	54.8%	36.0%	23




Figure 6: Scheduler simulation utility-state trajectories (mean over five seeds). (a) Nominal 2.0 s deadline, where FedRAS matches fixed rank 16. (b) 0.1 s deadline, where FedRAS downshifting separates from fixed rank 16.




Figure 7: Timely delivery ratio and attempted bytes per method across simulator regimes, including the 1000-client scalability regime (five-seed means, final round). Full-model updates deliver nothing under stress and cannot be admitted at all under the binding budget.

6.3.2. Solver optimality and runtime

Heuristic gaps and runtime. Table 8(b) reports the scheduling study with the identical ceiling discretization for the DP and every heuristic. When the byte budget is slack, value greedy and the fixed rank-16 rule are already optimal, so the choice of scheduler matters little; the value-per-byte greedy, by contrast, collapses to a smallest-rank preference and already loses up to 63.6% of the objective in the slack cells. The interesting regimes are the binding ones: once the budget binds, every heuristic loses a substantial fraction of the objective — up to 54.8% for the cohort-myopic rule — while the DP reaches the optimum of the discretized single-round estimated problem in every cell. Its runtime is sub-second for 500 clients across the evaluated grid widths and scales linearly to 1000 clients, as Fig. 8 shows, which is




Figure 8: Solver study. (a) Objective loss of the heuristics relative to the DP across deadline and budget cells. (b) DP runtime scaling with the client population.

compatible with per-round scheduling at minute-scale FL rounds.

Why the heuristics fail where they do. The failure modes are structural rather than numerical, and both were already visible in the models. Value-per-byte pricing divides a capacity gain that saturates with rank (Section 3) by a payload that grows linearly in (4), so its ratio favors the smallest rank regardless of link state. Fixed rank 16 and value greedy fail only under scarcity, where choosing which candidates to drop is precisely the admission coupling that per-client rules cannot resolve (Section 5). The DP runtime follows the budget grid width rather than the client count, which is why it is fastest under exactly the binding budgets that need it most.

Grid sweep. A dedicated grid sweep around the default step bounds the quantization error at about 3% in the binding regime and below 1% in slack regimes; a finer step reduces it further at a known runtime cost. The grid exactness claim of Section 5 therefore applies to a grid whose quantization error is bounded, measured, and adjustable.

6.3.3. Delivery-predictor sensitivity

The calibration study of Fig. 9 measures both the fidelity of the deployed predictor and the scheduling cost of its errors (500 clients). With the oracle link state of the setup, the hazard-form predictor (3) is calibrated by construction. Deliberately distorted variants — power distortions of the predicted probability and multiplicative lognormal noise — are measurably miscalibrated, yet the resulting assignment-objective loss, evaluated under the true probabilities, stays below 1% in every cell. The loss follows the structure of the error: power distortions cost most under the stress deadline, where rank ordering matters most, while noise costs most in the nominal slack cell,




Figure 9: Delivery-predictor calibration study (500 clients, 150 round-instances per cell). Left: reliability at the 0.1 s deadline; with oracle link state the hazard-form predictor is calibrated by construction, while the power-distorted (γ) and noisy variants are measurably miscalibrated. Right: assignment-objective loss of optimizing against the distorted predictor, evaluated under true probabilities, at most 1% in every cell.

where it perturbs an otherwise near-uniform rank preference. Mis-prediction therefore degrades the objective smoothly rather than catastrophically, and the observed delivery outcomes of Algorithm 1 are exactly the signal from which a per-client predictor would be recalibrated.

Cross-tier summary. Taken together, the two evaluation tiers give a consistent picture. Rank choice does not measurably change accuracy for the frozen backbone at the 40-round horizon, and the headline comparisons against fixed rank 16 pass the TOST equivalence test fixed in advance at the ± 0.5 percentage-point margin; an offline control that ignores delivery modeling entirely and trains on every scheduled update reaches 0.913 ± 0.002 at the nominal deadline, close to the backbone's 0.914, separating learning capacity from delivery feasibility. The methods instead separate on the network side: FedRAS holds high ranks on healthy links and downshifts under pressure, full-parameter updates collapse once deadlines bind at real payload sizes, and the exact scheduler pays through admission over the candidate pool rather than in-cohort rank allocation (Proposition 2). Two stress tests bound these claims from both sides: the network-side gains survive stacking on an FP16 codec (Section 6.2.4), and a weaker backbone reveals accuracy value in the preserved capacity exactly where the strong-backbone regime shows none (Section 6.2.7). These tests rest on ten-seed replications of the headline trainer regimes; they support the stated network-side comparisons and the accuracy equivalence. Section 7 interprets these findings, states their scope conditions, and translates them into deployment guidance.

7. Discussion and limitations

7.1. Interpretation and deployment considerations

Why the gains are network-side. The trainer demonstrates parity and equivalence, not rank-dependent accuracy gains. With a strong frozen backbone and 40 adaptation rounds, transmitted rank does not measurably change test accuracy, because the accuracy is carried by the pretrained features while the scheduler shapes which updates arrive on time and at what byte cost. Claims that low rank limits adaptation quality would require longer horizons, weaker backbones, or distribution-shifted clients.

When FedRAS does not help. Three settings bound the method's value. First, when the candidate pool fits within the participation cap and the budget accommodates every candidate at the provisioned width, FedRAS reduces exactly to fixed rank 16 (Proposition 2): the scheduling layer adds coordination cost and nothing else. FedRAS is therefore worth its coordination cost when deadlines are tight relative to real payloads or when the byte budget binds; outside those regimes, fixed rank 16 is the identical and simpler choice. Second, under extreme label heterogeneity, higher ranks lose accuracy relative to low ranks through capacity-amplified client drift, and FedRAS follows the high-rank trajectory and inherits that loss; conditioning the capacity term $G(r)$ on measured heterogeneity is left as future work. Third, under tight deadlines the weakest client class still delivers least, because downshifting protects delivery but cannot create link capacity.

Deployment recipe. The results translate into four planning rules for a practitioner. First, calibrate the deadline ladder from the real payload of the widest provisioned rank, so that the nominal deadline leaves rank $r_{\max}$ near-constraint-free while at least one stress deadline drives its timely delivery below one half. Second, size the byte budget at ten times the grid cost of rank $r_{\max}$, which forces the budget to bind only through downshifting or skipping. Third, implement Proposition 2 as a runtime switch rather than a design-time choice: one pass over the candidate pool checks whether the pool fits the cap and whether the all-$r_{\max}$ profile fits the budget; if both hold, the per-client argmax rule runs and the dynamic program is skipped, and only a failing check pays for exact scheduling. Logging the check's pass rate over rounds also tells an operator which regime a deployment is in — a check that always passes means the scheduler is inert at fixed rank, so an operator who expects scheduling gains should retune the budget or the deadline calibration, not the scheduler. Fourth, treat the delivery predictor

as a monitored plug-in rather than a modeling investment: since distorted predictors cost at most about 1% of the assignment objective (Fig. 9), a lightweight per-client calibrator updated from observed delivery outcomes, with a drift alarm on its calibration error, is sufficient engineering; per-client deep predictors are not required at this objective scale.

Coordination cost and integration. FedRAS is an aggregator-side module and leaves client training untouched: clients receive their assigned rank with the round schedule, slice their factors to it, and run the local objective as before. The scheduler's inputs are the estimated uplink rates, the link-state history, and the payload table of the provisioned width; its outputs are the admission and rank decisions attached to the schedule. The aggregation change is confined to the rank mask of Section 4.4, a masked average rather than a new protocol. Its failure modes are bounded: a degraded predictor degrades the objective smoothly (Fig. 9) rather than derailing the schedule, and if link-state estimates are unavailable altogether the scheduler falls back to fixed $r_{\max}$, which Proposition 2 identifies as optimal in exactly that unconstrained regime.

7.2. Scope and limitations

Scope of claims. The results describe network-side gains in the evaluated frozen-backbone setting; they must not be read as universal accuracy gains. The simulator capacity model is a scheduling abstraction, and its accuracy column is a bounded scheduling proxy rather than a measured dataset accuracy.

Backbone pretraining. The centralized pretraining stage is a documented premise inherited from parameter-efficient FL practice; the federated phase adapts but does not train the backbone. Where no server-side corpus exists, self-supervised or public-data pretraining would be needed, and the parity result should be re-verified.

Estimator assumptions. The hazard-form delivery model (3) assumes the closed-form exponential realization, and the experiments supply generated link states as oracle estimates; training and processing times are included in the conceptual delivery model (1) but are not separately measured. Production deployments should calibrate P_{on} per client from observed outcomes, for example with isotonic or Platt scaling monitored by a Brier score, and the scheduler treats the predictor as a plug-in. Calibration on measured wireless traces remains open.

Myopia. The analysis is deliberately per-round (Section 5), and the guarantees are confined to the discretized single-round assignment and to frozen-factor aggregation; a horizon-aware policy that shifts admissions across rounds as budgets carry over and mobility correlates is a natural extension.

Evaluation horizon and topology. The trainer conclusions are horizon-bound: forty adaptation rounds on a strong frozen backbone is precisely the regime in which rank choice is accuracy-neutral, and longer horizons, weaker backbones, or distribution-shifted clients could re-open an accuracy gap that the equivalence tests employed here cannot see. The evaluation also assumes a star topology with a trusted aggregator that collects estimated link states and computes the schedule. Nothing in the formulation requires clients to report state beyond the delivery outcomes any FL round makes observable, but a decentralized or aggregator-less variant would need a different synchronization point and is not studied here.

Security. The adversary and trust assumptions are stated in Section 3.4. This work proposes no protection mechanism and makes no privacy claim; differential-privacy accounting, secure aggregation, and Byzantine robustness compose orthogonally with rank scheduling [40, 41].

Generality. The trainer validates adapters on convolutional and linear layers of a CNN at $r_{\max}$=16 with 20 clients, and the simulator extends the population to 1000, both under synthetic link distributions. Extension to transformer backbones, measured rather than synthetic links, and larger rank sets may change the payload slope, capacity curve, and empirical conclusions. The formulation can be tested in those settings. The study does not measure energy, system overhead beyond scheduler runtime, or client fairness and therefore makes no claim about those properties.

8. Conclusion

This paper asked what a network scheduler can do with the LoRA rank once the rank is treated as a network-visible resource accounted at its real serialized size, and the answer turned out to be a network-side one. Across both evaluation tiers, choosing the rank per client and per round left backbone accuracy unchanged within an equivalence margin fixed in advance, yet under deadline stress it delivered markedly more updates on time at markedly fewer bytes than a fixed rank, while link-oblivious low-rank schedules sat at

the opposite, low-capacity end of the same trade-off. The value of exact solving proved localizable and regime-bound: the dynamic program earned its cost through admission across a heterogeneous candidate pool rather than through in-cohort rank allocation, and only where deadlines or budgets bind — in slack regimes the scheduler degenerates to fixed-rank operation, which is the identical and simpler choice. The scheduler also proved forgiving of its own premise: distorted delivery predictions degraded the objective smoothly rather than catastrophically. Rank scheduling in federated LoRA is thus best read as deadline and budget engineering on the network side of the exchange, with training left untouched.

Several directions follow directly from what this study bounds but does not resolve. Horizon-aware scheduling that carries budgets across rounds and exploits mobility correlation would move beyond the per-round analysis. Per-client delivery predictors calibrated on measured wireless traces would replace the generated link states used here and turn the plug-in predictor of the deployment recipe into a monitored component. Composition with protection mechanisms is enabled by the reduced exposed transmission of the rank-sliced upload, but the interaction of privacy noise and accounting with the rank choice remains unexamined. Heterogeneity-aware capacity terms would address the drift amplification observed under extreme label skew. Finally, transformer backbones, measured rather than synthetic link laws, and wider rank sets would test how the payload slope and the capacity curve shape the regime in which rank scheduling pays — the question this paper reduced to a checkable condition.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgements

The authors thank the members of the Information Engineering University research group for many useful discussions and for hands-on assistance with the experimental implementation.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

CRediT authorship contribution statement

Wenyu Ma: Methodology, Software, Validation, Investigation, Writing – original draft. **Tao Hu:** Conceptualization, Formal analysis, Supervision, Writing – review and editing. **Xinlei Liu:** Data curation, Investigation, Visualization. All authors approved the submitted version and accept responsibility for the work.

Data availability

The reproducibility package accompanying this submission contains the complete source code (trainer, simulator, solver, and analysis scripts), per-run configuration files, per-seed result tables, and the raw training logs supporting every table and figure in this study; a permanent repository DOI will be supplied at publication.

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

During the preparation of this work the authors used AI-assisted tools for language editing and formatting support. The authors reviewed and edited all generated material and take full responsibility for the content of the published article.

References

[1] H. B. McMahan, E. Moore, D. Ramage, S. Hampson, B. A. y Arcas, Communication-efficient learning of deep networks from decentralized data, in: Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS), 2017, pp. 1273–1282.

[2] P. Kairouz, H. B. McMahan, B. Avent, A. Bellet, M. Bennis, A. N. Bhagoji, K. Bonawitz, Z. Charles, G. Cormode, R. Cummings, R. G. L.

D'Oliveira, H. Eichner, S. E. Rouayheb, D. Evans, J. Gardner, Z. Garrett, A. Gascón, B. Ghazi, P. B. Gibbons, M. Gruteser, Z. Harchaoui, C. He, L. He, Z. Huo, B. Hutchinson, J. Hsu, M. Jaggi, T. Javidi, G. Joshi, M. Khodak, J. Konečný, A. Korolova, F. Koushanfar, S. Koyejo, T. Lepoint, Y. Liu, P. Mittal, M. Mohri, R. Nock, A. Özgür, R. Pagh, M. Raykova, H. Qi, D. Ramage, R. Raskar, D. Song, W. Song, S. U. Stich, Z. Sun, A. T. Suresh, F. Tramèr, P. Vepakomma, J. Wang, L. Xiong, Z. Xu, Q. Yang, F. X. Yu, H. Yu, S. Zhao, Advances and open problems in federated learning, Foundations and Trends in Machine Learning 14 (1–2) (2021) 1–210. doi:10.1561/2200000083.

[3] D. C. Nguyen, M. Ding, P. N. Pathirana, A. Seneviratne, J. Li, H. V. Poor, Federated learning for internet of things: A comprehensive survey, IEEE Communications Surveys & Tutorials 23 (3) (2021) 1622–1658. doi:10.1109/COMST.2021.3075439.

[4] J. Liu, Y. Shi, Z. M. Fadlullah, N. Kato, Space-air-ground integrated network: A survey, IEEE Communications Surveys & Tutorials 20 (4) (2018) 2714–2741. doi:10.1109/COMST.2018.2841996.

[5] S. Mahboob, L. Liu, Revolutionizing future connectivity: A contemporary survey on ai-empowered satellite-based non-terrestrial networks in 6g, IEEE Communications Surveys & Tutorials 26 (2) (2024) 1279–1321. doi:10.1109/COMST.2023.3347145.

[6] R. Hamdi, M. Chen, A. Ben Said, M. Qaraqe, H. V. Poor, Federated learning over energy harvesting wireless networks, IEEE Internet of Things Journal 9 (1) (2022) 92–103. doi:10.1109/JIOT.2021.3089054.

[7] N. Razmi, B. Matthiesen, A. Dekorsy, P. Popovski, Ground-assisted federated learning in leo satellite constellations, IEEE Wireless Communications Letters 11 (4) (2022) 717–721. doi:10.1109/LWC.2022.3141120.

[8] F. Tang, C. Wen, X. Chen, N. Kato, Federated learning for intelligent transmission with space-air-ground integrated network toward 6g, IEEE Network 37 (2) (2023) 198–204. doi:10.1109/MNET.104.2100615.

[9] Y. Qin, Y. Yang, F. Tang, X. Yao, M. Zhao, N. Kato, Differentiated federated reinforcement learning based traffic offloading on space-air-ground integrated networks, IEEE Transactions on Mobile Computing 23 (12) (2024) 11000–11013. doi:10.1109/TMC.2024.3389011.

[10] M. Ribero, H. Vikalo, G. de Veciana, Federated learning under intermittent client availability and time-varying communication constraints, IEEE Journal of Selected Topics in Signal Processing 17 (1) (2023) 98–111. doi:10.1109/JSTSP.2022.3224590.

[11] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, W. Chen, LoRA: Low-rank adaptation of large language models, in: International Conference on Learning Representations (ICLR), 2022.

[12] S. Babakniya, A. R. Elkordy, Y. H. Ezzeldin, Q. Liu, K.-B. Song, M. El-Khamy, S. Avestimehr, SLoRA: Federated parameter efficient fine-tuning of language models, in: International Workshop on Federated Learning in the Age of Foundation Models (FedLLM), 2023, arXiv:2308.06522.

[13] J. Zhang, S. Vahidian, M. Kuo, C. Li, R. Zhang, T. Yu, G. Wang, Y. Zhang, Y. Chen, H. Li, Towards building the federated GPT: Federated instruction tuning, in: IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2024, pp. 6915–6919. doi:10.1109/ICASSP48485.2024.10447454.

[14] Y. Sun, Z. Li, Y. Li, B. Ding, Improving LoRA in privacy-preserving federated learning, in: International Conference on Learning Representations (ICLR), 2024.

[15] Z. Zhang, Y. Yang, Y. Dai, Q. Wang, Y. Yu, L. Qu, Z. Xu, FedPETuning: When federated learning meets the parameter-efficient tuning methods of pre-trained language models, in: Findings of the Association for Computational Linguistics: ACL 2023, 2023, pp. 9963–9977. doi:10.18653/v1/2023.findings-acl.632.

[16] Y. J. Cho, L. Liu, Z. Xu, A. Fahrezi, G. Joshi, Heterogeneous LoRA for federated fine-tuning of on-device foundation models, in: Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2024, pp. 12903–12913. doi:10.18653/v1/2024.emnlp-main.717.

[17] B. Fan, X. Su, S. Tarkoma, P. Hui, HeLoRA: LoRA-heterogeneous federated fine-tuning for foundation models, ACM Transactions on Internet Technology 25 (2) (2025) 11:1–11:22. doi:10.1145/3723877.

[18] F. Wu, J. Hu, G. Min, S. Wang, Adaptive rank allocation for federated parameter-efficient fine-tuning of language models, IEEE Transactions on Computers 75 (4) (2026) 1650–1663. doi:10.1109/TC.2026.3655161.

[19] Y. Yang, X. Liu, T. Gao, X. Xu, G. Wang, SA-FedLoRA: Adaptive parameter allocation for efficient federated learning with LoRA tuning, arXiv preprint arXiv:2405.09394v1 (2024).

[20] L. Yi, H. Zhang, H. Yu, G. Wang, X. Liu, Q. Hu, pFedLoRA: Model-heterogeneous personalized federated learning with homogeneous low-rank adapter sharing on mobile edge devices, IEEE Transactions on Mobile Computing 25 (9) (2026) 13898–13911. doi:10.1109/TMC.2026.3674996.

[21] Y. Yang, G. Long, T. Shen, J. Jiang, M. Blumenstein, Dual-personalizing adapter for federated foundation models, in: Advances in Neural Information Processing Systems 37 (NeurIPS), 2024.

[22] W. Ma, T. Hu, X. Liu, Mobility-predictive risk-budgeted protection selection for federated learning in space–air–ground mobile networks, in: Proceedings of the ACM International Conference on Modeling, Analysis and Simulation of Wireless and Mobile Systems (MSWiM), 2026, accepted poster paper; publication details to be updated when available.

[23] Z. Wang, Z. Gu, J. Weng, X. Shang, J. Li, J. Li, K. Wan, FLoRA: Federated fine-tuning large language models with heterogeneous low-rank adaptations, in: Advances in Neural Information Processing Systems (NeurIPS), 2024.

[24] P. Guo, S. Zeng, Y. Wang, Y. Fang, W. Huang, S. Liu, D. Guo, Selective aggregation for low-rank adaptation in federated learning, in: International Conference on Learning Representations (ICLR), 2025.

[25] Y. Lin, S. Han, H. Mao, Y. Wang, W. J. Dally, Deep gradient compression: Reducing the communication bandwidth for distributed training, in: International Conference on Learning Representations, 2018.

[26] H. Liu, F. He, G. Cao, Communication-efficient federated learning for heterogeneous edge devices based on adaptive gradient quantization, in: Proceedings of IEEE INFOCOM, 2023, pp. 1–10. doi:10.1109/INFOCOM53939.2023.10228970.

[27] A. Reisizadeh, A. Mokhtari, H. Hassani, A. Jadbabaie, R. Pedarsani, Fedpaq: A communication-efficient federated learning method with periodic averaging and quantization, in: Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics, Vol. 108 of Proceedings of Machine Learning Research, PMLR, 2020, pp. 2021–2031.

[28] Y. Oh, N. Lee, Y.-S. Jeon, H. V. Poor, Communication-efficient federated learning via quantized compressed sensing, IEEE Transactions on Wireless Communications 22 (2) (2023) 1087–1100. doi:10.1109/TWC.2022.3201207.

[29] Y. Oh, Y.-S. Jeon, M. Chen, W. Saad, Fedvqcs: Federated learning via vector quantized compressed sensing, IEEE Transactions on Wireless Communications 23 (3) (2024) 1755–1770. doi:10.1109/TWC.2023.3291877.

[30] M. Kim, A. L. Swindlehurst, D. Park, Beamforming vector design and device selection in over-the-air federated learning, IEEE Transactions on Wireless Communications 22 (11) (2023) 7464–7477. doi:10.1109/TWC.2023.3251339.

[31] F. Lai, X. Zhu, H. V. Madhyastha, M. Chowdhury, Oort: Efficient federated learning via guided participant selection, in: Proceedings of the 15th USENIX Symposium on Operating Systems Design and Implementation (OSDI), 2021, pp. 19–35.

[32] T. Nishio, R. Yonetani, Client selection for federated learning with heterogeneous resources in mobile edge, in: IEEE International Conference on Communications (ICC), 2019. doi:10.1109/ICC.2019.8761315.

[33] Z. Chai, A. Ali, S. Zawad, S. Truex, A. Anwar, N. Baracaldo, Y. Zhou, H. Ludwig, F. Yan, Y. Cheng, TiFL: A tier-based federated learning system, in: Proceedings of the 29th International Symposium on High-Performance Parallel and Distributed Computing (HPDC), 2020. doi:10.1145/3369583.3392686.

[34] X. Chen, X. Zhou, H. Zhang, M. Sun, H. V. Poor, Client selection for wireless federated learning with data and latency heterogeneity, IEEE Internet of Things Journal 11 (19) (2024) 32183–32196. doi:10.1109/JIOT.2024.3425757.

[35] L. Dong, Y. Zhou, L. Liu, Y. Qi, Y. Zhang, Age of information based client selection for wireless federated learning with diversified learning capabilities, IEEE Transactions on Mobile Computing 23 (12) (2024) 14934–14945. doi:10.1109/TMC.2024.3450549.

[36] B. Luo, X. Li, S. Wang, J. Huang, L. Tassiulas, Cost-effective federated learning in mobile edge networks, IEEE Journal on Selected Areas in Communications 39 (12) (2021) 3606–3621. doi:10.1109/JSAC.2021.3118436.

[37] D.-J. Han, W. Fang, S. Hosseinalipour, M. Chiang, C. G. Brinton, Orchestrating federated learning in space-air-ground integrated networks: Adaptive data offloading and seamless handover, IEEE Journal on Selected Areas in Communications 42 (12) (2024) 3505–3520. doi:10.1109/JSAC.2024.3459090.

[38] L. Yu, X. Sun, R. Albelaihi, C. Yi, Latency-aware semi-synchronous client selection and model aggregation for wireless federated learning, Future Internet 15 (11) (2023) 352. doi:10.3390/fi15110352.

[39] Z. Lin, Z. Chen, Z. Fang, X. Chen, X. Wang, Y. Gao, FedSN: A federated learning framework over heterogeneous LEO satellite networks, IEEE Transactions on Mobile Computing 24 (3) (2025) 1293–1307. doi:10.1109/TMC.2024.3481275.

[40] K. Bonawitz, V. Ivanov, B. Kreuter, A. Marcedone, H. B. McMahan, S. Patel, D. Ramage, A. Segal, K. Seth, Practical secure aggregation for privacy-preserving machine learning, in: Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security (CCS), 2017, pp. 1175–1191. doi:10.1145/3133956.3133982.

[41] K. Wei, J. Li, C. Ma, M. Ding, W. Chen, J. Wu, M. Tao, H. V. Poor, Personalized federated learning with differential privacy and convergence guarantee, IEEE Transactions on Information Forensics and Security 18 (2023) 4488–4503. doi:10.1109/TIFS.2023.3293417.