Typical Project's Health, Safety & Environmental Manganate System Plans & Procedures

Traffic Management Plan

HSE-DHR-003-1

DIJLAH RIVER COMPANY

For General Contracting Ltd.

This procedure / plan and all its content are part of the HSEMS of Dijlah River, all HSEMS documents are controlled copies, you are advised to seek the last version of it and all required information form the document controller, it may contain confidential information, re-transmission dissemination, distribution, printing or copying of this Document or any part thereof by any mean (electronically or mechanically) is strictly prohibited

REV	DATE	DESCRIPTION	PREPARED BY	CHECKED BY	APPROVED BY
			NAME &SIGN	NAME & SIGN	NAME & SIGN
		Issued for IMP			

REVISION HISTORY

REV.	DATE	DESCRIPTION OF CHANGE
0	19 Oct. 2024	ESTABLISHED / ISSUED FOR IMPLEMENTATION
		REVISED /ISSUED FOR IMPLEMENTATION

Table of Contents

1.0 PURPOSE **4**

2.0 SCOPE **4**

3.0 REFERENCES **4**

4.0 DEFINITION AND ABBREVIATION **4**

4.1 Definitions **4**

4.2 Abbreviation **5**

5.0 ROLES AND RESPONSIBILITIES **5**

5.1 Project Manager **5**

5.2 HSE Manager / Supervisor **5**

5.3 Traffic Safety Supervisor **6**

5.4 Drivers **6**

5.5 Maintenance Team **7**

5.6 Passengers **7**

6.0 TRAFFIC MANAGEMENT PLAN **7**

6.1 Requirements for Drivers **7**

6.2 Requirements for Driving **7**

6.3 Driver Hours and Rest Periods **8**

6.4 Maximum Speed Limits **8**

7.0 VEHICLE **9**

7.1 General requirement for Vehicles **9**

7.2 Requirements for Vehicles **9**

A- Light Vehicles 9

B- Heavy Goods Vehicles 10

C- Trailers 11

8.0 RECORD **11**

9.0 ATTACHMENT **12**

1.0 PURPOSE

This traffic Management Plan is a part of and a supporting document to the Project Execution Plan, providing an overview of the HSE component of the Project Management Systems and execution of HSE activities on the PROJECT. This Plan applies to all Dijlah River employees and SUBCONTRACTORS of the PROJECT.

2.0 SCOPE

The scope of this Plan is to define the HSE requirement and practices that shall be followed by all personnel involved in the PROJECT.

3.0 REFERENCES

- National Laws and Regulations
- Dijlah River HSEMS
- Project HSE Plan

4.0 DEFINITION AND ABBREVIATION

4.1 Definitions

PROJECT:	The Ongoing Project
COMPANY:	The Client Company
CONTRACTOR:	Dijlah River for engineering services and trading agencies Ltd (Dijlah River)
SUBCONTRACTOR:	Any company or person to whom CONTRACTOR or any of its subcontractors has subcontracted any part of the work.
MANUFACTURER/SUPPLIER/VENDOR:	Any person or COMPANY engaged by the Contractor to manufacture and/or supply Installation Equipment or other equipment and material for the PROJECT
"must":	It signifies a legal or statutory requirement
"shall":	It signifies a requirement made mandatory by this specification

4.2 Abbreviation

HSE	Health Safety Environment
HGV	Heavy Goods Vehicle
ABS	Anti-Lock Braking Systems
PTO	Power Take Off

5.0 ROLES AND RESPONSIBILITIES

5.1 Project Manager

- The Project Manager has the overall responsibilities for the facilitation of implementation of HSSE as described in this procedure;
- Take appropriate action when notified of disregard on site of the Safety Officer's advice or other unsafe conditions.

5.2 HSE Manager / Supervisor

- Discipline, re-educate and/or train any member of Staff failing to discharge satisfactorily their responsibilities for Safety, Security, Health and Environment;
- Check the Procedure regularly-and assist, when necessary, in the resolving of difficulties that arise in this regard;
- Discipline staff who do not comply with the requirements of this procedure;
- Ensure that all vehicles are safe, maintained and serviced as recommended and that all necessary tests, insurances, licenses, etc., are up to date, and in compliance with local requirements.
- Ensure that all drivers are in possession of the appropriate driving licenses or permits and that they are aware of any special requirements and restrictions that may be applicable.
- Ensure drivers are provided with any necessary safety equipment.
- Arrange for any necessary special training for drivers.

5.3 Traffic Safety Supervisor

- Read and understand Dijlah River's Policy on Safety, Security, Health and Environment and ensure that it is brought to the notice of all employees under your control.
- Ensure that all vehicles are safe and fully efficient, are maintained and serviced as recommended and that all necessary tests, insurances, licenses, etc., are up to date, and in compliance with local requirements.
- Ensure that all drivers are in possession of the appropriate driving license or permits and that they are aware of any special requirements and restrictions that may be applicable.
- Ensure that all defects reported are reported to immediately
- Ensure drivers are provided with necessary safety equipment.
- Give instructions where necessary on the safety of loads, in particular ensure all procedures are followed when hazardous loads are to be carried. Notify all appropriate authorities as required when moving large or unusual loads.
- Arrange for any necessary special training for drivers.
- Ensure that appropriate welfare facilities are provided and maintained for drivers.
- Ensure that vehicles are parked safely in the yard at the end of shift.
- Co-operate with HSSE Officer and act on his recommendations.
- Ensure that Fuels are stored and dispensed safely and in accordance with relevant statutory requirements.
- Ensure that Fire Protection measures are provided and maintained.
- Ensure First Aid facilities are provided and maintained.
- Ensure all accidents are reported as required by Dijlah River's Procedures.
- Set a personal example by using and wearing any necessary protective clothing, when appropriate.

5.4 Drivers

- Read and understand the COMPANY's HSE Policy and carry out work in accordance with its requirements.
- Ensure that any defect in vehicle is reported immediately to Foreman or Traffic Safety Supervisor.
- Make monthly inspections of the vehicle together with Traffic Safety Supervisor, also daily inspection of vehicle at the beginning of each shift should be made.
- Wear suitable safety footwear and protective clothing when not in the cab of the vehicle.
- Drive in a safe manner at all times and be particularly careful when driving on site taking into consideration the conditions of temporary access roads or roads that are under construction and being used for access purposes, pedestrians and construction activities.
- Report all accidents or damage, however minor, to the Project Management.
- Drivers are required to exercise care at all times and to comply strictly with all local traffic laws.
- Drivers and Passengers should wear seatbelts at all times when the Vehicle is in motion.

- Attend HSE trainings when requested.
- Comply with No-alcohol/No drugs policy.
- Do not use mobile phone/walkie-talkie while driving, follow the speed limit and use seat belt.

5.5 Maintenance Team

- Maintenance Personnel Should Follow lockout/tag-out procedures;
- Keep work area clean;
- Properly handle, store and dispose hazardous materials;
- Seek solid ground for lifting equipment;
- Use only approved proper tools and wear proper personal protective equipment.
- While working under vehicle do not rely on jack- use manufactured supports (not bricks).
- Maintain each vehicle's maintenance/inspection record.

5.6 Passengers

- Fasten seat belt before the vehicle was started to move.
- Supervise driver's driving behavior.
- Put forward reasonable suggestion for safety driving.

6.0 TRAFFIC MANAGEMENT PLAN

6.1 Requirements for Drivers

All drivers employed by the project shall be authorized to operate the vehicles to which they are assigned. Only drivers who have the proper license and permit by the Iraq authorities may drive the vehicle.

- Drivers shall be familiar with traffic rules and various traffic signs and signals of Iraq.
- Drivers shall be familiar with the function of their vehicles and be capable of checking and dealing with the engine malfunctions, brake adjustments and tire repair.
- Drivers should have valid driver certificate.

6.2 Requirements for Driving

- All vehicle occupants shall always be in a driver or passenger seat and wearing a seatbelt.
- The driver shall not put the vehicle into motion until all occupants have fastened their seatbelts. Every person of a vehicle shall wear a 3-point inertia reel seat belt.
- Drivers shall wear suitable sturdy footwear whilst driving.
- Drivers shall remove ignition keys from the vehicle when it is not in use.
- Safety devices (i.e. safety belts) shall not be tampered with. Appropriate disciplinary action shall be taken against those who do so.
- Drivers shall be rested, medically fit and not under the influence of alcohol or drugs, including those prescription medicines which can cause drowsiness.
- Drivers shall obey traffic signs at all times.

- Drivers shall carry out pre-trip checks on their vehicles prior to driving
- It is not permitted to carry loose items in the passenger cabins of a vehicle.
- Loads shall be secured.
- Number of passengers shall not exceed maximum number specified in the vehicle's technical specification.
- Transportation of personnel in the cargo compartments shall be strictly forbidden.

6.3 Driver Hours and Rest Periods

In order to ensure the drivers taking a good rest in a proper area they shall follow:

- Light vehicle drivers shall take 15 minutes' rest after 2 hours of continuous driving.
- Heavy Vehicle and bus (light and heavy bus) drivers shall take a minimum of 15 minutes' rest after 2 hours of continuous driving.
- Drivers shall not work more than a 12-hour shift period. The shift period shall include loading, unloading, any other work, compulsory rest time, waiting and driving time.
- Drivers shall drive a maximum of 10 hours within the 12-hour shift period.
- Drivers experiencing tiredness or fatigue, when driving, shall take additional rest as required.
- Rest shall not be taken on the ground underneath a vehicle or its trailer. Rest compartments that are slung under trailers shall be acceptable. Over-night rest during a journey shall not be taken within the vehicle cab, unless it is a sleeper cab.

6.4 Maximum Speed Limits

- Reduce speed according to prevailing road, traffic and environmental/weather conditions.
- Not exceed any sign posted speed limits.
- Not exceed the following maximum speed limits at any time:

Vehicle Type	Maximum Speed Limit (km/h) *	
Light Vehicle	Paved	80
	Gravel	60
	Rural carts road	50
Heavy Goods Vehicle	Paved	70
	Gravel	60
	Rural carts road	40
Bus	Paved	70
	Gravel	50
	Rural carts road	40
*Where posted sign indicates lower speed limit, it shall be followed regardless of the guideline on the table		

7.0 VEHICLE

7.1 General requirement for Vehicles

The requirements relating to vehicles of the different types used in Dijlah River operations are given. Vehicle types are:

- Light Vehicle
- Heavy Vehicle
- Bus
- Trailer

Basic requirements are given for each vehicle type for use on paved roads and additional requirements listed for vehicles used on graded roads. Further standards are included for vehicles used off road. Requirements for special vehicles are also listed. Special vehicles include tanker vehicles. All vehicles shall be maintained to at least manufacturers recommended standards.

7.2 Requirements for Vehicles

A- Light Vehicles

- Comply with the Laws and Standards of Iraq
- Be suitable for operation in ambient temperatures of up to 55 ºC
- No modification may be made to any vehicle without endorsement from the vehicle manufacturer or the local agent.
- Tires, including spares, of the same manufacturer, type, profile and tread pattern, except when the vehicle or tire manufacturer recommends a different type for certain axles.
- Tire type and pattern shall be recommended by the vehicle or tire manufacturer for use on the vehicle in Iraq,
- Be fitted with a spare wheel and equipment to safely change a wheel.
- 3-point seat belts for all the seats.
- Shall not be fitted with inward facing or folding seats.
- Signs, stickers or labels shall be fitted in such a manner that they do not obstruct the driver's vision or impede the driver's use of any controls.
- No decorative fittings mounted or hung inside the cab, or outside the vehicle which can obscure the driver's view.
- All light vehicles should be equipped with airbags for both the driver and front seat passenger.
- Fitted dry powder fire extinguisher The fire extinguisher shall be securely mounted on a bracket and located so that it is easily accessible in an emergency.
- Fitted with a securely stowed first aid kit
- Carry a minimum of one hazard warning triangle. Vehicles that are more than 2 meters wide shall carry a minimum of two.

B- Heavy Goods Vehicles

- Comply with the Laws and Standards of Iraq
- Be suitable for operation in ambient temperatures of up to 55 ºC
- No modification may be made to any vehicle without endorsement from the vehicle manufacturer or the local agent.
- Tires, including spares, of the same manufacturer, type, profile and tread pattern, except when the vehicle or tire manufacturer recommends a different type for certain axles.
- Tire type and pattern shall be recommended by the vehicle or tire manufacturer for use on the vehicle in Iraq,
- Be fitted with a spare wheel and equipment to safely change a wheel.
- 3-point seat belts for all the seats.
- The vehicle retarder which may be an exhaust brake.
- A dual-circuit, dual-line service brake system with a secondary braking system, and (for vehicles which will tow a trailer) two-line or three-line color coded trailer brake system fittings. All braking systems to be fail-safe in the event of loss of air pressure.
- Have the maximum payload details (in kilos) of a cargo or load area painted or applied so that it is clearly visible to persons loading the vehicle The maximum payload details shall be applied on both sides of the vehicle, except on prime-movers.
- Signs, stickers or labels shall be fitted in such a manner that they do not obstruct the driver's vision or impede the driver's use of any controls.
- No decorative fittings mounted or hung inside the cab, or outside the vehicle which can obscure the driver's view.
- A storage box for tools and auxiliary lashing equipment.
- Rigid HGVs and heavy trailers shall be fitted with a heavy-duty rear bumper.
- A band of alternate yellow and black chevrons, 150mm high, shall be painted across the entire rear width of the HGV, except on prime-movers.
- Fitted with an in-cab fire extinguisher The fire extinguisher shall be securely mounted on a bracket and located so that it is easily accessible in an emergency.
- Fitted with a securely stowed first aid kit. Be equipped with sufficient number of wheel stoppers.
- Carry a minimum of two hazard warning triangles Each hazard warning triangle shall be no less than 440mm wide and 440mm tall, and shall not weigh less than 1 kg.
- Fitted with Towing equipment by the vehicle manufacturer or shall comply with relevant international standards.
- Fitted with a rear mounted audible reversing alarm audible from 8 meters.

Civil, Electrical and Mechanical

C- Trailers

- Comply with the Laws, and Vehicle Standards of Iraq.
- To be suitable for operation in ambient temperatures of up to 55 ºC.
- Fitted with required fire extinguishers, toolkits, spare wheels and other accessories securely mounted.
- Have radial tires with a minimum tread depth of 1.6mm across 75% of the tire width.
- At least one spare wheel, securely mounted. (The spare wheels on the prime-mover are acceptable if the trailer wheels are the same size).
- Semi-trailer and trailer platforms for general cargo use shall be approximately level when coupled to the prime mover or the towing vehicle.
- The maximum payload details shall be displayed on both sides of the trailer.
- A band of painted alternate yellow and black chevrons on the bumper, at least 150mm high, across the entire rear width of the vehicle.
- Lighting which includes rear lights, brake lights and indicator/hazard warning lights, tail lights.
- Have a 'look down lens' in the rear window or a wide-angle mirror mounted at the rear of the vehicle.
- Fitted with a rear mounted audible reversing alarm.

8.0 RECORD

Dijlah River shall keep a proper, good maintain record on site for Client check / audit, this record shall be kept for all project life span, for each driver / operator and vehicle the list below shall available on site all time.

- Drivers' driving license copies.
- Drivers' training record.
- Drivers' medical record.
- Vehicle monthly maintenance record.

9.0 ATTACHMENT

Attachment 1 Vehicle Monthly Inspection Checklist.

Attachment 1

VEHICLE MONTHLY INSPECTION CHECKLIST							
Location:				Registration No.:			
Model:				Make:			
Driver's Name:							
INSTRUCTIONS: Check all items indicated. Inspect and indicate as satisfactory=S, Unsatisfactory=U, or not applicable=N/A							
Cab	**U**	**S**	**N/A**	Tires	**U**	**S**	**N/A**
Cleanliness				Tires			
Levers / Controls Operational				Wheels			
Seat Condition OK				Brakes			
Operator Restraint Provided							
Pedals in Good Condition				**Environmental**	**U**	**S**	**N/A**
First aid kit				Spill Kit			
No tools in passenger area				Clean, free of weeds prior to arrival			
Windows / Wipers / Washers				Motor	**U**	**S**	**N/A**
Rear View Mirrors fitted and clean				Fluid and oil levels			
Headlights				Connections (check for excessive wear, leaks and creep)			
Brake lights				Hoses			
Fire extinguisher				Exhaust			
Log Book							
				Comments:			
Warning Devices	**U**	**S**	**N/A**				
Horn							
Amber flashing beacon							
Reversing alarm							
WARNING SIGNS (in cabin)							
Such "NO SMOKING" etc.							
Operator's Name:				Supervisor's signature:			