

Product Specifications

Camera			
Image Sensor	1/2.8" 4K Sony Exmor CMOS	Operating Conditions	Temperature : 0 °C to +40 °C ; Humidity : 20% to 80%
Effective Picture Elements	8 Megapixels	Storage Conditions	Temperature : -20 °C to +60 °C ; Humidity: 20% to 95%
Output Resolutions	Resolution: 4K / 1080p / 720p Frame Rates: 60 / 59.94 / 50 / 30 / 29.97 / 25	Audio	
		Channel	2ch Stereo
Minimum Illumination	0.7 lux (IRE50, F1.6, 30fps)	Codec	AAC-LC (48K)
S / N Ratio	≥ 50 dB	Built-in Microphone	Yes, 2 Microphones
Gain	Auto, Manual	Interface	
TV Line	1000 (Center / Wide)	Video Outputs	HDMI®, IP, USB
Shutter Speed	1/1 to 1/10,000 sec	Audio Outputs	HDMI®, IP, USB
Exposure Control	Auto, Manual, Priority AE (Shutter, IRIS), BLC, WDR	Audio Inputs	N/A
White Balance	Auto, Manual	IP Streaming	
Optical Zoom	30X	Resolution	4K 60fps
Digital Zoom	1X	Network Video Compress Formats	H.264, H.265, MJPEG
Total Zoom	30X	Maximum Frame Rate	4K 60fps
Viewing Angles	DFOV: 75.5° (Wide) to 3.1° (Tele) HFOV: 68.0° (Wide) to 2.7° (Tele) VFOV: 41.7° (Wide) to 1.5° (Tele)	Bit-Rate Control Modes	VBR, CBR
		Range of Bit-Rate Setting	512 Kbps to 64 Mbps
		Network Interface	10 / 100 / 1000 Base-T
		Multi-Stream Capability	2 (RTSP / Web Page), 4K 60fps (max.)
Focal Length	f = 4.3 mm (Wide) to 129 mm (Tele)	Network Protocols	IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHCP, RTP / RTCP, RTSP, RTMP, VISCA over IP
Aperture (Iris)	F = 1.6 (Wide) to 4.7 (Tele)		
Minimum Working Distance	0.1 m (Wide), 1.2 m (Tele)	USB	
Pan / Tilt Angles	Pan: ±170°, Tilt: ±90°	Connector	USB Type-B 3.2 Gen 1
Preset Positions	10 (IR), 256 (IP)	Video Format	MJPEG, YUY2
Camera Control - Interface	USB, IP	Maximum Video Resolution	2160p
Camera Control - Protocols	USB, VISCA, CGI (IP)	USB Video Class (UVC)	UVC 1.1
Image Processing	Mirror / Flip / Freeze / WDR / BLC	USB Audio Class (UAC)	UVC 1.0
Image Stability	Yes	Web UI	
Power Frequencies	50 Hz, 60 Hz	Live Video Preview	Yes
AI Function		Camera PTZ Control	Pan, Tilt, Zoom, Focus, Preset Control
Modes	Face / Eyes Tracking, Fall / Bed Egress Detection	Camera / Image Adjustment	Exposure, White Balance
Privacy		Network Configuration	DHCP, IP Address, Gateway, Subnet Mask, DNS
Protection Modes	Local Privacy Mode, Mosaic Function	Software Tools	
General		ViewCare	Supports Windows® 10 or later
		Room Management	Supports Windows® 7 or later, macOS® 11.6 or later
Power Requirements	Adapter: AC 100 - 240V to DC 12V / 3.34A Power Input: DC 12–24V, 60W Max.	Warranty	
Power Consumption	60 W	Camera	3 Years
PoE	N / A	Accessories	1 Year
Dimensions (W x H x D)	195.0 x 222.4 x 155.0 mm	Package Contents	
Net Weight	2.6 kg	Camera, Remote Control, Power Adapter, Power Cord, USB 3.0 Type-A to B Cable, Quick Start Guide	
Housing Material	Anti-UV	Optional Accessories	
Application	Indoor	L-Type Wall Mount, Ceiling Mount Bracket, AVer CL01 PTZ Camera Controller, AVer Expansion Speakerphone, AVer Wi-Fi® Dongle	
IR Night Vision	Yes		
Security	Kensington Slot		
Remote Control	Infrared		

* Specifications may vary depending on location and are subject to change without notice.
† Wi-Fi®, Wi-Fi CERTIFIED®, Wi-Fi Alliance®, the Wi-Fi logo, the Wi-Fi CERTIFIED logo, and other marks are trademarks of Wi-Fi Alliance.
‡ All HDMI trademarks and trade dress are registered trademarks or trademarks of HDMI Licensing Administrator, Inc.

Product Appearance

Front



- 1 Camera Lens
- 2 Speaker
- 3 Microphone
- 4 Microphone Array
- 5 LED Indicator

Back



- 1 RJ-45
- 2 HDMI®
- 3 USB Type-A (USB Host)
- 4 USB Type-B 3.2 Gen 1
- 5 RJ-45 (Audio Expansion)
- 6 DC 12-24V
- 7 Kensington Slot



©2026 AVer Information Inc. All rights reserved.
All brand names and logos are trademarks of their respective companies.



Distributor/Dealer



HEARING
EVERY WORD.
SEEING EVERY
DETAIL.

AVer MD331UI
Medical Grade PTZ Camera



AVer MD331UI

Medical Grade PTZ Camera

Designed for virtual rounding and remote care, the MD331UI is built to meet the demands of fast-paced and unpredictable clinical environments. Beyond delivering lossless 4K Ultra HD clarity with 30X optical zoom, it features embedded two-way audio — and takes it further with AVer's Audio Processing AI, ensuring focused sound pickup on the patient. Compliant with IEC 60601-1-2 EMC standards, this medical grade PTZ camera also integrates an on-device clinical AI engine for real-time monitoring. When clinicians can see every detail and hear every word the patient says, care stays seamless — and every virtual round feels as natural as being there in person.



30X Optical Zoom



4K Output Resolution



Audio Processing AI



Manual Angle Adjustment



Wide Voltage Input



Audio Expansion Support



Auto IR for Night View



Edge-AI Support



Privacy Mode & Mosaic Function



Medical Grade Certification IEC 60601-1-2



Audio Processing AI: Hear Every Patient Clearly

Advanced Audio Processing AI captures the patient's voice clearly while minimizing environmental background noise, allowing remote clinicians to hear the patient without distraction.

Effortless Camera Positioning: Zero-Lag Healthcare Workflow

Nurses can manually fine-tune the camera's position without needing to recalibrate, as the system retains its absolute positioning. This allows quick, intuitive adjustments while maintaining a smooth and uninterrupted care workflow.

* Manual tilt of the camera head should not exceed 90°.

† This feature is designed for fine adjustments; we do not recommend frequent or continuous manual repositioning.

Ready for Battery-Powered High-Mobility Care

Experience uninterrupted clinical workflows with a 12–24V wide voltage input and optional Wi-Fi® connectivity, enabling seamless integration with battery-powered medical carts. Image Stabilization ensures a steady, blur-free view for remote specialists — even when the cart is moving between wards.

* By default, MD331UI supports the AVer Wi-Fi® Dongle. Third-party accessories may be supported through project-based system integration.

Expandable Audio Coverage for Any Ward Layout

The MD331UI comes with a built-in two-way audio for seamless communication, and for larger environments or multi-bed wards where greater audio coverage is needed, an external speakerphone can also be connected to ensure every corner of the room is reached.

* By default, MD331UI supports the AVer Expansion Speakerphone. Third-party accessories may be supported through project-based system integration.