

Manuscript (Survey): Quantum Diffusion Kernels on Graphs, Symmetries, Groups, and Speedups

Jue Xu*

June 21, 2022

Abstract

We discuss the quantum analogue of diffusion kernels on graphs. prove the quantum speedup in terms of groups and symmetries.

Contents

1	Introduction	1
1.1	Preliminary and Notations	2
1.2	SVM and Kernel trick	2
2	Diffusion Kernels and Continuous-Time Quantum Random Walk	3
2.1	Classical diffusion kernels on graphs	3
2.2	Continuous-time quantum random walk	4
2.3	Relation and examples	4
3	Quantum Speedups via QKE	5
3.1	Previous works: Quantum Kernel Estimation	5
3.2	Provable: Symmetries, graph properties, and quantum speedups	6
3.3	Heuristic: Group, invariance, symmetries, physical systems	7
4	Experiment	7
4.1	Datasets and benchmark	7
5	Discussion and Conclusion	7
	References	7
A	Machine Learning, Group Theory, and Lagrangian	8
A.1	Machine learning	8
A.2	Group theory and symmetries	8
A.3	Lagrangian formalism	8

1 Introduction

group theoretical methods in machine learning by Kondor [Kon08]. diffusion kernel on graphs [KL02]

Many insightful and powerful models, like adiabatic quantum computation [Far+00], quantum random walks [Chi04]

*juexu@cs.umd.edu

1.1 Preliminary and Notations

a datum $\mathbf{x} := (x_1, x_2, \dots, x_n) \in \mathbb{R}^n$ is a vector where n is the number of *features*; dataset $\{\mathbf{x}^{(m)}, y\}$ where the *label* $y \in \{-1, 1\}$, Ω ; quantum state $|z\rangle$ with $z \in 1, 2, \dots, 2^n$ where n is the number of qubits, computational basis; the binary representation $|\mathbf{x}\rangle = |x_1, x_2, \dots, x_n\rangle, x_i \in \{0, 1\}$. $|0\rangle^n$

1.2 SVM and Kernel trick

*supervised learning*¹

Support Vector Machine

training set, test set. training stage, classification stage. exponentially large space; hyperplane (\mathbf{w}, b) parametrized by a normal vector $\mathbf{w} \in \mathbb{R}^n$ and a bias term $b \in \mathbb{R}$. in the (high-dimensional) *feature space*. maximize the margin

$$\arg \max_f L(y, \tilde{y}) + ||| \quad (1)$$

where the loss function L , slackness. called *support vector*. objective (cost function): *empirical risk* (error rate, loss function)

$$R_{emp}(\theta) = \frac{1}{|T|} \sum_{\mathbf{x} \in T} \mathbb{P}(\tilde{y} \neq y) \quad (2)$$

the dual quadratic program that (only uses access to the kernel) we maximize

$$L_D(\alpha) = \sum_{i=1}^t \alpha_i - \frac{1}{2} \sum_{i,j=1}^t y_i y_j \alpha_i \alpha_j \mathcal{K}(\mathbf{x}_i, \mathbf{x}_j) \quad (3)$$

subject to $\sum_{i=1}^t \alpha_i y_i = 0$ and $\alpha_i \geq 0$ for each i ?

construct the classifier

$$\tilde{m}(\mathbf{s}) = (\text{sign}) \left(\sum_{i=1}^t y_i \alpha_i^* \mathcal{K}(\mathbf{x}_i, \mathbf{s}) + b \right) \quad (4)$$

Kernel trick (method)

kernel trick: *feature map* the input data to higher dimension such that the data are linearly separatable in this feature space. only depend on the inner product to avoid the expensive (exponential) calculation. a *kernel function* (mapping) $\mathcal{K} : \Omega \times \Omega \mapsto \mathbb{R}$, a *(feature) mapping* $\phi : \Omega \mapsto \mathcal{H}_{\mathcal{K}}$

$$\mathcal{K}(\mathbf{x}, \mathbf{x}') = \langle \phi(\mathbf{x}), \phi(\mathbf{x}') \rangle \quad (5)$$

inner product (Dirac notation?).

Definition 1 (Feature map). *feature map*;


$$\Phi(\mathbf{x}) : \mathbb{R}^n \rightarrow \mathcal{H} \quad (6)$$

from a low dimensional space non-linearly in to a high dimensional Hilbert-space \mathcal{H} which is commonly referred to as the *feature space*.


Definition 2 (Kernel function). A function \mathcal{K} is a valid kernel (in machine learning) if and only if? the matrix $\mathcal{K}(x, x')$ is symmetric and positive semi-definite.

Some common kernels:

¹unsupervised learning



(a) linearly separable SVM



(b) kernel trick idea: SVM with kernel given by $\phi(\mathbf{x} := (a, b)) = (a, b, a^2 + b^2)$ and thus $\mathcal{K}(\mathbf{x}, \mathbf{y}) = \mathbf{x} \cdot \mathbf{y} + \|\mathbf{x}\|^2 \|\mathbf{y}\|^2$ that only depends on inner product. The training points are mapped to a 3-dimensional space where a separating hyperplane can be easily found. (from Wikipedia: Kernel method)

- polynomial kernel:
- radial:
- Gaussian kernel:

Definition 3 (Reproducing Kernel Hilbert Space).

Theorem 1 (Representer).

Hilbert space

2 Diffusion Kernels and Continuous-Time Quantum Random Walk

2.1 Classical diffusion kernels on graphs

[KL02] with Euclidean space $\Omega = \mathbb{R}^m$

Definition 4 (Adjacency matrix). Given a (undirected, unweighted) graph $G = (V, E)$, its *adjacency matrix* \hat{A} is defined as

$$\hat{A}(v, v') := \begin{cases} 1, & (v, v') \in E \\ 0, & \text{otherwise} \end{cases} \quad (7)$$

where the matrix entry is 1 if the two vertices (labels of the column and the row) are connected by an edge, otherwise 0.

Definition 5 (Graph Laplacian). With the adjacency matrix \hat{A} , the graph Laplacian is defined as

$$\hat{\mathcal{L}} := \hat{A} - \hat{D} \quad (8)$$

where $\hat{D}_{vv} := \deg(v)$ is its diagonal degree of (vertex v) matrix.

Remark 1. Graph Laplacian $\hat{\mathcal{L}}$ is the discrete version of (continuous) Laplacian operator ∇^2 .

Lemma 1. exponential of i.e., $e^{\beta \hat{H}}$ is a valid kernel

2.1.1 Diffusion, heat equation, random walk,

The continuous-time random walk on G is defined as the **solution of the differential equation**

$$\frac{d}{dt}p_j(t) = \sum_{k \in V} \hat{\mathcal{L}}_{jk} p_k(t), \quad (9)$$

where $p_j(t)$ denotes the probability associated with vertex j at time t and $\hat{\mathcal{L}}$ is [Graph Laplacian](#).

Since the columns of L sum to 0

$$\frac{d}{dt} \sum_{j \in V} p_j(t) = \sum_{j,k \in V} \hat{\mathcal{L}}_{jk} p_k(t) = 0 \quad (10)$$

which shows that an initially normalized distribution remains normalized: the evolution of the continuous-time random walk for any time t is a *stochastic process. random walk, heat equation*

2.2 Continuous-time quantum random walk

The continuous-time quantum random walk [[CFG02](#)] is the quantum analogue of classical diffusion (continuous-time random walk). By a direct observation, Eq. (9) is very similar to the time-dependent (evolution) schrodinger equation governed by a Hamiltonian operator \hat{H}

$$i\hbar \frac{d}{dt}|\psi\rangle = \hat{H}|\psi\rangle \quad (11)$$

except that the factor of $i\hbar$.

Definition 6 (Quantum propagator, kernel, transition).

2.3 Relation and examples

2.3.1 Ring (closed line)

classical kernel

$$\mathcal{K}() \quad (12)$$

quantum propagation (kernel)

$$\langle z_F | e^{-it\hat{H}_0} | z_I \rangle = \sum_{p=1}^N e^{-it2 \cos(\frac{2\pi}{N}p) + i\frac{2\pi}{N}p(z_I - z_F)} \quad (13)$$

$$\approx e^{2it}(-i)^d J_d(2t) \quad (14)$$

Remark 2. The random walk on this graph starting from the origin (in either continuous or discrete time) typically moves a distance proportional to \sqrt{t} in time t . In contrast, the quantum random walk evolves as a wave packet with speed 2.

2.3.2 Tree

2.3.3 Hyercube

2.3.4 Cayley graphs

Definition 7 (Cayley graph). Cayley graph is a graph that encodes the abstract structure of a group.




Figure 2

3 Quantum Speedups via QKE

A quantum version of this approach has already been proposed in [RML14], where an exponential improvement can be achieved if data is provided in a coherent superposition.

Remark 3. However, when data is provided in the conventional way, i.e. from a classical computer, then the methods of [15] cannot be applied.

input model, quantum RAM; quantum-inspired [Tan19]

3.1 Previous works: Quantum Kernel Estimation

quantum kernel estimation [SK19] [Hav+19] the quantum state space (Hilbert space) as the feature space to still obtain a quantum advantage mapping the input data non-linearly to a quantum state

$$\Phi(\mathbf{x}) : \Omega \rightarrow |\Phi(\mathbf{x})\rangle\langle\Phi(\mathbf{x})|, \quad (15)$$

the direct quantum analogy of classical [Feature map](#)

3.1.1 Explicit method (Quantum Variational Classification)

variational quantum circuit: generates a separating hyperplane in the quantum feature space

1. $\mathbf{x} \in \Omega$ (feature) mapped to a quantum state by applying a unitary circuit $U_{\Phi(\mathbf{x})}$ to a reference (initial) state $|0\rangle^n$
2. a short depth quantum circuit $W(\theta)$
3. for binary classification, apply a binary measurement $\{M_y\} = 2^{-1}(\mathbb{1} + y\mathbf{f})$?
4. to obtain the empirical distribution $p_y(\mathbf{x})$, perform repeated measurement shots. then assign the label according to p_y ?

3.1.2 Implicit method (QKE)

estimate the kernel function quantumly and implement a conventional SVM. Rather than using a variational quantum circuit to generate the separating hyperplane, we use a classical SVM for classification.

1. the kernel $\mathcal{K}(\mathbf{x}, \mathbf{x}')$ is estimated on a quantum computer
2. the quantum computer is used a second time to estimate the kernel for a new datum (test) $\mathbf{s} \in S$ with all the support vectors.

The kernel entries are the fidelities between different feature vectors. The overlap can be estimated directly from the transition amplitude

$$|\langle \Phi(\mathbf{x}) | \Phi(\mathbf{x}') \rangle|^2 = \left| \langle 0^n | U_{\Phi(\mathbf{x})}^\dagger U_{\Phi(\mathbf{x}')} | 0^n \rangle \right|^2 \quad (16)$$

measure the final state in the Z-basis R-times and record the number of $|0^n\rangle$. The frequency of this string is the estimate of the transition probability. The kernel entry is obtained to an additive sampling error of $\tilde{\epsilon}$ when $\mathcal{O}(\tilde{\epsilon}^{-2})$ shots are used. *quantum feature map*. quantum propagation, kernel in the path-integral formalism.

Theorem 2 ([Chi+03]). *There exists exponential separation with respect to query complexity in the adjacency matrix model*

[Zhe+22]

[LAT21]

3.2 Provable: Symmetries, graph properties, and quantum speedups

symmetric functions rule out exponential speedup [Ben+20]

3.2.1 Permutation, symmetry, and speedup




Figure 3: [Chi+03]

3.3 Heuristic: Group, invariance, symmetries, physical systems

3.3.1 Group, symmetries in physics

covariant [Gli+21] group theory, [Kon08]; symmetries in physics [Bog+20]; equivariant CNN [Zhe+22]

3.3.2 Group theory and machine learning

[KL02]

4 Experiment

4.1 Datasets and benchmark

4.1.1 Artificial data

we generate artificial data that can be fully separated by our feature map.

4.1.2 Real dataset

JET?; quantum phase transition? order?

5 Discussion and Conclusion

References

- [Ben+20] Shalev Ben-David et al. [Symmetries, Graph Properties, and Quantum Speedups](#). *2020 IEEE 61st Annu. Symp. Found. Comput. Sci. FOCS* (Nov. 2020), pp. 649–660. arXiv: [2006.12760](#) (cit. on p. 6).
- [Bog+20] Alexander Bogatskiy et al. [Lorentz Group Equivariant Neural Network for Particle Physics](#). Proceedings of the 37th International Conference on Machine Learning. International Conference on Machine Learning. PMLR, Nov. 21, 2020, pp. 992–1002 (cit. on p. 7).
- [CFG02] Andrew M. Childs, Edward Farhi, and Sam Gutmann. [An Example of the Difference between Quantum and Classical Random Walks](#). *Quantum Inf. Process.* 1.1/2 (2002), pp. 35–43. arXiv: [quant-ph/0103020](#) (cit. on p. 4).
- [Chi+03] Andrew M. Childs et al. [Exponential Algorithmic Speedup by Quantum Walk](#). *Proc. Thirty-Fifth ACM Symp. Theory Comput. - STOC 03* (2003), p. 59. arXiv: [quant-ph/0209131](#) (cit. on p. 6).
- [Chi04] Andrew MacGregor Childs. “Quantum Information Processing in Continuous Time”. Thesis. Massachusetts Institute of Technology, 2004 (cit. on p. 1).
- [Far+00] Edward Farhi et al. “Quantum Computation by Adiabatic Evolution”. Jan. 28, 2000. arXiv: [quant-ph/0001106](#) (cit. on p. 1).
- [Gli+21] Jennifer R. Glick et al. “Covariant Quantum Kernels for Data with Group Structure”. May 7, 2021. arXiv: [2105.03406 \[quant-ph\]](#) (cit. on p. 7).
- [Hav+19] Vojtech Havlicek et al. [Supervised Learning with Quantum Enhanced Feature Spaces](#). *Nature* 567.7747 (Mar. 2019), pp. 209–212. arXiv: [1804.11326](#) (cit. on p. 5).
- [KL02] Risi Imre Kondor and John Lafferty. [Diffusion Kernels on Graphs and Other Discrete Structures](#) (2002), p. 8 (cit. on pp. 1, 3, 7).

- [Kon08] Risi Kondor. “Group Theoretical Methods in Machine Learning”. Thesis. Columbia University, 2008 (cit. on pp. 1, 7).
- [LAT21] Yunchao Liu, Srinivasan Arunachalam, and Kristan Temme. [A Rigorous and Robust Quantum Speed-up in Supervised Machine Learning](#). *Nat. Phys.* 17.9 (Sept. 2021), pp. 1013–1017. arXiv: [2010.02174 \[quant-ph\]](#) (cit. on p. 6).
- [RML14] Patrick Rebentrost, Masoud Mohseni, and Seth Lloyd. [Quantum Support Vector Machine for Big Data Classification](#). *Phys. Rev. Lett.* 113.13 (Sept. 25, 2014), p. 130503. arXiv: [1307.0471 \[quant-ph\]](#) (cit. on p. 5).
- [SK19] Maria Schuld and Nathan Killoran. [Quantum Machine Learning in Feature Hilbert Spaces](#). *Phys. Rev. Lett.* 122.4 (Feb. 1, 2019), p. 040504. arXiv: [1803.07128 \[quant-ph\]](#) (cit. on p. 5).
- [Tan19] Ewin Tang. [A Quantum-Inspired Classical Algorithm for Recommendation Systems](#). *Proc. 51st Annu. ACM SIGACT Symp. Theory Comput.* (June 23, 2019), pp. 217–228. arXiv: [1807.04271](#) (cit. on p. 5).
- [Xu21] Jue Xu. “On Lagrangian Formalism of Quantum Computation”. Dec. 7, 2021. arXiv: [2112.04892 \[quant-ph\]](#) (cit. on p. 8).
- [Zhe+22] Han Zheng et al. “Speeding up Learning Quantum States through Group Equivariant Convolutional Quantum Ansatz”. Jan. 20, 2022. arXiv: [2112.07611 \[math-ph, physics:quant-ph, stat\]](#) (cit. on pp. 6, 7).

A Machine Learning, Group Theory, and Lagrangian

A.1 Machine learning

A.2 Group theory and symmetries

A.2.1 Representation

A.3 Lagrangian formalism

[Xu21]