org.eclipse.etrice.examples.dynamicactors6 Model Documentation

generated by eTrice

August 14, 2013

Contents

List of Figures

1 Model Description

2 Logical System Description

2.1 LS

2.1.1 Instance Tree

Figure 1: LS Instance Tree

3 Subsystem Description

3.1 Main

3.1.1 Structure

Figure 2: Main Structure

4 Protocol Class Description

4.1 PC

4.1.1 Incoming Messages

Message	Data	Description
sayHello		

4.1.2 Outgoing Messages

Message	Data	Description
hello	txt	

5 Data Class Description

6 Actor Class Description

6.1 Appl

6.1.1 Structure


Figure 3: Appl Structure

6.1.2   Attributes

6.1.3   Operations

6.2   Container

6.2.1   Structure

Figure 4: Container Structure

6.2.2   Attributes

6.2.3   Operations

Name:	dumpTree
ReturnType:	void
Arguments:	msg:string

### 6.2.4 Statemachine

6.2.4.1 Top Level

Figure 5: Container Top State

## 6.3 Optional1

6.3.1 Structure

Figure 6: Optional1 Structure

6.3.2 Attributes

6.3.3 Operations

6.4 Optional2

6.4.1 Structure

Figure 7: Optional2 Structure

6.4.2 Attributes

### 6.4.3 Operations

6.5 AC1

6.5.1 Structure

Figure 8: AC1 Structure

6.5.2 Attributes

6.5.3 Operations

6.5.4 Statemachine

6.5.4.1 Top Level


Figure 9: AC1 Top State

6.6 AC2

6.6.1 Structure

Figure 10: AC2 Structure

6.6.2 Attributes

6.6.3 Operations

6.7 AC3

6.7.1 Structure

Figure 11: AC3 Structure

6.7.2 Attributes

6.7.3 Operations

6.7.4 Statemachine

6.7.4.1 Top Level

Figure 12: AC3 Top State