

CENTRIFUGAL PUMP DATASHEET – A2 (01-A2A)

Service: Crude charge booster pump, CDU-1. Standby: A2B (01-A2B). Manufacturer: Kirlo Pumps Ltd, model KPL-OH2-150x315 (API 610 OH2). Driver: motor M-A2 (Bharat Motors). Revision 1 dated 2019-06-15.

1. Operating / performance data

Parameter	Value	Unit	Remarks
Rated flow	180	m3/h	Normal 160 m3/h
Rated differential head	95	m	
NPSH required (NPSHr)	3.2	m	At rated flow; NPSHa 6.0 m
Pumping temperature	45	degC	Desalted crude
Specific gravity	0.86	-	
Pump speed	2960	rpm	
Shut-off head	118	m	
Minimum continuous flow	55	m3/h	Min-flow line via FIC-101

2. Mechanical seal

Item	Value
Seal type	Single cartridge mechanical seal, API 682 Plan 11
Seal vendor	Sahyadri Seals (fictional)
Faces	SiC vs carbon
Flush	Plan 11 – discharge to seal chamber via orifice

3. Driver (motor M-A2)

Parameter	Value	Unit
Rated power	45	kW
Voltage / phase / frequency	415 / 3 / 50	V / - / Hz
Full load current (FLA)	78	A
Enclosure / protection	TEFC, IP55	-
Insulation class	F (temp rise B)	-
Starting	DOL	-
Power supply feeder	MCC-2-F07	-

4. Notes

- Motor rating per this datasheet is 45 kW. Any other value in the asset master must be verified against the motor nameplate.
- Isolation valves: suction XV-2041; discharge isolation valve per current P&ID PID-CDU-03.
- Troubleshooting: refer TG-A2. Electrical isolation: refer SOP-EL-014 (current revision).

Prepared	Checked	Approved	Date
M. Shetty (Mech)	S. Kulkarni	I. Shaikh, Head-Mechanical	2019-06-15