

```
start transaction;

create database `Acme-Broker`;

use `Acme-Broker`;

create user 'acme-user'@'%'identified by password
'*4F10007AADA9EE3DBB2CC36575DFC6F4FDE27577';

create user 'acme-manager'@'%'identified by password
'*FDB8CD304EB2317D10C95D797A4BD7492560F55F';

grant select, insert, update, delete on `Acme-Broker`.* to 'acme-user'@'%';

grant select, insert, update, delete, create, drop, references, index,

alter,create temporary tables, lock tables, create view, create routine,

alter routine, execute, trigger, show view

on `Acme-Broker`.* to 'acme-manager'@'%';
```

```
-- MySQL dump 10.13 Distrib 5.5.29, for Win64 (x86)
```

```
--
```

```
-- Host: localhost Database: AcmePilgrim
```

```
-- -----
```

```
-- Server version 5.5.29
```

```
/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
```

```
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
```

```
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
```

```
/*!40101 SET NAMES utf8 */;
```

```
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
```

```

/*!40103 SET TIME_ZONE='+00:00' */;

/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;

/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS,
FOREIGN_KEY_CHECKS=0 */;

/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO'
*/;

/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;

--

-- Table structure for table `actor`

--

DROP TABLE IF EXISTS `actor`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `actor` (
  `id` int(11) NOT NULL,
  `version` int(11) NOT NULL,
  `contactPhone` varchar(255) DEFAULT NULL,
  `emailAddress` varchar(255) DEFAULT NULL,
  `name` varchar(255) DEFAULT NULL,
  `surname` varchar(255) DEFAULT NULL,
  `url` varchar(255) DEFAULT NULL,
  `userAccount_id` int(11) NOT NULL,
  PRIMARY KEY (`id`),
  UNIQUE KEY `UK_cgls5lrufx91ufsyh467spwa3` (`userAccount_id`),
  CONSTRAINT `FK_cgls5lrufx91ufsyh467spwa3` FOREIGN KEY (`userAccount_id`) REFERENCES
`useraccount` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `actor`
```

```
--
```

```
LOCK TABLES `actor` WRITE;
```

```
/*!40000 ALTER TABLE `actor` DISABLE KEYS */;
```

```
/*!40000 ALTER TABLE `actor` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `actor_folder`
```

```
--
```

```
DROP TABLE IF EXISTS `actor_folder`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!40101 SET character_set_client = utf8 */;
```

```
CREATE TABLE `actor_folder` (
```

```
  `Actor_id` int(11) NOT NULL,
```

```
  `folders_id` int(11) NOT NULL,
```

```
  UNIQUE KEY `UK_dp573h40udupcm5m1kgn2bc2r` (`folders_id`),
```

```
  CONSTRAINT `FK_dp573h40udupcm5m1kgn2bc2r` FOREIGN KEY (`folders_id`) REFERENCES  
  `folder` (`id`)
```

```
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `actor_folder`
```

```
--
```

```
LOCK TABLES `actor_folder` WRITE;
```

```
/*!40000 ALTER TABLE `actor_folder` DISABLE KEYS */;
```

```
INSERT INTO `actor_folder` VALUES (9,3),(9,4),(9,5),(10,6),(10,7),(10,8);
```

```
/*!40000 ALTER TABLE `actor_folder` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `administrator`
```

```
--
```

```
DROP TABLE IF EXISTS `administrator`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!40101 SET character_set_client = utf8 */;
```

```
CREATE TABLE `administrator` (
```

```
  `id` int(11) NOT NULL,
```

```
  `version` int(11) NOT NULL,
```

```
  `contactPhone` varchar(255) DEFAULT NULL,
```

```
  `emailAddress` varchar(255) DEFAULT NULL,
```

```
  `name` varchar(255) DEFAULT NULL,
```

```
  `surname` varchar(255) DEFAULT NULL,
```

```
  `url` varchar(255) DEFAULT NULL,
```

```
  `userAccount_id` int(11) NOT NULL,
```

```
  PRIMARY KEY (`id`),
```

```
  UNIQUE KEY `UK_idt4b4u259p6vs4pyr9lax4eg` (`userAccount_id`),
```

```
CONSTRAINT `FK_idt4b4u259p6vs4pyr9lax4eg` FOREIGN KEY (`userAccount_id`) REFERENCES  
`useraccount` (`id`)
```

```
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

```
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `administrator`
```

```
--
```

```
LOCK TABLES `administrator` WRITE;
```

```
/*!40000 ALTER TABLE `administrator` DISABLE KEYS */;
```

```
INSERT INTO `administrator` VALUES
```

```
(9,0,'655892409','admin1@gmail.com','adminName1','Surname1',NULL,1),(10,0,'655312843','a  
dmin2@gmail.com','adminName2','Surname2',NULL,2);
```

```
/*!40000 ALTER TABLE `administrator` ENABLE KEYS */;
```

```
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `anecdote`
```

```
--
```

```
DROP TABLE IF EXISTS `anecdote`;
```

```
/*!40101 SET @saved_cs_client = @@character_set_client */;
```

```
/*!40101 SET character_set_client = utf8 */;
```

```
CREATE TABLE `anecdote` (
```

```
  `id` int(11) NOT NULL,
```

```
  `version` int(11) NOT NULL,
```

```
  `creationMoment` datetime DEFAULT NULL,
```

```
  `description` varchar(255) DEFAULT NULL,
```

```

`eventMoment` datetime DEFAULT NULL,

`title` varchar(255) DEFAULT NULL,

`pilgrim_id` int(11) NOT NULL,

`route_id` int(11) DEFAULT NULL,

PRIMARY KEY (`id`),

KEY `FK_cj47e8ifyepvgk8mnqbi9kbip` (`pilgrim_id`),

KEY `FK_s8b24re90ku9bkralr5d91gt7` (`route_id`),

CONSTRAINT `FK_s8b24re90ku9bkralr5d91gt7` FOREIGN KEY (`route_id`) REFERENCES `route`
(`id`),

CONSTRAINT `FK_cj47e8ifyepvgk8mnqbi9kbip` FOREIGN KEY (`pilgrim_id`) REFERENCES
`pilgrim` (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `anecdote`

--

LOCK TABLES `anecdote` WRITE;

/*!40000 ALTER TABLE `anecdote` DISABLE KEYS */;

/*!40000 ALTER TABLE `anecdote` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `complaint`

--

DROP TABLE IF EXISTS `complaint`;

```

```

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `complaint` (
  `id` int(11) NOT NULL,
  `version` int(11) NOT NULL,
  `creationMoment` datetime DEFAULT NULL,
  `description` varchar(255) DEFAULT NULL,
  `resolution` varchar(255) DEFAULT NULL,
  `status` varchar(255) DEFAULT NULL,
  `title` varchar(255) DEFAULT NULL,
  `administrator_id` int(11) DEFAULT NULL,
  `pilgrim_id` int(11) NOT NULL,
  PRIMARY KEY (`id`),
  KEY `FK_4ni2quoorj8y99dcww4rtgod5` (`administrator_id`),
  KEY `FK_qop8ryp98rsm07m4m22kq0eiq` (`pilgrim_id`),
  CONSTRAINT `FK_qop8ryp98rsm07m4m22kq0eiq` FOREIGN KEY (`pilgrim_id`) REFERENCES
`pilgrim` (`id`),
  CONSTRAINT `FK_4ni2quoorj8y99dcww4rtgod5` FOREIGN KEY (`administrator_id`)
REFERENCES `administrator` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `complaint`

--

LOCK TABLES `complaint` WRITE;

/*!40000 ALTER TABLE `complaint` DISABLE KEYS */;

```

```

/*!40000 ALTER TABLE `complaint` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `discuss`

--

DROP TABLE IF EXISTS `discuss`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `discuss` (
  `id` int(11) NOT NULL,
  `version` int(11) NOT NULL,
  `message` varchar(255) DEFAULT NULL,
  `momentDiscuss` datetime DEFAULT NULL,
  `actor_id` int(11) NOT NULL,
  `complaint_id` int(11) NOT NULL,
  PRIMARY KEY (`id`),
  KEY `FK_kph22wqj1fhl3f8588p4eptak` (`complaint_id`),
  CONSTRAINT `FK_kph22wqj1fhl3f8588p4eptak` FOREIGN KEY (`complaint_id`) REFERENCES
`complaint` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `discuss`

--

```



```

LOCK TABLES `discuss` WRITE;

/*!40000 ALTER TABLE `discuss` DISABLE KEYS */;

/*!40000 ALTER TABLE `discuss` ENABLE KEYS */;

UNLOCK TABLES;


--
-- Table structure for table `folder`
--


DROP TABLE IF EXISTS `folder`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `folder` (
  `id` int(11) NOT NULL,
  `version` int(11) NOT NULL,
  `name` varchar(255) DEFAULT NULL,
  PRIMARY KEY (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;


--
-- Dumping data for table `folder`
--


LOCK TABLES `folder` WRITE;

/*!40000 ALTER TABLE `folder` DISABLE KEYS */;

INSERT INTO `folder` VALUES
(3,0,'outbox'),(4,0,'inbox'),(5,0,'trashbox'),(6,0,'outbox'),(7,0,'inbox'),(8,0,'trashbox');

```

```

/*!40000 ALTER TABLE `folder` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `hibernate_sequences`

--

DROP TABLE IF EXISTS `hibernate_sequences`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `hibernate_sequences` (
  `sequence_name` varchar(255) DEFAULT NULL,
  `sequence_next_hi_value` int(11) DEFAULT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `hibernate_sequences`

--

LOCK TABLES `hibernate_sequences` WRITE;

/*!40000 ALTER TABLE `hibernate_sequences` DISABLE KEYS */;

INSERT INTO `hibernate_sequences` VALUES ('DomainEntity',1);

/*!40000 ALTER TABLE `hibernate_sequences` ENABLE KEYS */;

UNLOCK TABLES;

--

```

-- Table structure for table `message`

--

DROP TABLE IF EXISTS `message`;

/\*!40101 SET @saved\_cs\_client = @@character\_set\_client \*/;

/\*!40101 SET character\_set\_client = utf8 \*/;

CREATE TABLE `message` (

`id` int(11) NOT NULL,

`version` int(11) NOT NULL,

`body` varchar(255) DEFAULT NULL,

`moment` datetime DEFAULT NULL,

`subject` varchar(255) DEFAULT NULL,

`urlAttachment` varchar(255) DEFAULT NULL,

`folder\_id` int(11) NOT NULL,

`recipient\_id` int(11) NOT NULL,

`sender\_id` int(11) NOT NULL,

PRIMARY KEY (`id`),

KEY `FK\_7t1ls63lqb52igs4ms20cf94t` (`folder\_id`),

CONSTRAINT `FK\_7t1ls63lqb52igs4ms20cf94t` FOREIGN KEY (`folder\_id`) REFERENCES `folder` (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/\*!40101 SET character\_set\_client = @saved\_cs\_client \*/;

--

-- Dumping data for table `message`

--

LOCK TABLES `message` WRITE;

```

/*!40000 ALTER TABLE `message` DISABLE KEYS */;

/*!40000 ALTER TABLE `message` ENABLE KEYS */;

UNLOCK TABLES;


--
-- Table structure for table `pilgrim`
--


DROP TABLE IF EXISTS `pilgrim`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `pilgrim` (
  `id` int(11) NOT NULL,
  `version` int(11) NOT NULL,
  `contactPhone` varchar(255) DEFAULT NULL,
  `emailAddress` varchar(255) DEFAULT NULL,
  `name` varchar(255) DEFAULT NULL,
  `surname` varchar(255) DEFAULT NULL,
  `url` varchar(255) DEFAULT NULL,
  `userAccount_id` int(11) NOT NULL,
  `birthDate` datetime DEFAULT NULL,
  `brandName` varchar(255) DEFAULT NULL,
  `cvvCode` int(11) NOT NULL,
  `expirationMonth` int(11) NOT NULL,
  `expirationYear` int(11) NOT NULL,
  `holderName` varchar(255) DEFAULT NULL,
  `number` varchar(255) DEFAULT NULL,

```

```
`nationality` varchar(255) DEFAULT NULL,  
  
PRIMARY KEY (`id`),  
  
UNIQUE KEY `UK_o4nvphpkm5fr7d8xo9jh6vams` (`userAccount_id`),  
  
CONSTRAINT `FK_o4nvphpkm5fr7d8xo9jh6vams` FOREIGN KEY (`userAccount_id`)  
REFERENCES `useraccount` (`id`)  
  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;  
  
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
```

```
-- Dumping data for table `pilgrim`
```

```
--
```

```
LOCK TABLES `pilgrim` WRITE;  
  
/*!40000 ALTER TABLE `pilgrim` DISABLE KEYS */;  
  
/*!40000 ALTER TABLE `pilgrim` ENABLE KEYS */;  
  
UNLOCK TABLES;
```

```
--
```

```
-- Table structure for table `register`
```

```
--
```

```
DROP TABLE IF EXISTS `register`;  
  
/*!40101 SET @saved_cs_client = @@character_set_client */;  
  
/*!40101 SET character_set_client = utf8 */;  
  
CREATE TABLE `register` (  
  
  `id` int(11) NOT NULL,  
  
  `version` int(11) NOT NULL,  
  
  `pilgrim_id` int(11) DEFAULT NULL,
```

```

`route_id` int(11) DEFAULT NULL,

PRIMARY KEY (`id`),

KEY `FK_odymitpif4a1grn1arw06g6n2` (`pilgrim_id`),

KEY `FK_maiq8q5pidwuf7jdq1xogwsjh` (`route_id`),

CONSTRAINT `FK_maiq8q5pidwuf7jdq1xogwsjh` FOREIGN KEY (`route_id`) REFERENCES
`route` (`id`),

CONSTRAINT `FK_odymitpif4a1grn1arw06g6n2` FOREIGN KEY (`pilgrim_id`) REFERENCES
`pilgrim` (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `register`

--

LOCK TABLES `register` WRITE;

/*!40000 ALTER TABLE `register` DISABLE KEYS */;

/*!40000 ALTER TABLE `register` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `route`

--

DROP TABLE IF EXISTS `route`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `route` (

```

```

`id` int(11) NOT NULL,

`version` int(11) NOT NULL,

`actived` bit(1) DEFAULT NULL,

`description` varchar(255) DEFAULT NULL,

`name` varchar(255) DEFAULT NULL,

`ratingD` double DEFAULT NULL,

`ratingL` double DEFAULT NULL,

PRIMARY KEY (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `route`
--

LOCK TABLES `route` WRITE;

/*!40000 ALTER TABLE `route` DISABLE KEYS */;

INSERT INTO `route` VALUES (17,0,'ð','This is a nice route :)','Route1',0,0),(20,0,'ð','This is
another route','Route2',0,0),(23,0,'0','This is another route','Route3',0,0);

/*!40000 ALTER TABLE `route` ENABLE KEYS */;

UNLOCK TABLES;

--
-- Table structure for table `stage`
--

DROP TABLE IF EXISTS `stage`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

```

```

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `stage` (

  `id` int(11) NOT NULL,

  `version` int(11) NOT NULL,

  `briefTextDescription` varchar(255) DEFAULT NULL,

  `description` varchar(255) DEFAULT NULL,

  `destinationAltitude` double DEFAULT NULL,

  `destinationDescription` varchar(255) DEFAULT NULL,

  `destinationLatitude` double DEFAULT NULL,

  `destinationLongitude` double DEFAULT NULL,

  `destinationTitle` varchar(255) DEFAULT NULL,

  `difficultyLevel` int(11) DEFAULT NULL,

  `lenghtKm` double DEFAULT NULL,

  `lenghtMi` double DEFAULT NULL,

  `name` varchar(255) DEFAULT NULL,

  `originAltitude` double DEFAULT NULL,

  `originDescription` varchar(255) DEFAULT NULL,

  `originLatitude` double DEFAULT NULL,

  `originLongitude` double DEFAULT NULL,

  `originTitle` varchar(255) DEFAULT NULL,

  `ratingD` double DEFAULT NULL,

  `ratingL` double DEFAULT NULL,

  PRIMARY KEY (`id`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

```

```
--
```



-- Dumping data for table `stage`

--

LOCK TABLES `stage` WRITE;

/\*!40000 ALTER TABLE `stage` DISABLE KEYS \*/;

INSERT INTO `stage` VALUES (11,0,'This is the briefing from Stage 1','This is the description',NULL,'The city of Pontevedra',42.25,8.38,'Pontevedra',2,95.9,59.458000000000006,'Ourense-Pontevedra',NULL,'The city of Ourense',42.2,7.51,'Ourense',0,0),(12,0,'This is the briefing from Stage 2','This is the end of your trip',NULL,'The end of the path',42.5,8.32,'Santiago de Compostela',1,65.8,40.796,'Pontevedra-Santiago',NULL,'The city of Pontevedra',42.25,8.38,'Pontevedra',0,0),(13,0,'This is the briefing from Stage 3','This is the description',NULL,'The city of Pontevedra',42.25,8.38,'Pontevedra',3,27.4,16.988,'Vigo-Pontevedra',NULL,'The city of Vigo',42.14,8.43,'Vigo',0,0),(14,0,'This is the briefing from Stage 4','This is the description',NULL,'The small town of Avilés',43.33,5.55,'Avilés',6,199,123.38,'Santander-Avilés',NULL,'The city of Santander',43.27,3.48,'Santander',0,0),(15,0,'This is the briefing from Stage 5','This is the description',NULL,'The city of Lugo',43,7.34,'Lugo',5,197,122.14,'Avilés-Lugo',NULL,'The small town of Avilés',43.33,5.55,'Avilés',0,0),(16,0,'This is the briefing from Stage 6','The final Stage of our Route',NULL,'The end of the path',42.5,8.32,'Santiago de Compostela',5,116,71.92,'Lugo-Santiago',NULL,'The city of Lugo',43,7.34,'Lugo',0,0);

/\*!40000 ALTER TABLE `stage` ENABLE KEYS \*/;

UNLOCK TABLES;

--

-- Table structure for table `stageorder`

--

DROP TABLE IF EXISTS `stageorder`;

/\*!40101 SET @saved\_cs\_client = @@character\_set\_client \*/;

/\*!40101 SET character\_set\_client = utf8 \*/;

CREATE TABLE `stageorder` (

  `id` int(11) NOT NULL,

```

`version` int(11) NOT NULL,

`number` int(11) DEFAULT NULL,

`route_id` int(11) NOT NULL,

`stage_id` int(11) NOT NULL,

PRIMARY KEY (`id`),

KEY `FK_fxp fakgnn3sf26elfmaf k3v53` (`route_id`),

KEY `FK_tgoslr0krtwpd0w4kxcxrgeem` (`stage_id`),

CONSTRAINT `FK_tgoslr0krtwpd0w4kxcxrgeem` FOREIGN KEY (`stage_id`) REFERENCES `stage`
(`id`),

CONSTRAINT `FK_fxp fakgnn3sf26elfmaf k3v53` FOREIGN KEY (`route_id`) REFERENCES `route`
(`id`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `stageorder`

--

LOCK TABLES `stageorder` WRITE;

/*!40000 ALTER TABLE `stageorder` DISABLE KEYS */;

INSERT INTO `stageorder` VALUES
(18,0,1,17,11),(19,0,2,17,12),(21,0,1,20,13),(22,0,2,20,12),(24,0,NULL,23,14),(25,0,NULL,23,15)
,(26,0,NULL,23,16);

/*!40000 ALTER TABLE `stageorder` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `stagerating`

--

```

```

DROP TABLE IF EXISTS `stagerating`;

/*!40101 SET @saved_cs_client  = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `stagerating` (
  `id` int(11) NOT NULL,
  `version` int(11) NOT NULL,
  `commentAssessment` varchar(255) DEFAULT NULL,
  `creationMoment` datetime DEFAULT NULL,
  `ratingDifficulty` int(11) DEFAULT NULL,
  `ratingLenght` int(11) DEFAULT NULL,
  `comment` varchar(255) DEFAULT NULL,
  `endMoment` datetime DEFAULT NULL,
  `startMoment` datetime DEFAULT NULL,
  `register_id` int(11) NOT NULL,
  `stage_id` int(11) NOT NULL,
  PRIMARY KEY (`id`),
  KEY `FK_syssgflce7w4vjh293orbl2cd` (`register_id`),
  KEY `FK_bss4s98tf5qcjoadrg15mfpgb` (`stage_id`),
  CONSTRAINT `FK_bss4s98tf5qcjoadrg15mfpgb` FOREIGN KEY (`stage_id`) REFERENCES `stage`
  (`id`),
  CONSTRAINT `FK_syssgflce7w4vjh293orbl2cd` FOREIGN KEY (`register_id`) REFERENCES
  `register` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `stagerating`

```

--

LOCK TABLES `stagerating` WRITE;

/\*!40000 ALTER TABLE `stagerating` DISABLE KEYS \*/;

/\*!40000 ALTER TABLE `stagerating` ENABLE KEYS \*/;

UNLOCK TABLES;

--

-- Table structure for table `useraccount`

--

DROP TABLE IF EXISTS `useraccount`;

/\*!40101 SET @saved\_cs\_client = @@character\_set\_client \*/;

/\*!40101 SET character\_set\_client = utf8 \*/;

CREATE TABLE `useraccount` (

  `id` int(11) NOT NULL,

  `version` int(11) NOT NULL,

  `password` varchar(255) DEFAULT NULL,

  `username` varchar(255) DEFAULT NULL,

  PRIMARY KEY (`id`),

  UNIQUE KEY `UK\_csivo9yqa08nrbkog71ycilh5` (`username`)

) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/\*!40101 SET character\_set\_client = @saved\_cs\_client \*/;

--

-- Dumping data for table `useraccount`

--

```

LOCK TABLES `useraccount` WRITE;

/*!40000 ALTER TABLE `useraccount` DISABLE KEYS */;

INSERT INTO `useraccount` VALUES
(1,0,'e00cf25ad42683b3df678c61f42c6bda','admin1'),(2,0,'c84258e9c39059a89ab77d846ddab
909','admin2');

/*!40000 ALTER TABLE `useraccount` ENABLE KEYS */;

UNLOCK TABLES;

--

-- Table structure for table `useraccount_authorities`

--

DROP TABLE IF EXISTS `useraccount_authorities`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `useraccount_authorities` (
  `UserAccount_id` int(11) NOT NULL,
  `authority` varchar(255) DEFAULT NULL,
  KEY `FK_b63ua47r0u1m7ccc9lte2ui4r` (`UserAccount_id`),
  CONSTRAINT `FK_b63ua47r0u1m7ccc9lte2ui4r` FOREIGN KEY (`UserAccount_id`) REFERENCES
`useraccount` (`id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

--

-- Dumping data for table `useraccount_authorities`

--

```

```
LOCK TABLES `useraccount_authorities` WRITE;

/*!40000 ALTER TABLE `useraccount_authorities` DISABLE KEYS */;

INSERT INTO `useraccount_authorities` VALUES (1,'ADMIN'),(2,'ADMIN');

/*!40000 ALTER TABLE `useraccount_authorities` ENABLE KEYS */;

UNLOCK TABLES;

/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;

/*!40014 SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;

/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;

/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;

/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;

/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;

/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;

-- Dump completed on 2015-02-27 22:08:57

commit;
```