Waste & Recycling Management

Advanced Web project – Design documents

1. Use case diagram (overview) p. 2

2. Use case – Plan a collection (Manager) p. 3

3. Use case – Carry out a collection round (Driver) p. 4

4. Database – Table diagram (physical model) p. 5


5. Database – Conceptual view p. 6

6. Planned Gantt chart p. 7

7. Member diagrams – Amadeo Berthelot (wireframe, activity, sequence) p. 8–10


Jules Venot · Amadeo Berthelot · Hadi Daccache

Waste & Recycling Management – Use Case Diagram



Use Case – Plan a collection

Actor: Manager (admin) · Tables: collection, collection_point, treatment_center, app_user



ID / Name	UC-A – Plan a collection
Primary actor	Manager (role *manager* in *app_user*)
Goal	Schedule the pickup of a collection point on a given date, linked to a treatment center, with a driver and a vehicle.
Preconditions	The manager is logged in. At least one collection point and one **active** treatment center exist.
Postconditions	A new row is stored in *collection* with status **planned**; it appears in the drivers' "collection rounds" list.
Trigger	A bin is full, or the weekly planning of rounds is prepared.

Main success scenario


1. The manager opens the **Collections** page and clicks "Plan a collection".
2. The system displays a form with the list of collection points.
3. The manager selects a collection point.
4. The system pre-selects the treatment center linked to this point (*collection_point.center_id*).
5. The manager chooses the collection date, a driver and a vehicle plate.
6. The manager confirms the form.
7. The system validates the data, saves the collection with status **planned** and shows it in the list.

Alternative / error flows

- **4a.** The point has no linked center (deleted center → NULL): the manager picks an active center manually.
- **5a.** The date is in the past: the system refuses and asks for a valid date.
- **5b.** The driver already has a collection at that date: the system shows a warning; the manager confirms or picks another driver.
- **7a.** The selected center is inactive (*is_active* = false): the collection is rejected.
- **Extension.** Later, the manager can reschedule a planned collection or set it to **cancelled**.

Use Case – Carry out a collection round

Actor: Collection driver · Tables: collection, collection_waste, waste_type




ID / Name	UC-B – Carry out a collection round
Primary actor	Collection driver (role *driver* in *app_user*)
Goal	Follow the collections planned for the day, update their status and record the quantity of each type of waste collected.
Preconditions	The driver is logged in. At least one collection with status **planned** is assigned to the driver for today.
Postconditions	The collection is **completed** and one row per waste type is stored in *collection_waste*; the recycling statistics are updated.
Trigger	The driver starts the daily round.


Main success scenario

1. The driver opens the **Collections** page; the system lists the collections assigned for today.
2. On arrival at a collection point, the driver sets the collection status to **in_progress**.
3. The driver adds a line for each waste type collected: waste type, quantity (kg) and “sorted” yes/no.
4. The system checks the values and saves them in *collection_waste*.
5. The driver sets the status to **completed**.
6. The system confirms and the collection disappears from the list of remaining tasks.
7. Steps 2–6 are repeated for every point of the round.

Alternative / error flows

- **3a.** The same waste type is entered twice: the system refuses (primary key *collection_id* + *waste_type_id*) and offers to edit the existing line.
- **3b.** Quantity is negative or empty: the system shows an error.
- **5a.** No waste recorded: the system asks for confirmation before setting the status to completed (empty bin).
- **Extension.** The point is inaccessible (road works, blocked bin): the driver reports the problem and the collection is set to **cancelled**; the manager is notified to reschedule it.


treatment_center
center_id int(11) N
name varchar(100)
city varchar(80)
address varchar(150) N
capacity_tons decimal(10, 2)
opening_date date N
is_active int(1)
waste_type
waste_type_id int(11) N
label varchar(80)
category varchar(20)
is_recyclable int(1)
price_per_ton decimal(8, 2)
color_code char(7) N
collection_waste
collection_id int(11)
waste_type_id int(11)
quantity_kg decimal(10, 2)
is_sorted int(1)
collection
collection_id int(11) N
point_id int(11)
center_id int(11)
collection_date date
vehicle_plate varchar(15) N
driver_name varchar(100) N
status varchar(20)
collection_point
point_id int(11) N
name varchar(100)
point_type varchar(20)
address varchar(150) N
city varchar(80)
latitude decimal(9, 6) N
longitude decimal(9, 6) N
center_id int(11) N


WASTE MANAGEMENT SYSTEM - CONCEPTUAL LOGICAL VIEW
TREATMENT CENTER
Treatment Center
(1..1)
manages
(0..n)
COLLECTION POINT
Collection Point
supplies
(1..1)
(0..n)
(1..1)
processes
(1..n)
COLLECTION
Collection
WASTE TYPE
Waste Type
(1..1)
(1..1)
(1..n)
comprises
(0..n)
categorizes
COLLECTION WASTE
Collection Waste


Waste & Recycling Management – Planned Gantt (3 Sep → 17 Dec 2026)

Task	Owner	W1 31 Aug	W2 07 Sep	W3 14 Sep	W4 21 Sep	W5 28 Sep	W6 05 Oct	W7 12 Oct	W8 19 Oct	W9 26 Oct	W10 02 Nov	W11 09 Nov	W12 16 Nov	W13 23 Nov	W14 30 Nov	W15 07 Dec	W16 14 Dec
PHASE 1 – Analysis & database	All																
Topic, team, entities, planned functions (CRUD + non-CRUD)	All																
ER diagram + table structure diagram (PDF)	Jules																
◆ 10 Sep – email: topic + ER / table diagrams	Jules																
Full SQL (drop/create/insert) + fake JSON (10+ rows)	Hadi																
Git repo, .gitignore, README	Amadeo																
◆ 17 Sep – SQL + JSON + diagrams PDF in git	Amadeo																
PHASE 2 – Frontend (Vue.js, fake JSON)	All																
Vue setup, router, navbar, layout	Amadeo																
List / table pages (4 tables)	Amadeo / Hadi																
Use case diagram + planned Gantt	All																
◆ 15 Oct – use case, Gantt, 3 list pages, branches	All																
Wireframe, activity, sequence (1 each per member)	All																
Datasheet + editor pages: full CRUD on JSON	Hadi / Amadeo																
◆ 29 Oct – full frontend + member diagrams	Hadi / Amadeo																
◆ 4 Nov – Midterm	All																
PHASE 3 – Server (Express + MySQL)	All																
Express setup, MVC pipeline, DB controllers	Jules																
Component (per member) + class diagram	All																
◆ 26 Nov – server in git + component / class diagrams	Jules																
List controllers + Postman tests	Jules / Hadi																
Frontend fetch: at least 3 server reads	Amadeo																
Update diagrams to the real implementation + TODO list	All																
◆ 4 Dec – big project recheck	All																
PHASE 4 – Finish & exam	All																
Authentication (bcrypt) + authorization	Jules																
Full CRUD via server + business logic (views, GROUP BY, JOIN stats)	Hadi / Amadeo																
All diagrams in one PDF + actual Gantt	All																
◆ 17 Dec – project exam	All																

Project mgmt / UML Database Frontend Backend Quality & docs

Wireframe — Collection datasheet (driver view)

Screen used during use case **UC-B "Carry out a collection round"** · route `/collections/:id` · tables `collection`, `collection_waste`, `waste_type`




Annotations

1. Shared navbar; the current section (*Collections*) is highlighted.
2. Read-only facts of the `collection` row. Point and center are links to their own datasheets (FK `point_id`, `center_id`).
3. Status buttons follow the ENUM: *planned* → *in_progress* → *completed*, or *cancelled* when the point is inaccessible (UC-B steps 2, 5 and extension).
4. One row per `collection_waste` line (JOIN with `waste_type` for the label and colour). Each line can be edited or removed.
5. Inline "add line" row: waste type, sorted yes/no, quantity in kg. The total is recalculated after each change (SUM of `quantity_kg`).
6. Inline error message, no pop-up: duplicate waste type (PK `collection_id + waste_type_id`, flow 3a) or empty / negative quantity (flow 3b).

Legend
Dark button = main action · dashed border = exceptional action / message · ▾ = drop-down · □ = checkbox · hatched area = header picture.

Activity diagram — Carry out a collection round


Use case **UC-B** · actor: collection driver (role `driver` in `app_user`) · includes alternative flows 3a, 3b, 5a and the “point inaccessible” extension



Source: docs/diagrams/src/amadeo_activity.mmd (Mermaid, editable on mermaid.live)

Sequence diagram — Record a collected waste line

UC-B steps 3–4 · planned server flow (Express MVC pipeline + repository) · `POST /api/collections/:id/waste` → `INSERT INTO collection_waste`



Source: docs/diagrams/src/amadeo_sequence.mmd (Mermaid, editable on mermaid.live) · solid arrow = call, dashed = return