View product details on medias

06.03.2026, 15:52:00 CET

SCHAEFFLER



ZKLN60110-2Z-XL

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN..-2Z, double direction, gap seals on both sides

X-life

Technical information







Your current product variant

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	60 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0.008 mm	Bore diameter lower tolerance
D	110 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0.015 mm	Outside diameter lower tolerance
B	45 mm	Width
	0 mm	Width upper tolerance
	-0.25 mm	Width lower tolerance
C_a	93,000 N	Basic dynamic load rating, axial
C_{0a}	214,000 N	Basic static load rating, axial
C_{ua}	13,000 N	Fatigue load limit, axial
n_G Grease	4,000 1/min	Limiting speed for grease lubrication
n_ϑ	3,000 1/min	Thermally safe operating speed
M_R	1 Nm	Bearing frictional torque
≈m	1.8 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Mounting dimensions

$D_{a\ max}$	100 mm	Maximum diameter of housing
$d_{a\ min}$	82 mm	Minimum diameter shaft

Dimensions

d_1	85 mm	Rib diameter inner ring
r_{min}	0.6 mm	Minimum chamfer dimension
$r_{1\ min}$	0.6 mm	Minimum chamfer dimension
α	60 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

c_{aL}	1,300 N/µm	Rigidity axial
c_{kL}	1,650 Nm/mrad	Tilting rigidity
M_m	13.7 kg*cm2	Mass moment of inertia
	3 µm	Axial runout
	ZMA60/98	Recommended INA precision locknut for radial locking
	AM60	Recommended INA precision locknut for axial locking
M_A	100 Nm	Tightening torque for the recommended INA precision locknut
	16,700 N	Required locknut force axial

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Characteristics

- Radial load
- Axial load in one direction
- Axial load in two directions
- Lifetime lubrication, freedom from maintenance
- Grease Lubrication
- Sealed on both sides

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form