```
CREATE TABLE Client (
        client_id       SERIAL PRIMARY KEY,
        first_name              VARCHAR(100) NOT NULL,
        last_name               VARCHAR(100) NOT NULL,
        birth_date      DATE,
        date_added              DATE DEFAULT CURRENT_DATE,
    date_most_recent_contact DATE,
    passport_information TEXT,
        source          VARCHAR(150),
        company                 VARCHAR(150),
    mailing_address     TEXT,
        notes           TEXT,
    engagement_score            INT
);
CREATE TABLE Pipeline (
        pipeline_id     SERIAL PRIMARY KEY,
        client_id       INT NOT NULL,
        days_in_pipeline INT,
        lost_comment TEXT,
        location        VARCHAR(150),

        CONSTRAINT fk_pipeline_client
        FOREIGN KEY (client_id)
        REFERENCES Client(client_id)
```

```
        ON DELETE CASCADE
);
CREATE TABLE Contact_Information (
        contact_id      SERIAL PRIMARY KEY,
        client_id       INT NOT NULL,
        contact_info    VARCHAR(255) NOT NULL,
        type            VARCHAR(50),
    preferred_communication_method VARCHAR(50),

        CONSTRAINT fk_contact_client
        FOREIGN KEY (client_id)
        REFERENCES Client(client_id)
        ON DELETE CASCADE
);
CREATE TABLE Touchpoint (
        touchpoint_id   SERIAL PRIMARY KEY,
        client_id       INT NOT NULL,
        cost            DECIMAL(10,2),
        engagement_score INT,
        status          VARCHAR(50),
        due_date        DATE,
        type            VARCHAR(50),
        notes           TEXT,
        date_occurred   DATE,
```

```
    CONSTRAINT fk_touchpoint_client
    FOREIGN KEY (client_id)
    REFERENCES Client(client_id)
    ON DELETE CASCADE
);

CREATE TABLE Trip (
    trip_id  SERIAL PRIMARY KEY,
    client_id   INT NOT NULL,
    status  VARCHAR(50),
    start_date  DATE,

    CONSTRAINT fk_trip_client
    FOREIGN KEY (client_id)
    REFERENCES Client(client_id)
    ON DELETE CASCADE
);

CREATE TABLE Trip_Event (
    trip_event_id  SERIAL PRIMARY KEY,
    trip_id         INT NOT NULL,
    status          VARCHAR(50),
    due_date        DATE,
```

```
    type            VARCHAR(50),
    date_occurred  DATE,

    CONSTRAINT fk_trip_event_trip
    FOREIGN KEY (trip_id)
    REFERENCES Trip(trip_id)
    ON DELETE CASCADE
);

CREATE TABLE Post_Trip_Reflection (
    reflection_id  SERIAL PRIMARY KEY,
    trip_id         INT NOT NULL,
    client_notes   TEXT,
    follow_up_action TEXT,
    engagement_score INT,
    reflection_date DATE,

    CONSTRAINT fk_reflection_trip
    FOREIGN KEY (trip_id)
    REFERENCES Trip(trip_id)
    ON DELETE CASCADE
);

CREATE TABLE Itinerary (
```

```
    itinerary_id  SERIAL PRIMARY KEY,
    trip_id       INT NOT NULL,
    active        BOOLEAN DEFAULT TRUE,
    date_created  DATE DEFAULT CURRENT_DATE,

    CONSTRAINT fk_itinerary_trip
    FOREIGN KEY (trip_id)
    REFERENCES Trip(trip_id)
    ON DELETE CASCADE
);

CREATE TABLE Itinerary_Item (
    itinerary_item_id SERIAL PRIMARY KEY,
    itinerary_id  INT NOT NULL,
    location      VARCHAR(150),
    date          DATE,
    type          VARCHAR(100),

    CONSTRAINT fk_item_itinerary
    FOREIGN KEY (itinerary_id)
    REFERENCES Itinerary(itinerary_id)
    ON DELETE CASCADE
);
```

```
CREATE TABLE Cost (
        cost_id         SERIAL PRIMARY KEY,
    itinerary_item_id  INT NOT NULL,
        individuals     INT,
        couples         INT,
    number_of_people   INT,
        cost_single     DECIMAL(10,2),
        cost_couple     DECIMAL(10,2),
        active_choice           BOOLEAN DEFAULT FALSE,
        actual_cost     DECIMAL(10,2),

        CONSTRAINT fk_cost_item
        FOREIGN KEY (itinerary_item_id)
        REFERENCES Itinerary_Item(itinerary_item_id)
        ON DELETE CASCADE
);

CREATE TABLE Guests (
        guest_id        SERIAL PRIMARY KEY,
        first_name      VARCHAR(100) NOT NULL,
        last_name               VARCHAR(100) NOT NULL,
        birth_date      DATE,
    mailing_address     TEXT,
    passport_information TEXT,
```

```
    anniversary_date    DATE,
        notes           TEXT,
        removed         BOOLEAN DEFAULT FALSE
);



CREATE TABLE Guest_Itinerary (
        guest_id        INT NOT NULL,
        itinerary_id  INT NOT NULL,

        PRIMARY KEY (guest_id, itinerary_id),

        CONSTRAINT fk_guest_itinerary_guest
        FOREIGN KEY (guest_id)
        REFERENCES Guests(guest_id)
        ON DELETE CASCADE,

        CONSTRAINT fk_guest_itinerary_itinerary
        FOREIGN KEY (itinerary_id)
        REFERENCES Itinerary(itinerary_id)
        ON DELETE CASCADE
);
```