


What is MLflow?

INTRODUCTION TO MLFLOW



Weston Bassler
Senior MLOps Engineer

The machine learning lifecycle



¹ datacamp.com

Difficulties of machine learning

- **Tracking:**
 - Models and model metrics
- **Reproducibility:**
 - Platforms, environments and workspaces
- **Deployment:**
 - So many options and no standards

What is MLflow?




"An open source platform for the machine learning lifecycle" - [MLflow.org](https://mlflow.org)

¹ www.mlflow.org

Components of MLflow

- **MLflow Tracking:**
 - Record metrics and parameters from training runs
 - Query data from experiments
 - Store models, artifacts and code
- **Model Registry:**
 - Store and version ML models
 - Load and deploy ML models
- **MLflow Models:**
 - Standardize models for deployment
 - Build customized models
- **MLflow Projects:**
 - Package ML code for reproducibility
 - Package ML code for repeatability

Integrations with:





























¹ www.mlflow.org

MLflow experiments

Experiments



Search Experiments

- ☒ Default  
- ☐ Scores Experiment  
- ☐ Scores  
- ☐ Unicorn Experiment  
- ☐ Unicorn  
- ☐ Unicorn Model  
- ☐ 5  
- ☐ Test  
- ☐ 7  
- ☐ Test 2  
- ☐ 9  
- ☐ Test 3  
- ☐ 11  

Default

Share

 Track machine learning training runs in experiments. [Learn more](#) 

Experiment ID: 0 Artifact Location: ./mlruns/0

> Description [Edit](#)


 metrics.rmse < 1 and params.model = "tree" 

 Sort: Created 

 Columns 







 Refresh

Time created: All time 

State: Active 

Showing 3 matching runs

				Metrics	
<input type="checkbox"/>	Run Name	Created 	Duration	metric_1	metric_2
<input type="checkbox"/>	rumbling-deer-742	 3 months ago	2.0s	0.872	1.824
<input type="checkbox"/>	receptive-kit-255	 3 months ago	2.0s	0.86	1.356
<input type="checkbox"/>	bright-gnu-469	 3 months ago	2.0s	0.242	1.263

Working with experiments

MLflow Client

- Create Experiments

```
client.create_experiment("Name")
```

- Tag Experiments

```
client.set_experiment_tag("Name",  
k, v)
```

- Delete Experiments

```
client.delete_experiment("Name")
```

MLflow module

- Create Experiments

```
mlflow.create_experiment("Name")
```

- Tag Experiments

```
mlflow.set_experiment_tag(k, v)
```

- Delete Experiments

```
mlflow.delete_experiment("Name")
```

- Set Experiment

```
mlflow.set_experiment("Name")
```


Starting a new experiment

```
import mlflow
# Create new Experiment
mlflow.create_experiment("My Experiment")
# Tag new experiment
mlflow.set_experiment_tag("scikit-learn", "lr")
# Set the experiment
mlflow.set_experiment("My Experiment")
```

Let's practice!

INTRODUCTION TO MLFLOW


MLflow Tracking

INTRODUCTION TO MLFLOW



Weston Bassler
Senior MLOps Engineer

Tracking data about models



¹ istock.com

What is MLflow Tracking?

- Model Metrics
 - F1, Recall, Accuracy, MSE, etc...
- Parameters
 - library specific
- code
 - `train.py`
- other artifacts
 - tokenizers, pickle, etc...

Training runs

- How MLflow is organized
- New run equals new model training
- A run is placed within an experiment
- Invoked via `mlflow.start_run()`



¹ unsplash.com

Starting a training run

```
import mlflow

# Start a run
mlflow.start_run()
```

```
<ActiveRun: >
```

```
# End a run
mlflow.end_run()
```

Setting a training run variable

```
import mlflow
# Set experiment
mlflow.set_experiment("My Experiment")
# Start a run
run = mlflow.start_run()
# Print run info
run.info
```

```
<RunInfo: artifact_uri='./mlruns/0/9de5df4d19994546b03dce09aefb58af/artifacts',
  end_time=None, experiment_id='31', lifecycle_stage='active',
  run_id='9de5df4d19994546b03dce09aefb58af', run_name='big-owl-145',
  run_uuid='9de5df4d19994546b03dce09aefb58af', start_time=1676838126924,
  status='RUNNING', user_id='user'>
```


Logging to MLflow Tracking

- **Metrics**

- `log_metric("accuracy", 0.90)`
- `log_metrics({"accuracy": 0.90, "loss": 0.50})`

- **Parameters**

- `log_param("n_jobs", 1)`
- `log_params({"n_jobs": 1, "fit_intercept": False})`

- **Artifacts**

- `log_artifact("file.py")`
- `log_artifacts("./directory/")`

Logging a run

```
import mlflow
# Set Experiment
mlflow.set_experiment("LR Experiment")

# Start a run
mlflow.start_run()

# Model Training Code here
lr = LogisticRegression(n_jobs=1)

# Model evaluation Code here
lr.fit(X, y)
score = lr.score(X, y)
```

```
# Log a metric
mlflow.log_metric("score", score)

# Log a parameter
mlflow.log_param("n_jobs", 1)

# Log an artifact
mlflow.log_artifact("train_code.py")
```

Open MLflow UI

```
# Open MLflow Tracking UI  
mlflow ui
```

Go to: <http://localhost:5000>




Tracking UI experiment view



LR Experiment



Share


Experiment ID: 37 Artifact Location: ./mlruns/37

> Description [Edit](#)



 Sort: Created 



 Columns 

 Refresh

Time created: All time 

State: Active 

Showing 1 matching run

				Metrics	Parameters
<input type="checkbox"/>	Run Name	Created 	Models	score	n_jobs
<input type="checkbox"/>	silent-slug-662	 1 minute ago	-	0.951	1

Tracking UI run view

[LR Experiment](#) >

silent-slug-662

Run ID: a410480d4ccc4601904085b5651483b4

Date: 2023-02-20 08:14:05

Source: 

User: [weston](#)

Duration: 1.5min

Status: FINISHED


Lifecycle Stage: [active](#)

> Description [Edit](#)

Parameters (1)

Name	Value
n_jobs	1

Metrics (1)

Name	Value
score 	0.951

> Tags

Artifacts

 train_code.py

Let's practice!

INTRODUCTION TO MLFLOW

Querying runs

INTRODUCTION TO MLFLOW



Weston Bassler

Senior MLOps Engineer

Model data



¹ istock.com

Runs data

Insurnace Experiment

Experiment ID: 27 Artifact Location: ./mlruns/27

> Description [Edit](#)









Sort: accuracy_score ▾

 Columns ▾

Time created: All time ▾

State: Active ▾

			Metrics						
<input type="checkbox"/>	Run Name	Cr Models	accuracy_score	example_count	f1_score	false_negative	false_positives	precision_score	recall_score
<input type="checkbox"/>	wise-mole-318	 shap , 1 mo	0.621	335	0.623	65	62	0.629	0.618
<input type="checkbox"/>	invincible-lark-929	 shap , 1 mo	0.621	335	0.623	65	62	0.629	0.618
<input type="checkbox"/>	sedate-fawn-631	 shap , 1 mo	0.621	335	0.623	65	62	0.629	0.618
<input type="checkbox"/>	awesome-moth-449	 shap , 1 mo	0.621	335	0.623	65	62	0.629	0.618
<input type="checkbox"/>	fun-grub-597	 shap , 1 mo	0.621	335	0.623	65	62	0.629	0.618
<input type="checkbox"/>	...	 shap , 1 mo	0.621	335	0.623	65	62	0.629	0.618

Searching runs

```
mlflow.search_runs()
```



¹ <https://pandas.pydata.org/>

Output format

#	Column	Non-Null Count	Dtype
0	run_id	6 non-null	object
1	experiment_id	6 non-null	object
2	status	6 non-null	object
3	artifact_uri	6 non-null	object
4	start_time	6 non-null	datetime64[ns, UTC]
5	end_time	5 non-null	datetime64[ns, UTC]
6	metrics.test	1 non-null	float64
7	metrics.metric_2	3 non-null	float64
8	metrics.metric_1	3 non-null	float64
9	params.param_1	3 non-null	object
10	params.random_state	3 non-null	object
11	params.n_estimators	3 non-null	object
12	tags.mlflow.user	6 non-null	object
13	tags.mlflow.runName	6 non-null	object
14	tags.mlflow.source.type	6 non-null	object
15	tags.mlflow.source.name	6 non-null	object

Filtering run searches


- `max_results` - maximum number of results to return.
- `order_by` - column(s) to sort in `ASC` ending or `DESC` ending order.
- `filter_string` - string based query.
- `experiment_names` - name(s) of experiments to query.

Tracking UI

Insurance Experiment

Experiment ID: 27 Artifact Location: ./mlruns/27

> Description [Edit](#)



Sort: accuracy_score ▾

Columns ▾

Time created: All time ▾

State: Active ▾

S

				Metrics				
<input type="checkbox"/>	Run Name	Created	Duration	accuracy_score ▾	f1_score	false_negative	false_positives	precision_score
<input type="checkbox"/>	wise-mole-318	✔ 3 months ago	10.4s	0.621	0.623	65	62	0.629
<input type="checkbox"/>	powerful-shoat-853	✔ 3 months ago	5.0s	0.621	0.623	65	62	0.629
<input type="checkbox"/>	amazing-penguin-22	✔ 3 months ago	4.6s	0.537	0.485	97	58	0.557
<input type="checkbox"/>	traveling-snipe-808	✔ 3 months ago	5.6s	0.537	0.485	97	58	0.557

Search runs example

```
import mlflow
# Filter string
f1_score_filter = "metrics.f1_score > 0.60"
# Search runs
mlflow.search_runs(experiment_names=["Insurance Experiment"],
                   filter_string=f1_score_filter,
                   order_by=["metrics.precision_score DESC"])
```

```
# Create a filter string for R-squared score
= "metrics.r2_score > .70"# Search runs
(
    =["Unicorn Sklearn
Experiments", "Unicorn Other Experiments"],
    =
    =["metrics.r2_score DESC"])
```

Example output

```
# Search runs from Insurance Experiment
mlflow.search_runs(experiment_names=["Insurance Experiment"],
    filter_string=f1_score_filter,
    order_by=["metrics.precision_score DESC"])
```

	run_id	experiment_id	...	tags.mlflow.source.type	tags.mlflow.user
0	90407e29a5aa4a31954bed874c7d4337	27	...	LOCAL	user
1	c335c0b16a5d4cf398aaa7189362b577	27	...	LOCAL	user

Let's practice!

INTRODUCTION TO MLFLOW