

Julia Interfaces to Standard Ephemeris Platforms




Joseph D Carpinelli 

Abstract

Solar system ephemerides are available for free to researchers, students, and professionals in-industry through open source tools, and REST APIs, and web interfaces ([Giorgini, 2015](#)). Users commonly parse this data programatically with dynamic programming languages, including Python and Julia. This document presents several Julia packages which can aid ephemeris users in sourcing and parsing data with replicatability. Rather than include solar system ephemeris files in source code distributions, ephemeris data sourcing can be accomplished directly in-code. Three packages which interface to the JPL SPICE ephemeris platform are presented: `SPICEApplications.jl`, `SPICEKernels.jl`, and `SPICEBodies.jl`. In addition, two packages which interface with the JPL HORIZONS ephemeris platform are presented: `HorizonsAPI.jl` and `HorizonsEphemeris.jl`. All packages are described in-detail in their common documentation site: ephemeris.loopy.codes.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Introduction

Students and professionals in astronomy, astrodynamics, astrophysics, and other related fields often download and parse solar system ephemeris data from two major providers: [Generic JPL SPICE Kernels](#), and [JPL Horizons](#). SPICE Kernels are typically read through the SPICE Toolkit, which is available in a variety of programming languages, include the C Programming Language with CSPICE ([Acton, 1996](#)). The Julia packages `CSPICE.jl` and `SPICE.jl` expose many CSPICE functions through Julia functions. Julia users can load and interact with SPICE kernels `SPICE.furnsh` and `SPICE.spkez`. Horizons data is available through a variety of methods, including email, command-line, graphical web interfaces, and a [REST API](#).

This paper introduces several packages which allow users to download and process ephemeris data idiomatically, all from within Julia. Through the use of these packages, users can share replicatable code which automatically fetches publicly available ephemeris data, as opposed to manually including ephemeris data files with their source code distribution.

Statement of Need

While ephemeris users have all of the tools they need to fetch and parse ephemeris data within Julia, they do not have the tools to do so *simply* or *idiomatically*. [Section 2.1](#) and [Section 2.2](#) present the research needs filled by each of the five packages introduced in this paper.

JPL HORIZONS

The two HORIZONS-related packages presented in this paper — [HorizonsAPI.jl](#) and [HorizonsEphemeris.jl](#) — are respectively the first Julia packages to precisely match the REST API with tab-completion through static keyword arguments, and the first to offer automatic response parsing into `NamedTuple` types. The `NamedTuple` output of `HorizonsEphemeris.ephemeris`, the top-level method for fetching Cartesian state vectors from the HORIZONS platform, allows for easy plotting, file-saving, and `DataFrame` construction. Both `HorizonsAPI.jl` and `HorizonsEphemeris.jl` offer users a simple, repeatable way to query and parse HORIZONS ephemeris data.

JPL SPICE

The three SPICE-related packages presented in this paper — SPICEApplications.jl, SPICEKernels.jl, and SPICEBodies.jl — provide idiomatic kernel fetching, inspection, and caching from within Julia. While SPICE Toolkit executables were bundled in Julia through CSPICE_jll, they have not been previously exposed through Julia functions. SPICEApplications.jl wraps each executable with a Julia function, allowing users to easily call SPICE Toolkit executables within their Julia programs, just as they can with CSPICE routines wrapped in SPICE.jl.

Julia users interact with SPICE kernels by downloading publicly-available aGeneric Kernels, and parsing the data using SPICE.jl, or another ephemeris parsing source. This workflow requires that users know how to find the correct generic kernels for their chosen application, and that they know how to use CSPICE functions to retrieve their desired data. SPICEKernels.jl and SPICEBodies.jl offer idiomatic interfaces to ephemeris fetching and parsing parsing respectively. Continuous integration in the SPICEKernels.jl repository multiple times daily, and automatically exports all available generic kernels as variables in Julia. SPICE Toolkit executables (provided by SPICEApplications.jl) are used to retrieve a description of each kernel's contents, and place that description in the Julia variable's docstring. As a result, users can use tab-completion and Julia's built-in documentation tools to inspect kernel contents, and download the correct kernel for their application. Once each kernel is downloaded and loaded into the SPICE kernel pool with SPICE.jl, users can use SPICEBodies.jl to idiomatically fetch data at a provided instance in time.

Usage

For detailed usage examples, consult the common documentation site for all of the packages presented in this paper. The code examples below show how a user may retrieve data from the HORIZONS platform, inspect a SPICE kernel before downloading it, and retrieve Cartesian state data at an instance in time.

```
using Dates, DataFrames
using HorizonsEphemeris

ephemeris("earth", now()) |> DataFrame
```

	t	cal	x	y	z	\dot{x}
	Float64	String31	Float64	Float64	Float64	Float64
1	2.46042e6	A.D. 2024-Apr-21 17:40:38.3950	-0.861881	-0.488931	-0.211718	0.00878281

```
using SPICEApplications, SPICEKernels

brief(de440s()); # alternatively, check the kernel variable's docstring: @doc(de440s)

BRIEF -- Version 4.1.0, September 17, 2021 -- Toolkit Version N0067

Summary for: /Users/joey/.julia/scratchspaces/8e9d28ce-e483-4ef7-bfd9-45b8fef6369c/kerne

Bodies: MERCURY BARYCENTER (1) SATURN BARYCENTER (6) MERCURY (199)
         VENUS BARYCENTER (2)  URANUS BARYCENTER (7)  VENUS (299)
         EARTH BARYCENTER (3)  NEPTUNE BARYCENTER (8) MOON (301)
         MARS BARYCENTER (4)   PLUTO BARYCENTER (9)  EARTH (399)
         JUPITER BARYCENTER (5) SUN (10)
         Start of Interval (ET) End of Interval (ET)
         -----
         1849 DEC 26 00:00:00.000 2150 JAN 22 00:00:00.000
```

```

89 using Dates, SPICE
90 using SPICEKernels, SPICEBodies
91
92 return furnsh(
93     de432s(),           # position and velocity data for nearby planets
94     latest_leapseconds_lsk(), # timekeeping, parsing epochs
95     gm_de440(),         # mass parameters for major solar system bodies
96     pck00011(),         # physical properties of major solar system bodies
97 )
98
99 earth = KernelBody("earth")
100 x, y, z, ẋ, ẏ, ż = earth(now())
101
102 6-element Vector{Float64}:
103  -1.2893550563777173e8
104  -7.314298953640346e7
105  -3.1672573014385767e7
106  15.20706013822092
107  -23.339292185675234
108  -10.116328493074919

```

External Packages

The packages presented in this paper which interact with the SPICE Toolkit require users to use [SPICE.jl](#), or another SPICE-compatible kernel loading tool. Support for other SPICE kernel management packages, such as [Ephemerides.jl](#), may be added in the future.

In addition to the packages in this paper which interface with the JPL HORIZONS ephemeris platform, the [HORIZONS.JL](#) package offers simplified interfaces for constructing and sending queries to the JPL HORIZONS REST API.

References

- Acton, C. H. (1996). Ancillary Data Services of NASA's Navigation and Ancillary Information Facility. *Planetary and Space Science*, 44(1), 65–70.
- Giorgini, J. D. (2015). Status of the JPL horizons ephemeris system. *IAU General Assembly*, 29, 2256293.