

VanDerPol Work-Precision Diagrams

Chris Rackauckas

July 4, 2020

```
using OrdinaryDiffEq, DiffEqDevTools, Sundials, ParameterizedFunctions, Plots, ODE,  
ODEInterfaceDiffEq, ODEInterface, LSODA
```

Error: ArgumentError: Package ODEInterface not found in current path:
- Run `import Pkg; Pkg.add("ODEInterface")` to install the ODEInterface package.

```
gr()  
using LinearAlgebra  
LinearAlgebra.BLAS.set_num_threads(1)
```

```
van = @ode_def begin  
    dy =  $\mu * ((1-x^2)*y - x)$   
    dx =  $1*y$   
end  $\mu$ 
```


```
prob = ODEProblem(van, [0; 2.], (0.0, 6.3), 1e6)  
abstols = 1.0 ./ 10.0 .^ (5:9)  
reltols = 1.0 ./ 10.0 .^ (2:6)
```

```
sol = solve(prob, CVODE_BDF(), abstol=1/1014, reltol=1/1014)  
test_sol = TestSolution(sol)
```


```
retcode: Success  
Interpolation: 3rd order Hermite  
t: nothing  
u: nothing
```

0.0.1 Plot Test

```
plot(sol, ylim=[-4; 4])
```



```
plot(sol)
```



0.1 Omissions And Tweaking

The following were omitted from the tests due to convergence failures. ODE.jl's adaptivity is not able to stabilize its algorithms, while GeometricIntegratorsDiffEq has not upgraded to Julia 1.0. GeometricIntegrators.jl's methods used to be either fail to converge at comparable dts (or on some computers errors due to type conversions).

```
#sol = solve(prob,ode23s()); println("Total ODE.jl steps: $(length(sol))")
#using GeometricIntegratorsDiffEq
#try
#     sol = solve(prob,GIRadIIA3(),dt=1/1000)
#catch e
#     println(e)
#end
```

ARKODE needs a lower `nonlinear_convergence_coefficient` in order to not diverge.

```
sol = solve(prob,ARKODE(), abstol=1e-4, reltol=1e-2);
```

```
retcode: Success
Interpolation: 3rd order Hermite
t: 67-element Array{Float64,1}:
 0.0
 5.749667114830345e-12
 4.791703937695112e-10
 6.937321127653181e-9
 3.441348932456689e-8
 1.242075614319914e-7
 2.7833002915369977e-7
 5.271605941797656e-7
 7.759911592058314e-7
 1.1947346368487868e-6
```

```

:
0.0019907624998313864
0.002078339702740356
0.002339121422761175
0.0029039110661651796
0.0038578803826986837
0.004811849699232188
0.006545323108711468
0.008114583820483115
0.008115757710091452
u: 67-element Array{Array{Float64,1},1}:
 [0.0, 2.0]
 [-1.1499235054215125e-5, 2.0]
 [-0.0009576523046803073, 1.999999999997706]
 [-0.01373125939606262, 1.999999999952206]
 [-0.0653932867684174, 1.9999999988554367]
 [-0.20738269006768967, 1.9999999863225233]
 [-0.3774085043828771, 1.9999999402494826]
 [-0.5295224816821857, 1.9999998250670898]
 [-0.6016433974890778, 1.9999996832203253]
 [-0.6480986302315671, 1.999999419542989]
:
 [-0.6674068309061841, 1.9986723129231863]
 [-0.6674331992515048, 1.998613862027106]
 [-0.6674990719448132, 1.9984397938438712]
 [-0.667628994834417, 1.9980627178538726]
 [-0.6680671424810317, 1.997425540358304]
 [-0.6686940561037535, 1.9967880235133677]
 [-0.6703810243516862, 1.9956287106603585]
 [-0.5871133352574344, 1.994578210009938]
 [-0.5871133352574344, 1.994578210009938]

sol = solve(prob,ARKODE(nonlinear_convergence_coefficient =
1e-6), abstol=1e-4, reltol=1e-1);

retcode: Success
Interpolation: 3rd order Hermite
t: 4205-element Array{Float64,1}:
 0.0
 5.749667114830345e-12
 4.791703937695112e-10
 6.950174703123355e-9
 3.7680390665050866e-8
 1.6391466409237974e-7
 4.069899042614494e-7
 8.711024624587683e-7
 1.5770981486067485e-6
 2.7874280262519495e-6
:
 6.277376975965755
 6.28032019042069
 6.283183377375016
 6.286046564329342
 6.288830917074367
 6.291615269819391
 6.293711452364543
 6.295807634909695
 6.3

```

```

u: 4205-element Array{Array{Float64,1},1}:
 [0.0, 2.0]
 [-1.1499235054215125e-5, 2.0]
 [-0.0009576523046803073, 1.9999999999997706]
 [-0.013756436574222222, 1.999999999952029]
 [-0.07125740456649217, 1.999999998632208]
 [-0.2589579904135334, 1.9999999770428876]
 [-0.47000019019459244, 1.9999998853401242]
 [-0.6175523056172345, 1.9999996251157426]
 [-0.6604871146338989, 1.9999991687633294]
 [-0.6663384335769652, 1.9999983638263577]
 ⋮
 [1.31463273621472, -1.4502216551864824]
 [1.3246922387276845, -1.446337796343032]
 [1.3345752830424376, -1.4425309909553559]
 [1.3448465813800377, -1.4386953334012647]
 [1.3549410211470798, -1.4349369320413436]
 [1.3654276856618028, -1.4311498787918024]
 [1.3733682763660415, -1.4282794815915139]
 [1.3815556337247796, -1.4253921223642028]
 [1.398416750766739, -1.4195651966043268]

sol = solve(prob,ARKODE(order=3), abstol=1e-4, reltol=1e-1);

retcode: Success
Interpolation: 3rd order Hermite
t: 262-element Array{Float64,1}:
 0.0
 5.749667114830345e-12
 4.3901876795072515e-9
 8.774625691899672e-9
 9.646338593974809e-8
 1.841521461875965e-7
 7.700816631708706e-7
 1.3560111801541447e-6
 3.949082228420566e-6
 1.1789802601654659e-5
 ⋮
 0.11298197509967592
 0.11298380839542997
 0.11298801005740239
 0.1130053748623104
 0.1131068224569597
 0.11433905890366199
 0.12119409782603513
 0.12662926080921935
 0.12663568109568174
u: 262-element Array{Array{Float64,1},1}:
 [0.0, 2.0]
 [-1.1499235054215125e-5, 2.0]
 [-0.008722807633947647, 1.9999999999808107]
 [-0.017320283728176792, 1.9999999999236775]
 [-0.16757381900079926, 1.9999999915490156]
 [-0.28305989381061913, 1.9999999715852004]
 [-0.6105196086599589, 1.9999996901187271]
 [-0.65844900423416, 1.9999993154753626]
 [-0.6677400989652668, 1.9999975898561386]
 [-0.6666234193152477, 1.9999923623151088]

```

```

:
[-0.6818868924599188, 1.9221363875991244]
[-0.7175603752686264, 1.9221350930981596]
[-0.712803222902284, 1.9221320941669187]
[-0.7133631481534175, 1.9221197074757677]
[-0.7133326089415061, 1.922047338705792]
[-0.7071666434643885, 1.9211679276051756]
[-0.7375313167127185, 1.9162628557567793]
[0.24636917387811208, 1.9123576832843268]
[0.24636917387811208, 1.9123576832843268]

sol = solve(prob,ARKODE(nonlinear_convergence_coefficient =
1e-6,order=3),abstol=1e-4,reltol=1e-1);

retcode: Success
Interpolation: 3rd order Hermite
t: 5849-element Array{Float64,1}:
 0.0
 5.749667114830345e-12
 4.3901876795072515e-9
 8.774625691899672e-9
 9.646338593974809e-8
 1.841521461875965e-7
 7.700815831447913e-7
 1.3560110201019861e-6
 3.949079826682415e-6
 1.1785229199359805e-5
:
 6.282153578661474
 6.283343340084043
 6.286562194011398
 6.289781047938753
 6.292335785954065
 6.294890523969377
 6.296167892977032
 6.297445261984688
 6.3
u: 5849-element Array{Array{Float64,1},1}:
 [0.0, 2.0]
 [-1.1499235054215125e-5, 2.0]
 [-0.008722807633947647, 1.999999999808107]
 [-0.01732028372817669, 1.999999999236775]
 [-0.16757381900079918, 1.9999999915490156]
 [-0.28305989360558576, 1.9999999715852004]
 [-0.6105195898251164, 1.9999996901187744]
 [-0.6584488623090199, 1.999999315475422]
 [-0.6677348327309324, 1.9999975898559847]
 [-0.6665784454943076, 1.9999923653490723]
:
 [1.3318769391697618, -1.4435658592987184]
 [1.3360266395151414, -1.4419787997768507]
 [1.347573057047653, -1.4376598665968587]
 [1.3596736863373744, -1.4333033095612036]
 [1.369063223433025, -1.4298181052243777]
 [1.3790273626823555, -1.4263079600463464]
 [1.3840116143289856, -1.4245433523377944]
 [1.3890441690934623, -1.4227722880905949]
 [1.3994026774014128, -1.4192104815018525]

```

```
sol = solve(prob,ARKODE(order=5,nonlinear_convergence_coefficient =
1e-3),abstol=1e-4,reltol=1e-1);
```

```
retcode: Success
```

```
Interpolation: 3rd order Hermite
```

```
t: 175-element Array{Float64,1}:
```

```
0.0
5.749667114830345e-12
1.6131539822097798e-10
1.4178810016692538e-9
1.9467016298640084e-8
2.2299839492837688e-7
6.9410258452898e-7
2.2343380286801016e-6
4.996464072410812e-6
1.3177719769063345e-5
```

```
⋮
```

```
0.21781440165467003
0.2199025533902211
0.22199070512577218
0.22641165376385933
0.2295696852409037
0.2327277167179481
0.23588574819499247
0.2386710571263909
0.23867462686395108
```

```
u: 175-element Array{Array{Float64,1},1}:
```

```
[0.0, 2.0]
[-1.1499235054215124e-5, 2.0]
[-0.00032255274106088755, 1.9999999999999738]
[-0.0028297393861135135, 1.99999999997992]
[-0.037818950965746286, 1.9999999996283053]
[-0.32518303725581216, 1.9999999597287481]
[-0.5835225092949149, 1.9999997317724212]
[-0.6654167656320736, 1.9999987322462425]
[-0.6666680892850902, 1.9999968912426307]
[-0.6666946561472832, 1.999991437054497]
```

```
⋮
```

```
[-0.8724519534359474, 1.8446221534793241]
[-0.7681927666028643, 1.8430177005846022]
[-0.5135909560385096, 1.8414105680077564]
[-0.7892024587340847, 1.8379992706417554]
[-0.7635853085669171, 1.835555634927881]
[-0.47912592902732515, 1.8331058448058228]
[-0.7822581531401638, 1.830649920805241]
[0.034396436491437865, 1.8284785522385856]
[0.034396436491437865, 1.8284785522385856]
```

```
sol = solve(prob,ARKODE(order=5,nonlinear_convergence_coefficient =
1e-4),abstol=1e-4,reltol=1e-1);
```

```
retcode: Success
```

```
Interpolation: 3rd order Hermite
```

```
t: 1618-element Array{Float64,1}:
```

```
0.0
5.749667114830345e-12
1.6131539822097798e-10
1.4178810016692538e-9
```

```

1.9467016298640084e-8
2.2299839492837688e-7
6.9410258452898e-7
2.2343380286801016e-6
4.996413060669436e-6
1.3190337112605003e-5
:
6.2178735057716334
6.223969302456617
6.230065099141601
6.242805651978197
6.255546204814793
6.268286757651389
6.2810273104879855
6.2937678633245815
6.3
u: 1618-element Array{Array{Float64,1},1}:
 [0.0, 2.0]
 [-1.1499235054215124e-5, 2.0]
 [-0.00032255274106088755, 1.9999999999999738]
 [-0.0028297393861135135, 1.99999999997992]
 [-0.037818950965746286, 1.9999999996283053]
 [-0.32518303725581216, 1.9999999597287481]
 [-0.5835225092949149, 1.9999997317724212]
 [-0.6654163435076001, 1.999998732246102]
 [-0.666668908436716, 1.999996891276912]
 [-0.6666946904177468, 1.9999914286428866]
 :
 [1.1773599643774835, -1.5229500929729562]
 [1.1694104058742847, -1.5158725416037377]
 [1.1880494417611729, -1.5087098220173893]
 [1.2167569401714096, -1.4934498951780604]
 [1.2923315120460783, -1.4777690051239414]
 [1.2227371473134858, -1.4616291764474012]
 [1.3507951884062508, -1.444976089177088]
 [1.4624653585712566, -1.4277643260539639]
 [1.3983693066218381, -1.4191207815330689]

```

Additionally, the ROCK methods do not perform well on this benchmark.

```

setups = [
    #Dict(:alg=>ROCK2())      #Unstable
    #Dict(:alg=>ROCK4())      #needs more iterations
    #Dict(:alg=>ESERK5()),
]

```

```
0-element Array{Any,1}
```

Some of the bad Rosenbrocks fail:

```

setups = [
    #Dict(:alg=>Hairer4()),
    #Dict(:alg=>Hairer42()),
    #Dict(:alg=>Cash4()),
]

```

```
0-element Array{Any,1}
```

The EPIRK and exponential methods also fail:


```
sol = solve(prob,EXPRB53s3(),dt=2.0-8);

Error: InexactError: trunc(Int64, Inf)

sol = solve(prob,EPIRK4s3B(),dt=2.0-8);

Error: InexactError: trunc(Int64, Inf)

sol = solve(prob,EPIRK5P2(),dt=2.0-8);

Error: InexactError: trunc(Int64, Inf)
```

0.2 Low Order and High Tolerance

This tests the case where accuracy is not needed as much and quick robust solutions are necessary. Note that ARKODE's convergence coefficient must be lowered to $1e-7$ in order to converge.

Final timepoint error This measures the efficiency to get the value at the endpoint correct.

```
abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>ddebdf()),
          Dict(:alg=>rodas()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>radau())]

Error: UndefVarError: lsoda not defined

wp = WorkPrecisionSet(prob,abstols,reltols,setups;
                      save_everystep=false,appxsol=test_sol,maxiters=Int(1e5),seconds=5)
plot(wp)

Error: ArgumentError: At least one finite value must be provided to formatter.

setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>Rodas3()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>rodas()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>radau()),
          Dict(:alg=>RadauIIA5()),
          Dict(:alg=>ROS34PW1a()),
          ]

Error: UndefVarError: lsoda not defined

gr()
wp = WorkPrecisionSet(prob,abstols,reltols,setups;
                      save_everystep=false,appxsol=test_sol,maxiters=Int(1e5),numruns=10)
plot(wp)
```

Error: ArgumentError: At least one finite value must be provided to formatter.

```
setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>Kvaerno3()),
          Dict(:alg=>KenCarp4()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>KenCarp3()),
          Dict(:alg=>ARKODE(nonlinear_convergence_coefficient = 1e-6)),
          Dict(:alg=>SDIRK2()),
          Dict(:alg=>radau())]
```

```
names = ["Rosenbrock23" "Kvaerno3" "KenCarp4" "TRBDF2" "KenCarp3" "ARKODE" "SDIRK2"
         "radau"]
```

```
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
```

```
names=names, save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), seconds=5)
```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call loadODESolvers and check also this output. For further information see also ODEInterface.help_install.

```
plot(wp)
```

Error: ArgumentError: At least one finite value must be provided to formatter.


```
setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>KenCarp5()),
          Dict(:alg=>KenCarp4()),
          Dict(:alg=>KenCarp3()),
          Dict(:alg=>ARKODE(order=5, nonlinear_convergence_coefficient = 1e-4)),
          Dict(:alg=>ARKODE(nonlinear_convergence_coefficient = 1e-6)),
          Dict(:alg=>ARKODE(nonlinear_convergence_coefficient = 1e-6, order=3))]
```

```
names = ["Rosenbrock23" "KenCarp5" "KenCarp4" "KenCarp3" "ARKODE5" "ARKODE4" "ARKODE3"]
```

```
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
```

```
names=names, save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), seconds=5)
```


```
plot(wp)
```



```

setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>ImplicitEulerExtrapolation()),
          #Dict(:alg=>ImplicitDeufllhardExtrapolation()), # Diverges
          #Dict(:alg=>ImplicitHairerWannerExtrapolation()), # Diverges
          Dict(:alg=>ABDF2()),
          #Dict(:alg=>QNDF()), # ???
          #Dict(:alg=>Exprb43()), # Diverges
          Dict(:alg=>Exprb32()),
        ]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
                     save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
plot(wp)

```



Notice that **KenCarp4** is the same overarching algorithm as **ARKODE** here (with major differences to stage predictors and adaptivity though). In this case, **KenCarp4** is more robust and more efficient than **ARKODE**. **CVODE_BDF** does quite well here, which is unusual for it on small equations. You can see that the low-order Rosenbrock methods **Rosenbrock23** and **Rodas3** dominate this test.


Timeseries error Now we measure the average error of the timeseries.

```
abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)
```

```
setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>ddebdf()),
          Dict(:alg=>rodas()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>radau())]
```

Error: UndefVarError: lsoda not defined

```
wp = WorkPrecisionSet(prob,abstols,reltols,setups;
                      error_estimator=:l2,appxsol=test_sol,maxiters=Int(1e5),seconds=5)
plot(wp)
```



```

setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>Rodas3()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>rodas()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>radau()),
          Dict(:alg=>RadauIIA5()),
          Dict(:alg=>ROS34PW1a()),
        ]


```

Error: UndefVarError: lsoda not defined

```

gr()
wp = WorkPrecisionSet(prob, abstols, reltols, setups; error_estimator=:l2,
                     save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
plot(wp)

```



```

setups = [Dict(:alg=>Rosenbrock23(), :dense=>false),
          Dict(:alg=>Kvaerno3(), :dense=>false),
          Dict(:alg=>KenCarp4(), :dense=>false),
          Dict(:alg=>TRBDF2(), :dense=>false),
          Dict(:alg=>KenCarp3(), :dense=>false),
          Dict(:alg=>SDIRK2(), :dense=>false),
          Dict(:alg=>radau())]
names = ["Rosenbrock23" "Kvaerno3" "KenCarp4" "TRBDF2" "KenCarp3" "SDIRK2" "radau"]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;

```

```

names=names, appxsol=test_sol, maxiters=Int(1e5), error_estimator=:l2, seconds=5)


```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call loadODESolvers and check also this output. For further information see also ODEInterface.help_install.

```

plot(wp)


```



```

setups = [Dict(:alg=>Rosenbrock23()),
           Dict(:alg=>TRBDF2()),
           Dict(:alg=>ImplicitEulerExtrapolation()),
           #Dict(:alg=>ImplicitDeuflhardExtrapolation()), # Diverges
           #Dict(:alg=>ImplicitHairerWannerExtrapolation()), # Diverges
           Dict(:alg=>ABDF2()),
           #Dict(:alg=>QNDF()), # ???
           #Dict(:alg=>Exprb43()), # Diverges
           Dict(:alg=>Exprb32()),
]
wp = WorkPrecisionSet(prob, abstols, reltols, setups; error_estimator=:l2,
                     save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
plot(wp)

```




0.2.1 Higher accuracy tests

Now we transition to higher accuracy tests. In this domain higher order methods are stable and much more efficient.

```
abstols = 1.0 ./ 10.0 .^ (7:11)
reltols = 1.0 ./ 10.0 .^ (4:8)
setups = [Dict(:alg=>Rodas3()),
          Dict(:alg=>GRK4A()),
          Dict(:alg=>Rodas4P()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>Rodas4()),
          Dict(:alg=>rodas()),
          Dict(:alg=>radau()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>RadauIIA5()),
          Dict(:alg=>Rodas5())]
```

Error: UndefVarError: lsoda not defined

```
wp = WorkPrecisionSet(prob,abstols,reltols,setups;
                      save_everystep=false,appxsol=test_sol,maxiters=Int(1e6),seconds=5)
plot(wp)
```

```


abstols = 1.0 ./ 10.0 .^ (7:11)
reltols = 1.0 ./ 10.0 .^ (4:8)
setups = [Dict(:alg=>Rodas3()),
          Dict(:alg=>Kvaerno4()),
          Dict(:alg=>Kvaerno5()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>KenCarp4()),
          Dict(:alg=>KenCarp5()),
          Dict(:alg=>ARKODE()),
          Dict(:alg=>Rodas4()),
          Dict(:alg=>radau()),
          Dict(:alg=>Rodas5())]
names = ["Rodas3" "Kvaerno4" "Kvaerno5" "CVODE_BDF" "KenCarp4" "KenCarp5" "ARKODE"
"Rodas4" "radau" "Rodas5"]
wp = WorkPrecisionSet(prob,abstols,reltols,setups;

names=names,save_everystep=false,appxsol=test_sol,maxiters=Int(1e6),seconds=5)

```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call loadODESolvers and check also this output. For further information see also ODEInterface.help_install.

```
plot(wp)
```




```

setups = [Dict(:alg=>Rodas3()),
          Dict(:alg=>CVMODE_BDF()),
          Dict(:alg=>Rodas4()),
          Dict(:alg=>radau()),
          Dict(:alg=>Rodas5())]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
                      save_everystep=false, appxsol=test_sol, maxiters=Int(1e6), seconds=5)

```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call loadODESolvers and check also this output. For further information see also ODEInterface.help_install.

```
plot(wp)
```



```

abstols = 1.0 ./ 10.0 .^ (7:11)
reltols = 1.0 ./ 10.0 .^ (4:8)
setups = [Dict(:alg=>Rodas3()),
          Dict(:alg=>GRK4A()),
          Dict(:alg=>Rodas4P()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>Rodas4()),
          Dict(:alg=>rodas()),
          Dict(:alg=>radau()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>RadauIIA5()),
          Dict(:alg=>Rodas5())]

```

Error: UndefVarError: lsoda not defined


```

wp = WorkPrecisionSet(prob,abstols,reltols,setups;error_estimate=:l2,
                      save_everystep=false,appxsol=test_sol,maxiters=Int(1e6),seconds=5)

```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call lo adODESolvers and check also this output. For further information see also 0 DEInterface.help_install.

```
plot(wp)
```



```

setups = [Dict(:alg=>Rodas3()),
          Dict(:alg=>Kvaerno4()),
          Dict(:alg=>Kvaerno5()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>KenCarp4()),
          Dict(:alg=>KenCarp5()),
          Dict(:alg=>Rodas4()),
          Dict(:alg=>radau()),
          Dict(:alg=>Rodas5())]

names = ["Rodas3" "Kvaerno4" "Kvaerno5" "CVODE_BDF" "KenCarp4" "KenCarp5" "Rodas4"
         "radau" "Rodas5"]


wp = WorkPrecisionSet(prob, abstols, reltols, setups;

names=names, appxsol=test_sol, maxiters=Int(1e6), error_estimate=:l2, seconds=5)

```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call loadODESolvers and check also this output. For further information see also ODEInterface.help_install.

```
plot(wp)
```




```

setups = [Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>Rodas4()),
          Dict(:alg=>radau()),
          Dict(:alg=>Rodas5())]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
                      appxsol=test_sol, maxiters=Int(1e6), error_estimate=:l2, seconds=5)

```

Error: Cannot find method(s) for radau! I've tried to loadODESolvers(), but it didn't work. Please check ODEInterface.help_solversupport() and call loadODESolvers and check also this output. For further information see also ODEInterface.help_install.

```
plot(wp)
```



The timeseries test is a little odd here because of the high peaks in the VanDerPol oscillator. At a certain accuracy, the steps try to resolve those peaks and so the error becomes higher.

While the higher order order Julia-based Rodas methods (Rodas4 and Rodas4P) Rosenbrock methods are not viable at higher tolerances, they dominate for a large portion of this benchmark. When the tolerance gets low enough, `radau` adaptive high order (up to order 13) takes the lead.

0.2.2 Conclusion

Rosenbrock23 and Rodas3 do well when tolerances are higher. In most standard tolerances, Rodas4 and Rodas4P do extremely well. Only when the tolerances get very low does `radau` do well. The Julia Rosenbrock methods vastly outperform their Fortran counterparts. `CVODE_BDF` is a top performer in the final timepoint errors with low accuracy, but take that with a grain of salt because the problem is periodic which means it's getting the spikes wrong but the low parts correct. `ARKODE` does poorly in these tests. `lsoda` does quite well in both low and high accuracy domains, but is never the top.

```
using DiffEqBenchmarks
DiffEqBenchmarks.bench_footer(WEAVE_ARGS[:folder],WEAVE_ARGS[:file])
```

0.3 Appendix

These benchmarks are a part of the DiffEqBenchmarks.jl repository, found at: <https://github.com/JuliaDiffeq/DiffEqBenchmarks.jl>

To locally run this tutorial, do the following commands:

```
using DiffEqBenchmarks
DiffEqBenchmarks.weave_file("StiffODE", "VanDerPol.jmd")
```

Computer Information:

```
Julia Version 1.4.2
Commit 44fa15b150* (2020-05-23 18:35 UTC)
Platform Info:
  OS: Linux (x86_64-pc-linux-gnu)
  CPU: Intel(R) Core(TM) i7-9700K CPU @ 3.60GHz
  WORD_SIZE: 64
  LIBM: libopenlibm
  LLVM: libLLVM-8.0.1 (ORCJIT, skylake)
Environment:
  JULIA_DEPOT_PATH = /builds/JuliaGPU/DiffEqBenchmarks.jl/.julia
  JULIA_CUDA_MEMORY_LIMIT = 2147483648
  JULIA_PROJECT = @.
  JULIA_NUM_THREADS = 4
```

Package Information:

```
Status: `~/builds/JuliaGPU/DiffEqBenchmarks.jl/benchmarks/StiffODE/Project.toml`
[eb300fae-53e8-50a0-950c-e21f52c2b7e0] DiffEqBiological 4.3.0
[f3b72e0c-5b89-59e1-b016-84e28bfd966d] DiffEqDevTools 2.22.0
[5a33fad7-5ce4-5983-9f5d-5f26ceab5c96] GeometricIntegratorsDiffEq 0.1.0
[7f56f5a3-f504-529b-bc02-0b1fe5e64312] LSODA 0.6.1
[c030b06c-0b6d-57c2-b091-7029874bd033] ODE 2.5.0
[09606e27-ecf5-54fc-bb29-004bd9f985bf] ODEInterfaceDiffEq 3.7.0
[1dea7af3-3e70-54e6-95c3-0bf5283fa5ed] OrdinaryDiffEq 5.41.0
[65888b18-ceab-5e60-b2b9-181511a3b968] ParameterizedFunctions 5.3.0
[91a5bcdd-55d7-5caf-9e0b-520d859cae80] Plots 1.5.3
[b4db0fb7-de2a-5028-82bf-5021f5cfa881] ReactionNetworkImporters 0.1.5
[c3572dad-4567-51f8-b174-8c6c989267f4] Sundials 4.2.5
[a759f4b9-e2f1-59dc-863e-4aeb61b1ea8f] TimerOutputs 0.5.6
[37e2e46d-f89d-539d-b4ee-838fcccc9c8e] LinearAlgebra
```