

MultilayerGraphs.jl: Multilayer Network Science in Julia

Claudio Moroni ^{1,2*} and Pietro Monticone ^{1,2*}

¹ University of Turin, Italy ² Interdisciplinary Physics Team, Italy * These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

MultilayerGraphs.jl is a Julia package for the creation, manipulation and analysis of the structure, dynamics and functions of multilayer graphs.

A multilayer graph is a graph consisting of multiple standard subgraphs called *layers* which can be interconnected through [bipartite graphs](#) called *interlayers* composed of the vertex sets of two different layers and the edges between them. The vertices in each layer represent a single set of nodes, although not all nodes have to be represented in every layer.

Formally, a multilayer graph can be defined as a triple $G = (V, E, L)$, where:

- V is the set of vertices;
- E is the set of edges, pairs of nodes (u, v) representing a connection, relationship or interaction between the nodes u and v ;
- L is a set of layers, which are subsets of V and E encoding the nodes and edges within each layer.

Each layer ℓ in L is a tuple (V_ℓ, E_ℓ) , where V_ℓ is a subset of V that represents the vertices within that layer, and E_ℓ is a subset of E that represents the edges within that layer.

MultilayerGraphs.jl is an integral part of the [JuliaGraphs](#) ecosystem extending Graphs.jl ([Fairbanks et al., 2021](#)) so all the methods and metrics exported by Graphs.jl work for multilayer graphs, but due to the special nature of multilayer graphs the package features a peculiar implementation that maps a standard integer-labelled vertex representation to a more user-friendly framework exporting all the objects an experienced practitioner would expect such as nodes (`Node`), vertices (`MultilayerVertex`), layers (`Layer`), interlayers (`Interlayer`), etc.

MultilayerGraphs.jl features multilayer-specific methods and metrics including the global clustering coefficient, the overlay clustering coefficient, the multilayer eigenvector centrality, the multilayer modularity and the Von Neumann entropy.

Finally, MultilayerGraphs.jl has been integrated within the [JuliaDynamics](#) ecosystem so that any `Multilayer(Di)Graph` can be utilised as an argument to the `GraphSpace` constructor in `Agents.jl` ([Datseris et al., 2022](#)).

Statement of Need

Several theoretical frameworks have been proposed to formally subsume all instances of multilayer graphs ([Aleta & Moreno, 2019](#); [Artime et al., 2022](#); [Bianconi, 2018](#); [Boccaletti et al., 2014](#); [Cozzo et al., 2018](#); [M. D. Domenico et al., 2013](#); [M. D. Domenico, 2022](#); [Kivela et al., 2014](#); [Lee et al., 2015](#)).

Multilayer graphs have been adopted to model the structure and dynamics of a wide spectrum of high-dimensional, non-linear, multi-scale, time-dependent complex systems including physi-

cal, chemical, biological, neuronal, socio-technical, epidemiological, ecological and economic networks (Aleta et al., 2022, 2020; Amato et al., 2017; Arruda et al., 2017; Azimi-Tafreshi, 2016; Baggio et al., 2016; Buldú & Porter, 2018; Cozzo et al., 2013; M. D. Domenico, 2017; M. D. Domenico et al., 2016; Estrada & Gómez-Gardeñes, 2014; Gosak et al., 2018; Granell et al., 2013; Lim et al., 2019; Mangioni et al., 2020; Massaro & Bagnoli, 2014; Pilosof et al., 2017; Soriano-Paños et al., 2018; Timóteo et al., 2018).

We have chosen the [Julia language](#) for this software package because it is a modern, open-source, high-level, high-performance dynamic language for technical computing (Bezanson et al., 2017). At the best of our knowledge there are currently no software packages dedicated to the creation, manipulation and analysis of multilayer graphs implemented in the Julia language apart from MultilayerGraphs.jl itself (Moroni & Monticone, 2022).

Main Features

The two main data structures are MultilayerGraph and MultilayerDiGraph: collections of layers connected through interlayers.

The **vertices** of a multilayer graph are representations of one set of distinct objects called Nodes. Each layer may represent all the node set or just a subset of it. The vertices of Multilayer(Di)Graph are implemented via the MultilayerVertex custom type. Each MultilayerVertex encodes information about the node it represents, the layer it belongs to and its metadata.

Both the **intra-layer** and **inter-layer edges** are embedded in the MultilayerEdge struct, whose arguments are the two connected multilayer vertices, the edge weight and its metadata. It's important to highlight that Multilayer(Di)Graphs are weighted and able to store metadata by default (i.e. they have been assigned the IsWeighted and IsMeta traits from [SimpleTraits.jl](#)).

The **layers** are implemented via the Layer struct composed of an underlying graph and a mapping from its integer-labelled vertices to the collection of MultilayerVertices the layer represents. **Interlayers** are similarly implemented via the Interlayer mutable struct, and they are generally constructed by providing the two connected layers, the (multilayer) edge list between them and a graph. This usage of underlying graphs allows for an easier debugging procedure during construction and a more intuitive analysis afterwards allowing the package to leverage all the features of the JuliaGraphs ecosystem so that it can be effectively considered as a real proving ground of its internal consistency.

The Multilayer(Di)Graph structs are weighted and endowed with the functionality to store both vertex-level and edge-level metadata by default so that at any moment the user may add or remove a Layer or specify an Interlayer and since different layers and interlayers could be better represented by graphs that are weighted or unweighted and with or without metadata, it was crucial for us to provide the most general and adaptable structure. A Multilayer(Di)Graph is instantiated by providing the ordered list of layers and the list of interlayers to the constructor. The latter are automatically specified, so there is no need to instantiate all of them.

Alternatively, it is possible to construct a Multilayer(Di)Graph making use of a graph generator-like signature allowing the user to set the degree distribution or the degree sequence and employs graph realisation methods such as the Havel-Hakimi algorithm for undirected graphs (Hakimi, 1962) and the Kleitman-Wang algorithm for directed ones (Kleitman & Wang, 1973).

Multilayer(Di)Graphs structure may be represented via dedicated WeightTensor, MetadataTensor and SupraWeightMatrix structs, all of which support indexing with MultilayerVertices. Once a Multilayer(Di)Graph has been instantiated, its layers and interlayers can be accessed as their properties.

87 Installation and Usage

88 To install MultilayerGraphs.jl it is sufficient to activate the pkg mode by pressing] in the Julia
89 REPL and then run the following command:

```
pkg> add MultilayerGraphs
```

90 In the following code chunks we synthetically illustrate how to define, handle and analyse a
91 MultilayerGraph in order to showcase some of the main features outlined in the previous
92 section.

```
using Revise
using Graphs, SimpleValueGraphs
using Distributions
using MultilayerGraphs
```

```
# The objects represented by `MultilayerVertex`s are `Node`s
const n_nodes = 100
const node_list = [Node("node_$(i)") for i in 1:n_nodes]
```

```
#=
Each layer and Interlayer that is involved in a `Multilayer(Di)Graph` must have the same
vertex type (i.e. the type of the internal representation of vertices) and (edge) weight type.
We proceed by defining them:
const vertex_type = Int64
const weight_type = Float64
==
```

```
#=
We will instantiate layers and interlayers with randomly-selected edges and vertices added.
Here, we define a layer with an underlying simple directed graph
using a graph generator-like (or "configuration model"-like) constructor which allows
for specifying both the indegree and the outdegree sequences.
```

```
Before instantiating each layer we sample its number of vertices and, optionally, of edges.
==
n_vertices = rand(1:100) # Number of vertices
layer_simple_directed = layer_simpledigraph( # Layer constructor
    :layer_simpledigraph, # Layer name
    sample(node_list, n_vertices; replace=false), # Nodes represented in the layer
    Truncated(Normal(5, 5), 0, 20), # Indegree sequence sample distribution
    Truncated(Normal(5, 5), 0, 20) # Outdegree sequence sample distribution
)
```

```
#= Next, we define a layer with an underlying simple weighted directed graph.
This time we show another kind of constructor that allows the user to specify
the number of edges to be randomly distributed among the vertices.
The keyword argument `default_edge_weight` will assign a weight to such edges before the
==
```

```
n_vertices = rand(1:n_nodes) # Number of vertices
n_edges = rand(n_vertices:(n_vertices * (n_vertices - 1) - 1)) # Number of edges
layer_simple_directed_weighted = layer_simpleweighteddigraph( # Layer constructor
    :layer_simpleweighteddigraph, # Layer name
    sample(node_list, n_vertices; replace=false), # Nodes represented in the layer
    n_edges; # Number of randomly distributed edges
    default_edge_weight=(src, dst) -> rand() # Function assigning weights
)
```

```

)

#=#
## Similar constructors, more flexible at the cost of ease of use, allows for finer tuning
## NB: This constructor should be necessary only in rare circumstances, where e.g.
the equivalent simplified constructor `layer_simplevaldigraph` is not able to infer
the correct return types of the `default_vertex/edge_metadata`s, or to use underlying
graph that aren't currently supported.
=#
n_vertices = rand(1:n_nodes) # Number of vertices
n_edges = rand(n_vertices:(n_vertices * (n_vertices - 1) - 1)) # Number of edges
default_vertex_metadata = v -> ("vertex_$(v)_metadata") # Vertex metadata
default_edge_metadata = (s, d) -> (rand(),) # Edge metadata
layer_simple_directed_value = Layer( # Layer constructor
    :layer_simplevaldigraph, # Layer name
    sample(node_list, n_vertices; replace=false), # Nodes represented in the
    n_edges, # Number of randomly distributed
    ValDiGraph(
        SimpleDiGraph{Int64}();
        vertexval_types=(String,),
        vertexval_init=default_vertex_metadata,
        edgeval_types=(Float64,),
        edgeval_init=default_edge_metadata,
    ),
    Float64;
    default_vertex_metadata=default_vertex_metadata, # Vertex metadata
    default_edge_metadata=default_edge_metadata # Edge metadata
)

layers = [layer_simple_directed, layer_simple_directed_weighted, layer_simple_directed_weighted_value]

#=#
There are many more constructors that the user is encouraged to explore in the package
We may now move to Interlayers. Note that, in order to define a `Multilayer(Di)Graph`,
interlayers do not need to be explicitly constructed by the user,
since they are automatically specified by the `Multilayer(Di)Graph` constructor.
Anyway, more complex interlayers need to be manually instantiated.
The interface is very similar to the layers.
=#

# Interlayer with an underlying simple directed graph and `n_edges` edges
n_vertices_1 = nv(layer_simple_directed) # Number of vertices of layer 1
n_vertices_2 = nv(layer_simple_directed_weighted) # Number of vertices of layer 2
n_edges = rand(1:(n_vertices_1 * n_vertices_2 - 1)) # Number of interlayer edges
interlayer_simple_directed = interlayer_simplesdigraph( # Interlayer constructor
    layer_simple_directed, # Layer 1
    layer_simple_directed_weighted, # Layer 2
    n_edges # Number of edges
)

## The interlayer exports a more flexible constructor too.
n_vertices_1 = nv(layer_simple_directed_weighted) # Number of vertices of layer 1
n_vertices_2 = nv(layer_simple_directed_value) # Number of vertices of layer 2
n_edges = rand(1:(n_vertices_1 * n_vertices_2 - 1)) # Number of interlayer edges
interlayer_simple_directed_meta = interlayer_metadigraph( # Interlayer constructor

```

```

layer_simple_directed_weighted,          # Layer 1
layer_simple_directed_value,             # Layer 2
n_edges;                                # Number of edges
default_edge_metadata=(src, dst) ->      # Edge metadata
    (edge_metadata="metadata_of_edge_from_$(src)_to_$(dst)"),
transfer_vertex_metadata=true            # Boolean deciding layer vertex
)

interlayers = [interlayer_simple_directed, interlayer_simple_directed_meta]

# Layers and Interlayers are not immutable, and mostly behave like normal graphs. The re
# A MultilayerDiGraph (i.e. a directed multilayer graph, following the naming convention

multilayerdigraph = MultilayerDiGraph(
    layers,                               # The (ordered) collection of layers
    interlayers;                          # The manually specified interlayers
                                           # The interlayers that are left unspecified
                                           # will be automatically inserted according
                                           # to the keyword argument below
    default_interlayers_structure="multiplex" # The automatically specified interlayers
)

# Layers and interlayer may be accessed as properties using their names
multilayerdigraph.layer_simple_directed_value

# We proceed to show some basic functionality.
## Add a vertex
### The user may add vertices that do or do not represent node_list already present in t
new_node_1 = Node("new_node_1")
### Before adding any vertex representing such node to the multilayer graph, the user sh
add_node!(multilayerdigraph, new_node_1)
### Define a vertex that represents that node
new_vertex_1 = MV(                        # Constructor (alias for "MultilayerVertex")
    new_node_1,                           # Node represented by the vertex
    :layer_simplevaldigraph,              # Layer containing the vertex
    ("new_metadata")                      # Vertex metadata
)
### Add the vertex
add_vertex!(
    multilayerdigraph, # MultilayerDiGraph the vertex will be added to
    new_vertex_1        # MultilayerVertex to add
)
# NB: The vertex-level metadata are considered iff the graph underlying the layer/interl

### `add_vertex!` implements multiple interfaces.

## Add an edge
### Let's represent another node in another layer
new_node_2 = Node("new_node_2")
new_vertex_2 = MV(new_node_2, :layer_simpldigraph)
add_vertex!(
    multilayerdigraph,
    new_vertex_2;
    add_node=true # Add the associated node before adding the vertex
)

```

```

### Construct a new edge
new_edge = MultilayerEdge( # Constructor
    new_vertex_1,          # Source vertex
    new_vertex_2,          # Destination vertex
    ("some_edge_metadata") # Edge metadata
)
### Add the edge
add_edge!(
    multilayerdigraph, # MultilayerDiGraph the edge will be added to
    new_edge           # MultilayerVertex to add
)
# NB: The edge-level metadata and/or weight are considered iff the graph underlying the

#=
Using the provided `add_layer!`, `rem_layer!` and `specify_interlayer!`,
Layers and Interlayers may be added, removed or specified on the fly.
Since MultilayerGraphs.jl extends Graphs.jl, all metrics from the JuliaGraphs ecosystem
should be available by default. Anyway, some multilayer-specific metrics have been imple
and others required to be re-implemented.

We showcase a few of them here:
=#

## Compute the global clustering coefficient as in @DeDomenico2014
multilayer_global_clustering_coefficient(multilayerdigraph) # A weighted version `multil
## Compute the overlay clustering coefficient as in @DeDomenico2013
overlay_clustering_coefficient(multilayerdigraph)
## Compute the eigenvector centrality (the implementation is sp that it coincides with G
eigenvector_centrality(multilayerdigraph)
## Compute the multilayer modularity as in @DeDomenico2013
modularity(
    multilayerdigraph,
    rand([1, 2, 3, 4], length(nodes(multilayerdigraph)), length(multilayerdigraph.layers
)

## Currently, Von Neumann entropy is available only for undirected multilayer graphs.
# NB: this brief script is far from complete: many more features and functionalities are

93 For a more comprehensive exploration of the package features and functionalities we strongly
94 recommend consulting the tutorial included in the package documentation.

```

Related Packages

R

Here is a list of software packages for the creation, manipulation, analysis and visualisation of multilayer graphs implemented in the [R language](#):

- [muxViz](#) implements functions to perform multilayer correlation analysis, multilayer centrality analysis, multilayer community structure detection, multilayer structural reducibility, multilayer motifs analysis and utilities to statically and dynamically visualise multilayer graphs ([D. Domenico et al., 2014](#));
- [multinet](#) implements functions to import, export, create and manipulate multilayer graphs, several state-of-the-art multiplex graph analysis algorithms for centrality measures, layer comparison, community detection and visualization ([Magnani et al., 2021](#));

- `mully` implements functions to import, export, create, manipulate and merge multilayer graphs and utilities to visualise multilayer graphs in 2D and 3D (Hammoud & Kramer, 2018);
- `multinets` implements functions to import, export, create, manipulate multilayer graphs and utilities to visualise multilayer graphs (Lazega et al., 2008).

Python

Here is a list of software packages for the creation, manipulation, analysis and visualisation of multilayer graphs implemented in the `Python` language:

- `MultiNetX` implements methods to create undirected networks with weighted or unweighted links, to analyse the spectral properties of adjacency or Laplacian matrices and to visualise multilayer graphs and dynamical processes by coloring the nodes and links accordingly;
- `PyMNet` implements data structures for multilayer graphs and multiplex graphs, methods to import, export, create, manipulate multilayer graphs and for the rule-based generation and lazy-evaluation of coupling edges and utilities to visualise multilayer graphs (Kivela et al., 2014).

Acknowledgements

This open-source research software project received no financial support.

References

- Aleta, A., Martín-Corral, D., Bakker, M. A., Piontti, A. P. y, Ajelli, M., Litvinova, M., Chinazzi, M., Dean, N. E., Halloran, M. E., Longini, I. M., Pentland, A., Vespignani, A., Moreno, Y., & Moro, E. (2022). Quantifying the importance and location of SARS-CoV-2 transmission events in large metropolitan areas. *Proceedings of the National Academy of Sciences*, 119(26). <https://doi.org/10.1073/pnas.2112182119>
- Aleta, A., Martín-Corral, D., Piontti, A. P. y, Ajelli, M., Litvinova, M., Chinazzi, M., Dean, N. E., Halloran, M. E., Jr, I. M. L., Merler, S., Pentland, A., Vespignani, A., Moro, E., & Moreno, Y. (2020). Modelling the impact of testing, contact tracing and household quarantine on second waves of COVID-19. *Nature Human Behaviour*, 4(9), 964–971. <https://doi.org/10.1038/s41562-020-0931-9>
- Aleta, A., & Moreno, Y. (2019). Multilayer networks in a nutshell. *Annual Review of Condensed Matter Physics*, 10(1), 45–62. <https://doi.org/10.1146/annurev-conmatphys-031218-013259>
- Amato, R., Díaz-Guilera, A., & Kleineberg, K.-K. (2017). Interplay between social influence and competitive strategical games in multiplex networks. *Scientific Reports*, 7(1). <https://doi.org/10.1038/s41598-017-06933-2>
- Arruda, G. F. de, Cozzo, E., Peixoto, T. P., Rodrigues, F. A., & Moreno, Y. (2017). Disease localization in multilayer networks. *Physical Review X*, 7(1). <https://doi.org/10.1103/physrevx.7.011014>
- Artime, O., Benigni, B., Bertagnolli, G., dAndrea, V., Gallotti, R., Ghavasieh, A., Raimondo, S., & Domenico, M. D. (2022). *Multilayer network science*. Cambridge University Press. <https://doi.org/10.1017/9781009085809>
- Azimi-Tafreshi, N. (2016). Cooperative epidemics on multiplex networks. *Physical Review E*, 93(4). <https://doi.org/10.1103/physreve.93.042303>

- 149 Baggio, J. A., BurnSilver, S. B., Arenas, A., Magdanz, J. S., Kofinas, G. P., & Domenico, M.
150 D. (2016). Multiplex social ecological network analysis reveals how social changes affect
151 community robustness more than resource depletion. *Proceedings of the National Academy
152 of Sciences*, 113(48), 13708–13713. <https://doi.org/10.1073/pnas.1604401113>
- 153 Bezanson, J., Edelman, A., Karpinski, S., & Shah, V. B. (2017). Julia: A fresh approach to
154 numerical computing. *SIAM Review*, 59(1), 65–98. <https://doi.org/10.1137/141000671>
- 155 Bianconi, G. (2018). *Multilayer networks*. Oxford University Press. <https://doi.org/10.1093/oso/9780198753919.001.0001>
- 157 Boccaletti, S., Bianconi, G., Criado, R., Genio, C. I. del, Gómez-Gardeñes, J., Romance, M.,
158 Sendiña-Nadal, I., Wang, Z., & Zanin, M. (2014). The structure and dynamics of multilayer
159 networks. *Physics Reports*, 544(1), 1–122. <https://doi.org/10.1016/j.physrep.2014.07.001>
- 160 Buldú, J. M., & Porter, M. A. (2018). Frequency-based brain networks: From a multiplex
161 framework to a full multilayer description. *Network Neuroscience*, 2(4), 418–441. https://doi.org/10.1162/netn_a_00033
- 163 Cozzo, E., Arruda, G. F. de, Rodrigues, F. A., & Moreno, Y. (2018). *Multiplex networks*.
164 Springer International Publishing. <https://doi.org/10.1007/978-3-319-92255-3>
- 165 Cozzo, E., Baños, R. A., Meloni, S., & Moreno, Y. (2013). Contact-based social contagion in
166 multiplex networks. *Physical Review E*, 88(5). <https://doi.org/10.1103/physreve.88.050801>
- 167 Datseris, G., Vahdati, A. R., & DuBois, T. C. (2022). Agents.jl: A performant and
168 feature-full agent-based modeling software of minimal code complexity. *SIMULATION*,
169 003754972110688. <https://doi.org/10.1177/00375497211068820>
- 170 Domenico, D., Porter, & Arenas. (2014). MuxViz: A tool for multilayer analysis and
171 visualization of networks. *Journal of Complex Networks*, 3(2), 159–176. <https://doi.org/10.1093/comnet/cnu038>
- 173 Domenico, M. D. (2017). Multilayer modeling and analysis of human brain networks. *Giga-
174 Science*, 6(5). <https://doi.org/10.1093/gigascience/gix004>
- 175 Domenico, M. D. (2022). *Multilayer networks: Analysis and visualization*. Springer International
176 Publishing. <https://doi.org/10.1007/978-3-030-75718-2>
- 177 Domenico, M. D., Granell, C., Porter, M. A., & Arenas, A. (2016). The physics of spreading
178 processes in multilayer networks. *Nature Physics*, 12(10), 901–906. <https://doi.org/10.1038/nphys3865>
- 180 Domenico, M. D., Solé-Ribalta, A., Cozzo, E., Kivelä, M., Moreno, Y., Porter, M. A., Gómez,
181 S., & Arenas, A. (2013). Mathematical formulation of multilayer networks. *Physical Review
182 X*, 3(4). <https://doi.org/10.1103/physrevx.3.041022>
- 183 Estrada, E., & Gómez-Gardeñes, J. (2014). Communicability reveals a transition to coordinated
184 behavior in multiplex networks. *Physical Review E*, 89(4). <https://doi.org/10.1103/physreve.89.042819>
- 186 Fairbanks, J., Besançon, M., Simon, S., Hoffiman, J., Eubank, N., & Karpinski, S. (2021).
187 *JuliaGraphs/graphs.jl: An optimized graphs package for the julia programming language*.
188 <https://github.com/JuliaGraphs/Graphs.jl>
- 189 Gosak, M., Markovič, R., Dolensek, J., Rupnik, M. S., Marhl, M., Stožer, A., & Perc, M.
190 (2018). Network science of biological systems at different scales: A review. *Physics of Life
191 Reviews*, 24, 118–135. <https://doi.org/10.1016/j.plrev.2017.11.003>
- 192 Granell, C., Gómez, S., & Arenas, A. (2013). Dynamical interplay between awareness and
193 epidemic spreading in multiplex networks. *Physical Review Letters*, 111(12). <https://doi.org/10.1103/physrevlett.111.128701>

- 195 Hakimi, S. L. (1962). On realizability of a set of integers as degrees of the vertices of a linear
196 graph. i. *Journal of the Society for Industrial and Applied Mathematics*, 10(3), 496–506.
197 <https://doi.org/10.1137/0110037>
- 198 Hammoud, Z., & Kramer, F. (2018). Mully: An r package to create, modify and visualize
199 multilayered graphs. *Genes*, 9(11), 519. <https://doi.org/10.3390/genes9110519>
- 200 Kivela, M., Arenas, A., Barthélemy, M., Gleeson, J. P., Moreno, Y., & Porter, M. A. (2014).
201 Multilayer networks. *Journal of Complex Networks*, 2(3), 203–271. <https://doi.org/10.1093/comnet/cnu016>
- 202
- 203 Kleitman, D. J., & Wang, D. L. (1973). Algorithms for constructing graphs and digraphs with
204 given valences and factors. *Discrete Mathematics*, 6(1), 79–88. [https://doi.org/10.1016/0012-365x\(73\)90037-x](https://doi.org/10.1016/0012-365x(73)90037-x)
- 205
- 206 Lazega, E., Jourda, M.-T., Mounier, L., & Stofer, R. (2008). Catching up with big fish in
207 the big pond? Multi-level network analysis through linked design. *Social Networks*, 30(2),
208 159–176. <https://doi.org/10.1016/j.socnet.2008.02.001>
- 209 Lee, K.-M., Min, B., & Goh, K.-I. (2015). Towards real-world complexity: An introduction to
210 multiplex networks. *The European Physical Journal B*, 88(2). <https://doi.org/10.1140/epjb/e2015-50742-1>
- 211
- 212 Lim, S., Radicchi, F., Heuvel, M. P. van den, & Sporns, O. (2019). Discordant attributes of
213 structural and functional brain connectivity in a two-layer multiplex network. *Scientific*
214 *Reports*, 9(1). <https://doi.org/10.1038/s41598-019-39243-w>
- 215 Magnani, M., Rossi, L., & Vega, D. (2021). Analysis of multiplex social networks with r.
216 *Journal of Statistical Software*, 98(8). <https://doi.org/10.18637/jss.v098.i08>
- 217 Mangioni, G., Jurman, G., & Domenico, M. D. (2020). Multilayer flows in molecular networks
218 identify biological modules in the human proteome. *IEEE Transactions on Network Science*
219 *and Engineering*, 7(1), 411–420. <https://doi.org/10.1109/tNSE.2018.2871726>
- 220 Massaro, E., & Bagnoli, F. (2014). Epidemic spreading and risk perception in multiplex
221 networks: A self-organized percolation method. *Physical Review E*, 90(5). <https://doi.org/10.1103/PhysRevE.90.052817>
- 222
- 223 Moroni, C., & Monticone, P. (2022). *MultilayerGraphs.jl: A julia package for the creation,*
224 *manipulation and analysis of the structure, dynamics and functions of multilayer graphs.*
225 University of Turin (UniTO); Interdisciplinary Physics Team (InPhyT). <https://doi.org/10.5281/zenodo.7009172>
- 226
- 227 Pilosof, S., Porter, M. A., Pascual, M., & Kéfi, S. (2017). The multilayer nature of eco-
228 logical networks. *Nature Ecology & Evolution*, 1(4). <https://doi.org/10.1038/s41559-017-0101>
- 229
- 230 Soriano-Paños, D., Lotero, L., Arenas, A., & Gómez-Gardeñes, J. (2018). Spreading processes
231 in multiplex metapopulations containing different mobility networks. *Physical Review X*,
232 8(3). <https://doi.org/10.1103/PhysRevX.8.031039>
- 233 Timóteo, S., Correia, M., Rodríguez-Echeverría, S., Freitas, H., & Heleno, R. (2018). Multilayer
234 networks reveal the spatial structure of seed-dispersal interactions across the great rift
235 landscapes. *Nature Communications*, 9(1). <https://doi.org/10.1038/s41467-017-02658-y>