| Designator C1, C2, C4, C6, C8, | Description | Value | Valueld | Quantity |
|--|--|-------------|--|----------|
| C10, C11, C12, C13, C15, C17, C19, C21, C23, | | | | |
| C26, C28, C30, C33, C35, C40, C62, C64, C65, | | | | |
| C69, C70, C73, C74, C75, C76, C77, C78 | Capacitor | 0.1μ | Capacitor SMD0603 25V 0.1uF | 31 |
| | Polarized Capacitor (Axial) | 10μF | Capacitor Axial 25V 10uF | 8 |
| C5, C9, C16, C20, C66, C71 | Capacitor | 0.01μ | Capacitor SMD0603 25V 0.01uF | 6 |
| C22, C25, C27, C29, C32 | Polarized Capacitor (Axial) | 22μF | Capacitor Axial 25V 22uF | 5 |
| C24, C31, C36, C38, C42, C43, C46, C47, C48 | Capacitor | 1μF | Capacitor SMD0603 25V 1uF | 9 |
| | Polarized Capacitor (Axial) | 100μF | Capacitor Axial 25V 100uF | 7 |
| C37, C41, C44, C45 | Capacitor | 1000p | Capacitor SMD0603 25V 1000pF | 4 |
| C49, C52, C53, C56, C57, C60 | Capacitor | 0.047μF | Capacitor SMD0603 25V 0.047uF | 6 |
| C51, C58 | Capacitor | 470pF | Capacitor SMD0603 25V 470pF | 2 |
| C61 | Polarized Capacitor (Axial) | 4.7μF | Capacitor Axial 25V 4.7uF | 1 |
| C80, C81 | Capacitor | 20p | Capacitor SMD0603 25V 20pF | 2 |
| D1, D2 D3 | RS-232 Line Driver/ Receiver | | SC16IS752IBS TRS3232ECPW | 2 |
| D4, D5 | | | ADM2587E | 2 |
| D6 D7 | I2C Keypad Scan IC Remote 16-Bit I2C and SMBus | | TCA8418RTWR TCA9539PWR | 1 |
| D8 | Single 150mA LDO Low-Power Audio | | MIC5365 TLV320AIC3100IRH | 1 |
| D9 D10 | CODEC 10 W Mono Class- D Amplifier | | BR TPA3111D1PWPR | 1 |
| D11 D12 | Real Time Clock | | TPS54383PWPR PCF8563 | 1 |
| D13 | 256 kb Serial CMOS EEPROM | | I2C CMOS | 1 |
| K1_RL1, K1_RL2, | 2032 Battery holder | | Battery holder MPD BC2032-E2 | 1 |
| K1_RL3, K1_RL4, K1_RL5, K1_RL6, K1_RL7, K1_RL8, | Single-Pole Single- | | TDD4 45 | |
| K1_RL9, K1_RL10 L1, L2, L9, L10 | Throw Relay Inductor | 1.2mH | TRB1-12VDC-CD Inductor SDR0302- 122KL 1.2mH | 10 4 |
| L3, L4, L7, L8, L11, L12 | Inductor | 400nH | Inductor BLM18KG221SN1 400 nH | 6 |
| | Magnetic-Core Inductor | 47μH, 47uH | Inductor 47uH 4A | 2 |
| R1, R2 R3_RL1, R3_RL2, | Resistor | 120 | Resistor SMD0603 120 Ohm ±5% | 2 |
| R3_RL3, R3_RL4, R3_RL5, R3_RL6, R3_RL7, R3_RL8, | | | | |
| R3_RL9, R3_RL10, R8, R9 | Resistor | 10K | Resistor SMD0603 10 kOhm ±5% Resistor SMD0603 | 12 |
| R4, R7, R44 R5, R12, R21 | Resistor Resistor | 100k 10 | 100 kOhm ±5% Resistor SMD0603 10 Ohm ±5% | 3 |
| R6 | Resistor | 2.2K | Resistor SMD0603 2.2 kOhm ±5% | 1 |
| R10_S1, R10_S2, R10_S3, R10_S4, | | | | |
| R10_S5, R10_S6, R10_S7, R10_S8, R24_S1, R24_S2, | | | | |
| R24_S3, R24_S4, R24_S5, R24_S6, R24_S7, R24_S8, | | | | |
| R35, R36, R37, R38, R39, R40, R42 | Resistor | 4.7K | Resistor SMD0603 4.7 kOhm ±5% Resistor SMD0603 | 23 |
| R13, R43 R14, R15, R18, R19 | Resistor Resistor | 47K 0 | 47 kOhm ±5% Resistor 0603 Zero ohm | 2 |
| R16 | Resistor | 3.3K | Resistor SMD0603 3.3 kOhm ±5% Resistor SMD0603 | 1 |
| R17 R20 | Resistor | 820 4.3K | 820 Ohm ±5% Resistor SMD0603 4.3 kOhm ±5% | 1 |
| R22_S1, R22_S2, R22_S3, R22_S4, | Resistor | 4.3N | 4.5 KOIIII ±5% | 1 |
| R22_S5, R22_S6, R22_S7, R22_S8, R23_S1, R23_S2, | | | | |
| R23_S3, R23_S4, R23_S5, R23_S6, R23_S7, R23_S8 | Resistor | 550 | Resistor SMD0603 550 Ohm ±5% | 16 |
| R25, R26, R27, R28, R29, R30, R31, R32, R33, | | | Resistor SMD0603 | |
| R34, R41 S1 | Resistor DIP Switch, 2 Position, SPST | 1K | 1 kOhm ±5% 2-digit DIP Switch | 11 |
| U1_S1, U1_S2, U1_S3, U1_S4, U1_S5, U1_S6, | 4-Pin Phototransistor | | | |
| VD1, VD4_S1, VD4_S2, VD4_S3, | Optocoupler | | Оптрон HCPL-181 | 8 |
| VD4_S2, VD4_S3, VD4_S4, VD4_S5, VD4_S6, VD4_S7, VD4_S8, VD5, VD6, | | | | |
| VD4_S8, VD5, VD6, VD7 VD2, VD3 | Schottky Diode Schottky Diode | | Diode BAT54S Diode MBRA340 | 12 2 |
| VD8 VT1_RL1, VT1_RL2, VT1_RL3, VT1_RL4, | Schottky Diode | | Diode BAT54C | 1 |
| VT1_RL3, VT1_RL4, VT1_RL5, VT1_RL6, VT1_RL7, VT1_RL8, VT1_RL9, | | | | |
| V11_RL9, VT1_RL10, VT2, VT3, VT5_S1, VT5_S2, VT5_S3, | | | | |
| VT5_S4, VT5_S5, VT5_S6, VT5_S7, | N-Channel MOSFET | | Transistor BSS138LT3G | 22 |
| v 13_30, V 10, V 1/ | Receptacle Assembly, 9 | | 130L13G | 22 |
| X1, X2 | Position, Right Angle Header, 3-Pin, | | DB-Rihght Angle | 2 |
| | Header, 3-Pin, Header, 2-Pin, Right Angle, | | | |
| No. 11- | Header, 3-Pin, Header, 3-Pin, Header, 3-Pin, | | | |
| X3, X5, X20, X21_S1, X21_S2, X21_S3, X21_S4, | Header, 3-Pin, Header, 3-Pin, Header, 3-Pin, | | | |
| X21_S5, X21_S6, X21_S7, X21_S8 | Header, 3-Pin, Header, 3-Pin Header, 4-Pin, | | Разъем 15EDGRC- 3.5-3 Разъем RJ-45 FCI | 11 |
| X4, X6 X7 | Dual row Header, 4-Pin | | 54602-908LF Разъем 15EDGRC- 3.5-4 | 1 |
| | Header, 25-Pin, | | Вилка PLD-50 (DS1021-2x40 | |
| X8, X9 | Dual row | | исп.50 контактов) Вилка PLD-6 | 2 |
| X10 | Header, 3-Pin, Dual row Header, 20-Pin, | | (DS1021-2x40 исп.6 контактов) Вилка IDC-40 | 1 |
| X11 | Dual row | | угловая Вилка PLS-4 (DS1021-1x40 | 1 |
| X12, X14 | Header, 4-Pin | | исп.4 контактов) Вилка PLD-6 | 2 |
| X13, X15 | Header, 6-Pin, Dual row | | (DS1021-2x40 исп.12 контактов) | 2 |
| X16, X17, X19 | Header, 8-Pin, Dual row Header, 10-Pin, | | Разъем 15EDGRT- 3.5-16 Разъем 15EDGRT- | 3 |
| X18 X22, X23 | Dual row | | 3.5-20 Audio jack Mono | 2 |
| Z1 | Crystal Oscillator | | FC-135 32.768000 | 1 |