Medlyn: Task-Specific Clinical Views from Located Evidence

Julian Schmidt
Medlyn project

Technical report: experimental prototype

Abstract

We present Medlyn, a prototype that constructs a clinical view for a clinician's role and task. We extract atomic facts from a longitudinal record, retain their source locations, and select fact identifiers for registered display templates. We apply a shared claim validator to cards, chat answers, letters and text prepared for speech. We distinguish documented negatives, missing documentation and checks that could not be completed. We also describe a synthetic clinical corpus and an experiment that adapts a small language model to verify claims. We report regression, synthetic pipeline, retrieval and verifier evaluations separately. Measurements enter the manuscript only after human review of their values and source identities; unreviewed or missing measurements remain pending. We do not establish clinical efficacy or transfer from generated notes to patient care.

1 Introduction

A longitudinal patient record contains more information than a clinician needs for a single task. The relevant subset changes with the task. Preparing an intervention, reviewing a tumour-board recommendation and checking follow-up require different facts from the same documents. An accurate general summary can omit a required answer. A fluent task-specific summary can also change a recommendation into a completed procedure or treat missing documentation as a negative finding.

We study the construction of a clinical view with explicit evidence constraints. Medlyn maps a role and task to information needs, selects stored facts and presents short English statements linked to German passages. We call this view a *lens*. We use language models for extraction and selection, but registered templates render the fact lines. When a model composes a headline or answer, we validate its claims against the cited facts and original context before release.

Our contribution is a system design that joins task-specific selection to a common claim boundary. We use the same patient, corpus revision and evidence window across retrieval, documentation checks, findings and letters. We keep availability, assertion, temporal status, completeness, conflict and clinician review as separate state dimensions. We further describe a synthetic data pipeline and a local verifier experiment. These components provide testable mechanisms; their implementation alone does not establish their accuracy.

We use transformer language models (Vaswani et al., 2017) for extraction and selection, with source evidence retained outside the model parameters. We organise the report around the architecture, data construction and verification experiment. We exclude challenge passages, patient-level predictions and private evaluation evidence from this report.

2 Background

We distinguish factual support from answer coverage. Factuality studies in summarisation show why fluent text needs evaluation against its source (Maynez et al., 2020; Pagnoni et al., 2021). In clinical summarisation, both the evaluation metric and the kind of error matter. Adams et al. (2023) examine faithfulness metrics for hospital-course summaries, and Zhang et al. (2023) study medical-summary faithfulness. The reader study of Van Veen et al. (2024) evaluates adapted models on specified summarisation tasks. We do not transfer those results to our workflow or use a generic text score as a measure of clinical utility.

Evidence attribution and atomic decomposition provide relevant design choices. ALCE evaluates answer quality and citation support (Gao et al., 2023b); RARR retrieves attribution and revises unsupported output

(Gao et al., 2023a). FActScore assesses the support of atomic facts (Min et al., 2023). FactsR uses salient facts as an intermediate representation for healthcare documentation (Hansen et al., 2025). We adopt the separation of evidence and presentation, then constrain the final fact lines with templates. TBFact, described with the Healthcare Agent Orchestrator (Blondeel et al., 2025), motivates measuring additions and omissions separately. We do not claim to reproduce its benchmark.

A fact can be located in a document while its interpretation is wrong. NegEx (Chapman et al., 2001), ConText (Harkema et al., 2009) and German negation detection (Cotik et al., 2016) motivate explicit assertion and temporal labels. SummaC (Laban et al., 2022), AlignScore (Zha et al., 2023) and MiniCheck (Tang et al., 2024) provide approaches to checking consistency between claims and evidence. We retain location and semantic support as separate checks. We also distinguish strict contradictions from contextual ambiguity, following the problem formulation studied by Lu et al. (2026).

Retrieval-augmented generation combines retrieved evidence with generation (Lewis et al., 2020). Dense passage retrieval (Karpukhin et al., 2020) and lexical ranking address different matching failures. We combine lexical and vector candidates while reserving absence claims for a full-record check. For synthetic data, Synthea (Walonoski et al., 2018), Asclepius (Kweon et al., 2023) and longitudinal note generation (Poulett et al., 2026) motivate separating patient histories from rendered notes. We require labels to survive in the final text and distinguish code checks from human annotation.

3 System Architecture

Figure 1 gives the main data and control paths. We ingest evidence before serving a lens. The live path selects facts, checks apparent documentation gaps and validates claims. We store clinician reviews in an append-only overlay. Accepting a statement records a review action; it does not increase the statement's support in the documents.




Figure 1: Ingestion and live lens construction. Orange denotes model calls, blue code, yellow checks, pink data or embeddings, and green storage throughout. Grey groups repeated or composite operations; ⊕ denotes RRF. Outputs cross the claim boundary.

3.1 Ingestion and Location

We normalise line breaks and encoded entities while retaining a map to raw offsets. We segment the normalised text into headings, sentences, list items and medication rows. The segmenter protects common German abbreviations and joins wrapped prose. Structured extraction returns a fact kind, an English label, attributes, assertion, temporal status, event date and a source quote. We locate the quote within its segment and check sensitive values, including numbers, doses, dates and sides. We drop failures rather than store an unlocated fact.

We then compare the extracted meaning with the passage and neighbouring context. A repaired fact must pass location again. A negation trigger can request another semantic check; it does not decide the clinical assertion. We retain the source date and document identity on medication lists. We do not describe a historical list as current medication. LangExtract (Goel, 2026) provides a related source-grounded extraction tool, but its output would still require an independent label check.

For page-based inputs, we retain extracted text together with page and bounding-box provenance. Text recognition errors can produce apparently valid offsets into an incorrect transcription. We therefore distinguish text location from agreement with the rendered page. Image embeddings can retrieve a page; they cannot establish the support of a clinical statement. End-to-end PDF and scan accuracy remains an evaluation requirement.

3.2 Retrieval

We define knowledge-time eligibility once in the store. For patient p, corpus revision r and as-of date t, the eligible document set is

$$E(p, r, t) = \{d : \text{patient}(d) = p,\ \text{revision}(d) = r,\ \text{docDate}(d) \leq t\}. \tag{1}$$

All consumers receive this set. An eligible document can describe a future procedure; we retain its planned status rather than filtering on the event date. Revision guards reject reads whose evidence identity changed during the request.

For the small challenge record, the core selector receives every eligible fact of the relevant kinds. Investigation search and the scale extension use BM25 (Robertson and Zaragoza, 2009) and Gemini embeddings (Google DeepMind, 2026), with pgvector storage (pgvector contributors, 2026). We fuse rank lists $\mathcal{R}$ with reciprocal rank fusion (Cormack et al., 2009):

$$\text{RRF}(s) = \sum_{R \in \mathcal{R} : s \in R} \frac{1}{\kappa + \text{rank}_R(s)}. \tag{2}$$

We restrict both branches to the same patient, revision and eligible documents before ranking. Duplicate segment identifiers contribute once per branch. A lexical fallback is recorded when embedding configuration or quota prevents the vector branch from running. A retrieval hit is a candidate passage, not a supported claim.

3.3 Lens Selection

We parse free-text situations into a role, task, concerns and as-of date. Configured situations use a fixed needs catalog; unfamiliar roles combine catalog entries. Selection returns eligible fact identifiers, completeness and an optional headline. It does not return arbitrary card prose. We render the selected facts through registered templates, run section selection in parallel and stream completed sections. A section title alone does not count as an answering card.

An empty selection does not prove that information is missing. We expand the concept with synonyms, check the eligible text lexically and run a full-text model pass over every eligible document. We show a documentation gap only when these checks succeed without finding evidence. A lexical failure, full-text failure or timeout produces an unavailable state. The statement is always relative to the searched record and as-of date; it is not a statement that the patient lacks the condition.

3.4 Claim Validation

Figure 2 shows the common claim boundary. Template claims require valid identifiers, located passages and supported fields. Composed claims additionally undergo a semantic comparison with the cited facts and source context. Absence claims require the completed documentation check. We keep clinician annotations and fixed nonclinical boilerplate separately typed.




Figure 2: Claim boundary detail. Composed claims add a semantic check to code checks. Absence requires exhaustive lexical and full-text checks over the eligible record. The cache key binds the full evidence and claim identity. Check failures cannot establish absence.

We buffer generated answers until their sentence claims pass. A failed headline falls back to checked template lines. Letter edits retain citations and trigger revalidation; unsupported additions remain clinician annotations. Text prepared for speech uses the validated answer. These paths share evidence identity and validation results rather than treating each output channel as a new source of truth.

We bind a cached validation to the patient, corpus revision, full evidence window, validator version, normalised claim text, cited fact identifiers and content hashes, and segment identifiers. An absence claim can change when an uncited document is added, which makes revision and window identity necessary even when the claim text and cited facts are unchanged. Review actions do not alter these machine verdicts.

3.5 Contradiction Adjudication

We propose candidates with rules for sides, dates, arithmetic and restated values, and with a model sweep over contextual evidence. We require evidence that the statements describe the same event or measurement before classifying a strict contradiction. Similar wording alone does not establish event identity.

We distinguish contradiction, need for clarification, change over time, measurement variation, omission and different context. Only contradictions and clarification requests reach the findings view. Medication changes between dated source lists are trends. Public titles and explanations pass claim validation, including when a candidate is downgraded to a clarification. We test expected findings and dismissal fixtures separately to measure false alarms as well as recovered cases.

4 Synthetic Data

We generate structured histories from seeded clinical scenarios, then plan which parts each document states, negates, paraphrases or omits. We render German documents from fresh templates and apply controlled mutations such as side flips, dose changes, date shifts and arithmetic inconsistencies. Figure 3 shows the pipeline. We assign patient and generation-family splits before optional rewriting and hold out styles, scenarios and mutation types.

We derive labels from the final rendered documents and the mutation ledger. A condition present in the hidden history but absent from every eligible document is not documented in the record. It must not become a supported claim merely because we know the generated history. We check that intended values, spans and mutations survive a prose rewrite; if a check fails, we retain the original rendering.




Figure 3: Synthetic data construction. Patient and family splits precede rewriting. Labels follow the final text and mutation ledger. Optional rewrites retain the original on check failure. Code-checked labels are distinct from human gold.

The saved manifest reports *pending* generated patients, *pending* documents and *pending* code-checked facts. It records *pending* contradictions, *pending* distractors and *pending* documentation gaps. These counts describe generated artifacts, not clinical prevalence, an ingested database cohort or independently verified semantic labels. Human approval of an aggregate count also does not make the underlying labels human gold. We follow the documentation goals of dataset datasheets (Gebru et al., 2021) and keep the annotation source and label tier explicit.

Bulk data, rendered pages and model artifacts remain local. Only a fresh synthetic sample is eligible for repository distribution. We do not use challenge prose in templates, training examples, publication examples or source-controlled test fixtures. A separate human-reviewed sample is needed to estimate label noise and clinical plausibility.

5 Verifier Training

We formulate verification as classification of a claim and a passage with context into supported, unsupported or contradicted. We construct hard negatives from controlled mutations and keep assertion and timing information. We split by patient and family before adaptation. The training, validation and test manifests contain *pending*, *pending* and *pending* examples, respectively. We keep real-patient weak labels outside training and report them separately.

We adapt a quantised Qwen3 base (Yang et al., 2025) with low-rank updates (Hu et al., 2021) using MLX on Apple silicon (Hannun et al., 2023). For a frozen weight matrix W_0, the adapted projection has the form

$$h = W_0 x + \frac{\alpha}{r} BAx, \qquad A \in \mathbb{R}^{r \times d}, \quad B \in \mathbb{R}^{m \times r}. \tag{3}$$

The quantised-base approach is related to QLoRA (Dettmers et al., 2023). We do not equate this MLX run with the original CUDA implementation or assert that it uses all of its quantisation methods. We mask the prompt during training and bound the input length at 512 tokens. The configured wall-time cap is 45 minutes. A cap and an epoch target do not establish that a run completed.

We compare rules-only checks, the configured proxy semantic judge and the local adapter. We measure macro F-score, coverage and latency together. We reserve model confidence and calibration for experiments with recorded probabilities; a class prediction alone does not define a reliability curve. Calibration analysis follows the distinction between confidence and accuracy made by Guo et al. (2017). We use a model card to record the training conditions and intended use (Mitchell et al., 2019). The proxy judge remains the default semantic backend unless a separate integration decision approves the local verifier.

6 Results

6.1 Evaluation Protocol

We keep the challenge regression, blind challenge situations, synthetic pipeline, retrieval and verifier experiments separate. Evaluation uses an empty review layer. The regression protocol specifies 15 answers across 5 configured situations. The blind set specifies 20 independently authored situations. The paper build does not open its results by default; release requires the orchestrator's scheduled review.

All empirical quantities enter through `generated/numbers.tex`. We extract only numeric aggregates from allowlisted artifact fields and record input hashes. A human review must approve a value against the complete current source identity before the manuscript prints it. Missing, invalid and unapproved values render as *pending*; they never become zero observations. The machine-readable aggregate file remains available for that review. No approval of measurements is implied by this manuscript build.

6.2 Challenge Regression

Table 1 separates answer-and-citation passes from complete suite passes. The latter can additionally depend on timing, findings and audits. We report cold requests, warm attempts and confirmed cache hits separately. A failed browser launch is not an observed visibility failure rate. Counts of located references measure source location, while an audit of composed claims measures a different property. Neither establishes that all task-relevant facts were selected.

6.3 Synthetic Pipeline and Retrieval

Table 2 separates generated data from executed evaluation cases. We do not count an unexecuted challenge as a pass or a failure. The number of generated patients is also distinct from the number ingested into

Measure	Observed
Regression answer and citation passes	*pending*/*pending*
Full-suite question passes	*pending*/*pending*
Located fact references checked	*pending*
Location audit violations	*pending*
Composed claims independently audited	*pending*
Contradiction fixtures recovered	*pending*
Clarification fixtures recovered	*pending*
False alarms against dismissal fixtures	*pending*
Slowest cold engine/API request (s)	*pending*
Slowest warm attempt (s)	*pending*
Confirmed warm cache hits	*pending*/*pending*
Slowest confirmed cached request (s)	*pending*
Browser checks successfully completed	*pending*

Table 1: Challenge regression aggregates eligible for publication after human review. We do not merge rows or timing metadata from different saved runs.

the shared database. Table 3 compares query-level retrieval aggregates at the configured cutoffs. These experiments concern synthetic query labels and do not establish challenge-patient recall. Figure 4 reserves separate panels for retrieval, verifier quality, reliability and latency.

Research artifact	Observed
Generated synthetic patients	*pending*
Generated synthetic documents	*pending*
Code-checked facts / contradictions	*pending*/ *pending*
Distractors / documentation gaps	*pending*/ *pending*
Patients with rewritten prose	*pending*
Sample patients / documents	*pending*/ *pending*
Synthetic challenges generated	*pending*
Synthetic challenges evaluated	*pending*
Verifier training / validation / test examples	*pending*/ *pending*/ *pending*
Verifier macro F-score	*pending*
Verifier accuracy	*pending*
Verifier median latency (ms)	*pending*
Retrieval recall at configured cutoff	*pending*

Table 2: Synthetic and research artifact counts. Code-checked labels remain distinct from human gold. An experiment can have generated cases without measured cases.

Retrieval	Queries	Recall@5	Recall@10	MRR@10
BM25	*pending*	*pending*	*pending*	*pending*
Vector	*pending*	*pending*	*pending*	*pending*
Hybrid	*pending*	*pending*	*pending*	*pending*

Table 3: Synthetic retrieval evaluation. A missing or failed mode remains pending; we do not infer a retrieval benefit from the presence of a hybrid index.

6.4 Verifier Comparison

Table 4 reports each method's own sample count. Comparisons require matching evaluation populations and label definitions; unequal counts preclude a paired interpretation. Macro F-score averages class-specific F-

scores, and coverage records whether the method produced a decision. We do not infer calibrated confidence from classification accuracy or treat rules-only agreement as human annotation.

Verifier	Examples	Macro F-score	Coverage	Median ms
Rules only	*pending*	*pending*	*pending*	*pending*
Proxy semantic	*pending*	*pending*	*pending*	*pending*
Local adapter	*pending*	*pending*	*pending*	*pending*

Table 4: Verifier results on synthetic held-out generation families, kept separate from held-out mutation experiments and real-patient weak labels. Median latency is specific to the saved evaluation conditions.




Figure 4: Separate synthetic retrieval and verifier experiments. Only measurements approved against current source hashes are plotted. Pending panels have no measured marks. The dashed line is the calibration reference.

6.5 Limitations

We have a prototype, a narrow challenge workflow and synthetic data whose labels primarily follow code checks. We have not established clinical efficacy, diagnostic accuracy, reduced clinician workload or safety in deployment. Template rendering limits unsupported composition but cannot repair an incorrect extraction. A model judge can share systematic errors with the extractor. A source citation can be correctly located while the statement loses a qualification in translation.

Synthetic held-out families test a bounded kind of variation. They do not substitute for external records from different institutions, independent clinicians or new writing conventions. Real-patient weak labels measure agreement with a validator; they do not provide an adjudicated clinical test set. We also need

independent page-level verification for scans and PDFs. We do not infer a speed and quality tradeoff from runs with different populations or measurement conditions.

The record contains sensitive clinical content even when the challenge describes it as synthetic. We retain access restrictions and omit document text from this report. Before clinical use, we would need independent annotation, error analysis by claim type, prospective workflow evaluation and access-control review. A clinician review action is an authorship record, not a substitute for these studies.

7 Conclusion

We presented a task-specific clinical view built from located evidence. We separate fact selection from rendering, apply one validation boundary across output channels and preserve the distinction between missing documentation and a failed check. We described a synthetic data pipeline and a local verifier experiment with separate evaluation tracks. The next empirical step is independent annotation and matched comparisons of coverage, support and latency. Until then, we treat this system as an inspectable prototype with explicit unresolved measurements.

References

Griffin Adams, Jason Zuckerg, and Nóemie Elhadad. A meta-evaluation of faithfulness metrics for long-form hospital-course summarization. In *Proceedings of the 8th Machine Learning for Healthcare Conference*, volume 219, pages 2–30. PMLR, 2023. URL https://proceedings.mlr.press/v219/adams23a.html.

Matthias Blondeel, Noel Codella, Sam Preston, Hao Qiu, Leonardo Schettini, Frank Tuan, Wen-wai Yim, Smitha Saligrama, Mert Öz, Shrey Jain, Matthew P. Lungren, and Thomas Osborne. Demo: Healthcare agent orchestrator (HAO) for patient summarization in molecular tumor boards. arXiv:2509.06602, 2025. URL https://arxiv.org/abs/2509.06602.

Wendy W. Chapman, Will Bridewell, Paul Hanbury, Gregory F. Cooper, and Bruce G. Buchanan. A simple algorithm for identifying negated findings and diseases in discharge summaries. *Journal of Biomedical Informatics*, 34(5):301–310, 2001. doi: 10.1006/jbin.2001.1029. URL https://www.sciencedirect.com/science/article/pii/S1532046401910299.

Gordon V. Cormack, Charles L. A. Clarke, and Stefan Buettcher. Reciprocal rank fusion outperforms condorcet and individual rank learning methods. In *Proceedings of the 32nd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 758–759, 2009. doi: 10.1145/1571941.1572114. URL https://cormack.uwaterloo.ca/cormack/cormacksigir09-rrf.pdf.

Viviana Cotik, Roland Roller, Feiyu Xu, Hans Uszkoreit, Klemens Budde, and Danilo Schmidt. Negation detection in clinical reports written in german. In *Proceedings of the Fifth Workshop on Building and Evaluating Resources for Biomedical Text Mining (BioTxtM 2016)*, pages 115–124. The COLING 2016 Organizing Committee, 2016. URL https://aclanthology.org/W16-5113/.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. QLoRA: Efficient finetuning of quantized LLMs. arXiv:2305.14314, 2023. URL https://arxiv.org/abs/2305.14314.

Luyu Gao, Zhuyun Dai, Panupong Pasupat, Anthony Chen, Arun Tejasvi Chaganty, Yicheng Fan, Vincent Zhao, Ni Lao, Hongrae Lee, Da-Cheng Juan, and Kelvin Guu. RARR: Researching and revising what language models say, using language models. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16477–16508, Toronto, Canada, July 2023a. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.910. URL https://aclanthology.org/2023.acl-long.910/.

Tianyu Gao, Howard Yen, Jiatong Yu, and Danqi Chen. Enabling large language models to generate text with citations. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6465–6488, Singapore, December 2023b. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.398. URL https://aclanthology.org/2023.emnlp-main.398/.

Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daumé III, and Kate Crawford. Datasheets for datasets. *Communications of the ACM*, 64(12):86–92, 2021. doi: 10.1145/3458723. URL https://arxiv.org/abs/1803.09010.

Akshay Goel. LangExtract. Software, 2026. URL https://github.com/google/langextract. Official repository, accessed October 30, 2026.

Google DeepMind. Gemini Embedding 2. Official model documentation, 2026. URL https://ai.google.dev/gemini-api/docs/models/gemini-embedding-2. Accessed October 30, 2026.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pages 1321–1330. PMLR, 2017. URL https://proceedings.mlr.press/v70/guo17a.html.

Awni Hannun, Jagrit Digani, Angelos Katharopoulos, and Ronan Collobert. MLX: Efficient and flexible machine learning on apple silicon. Software, 2023. URL https://github.com/ml-explore/mlx.

Victor Petrén Bach Hansen, Lasse Krogsbøll, Jonas Lyngsø, Mathias Baltzersen, Andreas Motzfeldt, Kevin Pelgrims, and Lars Maaløe. FactsR: A safer method for producing high quality healthcare documentation. arXiv:2505.10360, 2025. URL https://arxiv.org/abs/2505.10360.

Henk Harkema, John N. Dowling, Tyler Thornblade, and Wendy W. Chapman. ConText: An algorithm for determining negation, experiencer, and temporal status from clinical reports. *Journal of Biomedical Informatics*, 42(5):839–851, 2009. doi: 10.1016/j.jbi.2009.05.002. URL https://pubmed.ncbi.nlm.nih.gov/19435614/.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. arXiv:2106.09685, 2021. URL https://arxiv.org/abs/2106.09685.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu, editors, *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.550. URL https://aclanthology.org/2020.emnlp-main.550/.

Sunjun Kweon, Junu Kim, Jiyoun Kim, Sujeong Im, Eunbyeol Cho, Seongsu Bae, Jungwoo Oh, Gyubok Lee, Jong Hak Moon, Seng Chan You, Seungjin Baek, Chang Hoon Han, Yoon Bin Jung, Yohan Jo, and Edward Choi. Publicly shareable clinical large language model built on synthetic clinical notes. arXiv:2309.00237, 2023. URL https://arxiv.org/abs/2309.00237.

Philippe Laban, Tobias Schnabel, Paul N. Bennett, and Marti A. Hearst. SummaC: Re-visiting NLI-based models for inconsistency detection in summarization. *Transactions of the Association for Computational Linguistics*, 10:163–177, 2022. doi: 10.1162/tacl_a_00453. URL https://aclanthology.org/2022.tacl-1.10/.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474, 2020. URL https://arxiv.org/abs/2005.11401.

Jian Lu, Panyu Chen, Miriam Treggiari, Robert Blessing, Danyang Zhuo, Chunhua Weng, William W. Stead, and Anru R. Zhang. Toward automated detection of documentation inconsistencies in electronic health records. arXiv:2607.22954, 2026. URL https://arxiv.org/abs/2607.22954.

Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. On faithfulness and factuality in abstractive summarization. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault, editors, *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1906–1919, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.173. URL https://aclanthology.org/2020.acl-main.173/.

Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. FActScore: Fine-grained atomic evaluation of factual precision in long form text generation. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12076–12100, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.741. URL https://aclanthology.org/2023.emnlp-main.741/.

Margaret Mitchell, Simone Wu, Andrew Zaldivar, Parker Barnes, Lucy Vasserman, Ben Hutchinson, Elena Spitzer, Inioluwa Deborah Raji, and Timnit Gebru. Model cards for model reporting. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, pages 220–229, 2019. doi: 10.1145/3287560.3287596. URL https://arxiv.org/abs/1810.03993.

Artidoro Pagnoni, Vidhisha Balachandran, and Yulia Tsvetkov. Understanding factuality in abstractive summarization with FRANK: A benchmark for factuality metrics. In Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tur, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou, editors, *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4812–4829, Online, June 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.383. URL https://aclanthology.org/2021.naacl-main.383/.

pgvector contributors. pgvector: Open-source vector similarity search for postgres. Software, 2026. URL https://github.com/pgvector/pgvector. Official repository, accessed October 30, 2026.

William Poulett, Alice Waterhouse, Ben Wallace, Scarlett Kynoch, Amaia Imaz Blanco, Michael Spence, and Jonathan Pearson. A pipeline for generating longitudinal synthetic clinical notes using large language models. arXiv:2606.26879, 2026. URL https://arxiv.org/abs/2606.26879.

Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389, 2009. doi: 10.1561/1500000019. URL https://www.nowpublishers.com/article/Details/INR-019.

Liyan Tang, Philippe Laban, and Greg Durrett. MiniCheck: Efficient fact-checking of LLMs on grounding documents. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen, editors, *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 8818–8847, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.499. URL https://aclanthology.org/2024.emnlp-main.499/.

Dave Van Veen, Cara Van Uden, Louis Blankemeier, Jean-Benoit Delbrouck, Asad Aali, Christian Bluethgen, Anuj Pareek, Malgorzata Polacin, Eduardo Pontes Reis, Anna Seehofnerová, Nidhi Rohatgi, Poonam Hosamani, William Collins, Neera Ahuja, Curtis P. Langlotz, Jason Hom, Sergios Gatidis, John Pauly, and Akshay S. Chaudhari. Adapted large language models can outperform medical experts in clinical text summarization. *Nature Medicine*, 30:1134–1142, 2024. doi: 10.1038/s41591-024-02855-5. URL https://www.nature.com/articles/s41591-024-02855-5.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. URL https://arxiv.org/abs/1706.03762.

Jason Walonoski, Mark Kramer, Joseph Nichols, Andre Quina, Chris Moesel, Dylan Hall, Carlton Duffett, Kudakwashe Dube, Thomas Gallagher, and Scott McLachlan. Synthea: An approach, method, and software mechanism for generating synthetic patients and the synthetic electronic health care record. *Journal of the American Medical Informatics Association*, 25(3):230–238, 2018. doi: 10.1093/jamia/ocx079. URL https://pubmed.ncbi.nlm.nih.gov/29025144/.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, et al. Qwen3 technical report. arXiv:2505.09388, 2025. URL https://arxiv.org/abs/2505.09388.

Yuheng Zha, Yichi Yang, Ruichen Li, and Zhiting Hu. AlignScore: Evaluating factual consistency with a unified alignment function. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11328–11348, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.634. URL https://aclanthology.org/2023.acl-long.634/.

Nan Zhang, Yusen Zhang, Wu Guo, Prasenjit Mitra, and Rui Zhang. FaMeSumm: Investigating and improving faithfulness of medical summarization. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 10915–10931, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.673. URL https://aclanthology.org/2023.emnlp-main.673/.