

StubHub Webhooks API (2.249.0.0)

Topics

When configuring a webhook, you can choose the topics you would like to receive payloads for. You should only subscribe to the specific topics that you plan on handling so that you can limit the number of HTTP requests to your server.

Sales Webhook

Triggered when something happens that affects a sale (e.g. you sell one or more tickets).

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

barcodes	Array of objects or null (BarcodeInformation) The barcodes that are linked to the sale.
----------	--

topic	string or null The topic of the webhook.
-------	---

action	string or null The action that triggered this webhook.
_links >	(SalesTopicLinks (object or null))
_embedded >	(SalesTopicEmbeddedResources (object or null))

Responses

— **200** The data was received successfully.

Request samples

Payload

Content type

application/json

```
{
  - "barcodes": [
    + { ... }
  ],
  "topic": "string",
```

Copy Expand all Collapse all

```
"action": "string",  
- "_links": {  
  + "self": { ... }  
},  
- "_embedded": {  
  + "event": { ... },  
  + "sale": { ... },  
  + "seller_listing": { ... },  
  + "venue": { ... },  
  + "webhook": { ... }  
}  
}
```

ProvisionalSale Webhook

Triggered when a provisional sale occurs. The normal `SalesTopic` webhook will confirm the provisional sale. If you want to reject the provisional sale, ignore it and reject the sale when it comes through as normal.

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

barcodes Array of objects or null (BarcodeInformation)
The barcodes that are linked to the sale.

topic	string or null The topic of the webhook.
action	string or null The action that triggered this webhook.
_links >	(ProvisionalSaleTopicLinks (object or null))
_embedded >	(ProvisionalSaleTopicEmbeddedResources (object or null))

Responses

— 200 The data was received successfully.

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "barcodes": [
    + { ... }
  ],
  "topic": "string",
  "action": "string",
  - "_links": {
    + "self": { ... }
  },
  - "_embedded": {
    + "event": { ... },
    + "sale": { ... },
    + "seller_listing": { ... },
    + "venue": { ... },
    + "webhook": { ... }
  }
}
```

CancelProvisionalSale Webhook

Triggered when a provisional sale is cancelled.

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

barcodes	Array of objects or null (BarcodeInformation)
-----------------	---

	The barcodes that are linked to the sale.
topic	string or null The topic of the webhook.
action	string or null The action that triggered this webhook.
_links >	(CancelProvisionalSaleTopicLinks (object or null))
_embedded >	(CancelProvisionalSaleTopicEmbeddedResources (object or null))

Responses

— 200 The data was received successfully.

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "barcodes": [
    + { ... }
  ],
  "topic": "string",
  "action": "string",
  - "_links": {
    + "self": { ... }
  },
  - "_embedded": {
    + "event": { ... },
    + "sale": { ... },
    + "seller_listing": { ... },
    + "venue": { ... },
    + "webhook": { ... }
  }
}
```

SaleUpdates Webhook

Triggered when an update is made to a sale that you did not initiate. You will need to filter by the action that you are interested in. The currently support action is `FailedBarcodeValidation` which will tell you if validation of a set of barcodes uploaded against an order has failed, and barcodes need re-uploading.

AUTHORIZATIONS: >

OAuth2

REQUEST BODY SCHEMA: application/json

barcodes	Array of objects or null (BarcodeInformation) The barcodes that are linked to the sale.
topic	string or null The topic of the webhook.
action	string or null The action that trigger this webhook. Can be <code>FailedBarcodeValidation</code>
_links >	(SaleUpdatesTopicLinks (object or null))
_embedded >	(SaleUpdatesTopicEmbeddedResources (object or null))

Responses

— **200** The data was received successfully.

Request samples

Payload

Content type

application/json

```
{
  - "barcodes": [
    + { ... }
  ],
  "topic": "string",
  "action": "string",
  - "_links": {
    + "self": { ... }
  },
  - "_embedded": {
    + "event": { ... },
    + "sale": { ... },
    + "seller_listing": { ... },
    + "venue": { ... },
    + "webhook": { ... }
  }
}
```

SellerListingUpdates Webhook

Triggered when an update is made to a listing that you did not initiate. You will need to filter by the action that you are interested in. The currently support actions are `FailedBarcodeValidation` and `ListingDeliverabilityExpired`.

`FailedBarcodeValidation` will tell you if validation of a set of barcodes uploaded against a listing has failed, and barcodes need re-uploading. `ListingDeliverabilityExpired` will tell you that a listing is not longer deliverable to a customer. To increase the deliverability of electronic type tickets, preupload them (e.g. pre-upload barcodes or PDF files.) To increase deliverability of paper tickets, opt your tickets into our LMS program.

[AUTHORIZATIONS:](#) >*OAuth2*REQUEST BODY SCHEMA: application/json

topic

string or null

The topic of the webhook.

action

string or null

The action that trigger this webhook. Can be `FailedBarcodeValidation` or `ListingDeliverabilityExpired`

barcodes

Array of objects or null (BarcodeInformation2)

The barcodes that are linked to the listing.

[_links](#) >(SellerListingUpdatesTopicLinks (object or null))

[_embedded](#) >(SellerListingUpdatesTopicEmbeddedResources (object or null))

Responses

— **200** The data was received successfully.

Request samples

Payload**Content type**

application/json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "topic": "string",
  "action": "string",
  - "barcodes": [
    + { ... }
  ],
  - "_links": {
    + "self": { ... }
  },
  - "_embedded": {
    + "event": { ... },
    + "seller_listing": { ... },
    + "venue": { ... },
    + "webhook": { ... }
  }
}
```

Ping Webhook

Triggered any time a Webhook is pinged.

[AUTHORIZATIONS:](#) >*OAuth2*REQUEST BODY SCHEMA: application/json

topic	string or null The topic of the webhook.
action	string or null The action that triggered this webhook.
_links >	(PingTopicLinks (object or null))
_embedded >	(PingTopicEmbeddedResources (object or null))

Responses

— **200** The data was received successfully.

Request samples

Payload

Content type

application/json

```
{
  "topic": "string",
  "action": "string",
  - "_links": {
    + "self": { ... }
  },
  - "_embedded": {
    + "webhook": { ... }
  }
}
```

ReTransferTicket Webhook

Triggered when a ticket was not received by the buyer, so the ticket must be re-transferred from the 3rd party provider.

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

barcodes	Array of objects or null (BarcodeInformation) The barcodes that are linked to the sale.
topic	string or null The topic of the webhook.

action	string or null The action that triggered this webhook.
_links >	(ReTransferTicketTopicLinks (object or null))
_embedded >	(ReTransferTicketTopicEmbeddedResources (object or null))

Responses

— **200** The data was received successfully.

Request samples

Payload

Content type

application/json

```
{
  - "barcodes": [
    + { ... }
  ],
  "topic": "string",
```

Copy Expand all Collapse all

```
    "action": "string",
  -  "_links": {
    +    "self": { ... }
  },
  -  "_embedded": {
    +    "event": { ... },
    +    "sale": { ... },
    +    "seller_listing": { ... },
    +    "venue": { ... },
    +    "webhook": { ... }
  }
}
```

Webhooks

List webhooks

List webhooks for the authenticated user.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

page	integer <int32> Specifies which page of data to retrieve.
page_size	integer <int32> Set custom page sizes on response.
sort	string Determines the ordering of items. A comma-separated string containing <code>created_at</code> .

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(WebhooksLinks (object or null))
_embedded >	(WebhooksEmbeddedResources (object or null))

- > **401** Authentication credentials were missing or incorrect.
- > **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.
- > **404** The URI requested is invalid or the resource requested, such as an event, does not exist.
- > **500** Internal server error

GET /webhooks

Response samples

200**401****403****404****500**

Content type

application/hal+json



```
"total_items": 0,  
"page": 0,  
"page_size": 0,
```

Copy Expand all Collapse all

```
- "_links": {  
  + "self": { ... },  
  + "first": { ... },  
  + "last": { ... },  
  + "next": { ... },  
  + "prev": { ... }  
},  
- "_embedded": {  
  + "items": [ ... ]  
}  
})
```

Create a webhook

AUTHORIZATIONS: >

OAuth2

REQUEST BODY SCHEMA: application/json

One of PostWebhookRequest

name

string or null

The name of the webhook.

url

string or null

The server endpoint that will receive the webhook payload.

authorization_header	string or null The Authorization header value that should be included in requests to the webhook.
topics	Array of strings or null An array of the topics the webhook is trigger for.

Responses

✓ 201

RESPONSE SCHEMA: application/hal+json

id	integer or null <int32> The webhook identifier.
name	string or null The name of the webhook.
created_at	string <date-time> The date when the webhook was created.
topics	Array of strings or null An array of the topics the webhook is trigger for.

<code>url</code>	string or null The server endpoint that will receive the webhook payload.
<code>authorization_header</code>	string or null The Authorization header value that should be included in requests to the webhook.
<code>_links ></code>	(WebhookLinks (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.**> 403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.**> 500** Internal server error

POST /webhooks

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{  
  "name": "string",  
  "url": "string",  
  "authorization_header": "string",  
  - "topics": [  
    "string"  
  ]  
}
```

Response samples

201**400****401****403****500****Content type**

application/hal+json

Copy

Expand all

Collapse all

```
{  
  "id": 0,  
  "name": "string",  
  "created_at": "2019-08-24T14:15:22Z",  
  - "topics": [  
    "string"  
  ],  
  "url": "string",  
  "authorization_header": "string",  
}
```

```
- "_links": {  
  + "self": { ... },  
  + "webhook:delete": { ... },  
  + "webhook:ping": { ... },  
  + "webhook:update": { ... }  
}  
}
```

Get a webhook

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

webhookId
required integer <int32>

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id integer or null <int32>

The webhook identifier.

name

string or null

The name of the webhook.

created_at

string <date-time>

The date when the webhook was created.

topics

Array of strings or null

An array of the topics the webhook is trigger for.

url

string or null

The server endpoint that will receive the webhook payload.

authorization_header

string or null

The Authorization header value that should be included in requests to the webhook.

_links >

(WebhookLinks (object or null))

- > **401** Authentication credentials were missing or incorrect.
- > **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.
- > **404** The URI requested is invalid or the resource requested, such as an event, does not exist.
- > **500** Internal server error

GET /webhooks/{webhookId}

Response samples

200**401****403****404****500**

Content type

application/hal+json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "id": 0,
  "name": "string",
  "created_at": "2019-08-24T14:15:22Z",
  - "topics": [
    "string"
  ],
  "url": "string",
  "authorization_header": "string",
  - "_links": {
    + "self": { ... },
    + "webhook:delete": { ... },
    + "webhook:ping": { ... },
    + "webhook:update": { ... }
  }
}
```

Update a webhook

AUTHORIZATIONS: > OAuth2

PATH PARAMETERS

webhookId integer <int32>
required

REQUEST BODY SCHEMA: application/json

One of PatchWebhookRequest

name	string or null The name of the webhook.
url	string or null The server endpoint that will receive the webhook payload.
authorization_header	string or null The Authorization header value that should be included in requests to the webhook.
topics	Array of strings or null An array of the topics the webhook is trigger for.

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id	integer or null <int32> The webhook identifier.
name	string or null The name of the webhook.
created_at	string <date-time> The date when the webhook was created.
topics	Array of strings or null An array of the topics the webhook is trigger for.
url	string or null The server endpoint that will receive the webhook payload.
authorization_header	string or null The Authorization header value that should be included in requests to the webhook.
_links >	(WebhookLinks (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

PATCH /webhooks/{webhookId}

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "name": "string",
  "url": "string",
  "authorization_header": "string",
  - "topics": [
    "string"
  ]
}
```

Response samples

200

400

401

403

500

Content type

application/hal+json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "id": 0,
  "name": "string",
  "created_at": "2019-08-24T14:15:22Z",
  - "topics": [
    "string"
  ],
  "url": "string",
  "authorization_header": "string",
  - "_links": {
    + "self": { ... },
    + "webhook:delete": { ... },
    + "webhook:ping": { ... },
    + "webhook:update": { ... }
  }
}
```

Delete a webhook

[AUTHORIZATIONS:](#) >*OAuth2*[PATH PARAMETERS](#)

webhookId
required integer <int32>

Responses

— 204

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

DELETE /webhooks/{webhookId}

Response samples

401

403

500

Content type

application/hal+json

{

"code": "string",

Copy Expand all Collapse all

```
"message": "string",  
- "errors": {  
  + "property1": [ ... ],  
  + "property2": [ ... ]  
}  
}
```

Ping a webhook

Triggers a request to be sent to your webhook. Call this endpoint to test your webhook.

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

webhookId
required integer <int32>

Responses

> 202

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

- > **401** Authentication credentials were missing or incorrect.
- > **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.
- > **500** Internal server error

POST /webhooks/{webhookId}/ping

Response samples

202**400****401****403****500**

Content type

application/hal+json

Copy Expand all Collapse all

```
{
  "id": 0,
  "name": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "topics": [
    "string"
  ],
  "url": "string",
  "authorization_header": "string",
}
```

```
- "_links": {  
  + "self": { ... },  
  + "webhook:delete": { ... },  
  + "webhook:ping": { ... },  
  + "webhook:update": { ... }  
}
```

Money

Returned for monetary values, such as ticket prices, fees charged and tax amounts.

amount
required

number or null <decimal>

The decimal amount of the money.

currency_code
required

string or null

The ISO 4217 currency code that the monetary value is represented in.

display

string or null

A user-friendly string representing the monetary value.

Copy

```
{  
  "amount": 0,  
  "currency_code": "string",  
  "display": "string"  
}
```

Webhook

A webhook is a subscription from a server application to certain topics on the StubHub platform. When an occurrence of a topic is triggered, we'll POST a payload to the webhook's configured url.

id	integer or null <int32> The webhook identifier.
name	string or null The name of the webhook.
created_at	string <date-time> The date when the webhook was created.

topics	Array of strings or null An array of the topics the webhook is trigger for.
url	string or null The server endpoint that will receive the webhook payload.
authorization_header	string or null The Authorization header value that should be included in requests to the webhook.
_links >	(WebhookLinks (object or null))

[Copy](#) [Expand all](#) [Collapse all](#)

```
{  
  "id": 0,  
  "name": "string",  
  "created_at": "2019-08-24T14:15:22Z",  
  "topics": [  
    "string"  
  ],  
  "url": "string",  
  "authorization_header": "string",  
}
```

```
- "_links": {  
  + "self": { ... },  
  + "webhook:delete": { ... },  
  + "webhook:ping": { ... },  
  + "webhook:update": { ... }  
}  
}
```

Webhooks

total_items integer or null <int32>

page integer or null <int32>

page_size integer or null <int32>

_links > (WebhooksLinks (object or null))

_embedded > (WebhooksEmbeddedResources (object or null))

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "items": [ ... ]
  }
}
```