

StubHub Account API (2.249.0.0)

Addresses

List addresses

List addresses for the current user.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

page

integer <int32>

Specifies which page of data to retrieve.

page_size

integer <int32>

Set custom page sizes on response.

sort

string

Determines the ordering of items. A comma-separated string containing `default`, or `id`.

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
-------------	-------------------------

page	integer or null <int32>
------	-------------------------

page_size	integer or null <int32>
-----------	-------------------------

_links >	(AddressssLinks (object or null))
----------	-----------------------------------

_embedded >	(AddressssEmbeddedResources (object or null))
-------------	---

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **404** The URI requested is invalid or the resource requested, such as an event, does not exist.

> **500** Internal server error

GET /addresses

Response samples

200

401

403

404

500

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "items": [ ... ]
  }
}
```

Create an address

AUTHORIZATIONS: >

OAuth2

REQUEST BODY SCHEMA: application/json

One of

PostAddressRequest

full_name	string or null The full name of the recipient.
default	boolean or null True if the address is the current user's default address; Otherwise, false.
address_1	string or null The first line of the address.
address_2	string or null The second line of the address.
address_3	string or null The third line of the address.
city	string or null The name of the city where the address is located.
state_province	string or null

	The name of the State or Province where the address is located.
postal_code	string or null The postal code for the address.
country_code	string or null The 2 character ISO code that identifies the country in which the address is located.

Responses

✓ 201

RESPONSE SCHEMA: application/hal+json

id	integer or null <int32> The address identifier.
full_name	string or null The full name of the recipient.
default	boolean or null True if the address is the user's default address; Otherwise, false.
address_1	string or null The first line of the address.

address_2	string or null The second line of the address.
address_3	string or null The third line of the address.
city	string or null The name of the city where the address is located.
state_province	string or null The name of the State or Province where the address is located.
postal_code	string or null The postal code for the address.
_links >	(AddressLinks (object or null))
_embedded >	(AddressEmbeddedResources (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.**> 403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.**> 500** Internal server error

POST /addresses

Request samples

Payload

Content type

application/json

Copy

```
{  
  "full_name": "string",  
  "default": true,  
  "address_1": "string",  
  "address_2": "string",  
  "address_3": "string",  
  "city": "string",  
  "state_province": "string",  
  "postal_code": "string",  
  "country_code": "string"  
}
```

Response samples

201

400

401

403

500

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{
  "id": 0,
  "full_name": "string",
  "default": true,
  "address_1": "string",
  "address_2": "string",
  "address_3": "string",
  "city": "string",
  "state_province": "string",
  "postal_code": "string",
  - "_links": {
    + "self": { ... },
    + "address:carrier": { ... },
    + "address:delete": { ... },
    + "address:update": { ... }
  },
  - "_embedded": {
    + "country": { ... }
  }
}
```

Get an address

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

addressId
required integer <int32>

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id	integer or null <int32> The address identifier.
full_name	string or null The full name of the recipient.
default	boolean or null True if the address is the user's default address; Otherwise, false.
address_1	string or null The first line of the address.
address_2	string or null The second line of the address.
address_3	string or null The third line of the address.

city	string or null The name of the city where the address is located.
state_province	string or null The name of the State or Province where the address is located.
postal_code	string or null The postal code for the address.
_links >	(AddressLinks (object or null))
_embedded >	(AddressEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **404** The URI requested is invalid or the resource requested, such as an event, does not exist.

> **500** Internal server error

GET /addresses/{addressId}

Response samples

200

401

403

404

500

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{
  "id": 0,
  "full_name": "string",
  "default": true,
  "address_1": "string",
  "address_2": "string",
  "address_3": "string",
  "city": "string",
  "state_province": "string",
  "postal_code": "string",
  - "_links": {
    + "self": { ... },
    + "address:carrier": { ... },
    + "address:delete": { ... },
    + "address:update": { ... }
  },
  - "_embedded": {
    + "country": { ... }
  }
}
```

Update an address

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

addressId

required

integer <int32>

REQUEST BODY SCHEMA: application/json

One of

PatchAddressRequest

full_name	string or null	The full name of the recipient.
default	boolean or null	True if the address is the current user's default address; Otherwise, false.
address_1	string or null	The first line of the address.
address_2	string or null	The second line of the address.
address_3	string or null	The third line of the address.
city	string or null	The name of the city where the address is located.
state_province	string or null	The name of the State or Province where the address is located.

postal_code	string or null The postal code for the address.
country_code	string or null The 2 character ISO code that identifies the country in which the address is located.

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id	integer or null <int32> The address identifier.
full_name	string or null The full name of the recipient.
default	boolean or null True if the address is the user's default address; Otherwise, false.
address_1	string or null The first line of the address.

address_2	string or null The second line of the address.
address_3	string or null The third line of the address.
city	string or null The name of the city where the address is located.
state_province	string or null The name of the State or Province where the address is located.
postal_code	string or null The postal code for the address.
_links >	(AddressLinks (object or null))
_embedded >	(AddressEmbeddedResources (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.**> 403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.**> 500** Internal server error

PATCH /addresses/{addressId}

Request samples

Payload

Content type

application/json

Copy

```
{  
  "full_name": "string",  
  "default": true,  
  "address_1": "string",  
  "address_2": "string",  
  "address_3": "string",  
  "city": "string",  
  "state_province": "string",  
  "postal_code": "string",  
  "country_code": "string"  
}
```

Response samples

200

400

401

403

500

Content type

application/hal+json

[Copy](#)[Expand all](#)[Collapse all](#)

```
{
  "id": 0,
  "full_name": "string",
  "default": true,
  "address_1": "string",
  "address_2": "string",
  "address_3": "string",
  "city": "string",
  "state_province": "string",
  "postal_code": "string",
  - "_links": {
    + "self": { ... },
    + "address:carrier": { ... },
    + "address:delete": { ... },
    + "address:update": { ... }
  },
  - "_embedded": {
    + "country": { ... }
  }
}
```

Delete an address

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

addressId
required integer <int32>

Responses

— 204

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

DELETE /addresses/{addressId}

Response samples

401

403

500

Content type

application/hal+json

{

"code": "string",

Copy Expand all Collapse all

```
"message": "string",  
- "errors": {  
  + "property1": [ ... ],  
  + "property2": [ ... ]  
}  
}
```

PaymentMethods

List payment methods

List payment methods for the authenticated user.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

buyer_method	boolean or null
--------------	-----------------

seller_method	boolean or null
---------------	-----------------

page	integer <int32> Specifies which page of data to retrieve.
page_size	integer <int32> Set custom page sizes on response.

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(PaymentMethodssLinks (object or null))
_embedded >	(PaymentMethodssEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **404** The URI requested is invalid or the resource requested, such as an event, does not exist.

> **500** Internal server error

GET /paymentmethods

Response samples

200

401

403

404

500

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "items": [ ... ]
  }
}
```



Get a payment method

AUTHORIZATIONS: > *OAuth2*

PATH PARAMETERS

paymentMethodId
required integer <int32>

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id integer or null <int32>
The payment method identifier.

details string or null
The obfuscated details of the payment method.

type string or null

	The type of the payment method.
type_description	string or null A localised string describing the type of payment method.
buyer_method	boolean or null True if the payment method can be used for purchasing listings; otherwise, false.
default_buyer_method	boolean or null True if the payment method is the user's default payment method for purchasing listings.
seller_method	boolean or null True if the payment method can be used for receiving payments; otherwise, false.
default_seller_method	boolean or null True if the payment method is the user's default payment method for receiving payments.
_links >	(PaymentMethodLinks (object or null))
_embedded >	(PaymentMethodEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **404** The URI requested is invalid or the resource requested, such as an event, does not exist.

> **500** Internal server error

GET /paymentmethods/{paymentMethodId}

Response samples

200**401****403****404****500**

Content type

application/hal+json

Copy Expand all Collapse all

```
{
  "id": 0,
  "details": "string",
  "type": "string",
  "type_description": "string",
  "buyer_method": true,
  "default_buyer_method": true,
  "seller_method": true,
  "default_seller_method": true,
  - "_links": {
    + "self": { ... },
    + "paymentmethod:delete": { ... },
    + "paymentmethod:updatecreditcard": { ... },
    + "paymentmethod:updatedefaults": { ... },
    + "paymentmethod:updatepaypal": { ... }
  },
}
```

```
- "_embedded": {  
  + "billing_address": { ... },  
  + "type_details": { ... }  
}  
}
```

List payment methods for a listing

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

listingId
required integer <int64>

QUERY PARAMETERS

page integer <int32>
Specifies which page of data to retrieve.

page_size integer <int32>
Set custom page sizes on response.

REQUEST BODY SCHEMA: application/json

One of PutListingPaymentMethodsRequest

number_of_tickets	integer or null <int32>
delivery_address_id	integer or null <int32>
delivery_method_id	integer or null <int32>
coupons	Array of strings or null
pickup_full_name	string or null

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(PaymentMethodsLinks (object or null))
_embedded >	(PaymentMethodsEmbeddedResources (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.**> 403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.**> 500** Internal server error

PUT /listings/{listingId}/paymentmethods

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{  
  "number_of_tickets": 0,  
  "delivery_address_id": 0,  
  "delivery_method_id": 0,  
  - "coupons": [  
    "string"  
  ],  
  "pickup_full_name": "string"  
}
```

Response samples

200**400****401****403****500**

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{  
  "total_items": 0,  
  "page": 0,  
  "page_size": 0,  
  - "_links": {  
    + "self": { ... },  
    + "first": { ... },  
    + "last": { ... },  
    + "next": { ... },  
    + "paymentmethod:createcreditcard": { ... },  
    + "paymentmethod:createpaypal": { ... },  
    + "prev": { ... }  
  },  
}
```

```
- "_embedded": {  
  + "items": [ ... ]  
}
```

User

Get the authenticated user

AUTHORIZATIONS: >

OAuth2

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

full_name

string or null

The full name of the user.

email	string or null The email address of the user.
primary_phone	string or null The primary phone number of the user.
email_optin	boolean True if the user is signed up for the StubHub email newsletter; otherwise, false.
_links >	(UserLinks (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **404** The URI requested is invalid or the resource requested, such as an event, does not exist.

> **500** Internal server error

GET /user

Response samples

200

401

403

404

500

Content type

application/hal+json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "full_name": "string",
  "email": "string",
  "primary_phone": "string",
  "email_optin": true,
  - "_links": {
    + "self": { ... },
    + "user:addresses": { ... },
    + "user:paymentmethods": { ... },
    + "user:sales": { ... },
    + "user:salesaggregates": { ... },
    + "user:sellerlistings": { ... },
    + "user:update": { ... },
    + "user:webhooks": { ... }
  }
}
```

Update the authenticated user

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

One of

PatchUserRequest

full_name

string or null

The full name of the user.

email_optin

boolean or null

True if the user is signed up for the StubHub email newsletter; otherwise, false.

Responses

✓ 200

RESPONSE SCHEMA: application/octet-stream

string <binary>

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.

> 403 The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> 500 Internal server error

PATCH /user

Request samples

Payload

Content type

application/json

Copy

```
{  
  "full_name": "string",  
  "email_optin": true  
}
```

Response samples

400

401

403

500

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{  
  "code": "string",  
  "message": "string",  
}
```

```
- "errors": {  
  + "property1": [ ... ],  
  + "property2": [ ... ]  
}  
}
```

Address

An address is a delivery, pickup or billing address associated with the current user.

id	integer or null <int32> The address identifier.
full_name	string or null The full name of the recipient.
default	boolean or null True if the address is the user's default address; Otherwise, false.
address_1	string or null The first line of the address.
address_2	string or null

	The second line of the address.
address_3	string or null The third line of the address.
city	string or null The name of the city where the address is located.
state_province	string or null The name of the State or Province where the address is located.
postal_code	string or null The postal code for the address.
_links >	(AddressLinks (object or null))
_embedded >	(AddressEmbeddedResources (object or null))

Copy Expand all Collapse all



```
"id": 0,  
"full_name": "string",  
"default": true,  
"address_1": "string",  
"address_2": "string",  
"address_3": "string",
```

```
"city": "string",
"state_province": "string",
"postal_code": "string",
- "_links": {
  + "self": { ... },
  + "address:carrier": { ... },
  + "address:delete": { ... },
  + "address:update": { ... }
},
- "_embedded": {
  + "country": { ... }
}
}
```

Address

total_items	integer or null <int32>
-------------	-------------------------

page	integer or null <int32>
------	-------------------------

page_size	integer or null <int32>
-----------	-------------------------

_links >	(AddressLinks (object or null))
----------	---------------------------------

`_embedded >` (AddressssEmbeddedResources (object or null))

Copy Expand all Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "items": [ ... ]
  }
}
```

PaymentMethod

A method to send or receive payment.

id	integer or null <int32> The payment method identifier.
details	string or null The obfuscated details of the payment method.
type	string or null The type of the payment method.
type_description	string or null A localised string describing the type of payment method.
buyer_method	boolean or null True if the payment method can be used for purchasing listings; otherwise, false.
default_buyer_method	boolean or null True if the payment method is the user's default payment method for purchasing listings.
seller_method	boolean or null True if the payment method can be used for receiving payments; otherwise, false.
default_seller_method	boolean or null True if the payment method is the user's default payment method for receiving payments.
_links >	(PaymentMethodLinks (object or null))

[_embedded >](#)

(PaymentMethodEmbeddedResources (object or null))

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "id": 0,
  "details": "string",
  "type": "string",
  "type_description": "string",
  "buyer_method": true,
  "default_buyer_method": true,
  "seller_method": true,
  "default_seller_method": true,
  - "_links": {
    + "self": { ... },
    + "paymentmethod:delete": { ... },
    + "paymentmethod:updatecreditcard": { ... },
    + "paymentmethod:updatedefaults": { ... },
    + "paymentmethod:updatepaypal": { ... }
  },
  - "_embedded": {
    + "billing_address": { ... },
    + "type_details": { ... }
  }
}
```

PaymentMethods

The PaymentMethods resource is a collection resource that contains zero or more references to a set of payment methods, and links that guide you on ways to interact with the payment methods. The collection offers a paginated view of payment methods.

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(PaymentMethodsLinks (object or null))
_embedded >	(PaymentMethodsEmbeddedResources (object or null))

Copy Expand all Collapse all

```
{  
  "total_items": 0,  
  "page": 0,  
  "page_size": 0,  
}
```

```
- "_links": {
  + "self": { ... },
  + "first": { ... },
  + "last": { ... },
  + "next": { ... },
  + "paymentmethod:createcreditcard": { ... },
  + "paymentmethod:createpaypal": { ... },
  + "prev": { ... }
},
- "_embedded": {
  + "items": [ ... ]
}
})
```

PaymentMethodss

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(PaymentMethodssLinks (object or null))

`_embedded >` (PaymentMethodssEmbeddedResources (object or null))

Copy Expand all Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "items": [ ... ]
  }
}
```

User

An authenticated user.

full_name	string or null The full name of the user.
email	string or null The email address of the user.
primary_phone	string or null The primary phone number of the user.
email_optin	boolean True if the user is signed up for the StubHub email newsletter; otherwise, false.
_links >	(UserLinks (object or null))

Copy Expand all Collapse all

```
{  
  "full_name": "string",  
  "email": "string",  
  "primary_phone": "string",  
  "email_optin": true,  
}
```

```
- "_links": {  
  + "self": { ... },  
  + "user:addresses": { ... },  
  + "user:paymentmethods": { ... },  
  + "user:sales": { ... },  
  + "user:salesaggregates": { ... },  
  + "user:sellerlistings": { ... },  
  + "user:update": { ... },  
  + "user:webhooks": { ... }  
}  
}
```