

StubHub Catalog API (1.0.0.75)

Categories

View categories on the StubHub platform

Search categories

Get matching category given the query string.

AUTHORIZATIONS: > *OAuth2*

QUERY PARAMETERS

q	string or null
	The query text to be used to match categories.

Responses

✓ 200

RESPONSE SCHEMA: application/octet-stream

string <binary>

- > **401** Authentication credentials were missing or incorrect.
- > **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.
- > **404** The URI requested is invalid or the resource requested, such as an event, does not exist.
- > **500** Internal server error

GET /catalog/categories/map

Response samples

401**403****404****500**

Content type

application/hal+json

```
{  
  "code": "string",  
  "message": "string",  
}
```

[Copy](#) [Expand all](#) [Collapse all](#)

```
- "errors": {  
  + "property1": [ ... ],  
  + "property2": [ ... ]  
}  
}
```

Events

View events on the StubHub platform

List events

Lists all events on the StubHub platform. Use this endpoint to sync the entire StubHub event catalog with your application.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

page

integer <int32>

Specifies which page of data to retrieve.

page_size

integer <int32>

Set custom page sizes on response.

updated_since	string <date-time> Filters the response to only return items that have been updated since the given timestamp
sort	string Determines the ordering of items. A comma-separated string containing <code>resource_version</code> .
min_resource_version	integer or null <int64>
country_code	string Filters results to only include events located in the specified country.
latitude	number or null <double> When provided with longitude and distance filters events returned to ones within the specified distance of the lat/long.
longitude	number or null <double> When provided with latitude and distance filters events returned to ones within the specified distance of the lat/long.
max_distance_in_meters	integer or null <int32> When provided with latitude and longitude filters events returned to ones within the specified distance of the lat/long.
genre_id	integer or null <int32> Filters results to only include events for the specified genre id.
exclude_parking_passes	boolean or null Filters results to remove parking passes

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(EventsLinks (object or null))
_embedded >	(EventsEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

GET /catalog/events

Response samples

200**401****403****500****Content type**

application/hal+json

Copy

Expand all

Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "deleted_items": [ ... ],
    + "items": [ ... ]
  }
}
```

List events by event ids.

List a specified set of events on the StubHub platform. Note that the eventId being passed can already be merged with another event. And in this case, details of the new event will be returned, if a different eventId is returned then it means that the event has been merged with the returned event. Also inside `_embedded` field of the response, a mapping between the original eventId and new eventId will be provided.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

page	integer <int32> Specifies which page of data to retrieve.
page_size	integer <int32> Set custom page sizes on response.
updated_since	string <date-time> Filters the response to only return items that have been updated since the given timestamp
sort	string Determines the ordering of items. A comma-separated string containing <code>resource_version</code> .
min_resource_version	integer or null <int64>
country_code	string Filters results to only include events located in the specified country.
latitude	number or null <double> When provided with longitude and distance filters events returned to ones within the specified distance of the lat/long.

longitude	number or null <double> When provided with latitude and distance filters events returned to ones within the specified distance of the lat/long.
max_distance_in_meters	integer or null <int32> When provided with latitude and longitude filters events returned to ones within the specified distance of the lat/long.
genre_id	integer or null <int32> Filters results to only include events for the specified genre id.
exclude_parking_passes	boolean or null Filters results to remove parking passes

REQUEST BODY SCHEMA: application/json

event_ids	Array of integers <int32> [items <int32 >] The StubHub event identifiers of the events to be retrieved.
-----------	--

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(EventsLinks (object or null))
_embedded >	(EventsEmbeddedResources (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.**> 403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.**> 500** Internal server error

PUT /catalog/events

Request samples

Payload

Content type

application/json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{  
  - "event_ids": [  
    0  
  ]  
}
```

Response samples

200**400****401****403****500****Content type**

application/hal+json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{  
  "total_items": 0,  
  "page": 0,  
  "page_size": 0,  
  - "_links": {  
    + "self": { ... },  
    + "first": { ... },  
    + "last": { ... },  
    + "next": { ... },  
    + "prev": { ... }  
  },  
}
```

```
- "_embedded": {  
  + "deleted_items": [ ... ],  
  + "items": [ ... ]  
}  
}
```

List events by category id.

List set of events filtered by category id on the StubHub platform.

AUTHORIZATIONS: > *OAuth2*

PATH PARAMETERS

categoryId
required integer <int32>

QUERY PARAMETERS

page integer <int32>
Specifies which page of data to retrieve.

page_size integer <int32>
Set custom page sizes on response.

updated_since string <date-time>
Filters the response to only return items that have been updated since the given timestamp

sort	string Determines the ordering of items. A comma-separated string containing <code>resource_version</code> .
min_resource_version	integer or null <int64>
country_code	string Filters results to only include events located in the specified country.
latitude	number or null <double> When provided with longitude and distance filters events returned to ones within the specified distance of the lat/long.
longitude	number or null <double> When provided with latitude and distance filters events returned to ones within the specified distance of the lat/long.
max_distance_in_meters	integer or null <int32> When provided with latitude and longitude filters events returned to ones within the specified distance of the lat/long.
genre_id	integer or null <int32> Filters results to only include events for the specified genre id.
exclude_parking_passes	boolean or null Filters results to remove parking passes

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(EventsLinks (object or null))
_embedded >	(EventsEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

GET /catalog/categories/{categoryId}/events

Response samples

200

401

403

500

Content type

application/hal+json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "deleted_items": [ ... ],
    + "items": [ ... ]
  }
}
```

Get an event on the StubHub platform using an identifier from an external platform.

[AUTHORIZATIONS:](#) >*OAuth2*PATH PARAMETERS

platform
required

string or null

The name of the external platform. Can be `legacy_stubhub`**externalEventId**
required

integer <int32>

The event identifier from the external platform.

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id

integer <int32>

The event identifier.

name

string

The name of the event.

start_date

string <date-time>

The date when the event starts.

end_date	string or null <date-time> The date when the event ends.
on_sale_date	string or null <date-time> The date when tickets for the event will go onsale.
date_confirmed	boolean True if the event start and end date have been confirmed; Otherwise, false.
time_confirmed	boolean True if the event start and end time have been confirmed; Otherwise, false.
type	string The type of the event. Can be <code>Main</code> or <code>Parking</code>
min_ticket_price >	Money (object) The minimum ticket price of the event.
status	string The status of the event. Can be <code>Normal</code> , <code>Postponed</code> , <code>Cancelled</code> , <code>Rescheduled</code> , <code>Relocated</code> , <code>RelocatedAndRescheduled</code> , <code>Draft</code> , <code>Contingent</code> and <code>Deleted</code>
_links >	(EventLinks (object or null))
_embedded >	(EventEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

- > **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.
- > **404** The URI requested is invalid or the resource requested, such as an event, does not exist.
- > **500** Internal server error

GET /catalog/events/external_mappings/{platform}/{externalEventId}

Response samples

200**401****403****404****500**

Content type

application/hal+json

Copy Expand all Collapse all

```
{  
  "id": 0,  
  "name": "string",  
  "start_date": "2019-08-24T14:15:22Z",  
  "end_date": "2019-08-24T14:15:22Z",  
  "on_sale_date": "2019-08-24T14:15:22Z",  
  "date_confirmed": true,  
  "time_confirmed": true,  
  "type": "string",  
}
```

```
- "min_ticket_price": {
  "amount": 0,
  "currency_code": "string",
  "display": "string"
},
"status": "string",
- "_links": {
  + "self": { ... },
  + "event:webpage": { ... }
},
- "_embedded": {
  + "categories": [ ... ],
  + "external_mappings": [ ... ],
  + "genre": { ... },
  + "merged_events": [ ... ],
  + "venue": { ... }
}
}
```

Get an event

Note that the eventId being passed can already be merged with another event. And in this case, details of the new event will be returned, if a different eventId is returned then it means that the event has been merged with the returned event. Also inside _embedded field of the response, a mapping between the original eventId and new eventId will be provided.

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

eventId

required

integer <int32>

The event identifier

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id	integer <int32> The event identifier.
name	string The name of the event.
start_date	string <date-time> The date when the event starts.
end_date	string or null <date-time> The date when the event ends.
on_sale_date	string or null <date-time> The date when tickets for the event will go onsale.

date_confirmed	boolean True if the event start and end date have been confirmed; Otherwise, false.
time_confirmed	boolean True if the event start and end time have been confirmed; Otherwise, false.
type	string The type of the event. Can be <code>Main</code> or <code>Parking</code>
min_ticket_price >	Money (object) The minimum ticket price of the event.
status	string The status of the event. Can be <code>Normal</code> , <code>Postponed</code> , <code>Cancelled</code> , <code>Rescheduled</code> , <code>Relocated</code> , <code>RelocatedAndRescheduled</code> , <code>Draft</code> , <code>Contingent</code> and <code>Deleted</code>
_links >	(EventLinks (object or null))
_embedded >	(EventEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **404** The URI requested is invalid or the resource requested, such as an event, does not exist.

> **500** Internal server error

GET /catalog/events/{eventId}

Response samples

200**401****403****404****500**

Content type

application/hal+json

Copy Expand all Collapse all

```
{
  "id": 0,
  "name": "string",
  "start_date": "2019-08-24T14:15:22Z",
  "end_date": "2019-08-24T14:15:22Z",
  "on_sale_date": "2019-08-24T14:15:22Z",
  "date_confirmed": true,
  "time_confirmed": true,
  "type": "string",
  - "min_ticket_price": {
    "amount": 0,
    "currency_code": "string",
    "display": "string"
  },
  "status": "string",
  - "_links": {
    + "self": { ... },
    + "event:webpage": { ... }
  },
}
```

```
- "_embedded": {  
  + "categories": [ ... ],  
  + "external_mappings": [ ... ],  
  + "genre": { ... },  
  + "merged_events": [ ... ],  
  + "venue": { ... }  
}  
)
```

Search events

Search for events on the StubHub platform. Use this endpoint to search the entire StubHub event catalog with your application.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

q	string or null The query text to be used to match events.
dateLocal	string or null <date-time> The specific date of the event, this is optional
page	integer <int32> Specifies which page of data to retrieve.

page_size	integer <int32> Set custom page sizes on response.
updated_since	string <date-time> Filters the response to only return items that have been updated since the given timestamp
sort	string Determines the ordering of items. A comma-separated string containing <code>resource_version</code> .
min_resource_version	integer or null <int64>
country_code	string Filters results to only include events located in the specified country.
latitude	number or null <double> When provided with longitude and distance filters events returned to ones within the specified distance of the lat/long.
longitude	number or null <double> When provided with latitude and distance filters events returned to ones within the specified distance of the lat/long.
max_distance_in_meters	integer or null <int32> When provided with latitude and longitude filters events returned to ones within the specified distance of the lat/long.
genre_id	integer or null <int32> Filters results to only include events for the specified genre id.

`exclude_parking_passes`

boolean or null

Filters results to remove parking passes

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

<code>total_items</code>	integer or null <int32>
--------------------------	-------------------------

<code>page</code>	integer or null <int32>
-------------------	-------------------------

<code>page_size</code>	integer or null <int32>
------------------------	-------------------------

<code>_links ></code>	(EventsLinks (object or null))
--------------------------	--------------------------------

<code>_embedded ></code>	(EventsEmbeddedResources (object or null))
-----------------------------	--

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

GET /catalog/events/search

Response samples

200

401

403

500

Content type

application/hal+json

Copy Expand all Collapse all

```

{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "deleted_items": [ ... ],
    + "items": [ ... ]
  }
}

```

Get all events under a CategoryId

Finds all CategoryIds under the parents, and finds all events under all of them- de-duped by storing in a HashSet.

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

categoryId integer <int32>
required

CategoryId for which we want all events

QUERY PARAMETERS

page	integer <int32> Specifies which page of data to retrieve.
page_size	integer <int32> Set custom page sizes on response.
updated_since	string <date-time> Filters the response to only return items that have been updated since the given timestamp
sort	string Determines the ordering of items. A comma-separated string containing <code>resource_version</code> .
min_resource_version	integer or null <int64>
country_code	string Filters results to only include events located in the specified country.
latitude	number or null <double> When provided with longitude and distance filters events returned to ones within the specified distance of the lat/long.
longitude	number or null <double> When provided with latitude and distance filters events returned to ones within the specified distance of the lat/long.
max_distance_in_meters	integer or null <int32>

When provided with latitude and longitude filters events returned to ones within the specified distance of the lat/long.

genre_id

integer or null <int32>

Filters results to only include events for the specified genre id.

exclude_parking_passes

boolean or null

Filters results to remove parking passes

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items integer or null <int32>

page integer or null <int32>

page_size integer or null <int32>

_links > (EventsLinks (object or null))

_embedded > (EventsEmbeddedResources (object or null))

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

GET /catalog/categories/{categoryId}/allevents

Response samples

200**401****403****500**

Content type

application/hal+json

Copy Expand all Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
}
```

```
- "_embedded": {  
  + "deleted_items": [ ... ],  
  + "items": [ ... ]  
}  
}
```

Map request to StubHub Event, Venue and Category

Finds mapped Event, Venue and Category information, if available.

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

Request metadata for which we want all mapped information

event_name	string
local_date	string <date-time>
venue_name	string
venue_state	string
venue_city	string
venue_country	string

category_name string or null

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

EventResource > (Event (object or null))

VenueResource > (Venue (object or null))

CategoryResource > (Category (object or null))

> 400

The request data is not valid. errors will contain an object with a localized message that describes the validation error for each property of the data.

> 401 Authentication credentials were missing or incorrect.

> 403 The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> 500 Internal server error

POST /catalog/mapevent

Request samples

Payload

Content type

application/json

Copy

```
{  
  "event_name": "string",  
  "local_date": "2019-08-24T14:15:22Z",  
  "venue_name": "string",  
  "venue_state": "string",  
  "venue_city": "string",  
  "venue_country": "string",  
  "category_name": "string"  
}
```

Response samples

200

400

401

403

500

Content type

application/hal+json

Copy

Expand all

Collapse all

```
{  
  - "EventResource": {  
    "id": 0,  
    "name": "string",  
    "start_date": "2019-08-24T14:15:22Z",  
    "end_date": "2019-08-24T14:15:22Z",  
    "on_sale_date": "2019-08-24T14:15:22Z",  
    "date_confirmed": true,  
    "time_confirmed": true,  
    "type": "string",  
    + "min_ticket_price": { ... },  
    "status": "string",  
    + "_links": { ... },  
    + "_embedded": { ... }  
  },  
  - "VenueResource": {  
    "id": 0,  
    "name": "string",  
    "city": "string",  
    "state_province": "string",  
    "postal_code": "string",  
    "latitude": 0,  
    "longitude": 0,  
    + "_links": { ... },  
    + "_embedded": { ... }  
  },  
  - "CategoryResource": {  
    "id": 0,  
    "name": "string",  
    + "_links": { ... }  
  }  
}
```

Venues

View venues on the StubHub platform

List venues

Lists all venues on the StubHub platform. Use this endpoint to sync the entire StubHub Venue catalog with your application.

AUTHORIZATIONS: >

OAuth2

QUERY PARAMETERS

page	integer <int32> Specifies which page of data to retrieve.
page_size	integer <int32> Set custom page sizes on response.
updated_since	string <date-time> Filters the response to only return items that have been updated since the given timestamp

sort

string

Determines the ordering of items. A comma-separated string containing `resource_version`.

country_code

string

Filters results to only include venues located in the specified country.

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

total_items	integer or null <int32>
--------------------	-------------------------

page	integer or null <int32>
-------------	-------------------------

page_size	integer or null <int32>
------------------	-------------------------

_links >	(VenuesLinks (object or null))
--------------------	--------------------------------

_embedded >	(VenuesEmbeddedResources (object or null))
-----------------------	--

> **401** Authentication credentials were missing or incorrect.

> **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.

> **500** Internal server error

GET /catalog/venues

Response samples

200

401

403

500

Content type

application/hal+json

Copy Expand all Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "deleted_items": [ ... ],
    + "items": [ ... ]
  }
}
```

Get a venue

AUTHORIZATIONS: >

OAuth2

PATH PARAMETERS

venueId integer <int32>
required

The venue identifier

Responses

✓ 200

RESPONSE SCHEMA: application/hal+json

id	integer <int32> The venue identifier.
name	string The name of the venue.
city	string The name of the city where the venue is located.
state_province	string The name of the State or Province where the venue is located.
postal_code	string The postal code for the venue.
latitude	number or null <double> The latitude for the venue.
longitude	number or null <double> The longitude for the venue.
_links >	(VenueLinks (object or null))

_embedded >

(VenueEmbeddedResources (object or null))

- > **401** Authentication credentials were missing or incorrect.
- > **403** The request is understood, but it has been refused or access is not allowed. An accompanying error message will explain why.
- > **404** The URI requested is invalid or the resource requested, such as an event, does not exist.
- > **500** Internal server error

GET /catalog/venues/{venueId}

Response samples

200

401

403

404

500

Content type

application/hal+json

```
{  
  "id": 0,  
  "name": "string",  
  "city": "string",  
  "state_province": "string",  
  "postal_code": "string",  
}
```

Copy Expand all Collapse all

```
"latitude": 0,  
"longitude": 0,  
- "_links": {  
  + "self": { ... }  
},  
- "_embedded": {  
  + "country": { ... },  
  + "external_mappings": [ ... ]  
}  
}
```

Money

Returned for monetary values, such as ticket prices, fees charged and tax amounts.

amount

number or null <decimal>

The decimal amount of the money.

currency_code

string

The ISO 4217 currency code that the monetary value is represented in.

display

string

A user-friendly string representing the monetary value.

Copy

```
{  
  "amount": 0,  
  "currency_code": "string",  
  "display": "string"  
}
```

Event

An event on the StubHub platform.

id

integer <int32>

The event identifier.

name	string The name of the event.
start_date	string <date-time> The date when the event starts.
end_date	string or null <date-time> The date when the event ends.
on_sale_date	string or null <date-time> The date when tickets for the event will go onsale.
date_confirmed	boolean True if the event start and end date have been confirmed; Otherwise, false.
time_confirmed	boolean True if the event start and end time have been confirmed; Otherwise, false.
type	string The type of the event. Can be <code>Main</code> or <code>Parking</code> .
min_ticket_price >	Money (object) The minimum ticket price of the event.
status	string The status of the event. Can be <code>Normal</code> , <code>Postponed</code> , <code>Cancelled</code> , <code>Rescheduled</code> , <code>Relocated</code> , <code>RelocatedAndRescheduled</code> , <code>Draft</code> , <code>Contingent</code> and <code>Deleted</code> .
_links >	(EventLinks (object or null))

[_embedded >](#)

(EventEmbeddedResources (object or null))

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "id": 0,
  "name": "string",
  "start_date": "2019-08-24T14:15:22Z",
  "end_date": "2019-08-24T14:15:22Z",
  "on_sale_date": "2019-08-24T14:15:22Z",
  "date_confirmed": true,
  "time_confirmed": true,
  "type": "string",
  - "min_ticket_price": {
    "amount": 0,
    "currency_code": "string",
    "display": "string"
  },
  "status": "string",
  - "_links": {
    + "self": { ... },
    + "event:webpage": { ... }
  },
}
```

```
- "_embedded": {
  + "categories": [ ... ],
  + "external_mappings": [ ... ],
  + "genre": { ... },
  + "merged_events": [ ... ],
  + "venue": { ... }
}
```

Events

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>
_links >	(EventsLinks (object or null))
_embedded >	(EventsEmbeddedResources (object or null))

[Copy](#) [Expand all](#) [Collapse all](#)

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "deleted_items": [ ... ],
    + "items": [ ... ]
  }
}
```

MapEventResponseModel

EventResource > (Event (object or null))

VenueResource > (Venue (object or null))

CategoryResource > (Category (object or null))

Copy Expand all Collapse all

```
{
  - "EventResource": {
    "id": 0,
    "name": "string",
    "start_date": "2019-08-24T14:15:22Z",
    "end_date": "2019-08-24T14:15:22Z",
    "on_sale_date": "2019-08-24T14:15:22Z",
    "date_confirmed": true,
    "time_confirmed": true,
    "type": "string",
    + "min_ticket_price": { ... },
    "status": "string",
    + "_links": { ... },
    + "_embedded": { ... }
  },
}
```

```
- "VenueResource": {
  "id": 0,
  "name": "string",
  "city": "string",
  "state_province": "string",
  "postal_code": "string",
  "latitude": 0,
  "longitude": 0,
+ "_links": { ... },
+ "_embedded": { ... }
},
- "CategoryResource": {
  "id": 0,
  "name": "string",
+ "_links": { ... }
}
}
```

Venue

An venue on the StubHub platform.

id	integer <int32>
	The venue identifier.

name	string The name of the venue.
city	string The name of the city where the venue is located.
state_province	string The name of the State or Province where the venue is located.
postal_code	string The postal code for the venue.
latitude	number or null <double> The latitude for the venue.
longitude	number or null <double> The longitude for the venue.
_links >	(VenueLinks (object or null))
_embedded >	(VenueEmbeddedResources (object or null))



"id": 0,

Copy Expand all Collapse all

```
    "name": "string",
    "city": "string",
    "state_province": "string",
    "postal_code": "string",
    "latitude": 0,
    "longitude": 0,
  - "_links": {
    + "self": { ... }
  },
  - "_embedded": {
    + "country": { ... },
    + "external_mappings": [ ... ]
  }
}
```

Venues

total_items	integer or null <int32>
page	integer or null <int32>
page_size	integer or null <int32>

<code>_links</code>	>	(VenuesLinks (object or null))
<code>_embedded</code>	>	(VenuesEmbeddedResources (object or null))

Copy Expand all Collapse all

```
{
  "total_items": 0,
  "page": 0,
  "page_size": 0,
  - "_links": {
    + "self": { ... },
    + "first": { ... },
    + "last": { ... },
    + "next": { ... },
    + "prev": { ... }
  },
  - "_embedded": {
    + "deleted_items": [ ... ],
    + "items": [ ... ]
  }
}
```