

Python Programmation

CM 3 : Functions and Strings

Julien Bezançon

julien.bezancon@univ-lorraine.fr / <https://julienbez.github.io>



1 Before we start...

2 Your First Functions

3 Parameters and Arguments

4 Variadic Arguments

5 Python Scope

6 Advanced Strings

What did you learn during last lecture ?
Any questions ?

Last Lecture Doggy bag

Data structures

- Lists
- Dictionaries
- Tuples
- Sets

Advanced Python Stuffs

- Advanced loops
- Functions



A quick word about TDs

Last TD

- Not graded
- 1 week before delivery

Next TDs

- Might be graded
- To send at the end of the session !

Not doing all exercises is ok.
Do what you can.

① Before we start...

② Your First Functions

③ Parameters and Arguments

④ Variadic Arguments

⑤ Python Scope

⑥ Advanced Strings

A Simple Function

```
def add_values(param1, param2):  
    value = param1 + param2  
    return value
```

```
add_values(2,4) # => 6
```

- Called by using its name
- Any number of parameters
- Parameters have no explicit type
- Returns "None" if no "return" statement

A Function that Returns Multiple Values

```
def add_values(param1, param2):  
    value1 = param1 + param2  
    value2 = param1 - param2  
    value3 = param1 * param2  
    return value1, value2, value3
```

```
add_values(2,4) # => 6, -2, 8
```

- Can return multiple values
- In that case, "return" works as a tuple

A Function with a Docstring

```
def add_values(param1, param2):  
    """  
    Add the values of param1 and param2.  
  
    Args: param1 (int), param2 (int)  
    Returns: value (int)  
    """  
    value = param1 + param2  
    return value
```

- The first string literal inside a function body is a docstring
- A docstring is optional but highly recommended
- Used to describe what the function does

Exercise Time !

1. Create a function that give you the maximum in a list.
2. Create a function that reverse a string.
3. Add a doctstring to each function.
4. Type the following line with your functions names. What happens ?

```
print(my_function.__doc__)
```

- 1 Before we start...
- 2 Your First Functions
- 3 Parameters and Arguments**
- 4 Variadic Arguments
- 5 Python Scope
- 6 Advanced Strings

Basic Parameters

```
def add_values(param1, param2):  
    value = param1 + param2  
    return value
```

```
add_values(2,4) # => 6
```

```
add_values()
```

```
# => TypeError: add_values() missing 2 required positional  
#           arguments: 'param1' and 'param2'
```

- This function has two parameters
- These parameters are mandatory, they must be **specified**
- You can add any number of parameters

Default/Named Parameters

```
def add_values(param1,param2,multiplier=5):  
    value = (param1 + param2) * multiplier  
    return value
```

```
add_values(2,4,multiplier=5)      # => 30  
add_values(2,4)                   # => 30  
add_values(2,4,multiplier=10)    # => 60  
add_values(2,4,10)                # => 60
```

- You can add a default value to a parameter
- A named parameter is optional when calling the function
- If a named parameter is not specified, its default value is used

Arguments

```
def ask_yn(prompt, retries=4, complaint='Enter Y/N!'):
    for i in range(retries):
        ok = input(prompt)

        if ok in ('Y', 'y'):
            return True
        if ok in ('N', 'n'):
            return False

    print(complaint)
    return False
```

- Mandatory argument: "prompt"
- Keyword argument: "retries" and "complaint"

Arguments

```
# ask_yn(prompt, retries=4, complaint='...')
```

```
# Call with only the mandatory argument
```

```
ask_yn('Really quit?')
```

```
# Call with one keyword argument
```

```
ask_yn('OK to overwrite the file?', retries=2)
```

```
# Call with one keyword argument - in any order!
```

```
ask_yn('Update status?', complaint='Just Y/N')
```

```
# Call with all of the keyword arguments
```

```
ask_yn('Send text?', retries=2, complaint='Y/N please!')
```

The Dead Parrot Example

```
def parrot(voltage, state='a stiff', action='vroom',
           type='Norwegian Blue'):
    print("-- This parrot wouldn't", action, end=' ')
    print("if you put", voltage, "volts through it.")
    print("-- Lovely plumage, the", type)
    print("-- It's", state, "!")
```

- What does this function do ?
- One variable name is ambiguous. Which one ?

Dead Parrot: Valid Calls

```
# def parrot(voltage, state='...', action='...', type='...')

# 1 positional argument
parrot(1000)

# 1 keyword argument
parrot(voltage=1000)

# 2 keyword arguments
parrot(voltage=1000000, action='VOOOOOM')

# 2 keyword arguments
parrot(action='VOOOOOM', voltage=1000000)

# 3 positional arguments
parrot('a million', 'bereft of life', 'jump')
```

Dead Parrot: Invalid Calls

```
# def parrot(voltage, state='...', action='...', type='...')
```

```
# required argument missing
```

```
parrot()
```

```
# non-keyword argument after a keyword argument
```

```
parrot(voltage=5.0, 'dead')
```

```
# duplicate value for the same argument
```

```
parrot(110, voltage=220)
```

```
# unknown keyword argument
```

```
parrot(actor='John Cleese')
```

Other Examples of Keyword Arguments

```
print("hello", sep=' ', end='\n', file=sys.stdout, flush=False)
range(start, stop, step=1)
enumerate(iter, start=0)
int(x, base=10)
seq.sort(*, key=None, reverse=None)
```

```
subprocess.Popen(args, bufsize=-1, executable=None,
stdin=None, stdout=None, stderr=None, preexec_fn=None,
close_fds=True, shell=False, cwd=None, env=None,
universal_newlines=None, startupinfo=None,
creationflags=0, restore_signals=True,
start_new_session=False, pass_fds=(), encoding=None,
errors=None, text=None)
```

A Weird Case: Mutable default parameter values

```
def my_func(my_list = []):  
    my_list.append("hello")  
    return my_list
```

```
my_func([1,2,3]) # => [1,2,3,"hello"]
```

```
my_func() # => ["hello"], but what happens if I repeat this line ?
```

```
my_func() # => ?
```

```
my_func() # => ?
```

- What happens if I repeat "my_func()" several times ?
- Why does this happen ?

A Weird Case: Explanation

```
def my_func(my_list = []):  
    print(id(my_list))  
    my_list.append("hello")  
    return my_list
```

```
my_func() # => 140095566958408, ["hello"]  
my_func() # => 140095566958408, ["hello", "hello"]  
my_func() # => 140095566958408, ["hello", "hello", "hello"]
```

- Default parameters values are defined only once, at function definition
- Each new call points to the same object

- 1 Before we start...
- 2 Your First Functions
- 3 Parameters and Arguments
- 4 Variadic Arguments**
- 5 Python Scope
- 6 Advanced Strings

Variadic Positional Arguments

```
def product(*nums, scale=1):  
    p = scale  
    for n in nums:  
        p *= n  
    return p
```

```
product(3,5) # => 15
```

```
product(3,4,2) # => 24
```

```
product(3,5,scale=10) # => 150
```

- A parameter of form "`*arg`" captures excess arguments
- These arguments are stored into the "`arg`" tuple
- Parameters after "`*args`" must be default/named ones !

```
print(*objects, sep=' ', end='\n', file="toto.txt", flush=False)
```

Unpacking Variadic Positional Arguments

```
def product(*nums, scale=1):  
    p = scale  
    for n in nums:  
        p *= n  
    return p
```

```
numbers = [1,2,3,4,5,6]  
product(*numbers) # equivalent to product(1,2,3,4,5,6)
```

- The syntax `"*seq"` unpack a sequence into its constituent components

Variadic Keyword Arguments

```
def authorize(quote, **speaker_info):  
    print(">", quote)  
    print("-" * (len(quote) + 2))  
    for k, v in speaker_info.items():  
        print(k, v, sep=': ')
```

```
authorize("If music be the food of love, play on.",  
         playwright="Shakespeare", act=1, scene=1,  
         speaker="Duke Orsino")
```

- A parameter of form "**kwargs" captures all excess keyword arguments
- These arguments are stored into the "kwargs" dictionary

Unpacking Variadic Keyword Arguments

```
authorize("If music be the food of love, play on.",  
          playwright="Shakespeare", act=1, scene=1,  
          speaker="Duke Orsino")
```

```
# > If music be the food of love, play on.  
# -----  
# act: 1  
# scene: 1  
# speaker: Duke Orsino  
# playwright: Shakespeare
```

Unpacking Variadic Keyword Arguments

```
info = {  
    'sonnet': 18,  
    'line': 1,  
    'author': "Shakespeare"  
}
```

```
authorize("Shall I compare thee to a summer's day", **info)
```

```
# > Shall I compare thee to a summer's day  
# -----  
# line: 1  
# sonnet: 18  
# author: Shakespeare
```

- 1 Before we start...
- 2 Your First Functions
- 3 Parameters and Arguments
- 4 Variadic Arguments
- 5 Python Scope**
- 6 Advanced Strings

Variables in Functions

```
def add_values(param1, param2):  
    value = param1 + param2  
    return value
```

```
print(value) # => NameError: name 'value' is not defined.
```

Variables in Functions

```
def add_values(param1, param2):  
    value = param1 + param2  
    return value
```

```
print(value) # => NameError: name 'value' is not defined.
```

- Variables defined inside a function only work in said function
- A variable is only available from inside the region it is created

The LEGB rule

When Python look up variable names, it does it in this order :¹

1. Local - inside the current function
2. Enclosing - inside enclosing functions
3. Global - at the top level of the module
4. Built-in - in Python's built-in namespace

¹https://www.w3schools.com/python/python_scope.asp

Local Scope

```
def add_values(param1, param2):  
    value = param1 + param2  
    return value
```

```
print(value) # => NameError: name 'value' is not defined.
```

- "value" is only available in the "add_values" function
- "value" does not exist outside of the "add_values" function

Enclosing Scope

```
def add_values(param1, param2):  
    value = param1 + param2  
    def show_value():  
        print(value)  
    show_value()
```

```
add_values(2,4) # => 6
```

- "value" can be accessed from a function within the "add_values" function
- Why? Because "show_value" is **inside** the "add_values" function

Global Scope

```
value = 300
```

```
def show_value():  
    print(value)
```

```
show_value() # => 300
```

- Variables created outside of a function can be used by anyone
- Variables created outside of a function == global scope


Built-in Scope

Built-ins are always available and have an usage

- `int()`, `bool()`, `str()`, `float()`, etc
- `print()`, `zip()`, `input()`, etc
- `sorted()`, `min()`, `max()`, `len()`, etc

Built-ins are always available.

Scopes Summary



Python checks scopes in this order :

1. Local scope
2. Enclosing scope
3. Global scope
4. Built-in scope

- If "x" not found, return an error

Almost Everything is Global Scope

```
success = True

if success:
    desc = "winner!"
else:
    desc = "loser"

print(desc)
```

- Only functions may define a new scope (local or enclosing)
- Other statements and loops does not define new scopes

- 1 Before we start...
- 2 Your First Functions
- 3 Parameters and Arguments
- 4 Variadic Arguments
- 5 Python Scope
- 6 Advanced Strings**

Special Characters Handling

<code>print('doesn\'t')</code>	<code># => doesn't</code>
<code>print("doesn't")</code>	<code># => doesn't</code>
<code>print('"Yes," he said.')</code>	<code># => "Yes," he said.</code>
<code>print("\\"Yes,\" he said.")</code>	<code># => "Yes," he said.</code>
<code>print('"Isn\'t," she said.')</code>	<code># => "Isn't," she said.</code>

Useful String Methods

```
greeting = "Hello world! "
```

```
greeting.find('lo')           # => 3 (-1 if not found)
```

```
greeting.replace('llo', 'y')  # => "Hey world!"
```

```
greeting.startswith('Hell')   # => True
```

```
greeting.isalpha()            # => False (due to '!')
```

```
greeting.lower()              # => "hello world! "
```

```
greeting.title()              # => "Hello World! "
```

```
greeting.upper()              # => "HELLO WORLD! "
```

```
greeting.strip()              # => "Hello world!"
```

```
greeting.strip('dH !')        # => "ello worl"
```

String Formatting

```
# Curly braces in strings are placeholders
```

```
'{} {}'.format('monty', 'python')
```

```
# => 'monty python'
```

```
# Provide values by position or by placeholder
```

```
"{0} can be {1} {0}s".format("strings", "formatted")
```

```
"{name} loves {food}".format(name="Sam", food="plums")
```

```
# Pro: Values are converted to strings
```

```
"{} squared is {}".format(5, 5 ** 2)
```

More String Formatting

```
# Pure C-style formatting, might be hard to read
"%s, %s, %s. (Act %d)" % ('Words', 'words', 'words', 2)
# => Words, words, words. (Act 2)
```

```
# String concatenation with +, is slower and clumsier
"I am " + str(age) + " years old."
```

```
# Newfangled formatted string literals, for Python 3.6 and over
f"I am {age} years old."
```

string.format() is a Function !

```
# string.format(*args, **kwargs)
```

```
# {n} refers to the nth positional argument in "args"
```

```
"First, thou shalt count to {0}".format(3) # args = (3)
```

```
"""{0} shalt thou not count, neither count thou {1},  
excepting that thou then proceed to {2}""".format(4, 2, 3)  
# args = (4,2,3)
```

```
# {key} refers to the optional argument bound by key
```

```
"lobbest thou thy {weapon} towards thy foe".format(  
weapon="Holy Hand Grenade of Antioch"  
)
```

```
# kwargs = {"weapon": "Holy Hand Grenade of Antioch"}
```

Exercise Time ! (1/2)

```
"{0}{b}{1}{a}{0}{2}".format(5, 8, 9, a="z", b="x")
```

1. Observe this sequence.
2. Find the list of args and kwargs.
3. What will be the output of this sequence ?

Exercise Time ! (2/2)

- `x = 3`
 - `foo = "fighter"`
 - `y = 4`
 - `learn = 2, "fly"`
 - `z = 5`
 - `sentence = "[x] [foo] fought [y] [foo] during [z] hours"`
1. Do a string formatting on the sentence using the other variables.
 2. Create a dictionary from these variables.
 3. Use this dictionary instead of the variables to do the string formatting.

Doggy bag

Functions

- Function definition and calling
- Parameters and arguments
- Variadic arguments
- Python scopes

Advanced strings

- Special characters handling
- String formatting

